

Package ‘Transition’

July 21, 2025

Type Package

Title Characterise Transitions in Test Result Status in Longitudinal Studies

Version 1.0.0

Date 2025-07-04

Description

Analyse data from longitudinal studies to characterise changes in values of semi-quantitative outcome variables within individual subjects, using high performance C++ code to enable rapid processing of large datasets. A flexible methodology is available for codifying these state transitions.

License MIT + file LICENSE

Imports Rcpp (>= 1.0.14)

LinkingTo Rcpp

RoxygenNote 7.3.2

Encoding UTF-8

Depends R (>= 4.1.0)

LazyData true

URL <https://mark-eis.github.io/Transition/>

NeedsCompilation yes

Author Mark Eisler [aut, cre, cph] (ORCID:

<https://orcid.org/0000-0001-6843-3345>),

Ana Rabaza [aut] (ORCID: <https://orcid.org/0000-0002-9713-0797>)

Maintainer Mark Eisler <mark.eisler@bristol.ac.uk>

Repository CRAN

Date/Publication 2025-07-08 10:00:02 UTC

Contents

Transition-package	2
Blackmore	3
PreviousDate	4

PreviousResult	6
Transitions	7
uniques	10
Index	12

Transition-package	<i>Characterise Transitions in Test Result Status in Longitudinal Studies</i>
--------------------	---

Description

Analyse data from longitudinal studies to characterise changes in values of semi-quantitative outcome variables within individual subjects, using high performance C++ code to enable rapid processing of large datasets. A flexible methodology is available for codifying these state transitions.

Package Content

Index of help topics:

Blackmore	Exercise Histories of Eating-Disordered and Control Subjects
PreviousDate	Find Previous Test Date for Subject
PreviousResult	Find Previous Test Result for Subject
Transition-package	Characterise Transitions in Test Result Status in Longitudinal Studies
Transitions	Identify Temporal Transitions in Longitudinal Study Data
uniques	Unique Values for Subject, Timepoint and Result

Maintainer

Mark Eisler <mark.eisler@bristol.ac.uk>

Author(s)

Mark Eisler [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0001-6843-3345>>), Ana Rabaza [aut] (ORCID: <<https://orcid.org/0000-0002-9713-0797>>)

Blackmore

Exercise Histories of Eating-Disordered and Control Subjects

Description

The Blackmore data frame has 945 rows and 4 columns. Blackmore and Davis's data on exercise histories of 138 teenaged girls hospitalized for eating disorders and 98 control subjects.

Usage

Blackmore

Format

This data frame contains the following columns:

subject a factor with subject id codes. There are several observations for each subject, but because the girls were hospitalized at different ages, the number of cases and the age at the last case vary.

age subject's age in years at the time of observation; all but the last observation for each subject were collected retrospectively at intervals of two years, starting at age 8.

exercise the amount of exercise in which the subject engaged, expressed as estimated hours per week.

group a factor with levels: control, Control subjects; patient, Eating-disordered patients.

Note

The original version in package **carData** states there are 98 control subjects, but the actual data only have 93 unique values, and that assuming subject id codes with suffixes a and b represent different individuals; otherwise, there are just 87.

Source

Personal communication from Elizabeth Blackmore and Caroline Davis, York University.

References

Davis C, Blackmore E, Katzman DK, Fox J. (2005). Female adolescents with anorexia nervosa and their parents: a case-control study of exercise attitudes and behaviours. *Psychological Medicine* 35(3):377-386. doi:10.1017/S0033291704003447

PreviousDate

Find Previous Test Date for Subject

Description

`get_prev_dates()` identifies the previous test date for individual subjects and timepoints in a longitudinal study.

`add_prev_date()` interpolates these previous test dates into a data frame for further analysis.

Usage

```
add_prev_date(  
  object,  
  subject = "subject",  
  timepoint = "timepoint",  
  result = "result"  
)
```

```
get_prev_date(  
  object,  
  subject = "subject",  
  timepoint = "timepoint",  
  result = "result"  
)
```

Arguments

<code>object</code>	a <code>data.frame</code> (or object coercible by <code>as.data.frame()</code> to a data frame) containing the data to be analysed.
<code>subject</code>	<code>character</code> , name of the column (of type <code>integer</code> or <code>factor</code>) identifying individual study subjects; default "subject".
<code>timepoint</code>	<code>character</code> , name of the column recording time points (as <code>Dates</code>) of testing of subjects; default "timepoint".
<code>result</code>	<code>character</code> , name of the column (of type <code>ordered factor</code>) recording test results; default "result".

Details

See [Transitions details](#).

Value

`add_prev_date()`

A `data.frame` based on `object`, with an added column of class `Date` containing the values of the previous test dates.

```
get_prev_date()
```

An vector of length `nrow(object)`, class `Date`, containing the values of the previous test dates ordered in the exact sequence of the subject and timepoint in object.

See Also

[data.frame](#), [Dates](#), [ordered factor](#).

Other transitions: [PreviousResult](#), [Transitions](#), [uniques\(\)](#)

Examples

```
## Continuing example from `add_transitions()`
# subject, timepoint and result arguments all defaults and required types
Blackmore |> str()

# Integer vector of the previous test dates
get_prev_date(Blackmore)

# Add column of previous test dates to data frame
add_prev_date(Blackmore) |> head(32)

rm(Blackmore)

###
## Example on formatting numeric values as R dates

# Data frame containing year as numeric: 2018 to 2025
(df <- data.frame(
  subject = rep(1001:1003),
  timepoint = rep(2018:2025, each = 3),
  result = gl(3, 4, lab = c("jolly", "good", "show"), ordered = TRUE)
))

# Convert to R dates
df <- transform(df,
  timepoint = as.Date(paste(timepoint, "01", "01", sep = "-"))
)

# Add column of test result transitions (defaults: cap = 0, modulate = 0)
(df <- add_transitions(df))

# Format R dates just to show the year
transform(df, timepoint = format(timepoint, "%Y"))

# Data frame containing year and month as numeric: July 2024 to June 2025
(df <- data.frame(
  subject = 1001:1002,
  year = rep(2024:2025, each = 12),
  month = rep(c(7:12, 1:6), each = 2),
```

```

        result = gl(2, 3, lab = c("low", "high"), ordered = TRUE)
    ))

# Convert to R dates
df <- transform(df, timepoint = as.Date(paste(year, month, "01", sep = "-")))

# Add column of test result transitions (defaults: cap = 0, modulate = 0)
(df <- add_transitions(df))

# Format R dates just to show the month and year
transform(df, timepoint = format(timepoint, "%b-%Y"))

rm(df)

```

PreviousResult

Find Previous Test Result for Subject

Description

`get_prev_results()` identifies the previous test result for individual subjects and timepoints in a longitudinal study.

`add_prev_result()` interpolates these previous test results into a data frame for further analysis.

Usage

```

add_prev_result(
  object,
  subject = "subject",
  timepoint = "timepoint",
  result = "result"
)

```

```

get_prev_result(
  object,
  subject = "subject",
  timepoint = "timepoint",
  result = "result"
)

```

Arguments

<code>object</code>	a <code>data.frame</code> (or object coercible by <code>as.data.frame()</code> to a data frame) containing the data to be analysed.
<code>subject</code>	<code>character</code> , name of the column (of type <code>integer</code> or <code>factor</code>) identifying individual study subjects; default "subject".

timepoint	character, name of the column recording time points (as Dates) of testing of subjects; default "timepoint".
result	character, name of the column (of type ordered factor) recording test results; default "result".

Details

See [Transitions details](#).

Value

`add_prev_result()`

A [data.frame](#) based on object, with an added column of type [ordered factor](#) containing the values of the previous test results.

`get_prev_result()`

An [ordered factor](#) of length `nrow(object)`, containing the values of the previous test results ordered in the exact sequence of the subject and timepoint in object.

See Also

[data.frame](#), [Dates](#), [ordered factor](#).

Other transitions: [PreviousDate](#), [Transitions](#), [uniques\(\)](#)

Examples

```
## Continuing example from `add_transitions()`
# subject, timepoint and result arguments all defaults and required types
Blackmore |> str()

# Previous test results as ordered factor
get_prev_result(Blackmore)

# Previous test result as column of data frame
(Blackmore <- add_prev_result(Blackmore)) |> head(32)

rm(Blackmore)
```

Description

`get_transitions()` identifies temporal transitions in test results for individual subjects in a longitudinal study.

`add_transitions()` interpolates these transitions into a data frame for further analysis.

Usage

```

add_transitions(
  object,
  subject = "subject",
  timepoint = "timepoint",
  result = "result",
  transition = "transition",
  cap = 0L,
  modulate = 0L
)

get_transitions(
  object,
  subject = "subject",
  timepoint = "timepoint",
  result = "result",
  cap = 0L,
  modulate = 0L
)

```

Arguments

object	a data.frame (or object coercible by as.data.frame() to a data frame) containing the data to be analysed.
subject	character , name of the column (of type integer or factor) identifying individual study subjects; default "subject".
timepoint	character , name of the column recording time points (as Dates) of testing of subjects; default "timepoint".
result	character , name of the column (of type ordered factor) recording test results; default "result".
transition	character , name to be used for a new column (of type integer) to record transitions; default "transition".
cap	integer , required for calculating transitions; default 0L.
modulate	integer , required for calculating transitions; default 0L.

Details

The data can be presented in any order e.g., ordered by subject, by timepoint, forwards or backwards in time, or entirely at random, and may have unbalanced designs with different time points or numbers of test results per subject. However, the *user* is responsible for ensuring the data contain unique combinations of subject, timepoint and result; if not, outputs will be undefined.

Time points should be formatted as [Dates](#) and included in data frame object in the column named as specified by argument timepoint (see *Note*).

Test results should be semi-quantitative, formatted as [ordered factor](#) and included in data frame object in the column named as specified by argument result (see *Note*).

Temporal transitions in the test results for each subject within the object `data.frame` are characterised using methods governed by options `cap` and `modulate`. If these two parameters are both zero (their defaults), a simple arithmetic difference between the levels of the present and previous result is calculated. Otherwise, if the value of `modulate` is a positive, non-zero integer, the arithmetic difference is subjected to integer division by that value. Finally, if `cap` is a positive, non-zero integer, the (possibly modulated) absolute arithmetic difference is capped at that value.

Value

`add_transitions()`

A `data.frame` based on `object`, with an added column of type `integer` containing the values of the test result transitions.

`get_transitions()`

An `integer vector` of length `nrow(object)`, containing the values of the test result transitions ordered in the exact sequence of the subject and timepoint in `object`.

Note

Time points represented by `integer` or `numeric` values can be converted to R Dates conveniently using `as.Date()`. If only *year* information is available, arbitrary values could be used consistently for month and day e.g., 1st of January of each year; likewise, the first day of each month could be used arbitrary, if only the *year* and *month* were known.

Quantitative results available as `numeric` data can be converted to a semi-quantitative `ordered factor` conveniently using `cut()` (see *examples*).

See Also

`data.frame`, `Dates`, and `ordered factor`.

Other transitions: `PreviousDate`, `PreviousResult`, `uniques()`

Examples

```
# Inspect Blackmore data frame using {base} str()
Blackmore |> str()

# {base} hist() gives insights into the "exercise" column,
# useful for choosing `breaks` and `labels` in cut() below
hist(Blackmore$exercise, include.lowest = TRUE, plot = FALSE)[1:2]

# Tweak Blackmore data frame by converting "age" to dates for the argument
# timepoint (using an arbitrary "origin" of 1-Jan-2000), and converting
# "exercise" to an ordered factor "result" with {base} cut()
Blackmore <- transform(Blackmore,
  timepoint = as.Date("2000-01-01") + round(age * 365.25),
  result = cut(
    exercise,
    breaks = seq(0, 30, 2),
    labels = paste0("<=", seq(0, 30, 2)[-1]),
    include.lowest = TRUE,
```

```

        ordered_result = TRUE
      )
    )

    # subject, timepoint and result arguments now defaults and required types
    Blackmore |> str()

    # Integer vector of test result transitions (defaults: cap = modulate = 0)
    get_transitions(Blackmore)

    # Tabulate values of transitions
    get_transitions(Blackmore) |> table()

    # Effect of cap argument
    get_transitions(Blackmore, cap = 6) |> table()

    # Effect of modulate argument
    get_transitions(Blackmore, modulate = 2) |> table()

    # Add column of test result transitions to data frame
    add_transitions(Blackmore) |> head(22)

    # Showing transitions as either positive (1) or negative (-1)
    # (defaults to modulate = 0)
    add_transitions(Blackmore, cap = 1) |> head(14)

    rm(Blackmore)

```

 uniques

Unique Values for Subject, Timepoint and Result

Description

`uniques()` identifies unique values for subjects, timepoints and test results in longitudinal study data.

Usage

```

uniques(
  object,
  subject = "subject",
  timepoint = "timepoint",
  result = "result"
)

```

Arguments

`object` a `data.frame` (or object coercible by `as.data.frame()` to a data frame) containing the data to be analysed.

subject	character, name of the column (of type integer or factor) identifying individual study subjects; default "subject".
timepoint	character, name of the column recording time points (as Dates) of testing of subjects; default "timepoint".
result	character, name of the column (of type ordered factor) recording test results; default "result".

Details

See [Transitions details](#).

Works for subject as either an [integer vector](#) or a [factor](#).

Value

A [list](#) of three elements

1. An [integer vector](#) or [factor](#) of unique subject identifications.
2. A [vector](#) of class [Date](#) of unique timepoints in the study.
3. An [ordered factor](#) of unique values for results of the study.

See Also

[data.frame](#), [Dates](#), [ordered factor](#).

Other transitions: [PreviousDate](#), [PreviousResult](#), [Transitions](#)

Examples

```
## Continuing example from `add_transitions()`  
# subject, timepoint and result arguments all defaults and required types  
# (native subject is factor)  
uniques(Blackmore)  
#  
Blackmore <- transform(Blackmore, subject = as.integer(subject))  
# subject now as integer  
Blackmore |> str()  
uniques(Blackmore)  
  
rm(Blackmore)
```

Index

- * **datasets**
 - Blackmore, [3](#)
- * **package**
 - Transition-package, [2](#)
- * **transitions**
 - PreviousDate, [4](#)
 - PreviousResult, [6](#)
 - Transitions, [7](#)
 - uniques, [10](#)

[add_prev_date \(PreviousDate\)](#), [4](#)
[add_prev_result \(PreviousResult\)](#), [6](#)
[add_transitions \(Transitions\)](#), [7](#)
[as.data.frame](#), [4, 6, 8, 10](#)
[as.Date](#), [9](#)

[Blackmore](#), [3](#)

[character](#), [4, 6, 8, 11](#)
[cut](#), [9](#)

[data.frame](#), [4–11](#)
[Date](#), [4, 5, 11](#)
[Dates](#), [4, 5, 7–9, 11](#)

[factor](#), [4, 6, 8, 11](#)

[get_prev_date \(PreviousDate\)](#), [4](#)
[get_prev_result \(PreviousResult\)](#), [6](#)
[get_transitions \(Transitions\)](#), [7](#)

[integer](#), [4, 6, 8, 9, 11](#)

[list](#), [11](#)

[nrow](#), [5, 7, 9](#)
[numeric](#), [9](#)

[PreviousDate](#), [4, 7, 9, 11](#)
[PreviousResult](#), [5, 6, 9, 11](#)

[Transition \(Transition-package\)](#), [2](#)
[Transition-package](#), [2](#)
[Transitions](#), [4, 5, 7, 7, 11](#)
[uniques](#), [5, 7, 9, 10](#)
[vector](#), [11](#)