

# Package ‘Clomial’

October 7, 2014

**Type** Package

**Title** Infers clonal composition of a tumor

**Version** 1.0.0

**Date** 2014-02-11

**Author** Habil Zare and Alex Hu

**Maintainer** Habil Zare <zare@u.washington.edu>

**Depends** R (>= 2.10), matrixStats

**Imports** methods

**Description** Clomial fits binomial distributions to counts obtained from Next Gen Sequencing data of multiple samples of the same tumor. The trained parameters can be interpreted to infer the clonal structure of the tumor.

**License** GPL (>= 2)

**biocViews** Genetics, GeneticVariability, Sequencing, Clustering, MultipleComparison, Bayesian, DNaseq, ExomeSeq, TargetedResequencing

**LazyLoad** yes

## R topics documented:

Clomial-package	2
breastCancer	3
choose.best	4
Clomial	5
Clomial.generate.data	8
Clomial.iterate	9
Clomial.likelihood	11
Clomial1000	13
compute.bic	14

<b>Index</b>	<b>16</b>
--------------	-----------

---

Clomial-package	<i>Fits a binomial model to data from multiple samples of a single tumor to infer its clonal decomposition.</i>
-----------------	---

---

## Description

Clomial fits binomial distributions to counts obtained from Next Gen Sequencing data of multiple samples of the same tumor. The trained parameters can be interpreted to infer the clonal structure of the tumor.

## Details

Package: Clomial  
Type: Package  
Version: 0.99.0  
Date: 2014-02-11  
License: GPL (>= 2)

The main function is `Clomial()` which requires 2 matrices `Dt` and `Dc` among its inputs. They contain the counts of the alternative allele, and the total number of processed reads, accordingly. Their rows correspond to the genomic loci, and their columns correspond to the samples. Several models should be trained using different initial values to escape from local optima, and the best one in terms of the likelihood can be chosen by `choose.best()` function.

## Author(s)

Habil Zare and Alex Hu

Maintainer: Habil Zare <zare@u.washington.edu>

## References

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

## See Also

[Clomial](#), [choose.best](#), [Clomial.iterate](#), [Clomial.likelihood](#), [compute.bic](#), [breastCancer](#)

## Examples

```
set.seed(1)
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
ClomialResult <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=4, doParal=FALSE, binomTryNum=2)
chosen <- choose.best(models=ClomialResult$models)
M1 <- chosen$bestModel
```

```
print("Genotypes:")
print(round(M1$Mu))
print("Clone frequencies:")
print(M1$P)
```

---

breastCancer

*Breast cancer data for clonal decomposition.*

---

### Description

Counts data from multiple samples of a single primary breast cancer obtained by deep, next-generation sequencing. The file is consist of two matrices Dt and Dc which contain the counts of the alternative alleles, and the total number of counts on each genomic loci for every tumor samples, accordingly.

### Usage

```
data(breastCancer)
```

### Format

A list containing 2 matrices.

### Details

Each matrix contains counts of reads mapped to 17 genomic loci for 12 tumor samples where the column A5-2 corresponds to the normal sample.

### References

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

### See Also

[Clomial](#)

### Examples

```
data(breastCancer)
breastCancer$Dt
```

---

 choose.best

*Chooses the best trained Clomial model.*


---

### Description

Given the output of Clomial function, the likelihoods of all models are compared, and the best model is determined.

### Usage

```
choose.best(models, U = NULL, PTrue = NULL, compareTo = NULL, upto =
"All", doTalk=FALSE)
```

### Arguments

models	The models trained by Clomial function.
U	The optional genotype matrix used for comparison.
PTrue	The optional clone frequency matrix used for comparison.
compareTo	The index of the model against which all other models are compared. Set to NULL to disable.
upto	The models with index less than this value are considered. Set to "All" to include every model.
doTalk	If TRUE, information on number of analyzed models is reported.

### Details

If compareTo, U, and PTrue are NULL no comparison will be done, and the function runs considerably faster.

### Value

A list will be made with the following entries:

err	A list with 2 entries; err\$P and err\$U the vectors of clonal frequency errors, and genotype errors, accordingly.
Li	A vector of the best obtained log-likelihood for each model.
bestInd	The index of the best model in terms of log-likelihood.
comparison	If compareTo is not NULL, the result of comparison with the corresponding model is reported.
bestModel	The best model in terms of log-likelihood.
seconds	A vector of the time taken, in seconds, to train each model.

**Note**

When the number of assumed clones,  $C$ , is greater than 6, the comparison will be time taking because all possible permutations of clones should be considered. The running time will be slowed down by  $C!$ .

**Author(s)**

Habil Zare

**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#), [Clomial.likelihood](#), [Clomial.iterate](#)

**Examples**

```
set.seed(4)
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
ClomialResult <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=4, doParal=FALSE, binomTryNum=5)
chosen <- choose.best(models=ClomialResult$models)
M1 <- chosen$bestModel
print("Genotypes:")
round(M1$Mu)
print("Clone frequencies:")
M1$P
bestInd <- chosen$bestInd
plot(chosen$Li, ylab="Log-likelihood", type="l")
points(x=bestInd, y=chosen$Li[bestInd], col="red", pch=19)
```

---

Clomial

*Fits several binomial models to data from multiple samples of a single tumor.*

---

**Description**

Using EM, trains several models using different initial values to escape from local optima. The best one in terms of the likelihood can be later chosen by `choose.best()` function.

**Usage**

```
Clomial(Dt = NULL, Dc = NULL, DcDtFile = NULL, C, doParal=FALSE,
outPrefix = NULL, binomTryNum = 1000, maxIt = 100, llCutoff = 0.001,
jobNamePrefix = "Bi", qstatWait = 2, fitBinomJobFile = NULL,
jobShare = 10, ignoredSample = c(), fliProb=0.05, conservative=TRUE,
doTalk=FALSE)
```

**Arguments**

Dt	A matrix which contains the counts of the alternative allele where rows correspond to the genomic loci, and columns correspond to the samples.
Dc	A matrix which contains the counts of the total number of mapped reads where rows correspond to the genomic loci, and columns correspond to the samples.
DcDtFile	A file from which the data can optionally be loaded. It should contain a the matrices Dc and Dt.
C	The assumed number of clones.
doParal	Boolean where TRUE means, in Linux, models with different initialization are trained in parallel on a cluster using qsub.
outPrefix	A prefix for the path to save the results.
binomTryNum	The number of models trained using different initialization.
maxIt	The maximum number of EM iterations.
llCutoff	EM iterations stops if the relative improvement in the log-likelihood is not more than this threshold.
jobNamePrefix	If run in parallel, this prefix will be used to name the jobs on the cluster.
qstatWait	The waiting time between qstat commands to assess the number of running and waiting jobs.
fitBinomJobFile	If run in parallel, this is the script which loads data, trains a model using a random initialization, and saves the results.
jobShare	If run in parallel, the job_share option of qsub determines the priority of jobs over other submitted jobs.
ignoredSample	A vector of samples indices which will be ignored in training. Used by experts only to measure the stability of the results.
fliProb	A "flipping probability" used for noise injection which can be disabled when fliProb=0. After the first EM iteration, each entry of the matrix Mu such as m may change to 1-m with this probability. This probability decreases on subsequent iterations.
conservative	Boolean where TRUE means noise will be injected only if likelihood is improved after an EM iteration, otherwise the original Mu matrix will be used for the next iteration. For expert use only.
doTalk	If TRUE, information on the EM optimization iterations is reported.

## Details

The likelihood of the model, given the hidden variables and the parameters, can be computed based on a combination of binomial distributions. In each EM iteration, the likelihood is increased, however, due to presence of local optima, several models should be tried using different random initialization. For higher number of assumed clones,  $C$ , the parameter `binomTryNum` should be increased because the dimension of the search space grows linearly with  $C$ .

## Value

Returns a list containing the entry called `models`, which is a list of the length equal to `binomTryNum` where each element is a trained model. For each trained model,  $\mu$  models the matrix of genotypes, where rows and columns correspond to genomic loci and clones, accordingly. Also,  $P$  is the matrix of clonal frequency where rows and columns correspond to clones and samples, accordingly. The first column of  $P$  corresponds to the normal clone. The history of  $\mu$ ,  $P$ , and the log-likelihood over iterations is saved in lists `Ps`, `Mus`, and `Likelihoods`, accordingly.

## Note

The parallel mode works only in Linux, and when `qsub` and `qstat` commands are available on a cluster.

## Author(s)

Habil Zare

## References

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

## See Also

[Clomial](#), [choose.best](#), [Clomial.iterate](#), [compute.bic](#), [breastCancer](#)

## Examples

```
set.seed(1)
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
ClomialResult <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=4, binomTryNum=2)
chosen <- choose.best(models=ClomialResult$models)
M1 <- chosen$bestModel
print("Genotypes:")
round(M1$Mu)
print("Clone frequencies:")
M1$P
```

---

Clomial.generate.data *Generates simulated data to test performance of Clomial algorithm.*

---

### Description

Data sets are simulated based on binomial distribution using random parameters for the model. The accuracy of the EM procedure can be estimated by comparing the inferred parameters vs. the known ones which were used to generate the data.

### Usage

```
Clomial.generate.data(N, C, S, averageCoverage, mutFraction,
doSample1Normal = FALSE)
```

### Arguments

N	The number of genomic loci.
C	The number of clones.
S	The number of samples.
averageCoverage	The average coverage over each loci, each sample.
mutFraction	Should be in range 0-1. Each loci in every sample can be mutated with this probability.
doSample1Normal	If TRUE, no contamination with the tumor content is allowed for the normal sample. I.e. the first column of the generated P matrix will start with 1, and the rest of its entries will be equal to 0.

### Details

See the reference below for details.

### Value

A list will be made with the following entries:

Dc	A matrix of simulated coverage for all loci and samples.
Dt	A matrix of alternative allele counts for all loci and samples.
Ptrue	The true clone frequency matrix used for generating the data.
U	The true genotype matrix used for generating the data.
Likelihood	The log-likelihood of the model with the true parameters.

### Author(s)

Habil Zare



**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#), [Clomial.likelihood](#)

**Examples**

```
set.seed(1)
simulated <- Clomial.generate.data(N=20, C=4, S=10,
  averageCoverage=1000, mutFraction=0.1)
simulated$Dc
```

---

Clomial.iterate

*Runs EM iterations until convergence of the Clomial model.*

---

**Description**

Given the data and the initial values for the model parameters, runs EM iterations until convergence of the Clomial model.

**Usage**

```
Clomial.iterate(Dt, Dc, Mu, P, maxIt=100, U = NULL, PTrue = NULL,
  llCutoff = 10^(-3), computePFunction = compute.P.reparam,
  doSilentOptim = TRUE, doTalk = TRUE, doLog = TRUE, debug = FALSE,
  noiseReductionRate = 0.01, fliProb=0.05, conservative=TRUE)
```

**Arguments**

maxIt	The maximum number of EM iterations.
Dt	A matrix which contains the counts of the alternative allele where rows correspond to the genomic loci, and columns correspond to the samples.
Dc	A matrix which contains the counts of the total number of mapped reads where rows correspond to the genomic loci, and columns correspond to the samples.
Mu	The initial value for the Mu matrix which models the genotypes, where rows and columns correspond to genomic loci and clones, accordingly.
P	The initial matrix of clonal frequency where rows and columns correspond to clones and samples, accordingly.
U	The true value for Mu, used for debugging purposes only.
PTrue	The true value for P, used for debugging purposes only.
llCutoff	EM iterations stops if the relative improvement in the log-likelihood is not more than this threshold.

computePFunction	The function used for updating P. For advanced development use only.
doSilentOptim	If TRUE, the optimization messages will not be reported.
doTalk	If FALSE, the function will be run in silent mode.
doLog	Highly recommended to set to TRUE. Then, the computations will be done in log space to avoid numerical issues.
debug	If TRUE, the debug mode will be turned on.
noiseReductionRate	The noise will be reduce by this rate after each EM iteration.
fliProb	A "flipping probability" used for noise injection which can be disabled when fliProb=0. After the first EM iteration, each entry of the matrix Mu such as m may change to 1-m with this probability. This probability decreases on subsequent iterations.
conservative	Boolean where TRUE means noise will be injected only if likelihood is improved after an EM iteration, otherwise the original Mu matrix will be used for the next iteration. For expert use only.

### Details

Injecting noise can be done by assigning a positive value to fliProb, and can be disabled by fliProb=0. Noise injection is recommended for training models with a high number of clones (>4).

### Value

A list will be made with the following entries:

Qs	The history of matrices containing the posterior Q values.
Ps	The history of P matrices.
Mus	The history of Mu matrices.
Mu	The value of Mu after convergence.
P	The value of P after convergence.
llCutoff	The threshold used to decide convergence.
LRatio	The final relative improvement in the log likelihood which lead to convergence.
Likelihoods	The history of log-likelihoods.
fliProb	The final value of fliProb used for noise injection.
timeTaken	An object of class " <a href="#">difftime</a> " which reports the total computational time for EM iterations.
endTaken	An object of class " <a href="#">POSIXct</a> " (see <a href="#">Date Time Classes</a> ) which reports the time EM iterations finished.

### Author(s)

Habil Zare

**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#), [Clomial](#), [breastCancer](#)

**Examples**

```
set.seed(1)
## Getting data:
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
freq1 <- Dt/Dc
N <- nrow(Dc)
S <- ncol(Dc)
Cnum <- 4 ## assumed number of clones.
## Random initialization:
random1 <- runif(n=N*(Cnum-1),min=rowMins(freq1)*0.9,max=rowMaxs(freq1)*1.1)
random1[random1>1] <- 1
random1[random1<0] <- 0
Mu <- matrix(random1,N,Cnum-1)
Mu <- cbind( matrix(0,N,1), Mu )
rownames(Mu) <- rownames(Dc)
colnames(Mu) <- paste("C",1:Cnum,sep="")
P <- matrix(runif(Cnum*S),Cnum,S)
rownames(P) <- colnames(Mu)
colnames(P) <- colnames(Dc)
## Normalizing P:
for( t in 1:S ){
s <- sum(P[,t])
P[,t] <- P[,t]/s
}##End for.

## Running EM:
model1 <- Clomial.iterate(Dt=Dt, Dc=Dc, Mu=Mu, P=P)
print("Genotypes:")
round(model1$Mu)
print("Clone frequencies:")
model1$P
```

---

Clomial.likelihood

*Computes the complete data log-likelihood of a Clomial model.*

---

**Description**

Computes the expected complete data log-likelihood of a Clomial model over all possible values of the hidden variables.

**Usage**

```
Clomial.likelihood(Dc, Dt, Mu, P)
```

**Arguments**

Dt	A matrix which contains the counts of the alternative allele where rows correspond to the genomic loci, and columns correspond to the samples.
Dc	A matrix which contains the counts of the total number of mapped reads where rows correspond to the genomic loci, and columns correspond to the samples.
Mu	The matrix which models the genotypes, where rows and columns correspond to genomic loci and clones, accordingly.
P	The matrix of clonal frequency where rows and columns correspond to clones and samples, accordingly.

**Details**

By assuming that the genomic loci and the samples are independent given the model parameters, the computation is simplified by first summing over the samples for a locus, and then summing over all the loci. This strategy avoids exploring the exponentially huge probability space.

**Value**

A list will be made with the following entries:

ll	The expectation of complete log-likelihood over the hidden variables.
llS	A vector of computed log-likelihoods at all loci.

**Note**

The likelihood is computed assuming the heterozygosity is 2.

**Author(s)**

Habil Zare

**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#), [choose.best](#), [compute.bic](#), [breastCancer](#)

**Examples**

```
set.seed(1)
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
ClomialResult <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=4, doParal=FALSE, binomTryNum=1)
model1 <- ClomialResult$models[[1]]
likelihood <- Clomial.likelihood(Dc=Dc, Dt=Dt, Mu=model1$Mu, P=model1$P)$ll
print(likelihood)
```

---

Clomial1000

*Pre-computed results of Clomial.*

---

**Description**

Pre-computed results of Clomial function are provided for demo purposes. It contains 1000 trained models on counts data from multiple samples of a single primary breast cancer obtained by deep, next-generation sequencing.

**Usage**

```
data(Clomial1000)
```

**Format**

Clomial1000[["models"]] is the list of trained models.

**Details**

Each model is the output of Clomial.iterate() function on the breastCancer data assuming there are 4 clones.

**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#), [Clomial.iterate](#), [choose.best](#), [breastCancer](#)

**Examples**

```
data(Clomial1000)
chosen <- choose.best(models=Clomial1000$models)
M1 <- chosen$bestModel
print("Genotypes:")
round(M1$Mu)
print("Clone frequencies:")
M1$P
```

```
bestInd <- chosen$bestInd
plot(chosen$Li,ylab="Log-likelihood",type="l")
points(x=bestInd,y=chosen$Li[bestInd],col="red",pch=19)
```

---

 compute.bic

*Computes BIC for a Clomial model.*


---

### Description

Computes the Bayesian Information Criterion (BIC) for a Clomial model, which might be useful to estimate the number of clones. A "significantly" smaller BIC is usually interpreted as a better fit to the data.

### Usage

```
compute.bic(Dc, Dt, Mu, P)
```

### Arguments

Dt	A matrix which contains the counts of the alternative allele where rows correspond to the genomic loci, and columns correspond to the samples.
Dc	A matrix which contains the counts of the total number of mapped reads where rows correspond to the genomic loci, and columns correspond to the samples.
Mu	The matrix which models the genotypes, where rows and columns correspond to genomic loci and clones, accordingly.
P	The matrix of clonal frequency where rows and columns correspond to clones and samples, accordingly.

### Details

The Bayesian Information Criterion (BIC) for a model is computed by subtracting the expected log-likelihood times 2, from the number of free parameters of the model times logarithm of the total number of observations. For a Clomial model, we have  $BIC = (NC+SC-S)\log(\text{sum}(Dc))-2L$ , where L is the likelihood, N is the number of genomic loci, C is the assumed number of clones, S is the number of samples, and  $\text{sum}(Dc)$  is the total number of observed reads.

### Value

A list will be made with the following entries:

bic	The BIC value.
aic	The AIC value.
obsNum	The total number of observed reads.

**Note**

Theoretically, a method such as the Bayesian information criterion (BIC) or the Akaike information criterion (AIC) may be applied to estimate the number of clones. However, in practice, the outcome of such approaches should be interpreted with great caution because some of the underlying assumptions of the statistical analysis may not be necessarily true for a given model. For example, while a "small" improvement in the BIC is generally considered as a sign to stop making the model more complicated, making such decisions is very subjective, and requires relying on thresholds with little statistical basis.

**Author(s)**

Habil Zare

**References**

Inferring clonal composition from multiple sections of a breast cancer, Zare et al., Submitted.

**See Also**

[Clomial](#)

**Examples**

```
set.seed(1)
data(breastCancer)
Dc <- breastCancer$Dc
Dt <- breastCancer$Dt
bics <- c()
Clomial3 <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=3, doParal=FALSE, binomTryNum=1)
model3 <- Clomial3$models[[1]]
bics[3] <- compute.bic(Dc=Dc, Dt=Dt, Mu=model3$Mu, P=model3$P)$bic
Clomial4 <- Clomial(Dc=Dc, Dt=Dt, maxIt=20, C=4, doParal=FALSE, binomTryNum=1)
model4 <- Clomial4$models[[1]]
bics[4] <- compute.bic(Dc=Dc, Dt=Dt, Mu=model4$Mu, P=model4$P)$bic
print(bics) ## 4 is a better estimate for the number of clones.
```

# Index

## \*Topic **datasets**

- breastCancer, 3
- Clomial-package, 2
- Clomial1000, 13

## \*Topic **documentation**

- choose.best, 4
- Clomial, 5
- Clomial-package, 2
- Clomial.generate.data, 8
- Clomial.iterate, 9
- Clomial.likelihood, 11
- compute.bic, 14

## \*Topic **iteration**

- Clomial, 5
- Clomial-package, 2
- Clomial.iterate, 9

## \*Topic **models**

- choose.best, 4
- Clomial, 5
- Clomial-package, 2
- Clomial.generate.data, 8
- Clomial.iterate, 9
- Clomial.likelihood, 11

## \*Topic **package**

- Clomial-package, 2

breastCancer, 2, 3, 7, 11–13

choose.best, 2, 4, 7, 12, 13

Clomial, 2, 3, 5, 5, 7, 9, 11–13, 15

Clomial-package, 2

Clomial.generate.data, 8

Clomial.iterate, 2, 5, 7, 9, 13

Clomial.likelihood, 2, 5, 9, 11

Clomial1000, 13

compute.bic, 2, 7, 12, 14

DateTimeClasses, 10

difftime, 10