

RCytoscape

March 24, 2012

CytoscapeConnection

CytoscapeConnection

Description

The constructor for the CytoscapeConnectionClass. This class is both the base class for CytoscapeWindow objects, and quite usefully, and instantiable object in its own right. It is very useful for calling the many RCytoscape methods which do not address a single window in particular: getWindowList, getWindowCount, deleteWindow, getNodeShapes, etc.

Usage

```
CytoscapeConnection (host = "localhost", rpcPort = 9000)
```

Arguments

host	Defaults to 'localhost', this is the domain name of a machine which is running Cytoscape with the appropriate XMLRPC server plugin.
rpcPort	Defaults to 9000, this may be any port to which the CytoscapeRPC server is listening.

Value

An object of the CytoscapeConnection Class.

Author(s)

Paul Shannon

See Also

ping version msg clearMsg getWindowCount getWindowID getWindowCount getWindowList deleteWindow deleteAllWindows getNodeShapes getAttributeClassNames getLineStylees getArrowShapes getLayoutNames haveNodeAttribute haveEdgeAttribute getGraphFromCyWindow hidePanel dockPanel floatPanel

Examples

```
cy <- CytoscapeConnection ()
deleteAllWindows (cy)
getNodeShapes (cy)
hidePanel (cy, 'Control')
```

CytoscapeConnectionClass-class
Class "CytoscapeConnectionClass"

Description

A class providing access to operations of the Cytoscape application which are not specific to a particular window.

Slots

uri: An `attrData` the address of the Cytoscape XMLRPC server.

Methods

ping
version
msg
clearMsg
getWindowcount
getWindowID
getWindowCount
getWindowList
destroyWindow
destroyAllWindows
getNodeShapes
getAttributeClassNames
getLineStyle
getArrowShapes
haveNodeAttribute
haveEdgeAttribute
copyNodeAttributesFromCyGraph
copyEdgeAttributesFromCyGraph
getGraphFromCyWindow
hidePanel
dockPanel
floatPanel

Author(s)

Paul Shannon

Examples

```
# create a CytoscapeConnectionClass object by calling the constructor
cy <- CytoscapeConnection (host='localhost', rpcPort=9000)
```

CytoscapeWindow *CytoscapeWindow*

Description

The constructor for the CytoscapeWindowClass

Usage

```
CytoscapeWindow(title, graph = new("graphNEL", edgemode='directed'), host = "localhost",
```

Arguments

title	A character string, this is the name you will see on the Cytoscape network window. Multiple windows with the same name are not permitted.
graph	A Bioconductor graph.
host	Defaults to 'localhost', this is the domain name of a machine which is running Cytoscape with the appropriate XMLRPC server plugin.
rpcPort	Defaults to 9000, this may be any port to which the CytoscapeRPC server is listening.
create.window	Defaults to TRUE, but if you wish to defer creating a window, set this argument to FALSE.

Value

An object of the CytoscapeWindow Class.

Author(s)

Paul Shannon

See Also

new.CytoscapeWindow existing.CytoscapeWindow

Examples

```
cw <- CytoscapeWindow ('cw demo', new ('graphNEL'))
```

CytoscapeWindowClass-class
Class "CytoscapeWindowClass"

Description

A class providing access to the Cytoscape application.

Slots

title: An attrData the name of the window.
window.id: An attrData Cytoscape's identifier.
graph: An attrData a graph instance.
uri: An attrData the address of the Cytoscape XMLRPC server.

Methods

createWindow
destroyWindow
destroyAllWindows
displayGraph
firstNeighbors
getArrowShapes
getLayoutNames
getLineStyle
getNodeShapes
getWindowCount

Author(s)

Paul Shannon

Examples

```
# create a CytoscapeWindowClass object by calling the constructor  
c2 <- CytoscapeWindow ('cwc demo', makeSimpleGraph ())
```

`addCyEdge`*addCyEdge*

Description

Given a CytoscapeWindow containing a (possibly empty) graph, this method adds a edge. Edge attributes are added separately, via successive calls to `sendEdgeAttributesDirect`. The two nodes must already exist in the Cytoscape network.

Usage

```
addCyEdge(obj, sourceNode, targetNode, edgeType, directed)
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>sourceNode</code>	a character string object.
<code>targetNode</code>	a character string object.
<code>edgeType</code>	a character string object.
<code>directed</code>	a boolean object.

Value

None.

Author(s)

Paul Shannon

See Also

`sendEdgeAttributesDirect` `addCyNode`

Examples

```
window.name <- 'demo addCyEdge'  
cw <- new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw)  
directed = TRUE  
addCyEdge (cw, 'A', 'B', 'synthetic rescue', directed)  
redraw (cw)  
layout (cw)
```

addCyNode	<i>addCyNode</i>
-----------	------------------

Description

Given a CytoscapeWindow containing a (possibly empty) graph, this method adds a node. Node attributes are added separately, via successive calls to sendNodeAttributesDirect. The new node must be unique – not already a member of the graph as known to Cytoscape.

Usage

```
addCyNode(obj, nodeName)
```

Arguments

obj	a CytoscapeWindowClass object.
nodeName	a character string object.

Value

None.

Author(s)

Paul Shannon

See Also

sendNodeAttributesDirect addCyEdge

Examples

```
window.name <- 'demo addCyNode'  
cw <- new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw)  
addCyNode (cw, 'A NEW NODE')  
redraw (cw)  
layout (cw)
```

addGraphToGraph *addGraphToGraph*

Description

Given a CytoscapeWindow containing a graph, this method adds new nodes, edges, and their attributes. Thus, it is the way to extend a graph – to merge a new graph with an existing one. A typical use would be to add a second KEGG pathway to a CytoscapeWindow upon discovering that two KEGG pathways overlap, sharing some enzymes and some reactions. No existing attributes are written over.

Usage

```
addGraphToGraph(obj, other.graph)
```

Arguments

`obj` a CytoscapeWindowClass object.
`other.graph` a graph object.

Value

None.

Author(s)

Paul Shannon

Examples

```
window.name <- 'demo addGraphToGraph'  
cw3 <- new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw3)  
redraw (cw3)  
layout (cw3)  
  
# create a new graph, which adds two nodes, and edges between them  
# and an existing node, A  
  
g2 <- new("graphNEL", edgemode = "directed")  
g2 <- graph::addNode ('A', g2)  
g2 <- graph::addNode ('D', g2)  
g2 <- graph::addNode ('E', g2)  
  
g2 <- initNodeAttribute (g2, "label", "char", "default node label")  
g2 <- initEdgeAttribute (g2, "edgeType", "char", "unspecified")  
g2 <- initEdgeAttribute (g2, "probability", "numeric", 0.0)  
  
nodeData (g2, 'D', 'label') <- 'Gene D'  
nodeData (g2, 'E', 'label') <- 'Gene E'  
  
g2 <- graph::addEdge ('D', 'E', g2)  
g2 <- graph::addEdge ('A', 'E', g2)
```

```
edgeData (g2, 'D', 'E', 'probability') <- 0.95
edgeData (g2, 'D', 'E', 'edgeType') <- 'literature'
edgeData (g2, 'A', 'E', 'edgeType') <- 'inferred'

addGraphToGraph (cw3, g2)
redraw (cw3)
layout (cw3)
```

clearMsg

clearMsg

Description

Clears any current message in the Cytoscape Desktop status bar.

Usage

```
clearMsg(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

Nothing.

Author(s)

Paul Shannon

See Also

msg

Examples

```
cy <- CytoscapeConnection ()
clearMsg (cy)
```

clearSelection *clearSelection*

Description

If any nodes are selected in the current Cytoscape window, they will be unselected.

Usage

```
clearSelection(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

Nothing

Author(s)

Paul Shannon

Examples

```
cw<- CytoscapeWindow ('clearSelection.test', graph=makeSimpleGraph())
displayGraph (cw)
selectNodes (cw, 'A')
print (getSelectedNodeCount (cw))    # should be 1
clearSelection (cw)
print (getSelectedNodeCount (cw))    # should be 0
```

copyVisualStyle *copyVisualStyle*

Description

Once you have designed a visual style, you may wish to duplicate it, perhaps in preparation for adding further mapping rules. Another scenario arises when style rules have been added to the 'default' style, and you wish to create a Cytoscape session file with your current network and this default style. However, the default style is not saved into a session, only explicitly named styles are. Use this method to achieve this.

Usage

```
copyVisualStyle(obj, from.style, to.style)
```

Arguments

<code>obj</code>	a <code>CytoscapeConnectionClass</code> object or <code>CytoscapeWindow</code> object.
<code>from.style</code>	a character string specifying the name of an existing style you wish to copy
<code>to.style</code>	a character string, the name of an as yet non-existent style

Value

Nothing.

Author(s)

Paul Shannon

See Also

`getVisualStyleNames` `setVisualStyle`

Examples

```

# create the usual demo graph and Cytoscape window, then
# specify that all the edges should be 5 pixels wide. This affects the 'default' style
# in order to save this style for later use, copy it to a
# new style named 'fatEdgeStyle'
# the related method 'setVisualStyle' must be called in order for
# the fatEdgeStyle to be associated with this window (and saved
# into the CytoscapeSession file from the Cytoscape application's
# File menu)

window.name = 'demo.copyVisualStyle'
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())
setDefaultEdgeLineWidth (cw, 5);
displayGraph (cw)
redraw (cw)
layout (cw)

# create a unique style name, using millisecond precision, so should be unique
time.msec = proc.time()[['elapsed']]
new.unique.style.name = paste ('fatEdgeStyle', time.msec, sep='.')

copyVisualStyle (cw, 'default', new.unique.style.name)
new.names = getVisualStyleNames (cw)
setVisualStyle (cw, new.unique.style.name)

# save the session from the Cytoscape application menu. the new
# style name will be saved along with the network and its attributes

```

createWindow	<i>createWindow</i>
--------------	---------------------

Description

Request that Cytoscape create a new window for the supplied CytoscapeWindowClass object. It will hold a new network, using the title supplied when the object's constructor was called.

This method will probably not often be useful: it is called behind the scenes by the CytoscapeWindow constructor unless you specify (in calling the constructor) 'create.window=FALSE'. In that case, or if you interactively delete the window in Cytoscape, or if you call the 'destroyWindow' or 'destroyAllWindows' methods, you can create a new window by calling this method.

Usage

```
createWindow(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

Nothing.

Author(s)

Paul Shannon

createWindowFromSelection	<i>createWindowFromSelection</i>
---------------------------	----------------------------------

Description

All selected nodes, their connecting edges, and associated attributes are copied into a new CytoscapeWindow, with the supplied title.

Usage

```
createWindowFromSelection(obj, new.windowTitle, return.graph)
```

Arguments

obj a CytoscapeWindowClass object.

new.windowTitle a String.

return.graph an logical object.

Value

A new CytoscapeWindow object, with the graph slot populated with the new selected subgraph, if requested. If not requested, the graph slot holds an empty graph.

Author(s)

Paul Shannon

See Also

selectNodes

Examples

```
cy <- CytoscapeConnection ()
title <- 'createWindowFromSelection demo'

cw <- new.CytoscapeWindow (title, makeSimpleGraph ())
displayGraph (cw)
redraw (cw)
layout (cw)
selectNodes (cw, c ('A', 'C'))

new.window.title <- 'NEW WINDOW'
if (new.window.title %in% as.character (getWindowList (cy)))
  deleteWindow (cy, new.window.title)

c2 <- createWindowFromSelection (cw, new.window.title, TRUE)
redraw (c2)
layout (c2)

clearSelection (c2)
selectNodes (c2, 'C')
print (getSelectedNodeCount (c2)) # should be 1
```

cy2.edge.names *cy2.edge.names*

Description

Bioconductor graph edges are named, i.e., A~B. The same edge in the Cytoscape domain would be 'A (<edgeType>) B', where '<edgeType>' might be 'phosphorylates' or 'represses'.

Usage

```
cy2.edge.names (graph, R.edge.names=NA)
```

Arguments

graph An R graph

R.edge.names one or more R graph-style edge names. default NA, in which case all edges in the graph are translated to cy2-style.

Value

A named list, in with Cytoscape edges names are the content, and bioc graph edge names are their names.

Author(s)

Paul Shannon

Examples

```
g <- makeSimpleGraph ()
cy2.edge.names (g)
#           A~B           B~C           C~A
# "A (phosphorylates) B" "B (synthetic lethal) C" "C (undefined) A"
cy2.edge.names (g, R.edge.names="B~C")
#           B~C
# "B (synthetic lethal) C"
```

deleteAllWindows *deleteAllWindows*

Description

Delete all the network windows currently held by Cytoscape, removing them from the screen, and deleting Cytoscape's copy of all of the graphs. The R graphs are unchanged.

Usage

```
deleteAllWindows (obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
cw1 = new.CytoscapeWindow ('cw1')
cw2 = new.CytoscapeWindow ('cw2')
deleteAllWindows (cy)
```

```
deleteEdgeAttribute  
    deleteEdgeAttribute
```

Description

Node and edge attributes are usually added to a Cytoscape network by defining them on the graph used to construct a CytoscapeWindow. Once Cytoscape has been passed an attribute, however, it persists until you exit the application or delete it – using the Cytoscape graphical user interface, or by calling this method.

Usage

```
deleteEdgeAttribute(obj, attribute.name)
```

Arguments

<code>obj</code>	a CytoscapeConnectionClass object or CytoscapeWindow object.
<code>attribute.name</code>	a character string, the name of the attribute you wish to delete.

Value

nothing

Author(s)

Paul Shannon

See Also

`getEdgeAttributeNames` `addEdgeAttribute` `deleteNodeAttribute`

Examples

```
window.name = 'demo.deleteEdgeAttribute'  
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
setDefaultEdgeLineWidth (cw, 5);  
displayGraph (cw)  
redraw (cw)  
layout (cw)  
  
print (paste ("before: ", getEdgeAttributeNames (cw)))  
deleteEdgeAttribute (cw, 'score')  
print (paste ("after: ", getEdgeAttributeNames (cw)))
```

```
deleteNodeAttribute  
    deleteNodeAttribute
```

Description

Node and node attributes are usually added to a Cytoscape network by defining them on the graph used to construct a CytoscapeWindow. Once Cytoscape has been passed an attribute, however, it persists until you exit the application or delete it – using the Cytoscape graphical user interface, or by calling this method.

Usage

```
deleteNodeAttribute(obj, attribute.name)
```

Arguments

`obj` a CytoscapeConnectionClass object or CytoscapeWindow object.
`attribute.name` a character string, the name of the attribute you wish to delete.

Value

nothing

Author(s)

Paul Shannon

See Also

getNodeAttributeNames addNodeAttribute

Examples

```
window.name = 'demo.deleteNodeAttribute'  
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw)  
redraw (cw)  
layout (cw)  
  
print (paste ("before: ", getNodeAttributeNames (cw)))  
deleteNodeAttribute (cw, 'count')  
print (paste ("after: ", getNodeAttributeNames (cw)))
```

`deleteSelectedEdges`*deleteSelectedEdges*

Description

In Cytoscape, remove all selected edges. These edges will still exist in the corresponding R graph until you delete them there as well.

Usage

```
deleteSelectedEdges (obj)
```

Arguments

`obj` a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

`selectEdges` `cy2.edge.names` `deleteSelectedNodes`

Examples

```
cw <- new.CytoscapeWindow ('deleteSelectedEdges.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (cy2.edge.names (cw@graph)) # find out Cytoscape's names for these edges
selectEdges (cw, "B (synthetic lethal) C")
deleteSelectedEdges (cw)
redraw (cw)
```

`deleteSelectedNodes`*deleteSelectedNodes*

Description

In Cytoscape, delete all the selected nodes. Edges originating or terminating in these nodes will be deleted also. The nodes will still exist in the corresponding R graph until you explicitly delete them there as well.

Usage

```
deleteSelectedNodes (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

selectNodes deleteSelectedEdges

Examples

```
cw <- new.CytoscapeWindow ('deleteSelectedNodes.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (nodes (cw@graph))
selectNodes (cw, "B")
deleteSelectedNodes (cw)
```

deleteWindow

deleteWindow

Description

Delete the window associated with the supplied CytoscapeConnection object. In addition, Cytoscape's copy of the network is deleted from Cytoscape's memory store, but the R graph object is unaffected.

There are two different ways to use this method. First, if you call it on a CytoscapeWindow object, using the default window.title value of NA, the Cytoscape window itself will be deleted. Alternatively, if you supply a window.title as the second argument – independent of whether or not the first argument is a CytoscapeConnection object, or its subclass, a CytoscapeWindow object, the named window is deleted.

Usage

```
deleteWindow(obj, window.title=NA)
```

Arguments

obj a CytoscapeConnectionClass object, or subclass
window.title a string object, optional title

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
window.title <- 'demo deleteWindow'  
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw)  
deleteWindow (cw)  
cw2 <- new.CytoscapeWindow ('demo 2')  
cy = CytoscapeConnection ()  
deleteWindow (cy, 'demo 2')
```

demoSimpleGraph *demoSimpleGraph*

Description

Create, display and render the 3-node, 3-edge graph, with some biological trappings.

Usage

```
demoSimpleGraph()
```

Value

Returns a CytoscapeWindow object, for subsequent manipulation

Author(s)

Paul Shannon

Examples

```
cwd <- demoSimpleGraph ()
```

displayGraph	<i>displayGraph</i>
--------------	---------------------

Description

This method transmits the CytoscapeWindowClass's graph data, from R to Cytoscape: nodes, edges, node and edge attributes, and displays it in a window titled as specified by the objects 'title' slot. With large graphs, this transmission may take a while. (todo: provide a few timing examples.) The resulting view, in Cytoscape, of the network will need layout and vizmap rendering; layout so that all the nodes and edges can be seen; rendering so that data attributes can control the appearance of the the nodes and edges.

Usage

```
displayGraph(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cw <- CytoscapeWindow ('displayGraph.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
```

dockPanel	<i>dockPanel</i>
-----------	------------------

Description

The specified panel is returned to its 'home' position in the Cytoscape Desktop if it had been previously floating or hidden. The panelName parameter is very flexible: a match is defined as a case-independent match of the supplied panelName to any starting characters in the actual panelName. Thus, 'd' and 'DA' both identify 'Data Panel'.

Usage

```
dockPanel(obj, panelName)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.
`panelName` a character string, providing a partial or complete case-independent match to the start of the name of an actual panel.

Value

Nothing.

Author(s)

Paul Shannon

See Also

`floatPanel` `hidePanel`

Examples

```
cy <- CytoscapeConnection ()
dockPanel (cy, 'Control Panel')
# or
dockPanel (cy, 'c')
```

eda

eda

Description

Obtain the value of the specified edge attribute for every edge in the graph.

Usage

```
eda(graph, edge.attribute.name)
```

Arguments

`graph` typically, a `bioc graphNEL` object
`edge.attribute.name`
a character string

Details

The `edge.attribute.name` may be obtained from the function, `eda.names`.

Value

A list, the contents of which are the attribute values, the names of which are the names of the edges.

Author(s)

Paul Shannon

See Also

eda.names

Examples

```
g <- makeSimpleGraph()
eda (g, 'edgeType')

## The function is currently defined as
function (graph, edge.attribute.name)
{
  unlist (sapply (names (edgeData (graph)), function (n) edgeData (graph)[[n]][[edge.attr
} # eda
```

eda.names

eda.names

Description

Retrieve the names of the edge attributes in the specified graph. These are typically strings like 'score', 'weight', 'link', and (strongly recommended when you create a graph) 'edgeType'. Once you are reminded of the names of the edge attributes, you can use the method 'eda' to get all the values of this attribute for the edges in the graph.

Usage

```
eda.names (graph)
```

Arguments

graph typically, a bioc graphNEL)

Value

A list, the contents of which are the attribute values, the names of which are the names of the edges.

Author(s)

Paul Shannon

See Also

eda

Examples

```
g <- makeSimpleGraph()
eda.names (g)
# "edgeType" "score" "misc"
```

```
existing.CytoscapeWindow  
    existing.CytoscapeWindow
```

Description

The constructor for the CytoscapeWindowClass, used when Cytoscape already contains and displays a network.

Usage

```
existing.CytoscapeWindow (title, host='localhost', rpcPort=9000, copy.graph.from
```

Arguments

title	A character string, this is the name of an existing Cytoscape network window. This name enables RCytoscape to identify and connect to the proper Cytoscape window and network that it contains.
host	Defaults to 'localhost', this is the domain name of a machine which is running Cytoscape with the appropriate XMLRPC server plugin.
rpcPort	Defaults to 9000, this may be any port to which the CytoscapeRPC server is listening.
copy.graph.from.cytoscape.to.R	Defaults to FALSE, but you may want a copy in R, for further exploration.

Value

An object of the existing.CytoscapeWindow Class.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()  
cw <- new.CytoscapeWindow ('demo.existing', graph=makeSimpleGraph ())  
displayGraph (cw)  
cw2 <- existing.CytoscapeWindow ('demo.existing', copy.graph.from.cytoscape.to.R=TRUE)
```

fitContent	<i>fitContent</i>
------------	-------------------

Description

Using all of the available window (the Cytoscape drawing canvas) display the current graph.

Usage

```
fitContent (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

setZoom fitSelectedContent

Examples

```
cw <- new.CytoscapeWindow ('fitContent.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setZoom (cw, 0.1)
fitContent (cw)
setZoom (cw, 10.0)
fitContent (cw)
```

fitSelectedContent	<i>fitSelectedContent</i>
--------------------	---------------------------

Description

Using all of the available window (the Cytoscape drawing canvas) display the current graph.

Usage

```
fitSelectedContent (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

setZoom fitContent

Examples

```

cw <- new.CytoscapeWindow ('fitSelectedContent.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setZoom (cw, 0.1)
selectNodes (cw, 'A')
fitSelectedContent (cw)
setZoom (cw, 10.0)
fitSelectedContent (cw)

```

floatPanel

floatPanel

Description

The specified panel will 'float' detached from its 'home' position in the Cytoscape Desktop. As of this writing (10 aug 2010) the panel will tenaciously claim the topmost (visual) position on the screen... The `panelName` parameter is very flexible: a match is defined as a case-independent match of the supplied `panelName` to any starting characters in the actual `panelName`. Thus, 'd' and 'DA' both identify 'Data Panel'.

Usage

```
floatPanel(obj, panelName)
```

Arguments

<code>obj</code>	a <code>CytoscapeConnectionClass</code> object.
<code>panelName</code>	a character string, providing a partial or complete case-independent match to the start of the name of an actual panel.

Value

Nothing.

Author(s)

Paul Shannon

See Also

hidePanel dockPanel

Examples

```
cy <- CytoscapeConnection ()
floatPanel (cy, 'Control Panel')
# or with less typing
floatPanel (cy, 'c')
```

```
getAllEdgeAttributes
      getAllEdgeAttributes
```

Description

Create a data frame with all the edge attributes for the graph contained by the supplied CytoscapeWindow object. Only the local copy of the graph is queried. If you want all the (possibly different) edge attributes from the Cytoscape network which corresponds to this graph, one option is to create a new CytoscapeWindow; see the existing.CytoscapeWindow function.

Usage

```
getAllEdgeAttributes(obj, onlySelectedEdges=FALSE)
```

Arguments

obj a CytoscapeWindowClass object object.
onlySelectedEdges a logical variable, used to restrict the query.

Value

A data frame, with a column for each attribute, a row for each edge.

Author(s)

Paul Shannon

See Also

getEdgeAttribute deleteEdgeAttribute getAllNodeAttributes

Examples

```
window.name = 'demo.getAllEdgeAttributes'
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())
displayGraph (cw)
redraw (cw)
layout (cw)
# get all attributes for all edges
tbl.noa = getAllEdgeAttributes (cw, onlySelectedEdges=FALSE)
```

```
getAllEdges          getAllEdges
```

Description

Retrieve all edges in the current graph, expressed in the standard Cytoscape notation.

Usage

```
getAllEdges(obj)
```

Arguments

`obj` a `CytoscapeWindowClass` object.

Value

A list of character strings.

Author(s)

Paul Shannon

Examples

```

cw <- CytoscapeWindow ('getAllEdges.test', graph=makeSimpleGraph())
# [1] "C (undefined) A" "B (synthetic lethal) C" "A (phosphorylates) B"

```

```
getAllNodeAttributes
          getAllNodeAttributes
```

Description

Create a data frame with all the node attributes for the graph contained by the supplied `CytoscapeWindow` object. Only the local copy of the graph is queried. If you want all the (possibly different) node attributes from the Cytoscape network which corresponds to this graph, one option is to create a new `CytoscapeWindow`; see the existing `CytoscapeWindow` function.

Usage

```
getAllNodeAttributes(obj, onlySelectedNodes=FALSE)
```

Arguments

`obj` a `CytoscapeWindowClass` object object.
`onlySelectedNodes` a logical variable, used to restrict the query.

Value

A data frame, with a column for each attribute, a row for each node.

Author(s)

Paul Shannon

See Also

getNodeAttribute deleteNodeAttribute

Examples

```
window.name = 'demo.getAllNodeAttributes'  
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw)  
redraw (cw)  
layout (cw)  
# get all attributes for all nodes  
tbl.noa = getAllNodeAttributes (cw, onlySelectedNodes=FALSE)
```

getAllNodes

getAllNodes

Description

Retrieve the identifiers of all the nodes in the current graph - a list of strings.

Usage

```
getAllNodes (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A list of character strings. Note that node names are returned – their original and primary identifiers – and that these may be different from the node labels that you see when you look at the graph in Cytoscape.

Author(s)

Paul Shannon

Examples

```
cw <- CytoscapeWindow ('getAllNodes.test', graph=makeSimpleGraph())  
getAllNodes (cw)  
# [1] "C" "B" "A"
```

```
getArrowShapes      getArrowShapes
```

Description

Retrieve the names of the currently supported 'arrows' – the decorations can (optionally) appear at the ends of edges, adjacent to the nodes they connect, and conveying information about the nature of the nodes' relationship. of strings.

Usage

```
getArrowShapes(obj)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.

Value

A list of character strings, e.g., 'WHITE_DIAMOND', 'BLACK_T'

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
getArrowShapes (cy)
# [1] "No Arrow" "Diamond" "Delta" "Arrow" "T" "Circle" "Half Arrow Top" "Half Arrow
```

```
getAttributeClassNames
      getAttributeClassNames
```

Description

Retrieve the names of the recognized and supported names for the class of any node or edge attribute. Two or three options are provided for each of the basic types, with the intention that you can use names that seem natural to you, and RCytoscape will recognize them.

Usage

```
getAttributeClassNames(obj)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.

Value

A list of character strings group, e.g., "floating|numeric|double", "integer|int", "string|char|character"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
getAttributeClassNames (cy)
# [1] "floating|numeric|double" "integer|int" "string|char|character"
```

getCenter

getCenter

Description

This method returns the coordinates of the current center of the visible Cytoscape canvas, or drawing surface. The initial values are a little unpredictable, but seem to be on the order of 100 for both x and y.

Usage

```
getCenter (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A names list, x and y.

Author(s)

Paul Shannon

See Also

getCenter getZoom setZoom

Examples

```
window.title = 'getCenter demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (getCenter (cw))
```

```
getDefaultBackgroundColor  
getDefaultBackgroundColor
```

Description

Retrieve the default color for the next CytoscapeWindow.

Usage

```
getDefaultBackgroundColor(obj, vizmap.style.name)
```

Arguments

obj a CytoscapeConnectionClass object.
vizmap.style.name a character object, 'default' by default

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()  
print (getDefaultBackgroundColor (cy)) # "java.awt.Color[r=204,g=204,b=255]"
```

```
getDefaultEdgeReverseSelectionColor  
getDefaultEdgeReverseSelectionColor
```

Description

Retrieve the default color used to display selected edges.

Usage

```
getDefaultEdgeReverseSelectionColor(obj, vizmap.style.name)
```

Arguments

obj a CytoscapeConnectionClass object.
vizmap.style.name a character object, 'default' by default

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (getDefaultEdgeReverseSelectionColor (cy)) # "java.awt.Color[r=0,g=255,b=0]"
```

getDefaultEdgeSelectionColor
getDefaultEdgeSelectionColor

Description

Retrieve the default color used to display selected edges.

Usage

```
getDefaultEdgeSelectionColor(obj, vizmap.style.name)
```

Arguments

obj a CytoscapeConnectionClass object.
vizmap.style.name a character object, 'default' by default

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (getDefaultEdgeSelectionColor (cy)) # "java.awt.Color[r=255,g=0,b=0]"
```

```
getDefaultNodeReverseSelectionColor
    getDefaultNodeReverseSelectionColor
```

Description

Retrieve the default color used to display selected nodes.

Usage

```
getDefaultNodeReverseSelectionColor(obj, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`vizmap.style.name` a character object, 'default' by default

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (getDefaultNodeReverseSelectionColor (cy)) # "java.awt.Color[r=0,g=255,b=0]"
```

```
getDefaultNodeSelectionColor
    getDefaultNodeSelectionColor
```

Description

Retrieve the default color used to display selected nodes.

Usage

```
getDefaultNodeSelectionColor(obj, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`vizmap.style.name` a character object, 'default' by default

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (getDefaultNodeSelectionColor (cy)) # "java.awt.Color[r=0,g=255,b=0]"
```

```
getDirectlyModifiableVisualProperties
      getDirectlyModifiableVisualProperties
```

Description

Retrieve the names of those visual attributes which can be set directly, bypassing vizmap rules.

Usage

```
getDirectlyModifiableVisualProperties(obj)
```

Arguments

obj a *CytoscapeConnectionClass* object.

Value

A list of about 60 character strings, e.g., "Node Color" and "Edge Font Size"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
getDirectlyModifiableVisualProperties (cy)
# [1] "Node Color"                    "Node Border Color"                    "Node Line
# [5] "Node Size"                    "Node Width"                    "Node Heigh
# ...
```

getEdgeAttribute *getEdgeAttribute*

Description

Node and edge attributes are usually added to a Cytoscape network by defined them on the graph used to construct a CytoscapeWindow. The small family of methods described here, however, provide another avenue for adding an edge attribute, for learning which are currently defined, and for deleting and edge attribute.

Note that edge (and node) attributes are defined, not just for a specific, single CytoscapeWindow, but for an entire Cytoscape application session. Thus if you have two nodes (or edges) with the same ID (the same name) in two different windows, adding a node attribute results in both nodes having that attribute.

Usage

```
getEdgeAttribute(obj, edge.name, attribute.name)
```

Arguments

obj	a CytoscapeConnectionClass object or CytoscapeWindow object.
edge.name	a character string specifying the Cytoscape-style name of an edge.
attribute.name	a character string, the name of the attribute you wish to retrieve.

Value

The attribute in question, which may be of any scalar type.

Author(s)

Paul Shannon

See Also

getEdgeAttributeNames deleteEdgeAttribute

Examples

```
window.name = 'demo.getEdgeAttribute'
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())
setDefaultEdgeLineWidth (cw, 5);
displayGraph (cw)
redraw (cw)
layout (cw)

score.bc = getEdgeAttribute (cw, "B (synthetic lethal) C", 'score')
print (paste ("should be -12: ", score.bc))
```

```
getEdgeAttributeNames  
    getEdgeAttributeNames
```

Description

Node and edge attributes belong to the Cytoscape session as a whole, not to a particular window. Use this method to find out the name of the currently defined edge attributes.

Usage

```
getEdgeAttributeNames (obj)
```

Arguments

obj a CytoscapeConnectionClass object or CytoscapeWindow object.

Value

A list of names.

Author(s)

Paul Shannon

See Also

getEdgeAttribute deleteEdgeAttribute getNodeAttributeNames

Examples

```
cy = CytoscapeConnection ()  
print (getEdgeAttributeNames (cy))
```

```
getEdgeCount            getEdgeCount
```

Description

Reports the number of the edges in the current graph.

Usage

```
getEdgeCount (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A list of character strings.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getEdgeCount.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
# in Cytoscape, interactively select two nodes, or
getEdgeCount (cw)
# [1] 3
```

getFirstNeighbors *getFirstNeighbors*

Description

Returns a non-redundant ('uniquified') list of all of the first neighbors of the supplied list of nodes.

Usage

```
getFirstNeighbors(obj, node.names)
```

Arguments

obj a CytoscapeWindowClass object.
node.names a String list object.

Value

A list of node names.

Author(s)

Paul Shannon

See Also

selectNodes selectFirstNeighborsOfSelectedNodes

Examples

```
cw <- new.CytoscapeWindow ('getFirstNeighbors.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (getFirstNeighbors (cw, 'A'))
selectNodes (cw, getFirstNeighbors (cw, 'A')) # note that A is not selected
```

`getGraph`*getGraph*

Description

Returns the bioconductor graph object which belongs to the specified CytoscapeWindow object

Usage

```
getGraph(obj)
```

Arguments

`obj` a CytoscapeWindowClass object.

Value

A graph object.

Author(s)

Paul Shannon

Examples

```
cw <- CytoscapeWindow ('getGraph.test', graph=makeSimpleGraph())
print (getGraph (cw))
```

`getGraphFromCyWindow`*getGraphFromCyWindow*

Description

Returns the Cytoscape network as a bioconductor graph

Usage

```
getGraphFromCyWindow(obj, window.title)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`window.title` a string object.

Value

A bioconductor graph object.

Author(s)

Paul Shannon

Examples

```

cw <- CytoscapeWindow ('getGraphFromCyWindow.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw)
redraw (cw)
g.cy <- getGraphFromCyWindow (cw, 'getGraphFromCyWindow.test')
print (g.cy) # 3 nodes, 3 edges

```

getLayoutNameMapping

getLayoutNameMapping

Description

The Cytoscape 'Layout' menu lists many layout algorithms, but the names presented there are different from the names by which these algorithms are known to layout method. This method returns a named list in which the names are from the GUI, and the values identify the names you must use to choose an algorithms in the programmatic interface.

Usage

```
getLayoutNameMapping(obj)
```

Arguments

`obj` a CytoscapeConnectionClass object.

Value

A named list of strings.

Author(s)

Paul Shannon

See Also

layout getLayoutNames getLayoutPropertyNames getLayoutPropertyType getLayoutPropertyValue
setLayoutProperties

Examples

```

cy <- CytoscapeConnection ()
layout.name.map <- getLayoutNameMapping (cy)
print (head (names (layout.name.map), n=3))
# [1] "Inverted Self-Organizing Map Layout" "Group Attributes Layout" "MOEN Layout"
print (head (as.character (layout.name.map), n=3))
# [1] "isom" "attributes-layout" "jgraph-moen"

```

getLayoutNames *getLayoutNames*

Description

Retrieve the names of the currently supported layout algorithms. These may be used in subsequent calls to the 'layout' function. Note that some of the more attractive layout options, from yFiles, cannot be run except from the user interface; their names do not appear here.

Usage

```
getLayoutNames(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

A list of character strings, e.g., "jgraph-circle" "attribute-circle" "jgraph-annealing"

Author(s)

Paul Shannon

See Also

getLayoutNameMapping getLayoutNames getLayoutPropertyName getLayoutPropertyType getLayoutPropertyValue setLayoutProperties

Examples

```
cy <- CytoscapeConnection ()
getLayoutNames (cy)
# [1] "jgraph-circle" "attribute-circle" "jgraph-annealing" ...
```

getLayoutPropertyName
getLayoutPropertyName

Description

Returns a list of the tunable properties for the specified layout.

Usage

```
getLayoutPropertyName(obj, layout.name)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.
`layout.name` a string object.

Value

A named list of strings.

Author(s)

Paul Shannon

See Also

`layout` `getLayoutNames` `getLayoutNameMapping` `getLayoutPropertyType` `getLayoutPropertyValue`
`setLayoutProperties`

Examples

```
cy <- CytoscapeConnection ()
prop.names <- getLayoutPropertyNames (cy, 'isom')
print (prop.names)
# "maxEpoch" "sizeFactor" "radiusConstantTime" "radius" "minRadius" "initialAdapt
```

```
getLayoutPropertyType
      getLayoutPropertyType
```

Description

Returns a list of the tunable properties for the specified layout.

Usage

```
getLayoutPropertyType(obj, layout.name, property.name)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.
`layout.name` a string object.
`property.name`
a string object.

Value

A character string specifying the type. These types do not always necessarily to R types.

Author(s)

Paul Shannon

See Also

layout getLayoutNames getLayoutNameMapping getLayoutPropertyNames getLayoutPropertyValue
setLayoutProperties

Examples

```
cy <- CytoscapeConnection ()
prop.names <- getLayoutPropertyNames (cy, 'isom')
print (prop.names)
# "maxEpoch" "sizeFactor" "radiusConstantTime" "radius" "minRadius" "initialAdapt
sapply (prop.names, function (pn) getLayoutPropertyType (cy, 'isom', pn))
# maxEpoch sizeFactor radiusConstantTime radius minRadius initialA
# "INTEGER" "INTEGER" "INTEGER" "INTEGER" "INTEGER"
```

```
getLayoutPropertyValue
      getLayoutPropertyValue
```

Description

Returns the appropriately typed value of the specified tunable property for the specified layout.

Usage

```
getLayoutPropertyValue(obj, layout.name, property.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`layout.name` a string object.
`property.name` a string object.

Value

Typically an integer, numeric or string value, the current setting of this property for this layout.

Author(s)

Paul Shannon

See Also

layout getLayoutNames getLayoutNameMapping getLayoutPropertyNames getLayoutPropertyType
setLayoutProperties

Examples

```

cy <- CytoscapeConnection ()
prop.names <- getLayoutPropertyNames (cy, 'isom')
print (prop.names)
# "maxEpoch" "sizeFactor" "radiusConstantTime" "radius" "minRadius" "initialAdapt
sapply (prop.names, function (pn) getLayoutPropertyValue (cy, 'isom', 'coolingFactor'))
#          maxEpoch          sizeFactor radiusConstantTime          radius          m
#              2              2              2              2              2

```

getLineStylees *getLineStylees*

Description

Retrieve the names of the currently supported line types – values which can be used to render edges, and thus can be used in calls to 'setEdgeLineStyleRule'

Usage

```
getLineStylees (obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

A list of character strings, e.g., 'SOLID', 'DOT'

Author(s)

Paul Shannon

Examples

```

cy <- CytoscapeConnection ()
getLineStylees (cy)
# [1] "SOLID" "LONG_DASH" "EQUAL_DASH" ...

```

getNodeAttribute *getNodeAttribute*

Description

Node and node attributes are usually added to a Cytoscape network by defined them on the graph used to construct a CytoscapeWindow. The small family of methods described here, however, provide another avenue for adding an node attribute, for learning which are currently defined, and for deleting and node attribute.

Note that node (and node) attributes are defined, not just for a specific, single CytoscapeWindow, but for an entire Cytoscape application session. Thus if you have two nodes (or nodes) with the same ID (the same name) in two different windows, adding a node attribute results in both nodes having that attribute.

Usage

```
getNodeAttribute(obj, node.name, attribute.name)
```

Arguments

`obj` a CytoscapeConnectionClass object or CytoscapeWindow object.
`node.name` a character string specifying the Cytoscape-style name of a node.
`attribute.name` a character string, the name of the attribute you wish to retrieve.

Value

The attribute in question, which may be of any scalar type.

Author(s)

Paul Shannon

See Also

getNodeAttributeNames deleteNodeAttribute

Examples

```
window.name = 'demo.getNodeAttribute'  
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())  
displayGraph (cw)  
redraw (cw)  
layout (cw)  
  
count.B = getNodeAttribute (cw, "B", 'count')
```

```
getNodeAttributeNames  
getNodeAttributeNames
```

Description

Node and node attributes belong to the Cytoscape session as a whole, not to a particular window. Use this method to find out the name of the currently defined node attributes.

Usage

```
getNodeAttributeNames (obj)
```

Arguments

`obj` a CytoscapeConnectionClass object or CytoscapeWindow object.

Value

A list of names.

Author(s)

Paul Shannon

See Also

`getNodeAttribute` `deleteNodeAttribute` `getEdgeAttributeNames`

Examples

```
cy = CytoscapeConnection ()
print (getNodeAttributeNames (cy))
```

<code>getNodeCount</code>	<i>getNodeCount</i>
---------------------------	---------------------

Description

Reports the number of nodes in the current graph.

Usage

```
getNodeCount (obj)
```

Arguments

`obj` a `CytoscapeWindowClass` object.

Value

A list of character strings.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getNodeCount.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
# in Cytoscape, interactively select two nodes, or
getNodeCount (cw)
# [1] 3
```

getNodeShapes *getNodeShapes*

Description

Retrieve the names of the currently supported node shapes, which can then be used in calls to setNodeShapeRule and setDefaultVizMapValue

Usage

```
getNodeShapes(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

A list of character strings, e.g., 'trapezoid', 'ellipse', 'rect'

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
getNodeShapes(cy)
# "trapezoid" "round_rect" "ellipse" "triangle" "rect_3d" "diamond" "parallelogram"
```

getPosition *getPosition*

Description

Get the position of the specified nodes on the CytoscapeWindow canvas. Useful in retrieving the current position of nodes in the window.

Usage

```
getPosition(obj, node.names)
```

Arguments

obj a CytoscapeWindowClass object.
node.names a list of strings, the names of nodes to select.

Value

A names list of x,y pairs; names are the identifiers of nodes supplied when the graph was created.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getPosition.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw)
getPosition (cw, c ('A', 'B', 'C'))
```

```
getSelectedEdgeCount
getSelectedEdgeCount
```

Description

Returns the number of edge currently selected.

Usage

```
getSelectedEdgeCount (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

An integer.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getSelectedEdgeCount.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
clearSelection (cw)
getSelectedEdgeCount (cw) # should be 0
# in Cytoscape, interactively select an edge, or programmatically (doesn't work yet)
# selectEdges (cwe, "A (phosphorylates) B")
getSelectedEdgeCount (cw)
# should be 1
```

getSelectedEdges *getSelectedEdges*

Description

Retrieve the identifiers of all the edges selected in the current graph.

Usage

```
getSelectedEdges (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A list of character strings.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getSelectedEdges.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
# in Cytoscape, interactively select two edges
# doesn't work yet: selectEdges (cwe, "A (phosphorylates) B")
getSelectedEdges (cw)
```

getSelectedNodeCount
getSelectedNodeCount

Description

Returns the number of node currently selected.

Usage

```
getSelectedNodeCount (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

An integer.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getSelectedNodeCount.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
# in Cytoscape, interactively select two nodes, or
selectNodes (cw, c ('A','B'))
getSelectedNodeCount (cw)
# [1] 2
```

getSelectedNodes *getSelectedNodes*

Description

Retrieve the identifiers of all the nodes selected in the current graph.

Usage

```
getSelectedNodes (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A list of character strings.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('getSelectedNodes.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
# in Cytoscape, interactively select two nodes, or
selectNodes (cw, c ('A','B'))
getSelectedNodes (cw)
# [1] "A" "B"
```

`getViewCoordinates` *getViewCoordinates*

Description

This method returns the four numbers (top.x, top.y, bottom.x, bottom.y) which implicitly specify the bounds of the current window.

Usage

```
getViewCoordinates(obj)
```

Arguments

`obj` a `CytoscapeWindowClass` object.

Value

A named list of four numbers, with these names: top.x, top.y, bottom.x, bottom.y

Author(s)

Paul Shannon

See Also

`getViewCoordinates` `getZoom` `setZoom`

Examples

```
window.title = 'getViewCoordinates demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (getViewCoordinates (cw))
```

`getVisualStyleNames`*getVisualStyleNames*

Description

Cytoscape provides a number of canned visual styles, to which you may add your own. Use this method to find out the names of those which are currently defined.

Usage

```
getVisualStyleNames(obj)
```

Arguments

`obj` a `CytoscapeConnectionClass` object or `CytoscapeWindow` object.

Value

a list of character strings.

Author(s)

Paul Shannon

See Also

`copyVisualStyle` `setVisualStyle`

Examples

```
cy = CytoscapeConnection ()
print (getVisualStyleNames (cy))
```

`getWindowCount` *getWindowCount*

Description

Returns the number of windows which currently exist in the Cytoscape Desktop.

Usage

```
getWindowCount (obj)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.

Value

An integer.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
count.at.start = getWindowCount (cy)
cw2 <- CytoscapeWindow ('getWindowCount.test1', graph=makeSimpleGraph())
cw3 <- CytoscapeWindow ('getWindowCount.test2', graph=makeSimpleGraph())
getWindowCount (cy)
# should be two greater than 'count.at.start'
```

getWindowID	<i>getWindowID</i>
-------------	--------------------

Description

Windows in Cytoscape have both a title and an identifier. The title is useful for human readers; the identifier is used by Cytoscape internals, and is sometimes useful to obtain. This method returns the identifier associated with the window title.

Usage

```
getWindowID(obj, window.title)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`window.title` a string.

Value

The identifier (id) of a window, which is always a string – even if the identifier appears to be an integer.

Author(s)

Paul Shannon

See Also

`getWindowList`

Examples

```
cy <- CytoscapeConnection ()
cw <- new.CytoscapeWindow ('getWindowID.test', graph=makeSimpleGraph())
displayGraph (cw)
getWindowID (cy, 'getWindowID.test')
```

getWindowList	<i>getWindowList</i>
---------------	----------------------

Description

Returns a named list of windows in the current Cytoscape Desktop.

Usage

```
getWindowList(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

A named list, in which the values are the titles of the windows; the names of the list are integers.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
getWindowList (cy)
```

getZoom

getZoom

Description

This method returns the zoom level of the CytoscapeWindow. A value of 1.0 typically renders the graph with an ample margin. A call to fitContent produces a zoom level of about 1.5.

Usage

```
getZoom(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

A names list, x and y.

Author(s)

Paul Shannon

See Also

setZoom getCenter setCenter getViewCoordinates fitContent

Examples

```
window.title = 'getZoom demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
print (getZoom (cw))
```

hideAllPanels	<i>hideAllPanels</i>
---------------	----------------------

Description

All panels will be hidden, and no longer visible in the Cytoscape Desktop of, if floating, elsewhere on the computer screen.

Usage

```
hideAllPanels(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

Nothing.

Author(s)

Paul Shannon

See Also

floatPanel dockPanel hidePanel

Examples

```
cy <- CytoscapeConnection ()
hideAllPanels (cy)
```

hideNodes	<i>hideNodes</i>
-----------	------------------

Description

Hide (but do not delete) the currently nodes. Highly recommended: save the current layout before hiding, since 'unhideAll' will, in addition to restoring hidden nodes to view, will place them in unpredictable locations on the screen.

Usage

```
hideNodes(obj, node.names)
```

Arguments

obj a CytoscapeWindowClass object.
node.names a character list object.

Value

None.

Author(s)

Paul Shannon

See Also

hideSelectedNodes unhideAll saveLayout restoreLayout

Examples

```
cw <- new.CytoscapeWindow ('hideNodes.test', graph=makeSimpleGraph())
redraw (cw)
layout (cw, 'jgraph-spring')
# saveLayout (cw, 'layout.tmp.RData')
hideNodes (cw, c ('A', 'B'))
unhideAll (cw)
# restoreLayout (cw, 'layout.tmp.RData')
```

hidePanel

hidePanel

Description

The specified panel will be hidden, and no longer visible in the Cytoscape Desktop of, if floating, elsewhere on the computer screen. The `panelName` parameter is very flexible: a match is defined as a case-independent match of the supplied `panelName` to any starting characters in the actual `panelName`. Thus, 'd' and 'DA' both identify 'Data Panel'.

Usage

```
hidePanel(obj, panelName)
```

Arguments

<code>obj</code>	a <code>CytoscapeConnectionClass</code> object.
<code>panelName</code>	a character string, providing a partial or complete case-independent match to the start of the name of an actual panel.

Value

Nothing.

Author(s)

Paul Shannon

See Also

floatPanel dockPanel hideAllPanels

Examples

```
cy <- CytoscapeConnection ()
hidePanel (cy, 'Control Panel')
# or
hidePanel (cy, 'c')
```

hideSelectedEdges *hideSelectedEdges*

Description

Hide (but do not delete) the currently selected edges. 'Unhide' is supposed to return them to view, but this is broken in Cytoscape 2.7.

Usage

```
hideSelectedEdges (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

unhideAll

Examples

```
cw <- new.CytoscapeWindow ('hideSelectedEdges.test', graph=makeSimpleGraph())
# selectEdges (cw, 'B (synthetic lethal) C')
hideSelectedEdges (cw)
unhideAll (cw)
# alas, Cytoscape requires that you render these edges, and redo the
# layout, so that they are visible again
redraw (cw)
layout (cw, 'jgraph-spring')
```

hideSelectedNodes *hideSelectedNodes*

Description

Hide (but do not delete) the currently selected nodes. We strongly recommend that you save the current layout before hiding any nodes: 'unhideAll' often places restored nodes in unpredictable positions.

Usage

```
hideSelectedNodes(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

unhideAll

Examples

```
cw <- new.CytoscapeWindow ('hideSelectedNodes.test', graph=makeSimpleGraph())
# saveLayout (cw, 'layout.tmp.RData')
selectNodes (cw, c ('A', 'B'))
hideSelectedNodes (cw)
unhideAll (cw)
# restoreLayout (cw, 'layout.tmp.RData')
```

initEdgeAttribute *initEdgeAttribute*

Description

Create the edge attribute slot that the Bioconductor graph class requires, including a default value, and then specifying what the base type (or 'class') is – 'char', 'integer', or 'numeric' – which is needed by RCytoscape. This method converts these standard R data type names, to the forms needed by Cytoscape.

Usage

```
initEdgeAttribute(graph, attribute.name, attribute.type, default.value)
```

Arguments

graph a Bioconductor graph object.
 attribute.name a string, the name of the new edge attribute.
 attribute.type a string, either 'char', 'integer', or 'numeric'
 default.value something sensible, of the right type

Value

Returns the modified graph.

Author(s)

Paul Shannon

See Also

initNodeAttribute makeSimpleGraph

Examples

```
g = new ('graphNEL', edgemode='directed')
g = initEdgeAttribute (g, 'edgeType', 'char', 'associates with')
```

initNodeAttribute *initNodeAttribute*

Description

Create the node attribute slot that the Bioconductor graph class requires, including a default value, and then specifying what the base type (or 'class') is – 'char', 'integer', or 'numeric' – which is needed by RCytoscape. This method converts these standard R data type names, to the forms needed by Cytoscape.

Usage

```
initNodeAttribute(graph, attribute.name, attribute.type, default.value)
```

Arguments

graph a Bioconductor graph object.
 attribute.name a string, the name of the new node attribute.
 attribute.type a string, either 'char', 'integer', or 'numeric'
 default.value something sensible, of the right type

Value

Returns the modified graph.

Author(s)

Paul Shannon

See Also

initEdgeAttribute makeSimpleGraph

Examples

```
g = new ('graphNEL', edgemode='directed')
g = initNodeAttribute (g, 'lfc', 'numeric', 1.0)
```

invertEdgeSelection

invertEdgeSelection

Description

Select the specified nodes.

Usage

```
invertEdgeSelection(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

clearSelection invertNodeSelection

Examples

```
cw <- new.CytoscapeWindow ('invertEdgeSelection demo', graph=makeSimpleGraph())
# all edges should be selected, since none were before
invertEdgeSelection (cw)
redraw (cw)
# a richer test will be to programmatically select edges, but that
# does not work yet (pshannon, 13 jan 2011)
```

```
invertNodeSelection  
    invertNodeSelection
```

Description

Select the specified nodes.

Usage

```
invertNodeSelection(obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

clearSelection invertNodeSelection

Examples

```
cw <- new.CytoscapeWindow ('invertNodeSelection demo', graph=makeSimpleGraph())  
  # all nodes should be selected, since none were before  
selectNodes (cw, 'A')  
invertNodeSelection (cw)  
redraw (cw)  
  # a richer test will be to programmatically select nodes, but that  
  # does not work yet (pshannon, 13 jan 2011)
```

```
layout            layout
```

Description

Layout the current graph according to the specified algorithm.

Usage

```
layout(obj, layout.name='jgraph-spring')
```

Arguments

`obj` a CytoscapeWindowClass object.
`layout.name` a string, one of the values returned by `getLayoutNames`, 'jgraph-spring' by default.

Value

Nothing.

Author(s)

Paul Shannon

See Also

`getNodeShapes`

Examples

```
cw <- new.CytoscapeWindow ('layout.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw) # applies default vizmap (rendering) rules, plus any you
            # have specified
```

`lockNodeDimensions` *lockNodeDimensions*

Description

Select the specified nodes.

Usage

```
lockNodeDimensions(obj, new.state, visual.style.name='default')
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.state` a boolean object, TRUE or FALSE
`visual.style.name` a string object, naming the visual style whose 'locked' you wish to change. Defaults to 'default'

Value

None.

Author(s)

Paul Shannon

See Also

setNodeSizeDirect setNodeWidthDirect setNodeHeightDirect

Examples

```

cw <- new.CytoscapeWindow ('lockNodeDimensions demo', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw)
redraw (cw)
lockNodeDimensions (cw, FALSE)
setNodeWidthDirect (cw, 'A', 100)
setNodeHeightDirect (cw, 'A', 50)

```

makeRandomGraph *makeRandomGraph*

Description

Create a random undirected graphNEL, useful for testing. Two default edge attributes are added, for demonstration purposes.

Usage

```
makeRandomGraph (node.count=12, seed=123)
```

Arguments

node.count the number of nodes you wish to see in the graph
seed an integer which, when supplied, allows reproducibility

Value

Returns (by default) a 12-node, rather dense undirected graph, with some attributes on the nodes and edges.

Author(s)

Paul Shannon

Examples

```

g = makeRandomGraph (node.count=12, seed=123)

## The function is currently defined as
function (node.count = 12, seed = 123)
{
  set.seed(seed)
  node.names = as.character(1:node.count)
  g = randomGraph(node.names, M <- 1:2, p = 0.6)
  attr(edgeDataDefaults(g, attr = "weight"), "class") = "DOUBLE"
  edgeDataDefaults(g, "pmid") = "9988778899"
  attr(edgeDataDefaults(g, attr = "pmid"), "class") = "STRING"
}

```

```

    return(g)
}

```

```

makeSimpleGraph      makeSimpleGraph

```

Description

A 3-node, 3-edge graph, with some biological trappings, useful for demonstrations.

Usage

```
makeSimpleGraph()
```

Value

Returns a 3-node, 3-edge graph, with some attributes on the nodes and edges.

Author(s)

Paul Shannon

Examples

```

g = makeSimpleGraph ()

## The function is currently defined as
function ()
{
  g = new("graphNEL", edgemode = "directed")
  nodeDataDefaults(g, attr = "type") = "undefined"
  attr(nodeDataDefaults(g, attr = "type"), "class") = "STRING"
  nodeDataDefaults(g, attr = "lfc") = 1
  attr(nodeDataDefaults(g, attr = "lfc"), "class") = "DOUBLE"
  nodeDataDefaults(g, attr = "label") = "default node label"
  attr(nodeDataDefaults(g, attr = "label"), "class") = "STRING"
  nodeDataDefaults(g, attr = "count") = "0"
  attr(nodeDataDefaults(g, attr = "count"), "class") = "INTEGER"
  edgeDataDefaults(g, attr = "edgeType") = "undefined"
  attr(edgeDataDefaults(g, attr = "edgeType"), "class") = "STRING"
  edgeDataDefaults(g, attr = "score") = 0
  attr(edgeDataDefaults(g, attr = "score"), "class") = "DOUBLE"
  edgeDataDefaults(g, attr = "misc") = ""
  attr(edgeDataDefaults(g, attr = "misc"), "class") = "STRING"
  g = graph::addNode("A", g)
  g = graph::addNode("B", g)
  g = graph::addNode("C", g)
  nodeData(g, "A", "type") = "kinase"
  nodeData(g, "B", "type") = "transcription factor"
  nodeData(g, "C", "type") = "glycoprotein"
  nodeData(g, "A", "lfc") = "-3.0"
  nodeData(g, "B", "lfc") = "0.0"
  nodeData(g, "C", "lfc") = "3.0"
}

```

```

nodeData(g, "A", "count") = "2"
nodeData(g, "B", "count") = "30"
nodeData(g, "C", "count") = "100"
nodeData(g, "A", "label") = "Gene A"
nodeData(g, "B", "label") = "Gene B"
nodeData(g, "C", "label") = "Gene C"
g = graph::addEdge("A", "B", g)
g = graph::addEdge("B", "C", g)
g = graph::addEdge("C", "A", g)
edgeData(g, "A", "B", "edgeType") = "phosphorylates"
edgeData(g, "B", "C", "edgeType") = "synthetic lethal"
edgeData(g, "A", "B", "score") = 35
edgeData(g, "B", "C", "score") = -12
return(g)
}

```

msg

msg

Description

Display the supplied string in the Cytoscape Desktop status bar

Usage

```
msg(obj, string)
```

Arguments

obj	a CytoscapeConnectionClass object.
string	a char, an arbitrary string, which can be used to inform the user of things they may wish to know

Value

Nothing.

Author(s)

Paul Shannon

See Also

clearMsg

Examples

```

cy <- CytoscapeConnection ()
msg (cy, 'this message will appear in the Cytoscape Desktop status bar, which is found

```

```
new.CytoscapeWindow
      new.CytoscapeWindow
```

Description

The constructor for the CytoscapeWindowClass

Usage

```
new.CytoscapeWindow(title, graph = new("graphNEL", edgemode='directed'), host =
```

Arguments

title	A character string, this is the name you will see on the Cytoscape network window. Multiple windows with the same name are not permitted.
graph	A Bioconductor graph.
host	Defaults to 'localhost', this is the domain name of a machine which is running Cytoscape with the appropriate XMLRPC server plugin.
rpcPort	Defaults to 9000, this may be any port to which the CytoscapeRPC server is listening.
create.window	Defaults to TRUE, but if you want a CytoscapeWindow just to call what in Java we would call 'class methods' – getWindowList () for instance, a CytoscapeWindow without an actual window can be useful.

Value

An object of the CytoscapeWindow Class.

Author(s)

Paul Shannon

See Also

CytoscapeWindow existing.CytoscapeWindow

Examples

```
cw <- new.CytoscapeWindow ('new.demo', new ('graphNEL'))
```

noa	<i>noa</i>
-----	------------

Description

Retrieve the value of the specified node attribute for every node in the graph.

Usage

```
noa(graph, node.attribute.name)
```

Arguments

```
graph           typically, a bioc graphNEL)
node.attribute.name
                 a character string
```

Value

A list, the contents of which are the attribute values, the names of which are the names of the nodes.

Author(s)

Paul Shannon

See Also

noa.names

Examples

```
g <- makeSimpleGraph ()
noa (g, 'type')
#           A.A           B.B           C.C
#           "kinase" "transcription factor" "glycoprotein"
```

noa.names	<i>noa.names</i>
-----------	------------------

Description

Retrieve the names of the node attributes in the specified graph.

Usage

```
noa.names(graph)
```

Arguments

```
graph
```

Author(s)

Paul Shannon

See Also

noa, eda, eda.names

Examples

```
g <- makeSimpleGraph()
noa.names (g)
# [1] "type" "lfc" "label" "count"
```

ping

ping

Description

Test the connection to Cytoscape.

Usage

```
ping(obj)
```

Arguments

obj a CytoscapeConnectionClass object.

Value

"It works!"

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
ping (cy)
# "It works!"
```

raiseWindow	<i>raiseWindow</i>
-------------	--------------------

Description

Raise this window to the top on the Cytoscape desktop, so that it can be seen.

Usage

```
raiseWindow(obj, window.title=NA)
```

Arguments

`obj` a CytoscapeConnectionClass object, or its subclass, CytoscapeWindowClass.
`window.title` a string.

Value

None.

Author(s)

Paul Shannon

See Also

resizeWindow

Examples

```
cw <- new.CytoscapeWindow ('raiseWindow.test', graph=makeSimpleGraph())  
raiseWindow (cw)
```

redraw	<i>redraw</i>
--------	---------------

Description

Asks Cytoscape to redraw all nodes and edges, applying the vizmap rules.

Usage

```
redraw(obj)
```

Arguments

`obj` a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

displayGraph layout

Examples

```
cw <- new.CytoscapeWindow ('redraw.test', graph=makeSimpleGraph())
redraw (cw)
```

restoreLayout	<i>restoreLayout</i>
---------------	----------------------

Description

restore the current layout (that is, node positions) from the information saved in the supplied filename.

Usage

```
restoreLayout(obj, filename)
```

Arguments

obj	a CytoscapeWindowClass object.
filename	a string

Value

Nothing.

Author(s)

Paul Shannon

See Also

saveLayout

Examples

```
cw <- new.CytoscapeWindow ('restoreLayout.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
saveLayout (cw, 'layout.RData')
layout (cw, 'jgraph-circle')
restoreLayout (cw, 'layout.RData')
```

saveImage	<i>saveImage</i>
-----------	------------------

Description

Write an image of the specified type to the specified file, at the specified scaling factor. Note: the file is written to the file system of the computer upon which Cytoscape is running, not R – in those cases where they are different.

Usage

```
saveImage(obj, file.name, image.type, scale)
```

Arguments

obj	a CytoscapeWindowClass object.
file.name	a char object.
image.type	a char object. 'jpeg' is the only image type currently supported
scale	a numeric object. How large (or small) to scale the image.

Value

None.

Author(s)

Paul Shannon

See Also

selectNodes clearSelection

Examples

```
cw <- new.CytoscapeWindow ('saveImage.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
filename = tempfile () # paste (getwd (), 'saveImageTest.jpg', sep='/')
# saveImage (cw, filename, 'jpeg', 2.0) # doesn't yet work reliably at bioc
```

`saveLayout`*saveLayout*

Description

save the current layout (that is, node positions) to the specified file.

Usage

```
saveLayout(obj, filename)
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>filename</code>	a string

Value

Nothing.

Author(s)

Paul Shannon

See Also

`restoreLayout`

Examples

```
cw <- new.CytoscapeWindow ('saveLayout.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
saveLayout (cw, 'layout.RData')
layout (cw, 'jgraph-circle')
restoreLayout (cw, 'layout.RData')
```

`saveNetwork`*saveNetwork*

Description

Write a network of the specified type to the specified file, at the specified scaling factor. Note: the file is written to the file system of the computer upon which Cytoscape is running, not R – in those cases where they are different.

Usage

```
saveNetwork(obj, file.name, format='gml')
```

Arguments

obj a CytoscapeWindowClass object.
file.name a char object.
format a char object. 'gml' is the only type currently supported

Value

None.

Author(s)

Paul Shannon

See Also

saveImage

Examples

```

cw <- new.CytoscapeWindow ('saveNetwork.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

#filename <- sprintf ('%s/%s', tempdir (), 'saveNetworkTest.gml')
#not sure if this will work at bioc
#saveNetwork (cw, filename)
#print (sprintf ('gml file exists? %s', file.exists (filename)))

```

selectEdges

selectEdges

Description

Select the specified edges.

Usage

```
selectEdges(obj, edge.names, preserve.current.selection=TRUE)
```

Arguments

obj a CytoscapeWindowClass object.
edge.names a list of strings, the names of edges to select.
preserve.current.selection
 a logical object.

Value

None.

Author(s)

Paul Shannon

See Also

clearSelection selectEdge getSelectedEdgeCount getSelectedEdges hideSelectedEdges

Examples

```

cw <- new.CytoscapeWindow ('selectEdges.test', graph=makeSimpleGraph())
displayGraph (cw); layout (cw); redraw (cw)
clearSelection (cw)
selectEdges (cw, c ("A (phosphorylates) B", "B (synthetic lethal) C"))
getSelectedEdges (cw)
# more complicated, but more realistic:
#selectEdges (cw, as.character ( cy2.en (g, names (which (eda (g, 'edgeType') == 'phosp

```

```

selectFirstNeighborsOfSelectedNodes
selectFirstNeighborsOfSelectedNodes

```

Description

Expand the selection by adding the first neighbors, in the Cytosape network, of the nodes currently selected (again, in the Cytosape network). The R graph is unchanged

Usage

```
selectFirstNeighborsOfSelectedNodes (obj)
```

Arguments

obj a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

clearSelection getSelectedNodeCount getSelectedNodes hideSelectedNodes getFirstNeighbors

Examples

```

cw <- new.CytoscapeWindow ('selectFirstNeighborsOfSelectedNodes.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw)
clearSelection (cw)
selectNodes (cw, 'A')
selectFirstNeighborsOfSelectedNodes (cw)
print (sort (getSelectedNodes (cw)))
# [1] "A" "B" "C"

```

selectNodes	<i>selectNodes</i>
-------------	--------------------

Description

Select the specified nodes.

Usage

```
selectNodes(obj, node.names, preserve.current.selection=TRUE)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.names` a list of strings, the names of nodes to select.
`preserve.current.selection` a logical object.

Value

None.

Author(s)

Paul Shannon

See Also

`clearSelection` `getSelectedNodeCount` `getSelectedNodes` `hideSelectedNodes`

Examples

```

cw <- new.CytoscapeWindow ('selectNodes.test', graph=makeSimpleGraph())
clearSelection (cw)
selectNodes (cw, c ('A', 'B'))
getSelectedNodes (cw)
# [1] "A" "B"

```

`sendEdges`*sendEdges*

Description

Transfer the edges of the R graph (found in `obj@graph`) to Cytoscape. This method is not recommended for the average user. It is called behind the scenes by `displayGraph`.

Usage

```
sendEdges (obj)
```

Arguments

`obj` a `CytoscapeWindowClass` object.

Value

None.

Author(s)

Paul Shannon

See Also

`displayGraph` `sendNodes`

Examples

```
cw <- new.CytoscapeWindow ('sendEdges.test', graph=makeSimpleGraph())
sendEdges (cw)
```

`sendNodes`*sendNodes*

Description

Transfer the nodes of the R graph (found in `obj@graph`) to Cytoscape. This method is not recommended for the average user. It is called behind the scenes by `displayGraph`.

Usage

```
sendNodes (obj)
```

Arguments

`obj` a `CytoscapeWindowClass` object.

Value

None.

Author(s)

Paul Shannon

See Also

displayGraph sendEdges

Examples

```
cw <- new.CytoscapeWindow ('sendNodes.test', graph=makeSimpleGraph())
sendNodes (cw)
```

setCenter

setCenter

Description

This method can be used to pan and scroll the Cytoscape canvas, which is adjusted (moved) so that the specified x and y coordinates are at the center of the visible window.

Usage

```
setCenter(obj, x, y)
```

Arguments

obj	a CytoscapeWindowClass object.
x	a numeric object.
y	a numeric object.

Value

None.

Author(s)

Paul Shannon

See Also

getCenter getZoom setZoom

Examples

```

window.title = 'setCenter demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
original.center <- getCenter (cw) # named list, "x" and "y". initial values might be
# now pan the display to the left, by setting the the visual center
# to increasing values of x, without changing the location of the
# simple graph
setCenter (cw, 200, 90)
system ('sleep 1')
setCenter (cw, 300, 90)
system ('sleep 1')
setCenter (cw, 400, 90)
system ('sleep 1')
# and now pan back to the original position
setCenter (cw, 300, 90)
system ('sleep 1')
setCenter (cw, 200, 90)
system ('sleep 1')
setCenter (cw, original.center$x, original.center$y)

```

```

setDefaultBackgroundColor
      setDefaultBackgroundColor

```

Description

Retrieve the default color for the next CytoscapeWindow.

Usage

```
setDefaultBackgroundColor(obj, new.color, vizmap.style.name)
```

Arguments

```

obj          a CytoscapeConnectionClass object.
new.color    a character object, in quoted hexadecimal format
vizmap.style.name
              a character object, 'default' by default

```

Value

A character string, eg "java.awt.Color[r=204,g=204,b=255]"

Author(s)

Paul Shannon

Examples

```

cy <- CytoscapeConnection ()
setDefaultBackgroundColor (cy, '#CCCC00')

```

```
setDefaultEdgeColor  
    setDefaultEdgeColor
```

Description

In the specified CytoscapeConnection, stipulate the color for all edges other than those mentioned in a edge color rule.

Usage

```
setDefaultEdgeColor(obj, new.color, vizmap.style.name = "default")
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a String object, a hex string, of the form '#RRGGBB'.
`vizmap.style.name` a String object, if this vizmap style needs to be distinguished from the default type.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultEdgeColor.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultEdgeColor (cw, '#FFFFFF') # white edges  
redraw (cw)
```

```
setDefaultEdgeLineWidth  
    setDefaultEdgeLineWidth
```

Description

In the specified CytoscapeConnection, stipulate the line width, in pixels for all edges.

Usage

```
setDefaultEdgeLineWidth(obj, new.width, vizmap.style.name = "default")
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.width` an integer object, typically from 0 to 5.
`vizmap.style.name`
a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setEdgeColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultEdgeLineWidth.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultEdgeLineWidth (cw, 5)  
redraw (cw)
```

```
setDefaultEdgeReverseSelectionColor  
  setDefaultEdgeReverseSelectionColor
```

Description

Retrieve the default color used to display selected edges.

Usage

```
setDefaultEdgeReverseSelectionColor(obj, new.color, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a character object, in quoted hexadecimal format
`vizmap.style.name`
a character object, 'default' by default

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()  
print (setDefaultEdgeReverseSelectionColor (cy, '#FF0000'))
```

```
setDefaultEdgeSelectionColor  
  setDefaultEdgeSelectionColor
```

Description

Retrieve the default color used to display selected edges.

Usage

```
setDefaultEdgeSelectionColor(obj, new.color, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a character object, in quoted hexadecimal format
`vizmap.style.name`
a character object, 'default' by default

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (setDefaultEdgeSelectionColor (cy, '#FF0000'))
```

```
setDefaultNodeBorderColor
setDefaultNodeBorderColor
```

Description

In the specified CytoscapeConnection, stipulate the color for all nodeBorders other than those mentioned in a node border color rule.

Usage

```
setDefaultNodeBorderColor(obj, new.color, vizmap.style.name = "default")
```

Arguments

```
obj          a CytoscapeConnectionClass object.
new.color    a String object, a hex string, of the form '#RRGGBB'.
vizmap.style.name
              a String object.
```

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeBorderColor.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setDefaultNodeBorderColor (cw, '#FFFFFF') # white borders
redraw (cw)
```

```
setDefaultNodeBorderWidth  
    setDefaultNodeBorderWidth
```

Description

In the specified CytoscapeConnection, stipulate the color for all nodeBorders other than those mentioned in a node border color rule.

Usage

```
setDefaultNodeBorderWidth(obj, new.width, vizmap.style.name = "default")
```

Arguments

obj a CytoscapeConnectionClass object.
new.width a String object, a hex string, of the form '#RRGGBB'.
vizmap.style.name a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeBorderWidth.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultNodeBorderWidth (cw, 5)  
redraw (cw)
```

```
setDefaultNodeColor  
    setDefaultNodeColor
```

Description

In the specified CytoscapeWindow, stipulate the color for all nodes other than those mentioned in a node border color rule.

Usage

```
setDefaultNodeColor(obj, new.color, vizmap.style.name = "default")
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a String object, a hex string, of the form '#RRGGBB'.
`vizmap.style.name`
a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeColor.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultNodeColor (cw, '#8888FF') # light blue  
redraw (cw)
```

```
setDefaultNodeFontSize  
    setDefaultNodeFontSize
```

Description

In the specified CytoscapeWindow, stipulate the color for all nodeBorders other than those mentioned in a node border color rule.

Usage

```
setDefaultNodeFontSize(obj, new.size, vizmap.style.name = "default")
```

Arguments

obj a CytoscapeConnectionClass object.
new.size a String object, a hex string, of the form '#RRGGBB'.
vizmap.style.name a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeFontSize.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultNodeFontSize (cw, 32)  
redraw (cw)
```

```
setDefaultNodeLabelColor  
    setDefaultNodeLabelColor
```

Description

In the specified CytoscapeWindow, stipulate the color for all node labels. There is, at present, no mapping rule for this trait.

Usage

```
setDefaultNodeLabelColor(obj, new.color, vizmap.style.name = "default")
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a String object, a hex string, of the form '#RRGGBB'.
`vizmap.style.name`
a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeLabelColor.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setDefaultNodeLabelColor (cw, '#FFFFFF') # white node labels  
redraw (cw)
```

```
setDefaultNodeReverseSelectionColor  
setDefaultNodeReverseSelectionColor
```

Description

Retrieve the default color used to display selected nodes.

Usage

```
setDefaultNodeReverseSelectionColor(obj, new.color, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a character object, in quoted hexadecimal format
`vizmap.style.name`
a character object, 'default' by default

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()  
print (setDefaultNodeReverseSelectionColor (cy, '#FF0000'))
```

```
setDefaultNodeSelectionColor  
setDefaultNodeSelectionColor
```

Description

Retrieve the default color used to display selected nodes.

Usage

```
setDefaultNodeSelectionColor(obj, new.color, vizmap.style.name)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.color` a character object, in quoted hexadecimal format
`vizmap.style.name`
a character object, 'default' by default

Value

Nothing.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (setDefaultNodeSelectionColor (cy, '#FF0000'))
```

```
setDefaultNodeShape
      setDefaultNodeShape
```

Description

For all CytoscapeWindow's, specify the default node shape.

Usage

```
setDefaultNodeShape(obj, new.shape, vizmap.style.name = "default")
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.shape` a String object, one of the permissible values (see getNodeShapes).
`vizmap.style.name` a String object.

Value

None.

Author(s)

Paul Shannon

See Also

getNodeShapes setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeShape.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
legal.shapes <- getNodeShapes (cw)
# stopifnot ('diamond' %in% legal.shapes)
setDefaultNodeShape (cw, 'diamond')
redraw (cw)
```

setDefaultNodeSize *setDefaultNodeSize*

Description

In the specified CytoscapeConnection, stipulate the color for all nodeBorders other than those mentioned in a node border color rule.

Usage

```
setDefaultNodeSize(obj, new.size, vizmap.style.name = "default")
```

Arguments

obj a CytoscapeConnectionClass object.
new.size a integer object, typically 20 to 100.
vizmap.style.name a String object.

Value

None.

Author(s)

Paul Shannon

See Also

setDefaultNodeShape setDefaultNodeColor setDefaultNodeSize setDefaultNodeColor setDefaultNodeBorderColor setDefaultNodeBorderWidth setDefaultNodeFontSize setDefaultNodeLabelColor setDefaultEdgeLineWidth setEdgeColorRule setNodeBorderColorRule

Examples

```
cw <- new.CytoscapeWindow ('setDefaultNodeSize.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setDefaultNodeSize (cw, 60) # an intermediate value
redraw (cw)
```

```
setEdgeAttributes setEdgeAttributes
```

Description

Transfer the named edge attribute from the the R graph (found in `obj@graph`) to Cytoscape. This method is typically called by `displayGraph`, which will suffice for most users' needs. It transfers the specified edge attributes, for all edges, from the `cw@graph` slot to Cytoscape.

Usage

```
setEdgeAttributes(obj, attribute.name)
```

Arguments

```
obj          a CytoscapeWindowClass object.
attribute.name a string one of the attributes defined on the edges.
```

Value

None.

Author(s)

Paul Shannon

See Also

```
setEdgeAttributesDirect setNodeAttributes setNodeAttributesDirect
```

Examples

```

cw <- new.CytoscapeWindow ('setEdgeAttributes.test', graph=makeSimpleGraph())
attribute.names = eda.names (cw@graph)

for (attribute.name in attribute.names)
  result = setEdgeAttributes (cw, attribute.name)

```

```
setEdgeAttributesDirect
      setEdgeAttributesDirect
```

Description

Transfer the named edge attribute to Cytoscape. This method is required, for instance, if you wish to run a 'movie.' For example, if you have a timecourse experiment, with different values at successive time points of the 'phosphorylates' or 'binds' relationship between two nodes. With an `edgeColor` rule already specified, you can animate the display of the edges in the graph by pumping new values of the edge attributes, and then asking for a redraw. An example of such edge-attribute-driven animation can be found here....[todo].

Usage

```
setEdgeAttributesDirect(obj, attribute.name, attribute.type, edge.names, values)
```

Arguments

`obj` a CytoscapeWindowClass object.

`attribute.name` a string one of the attributes defined on the edges.

`attribute.type` a string from one of these three groups: (floating, numeric, double), (integer, int), (string, char, character). This parameter is required because RCytoscape cannot always infer the type of an attribute.

`edge.names` a list of strings, edge names

`values` a list of objects of the type specified by 'attribute.name', one per edge

Value

None.

Author(s)

Paul Shannon

See Also

setEdgeAttributes setNodeAttributes setNodeAttributesDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeAttributesDirect.test', graph=makeSimpleGraph())
edge.names = as.character (cy2.edge.names (cw@graph))
stopifnot (length (edge.names) == 3)
edge.values = c ('alligator', 'hedgehog', 'anteater')
result = setEdgeAttributesDirect (cw, 'misc', 'string', edge.names, edge.values)

```

setEdgeColorDirect *setEdgeColorDirect*

Description

In the specified CytoscapeWindow, set the color of the specified edge or edges.

Usage

```
setEdgeColorDirect(obj, edge.names, new.value)
```

Arguments

`obj` a CytoscapeWindowClass object.

`edge.names` one ore more String objects, cy2-style edge names.

`new.value` a numeric object, a color in hex notation.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeColorDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeColorDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edge.names = as.character (cy2.edge.names (cw@graph))[1:2]
setEdgeColorDirect (cw, edge.names, '#F833AA')
redraw (cw)

```

setEdgeColorRule *setEdgeColorRule*

Description

Specify how data attributes – for the specified named attribute – is mapped to edge color.

Usage

```
setEdgeColorRule(obj, edge.attribute.name, control.points, colors, mode, default
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>edge.attribute.name</code>	the edge attribute whose values will, when this rule is applied, determine the color of each edge.
<code>control.points</code>	a list of values, either numeric (for interpolate mode) or character strings (for 'lookup' mode).
<code>colors</code>	a list of colors, expressed as hexadecimal RGB, like this: '#FF0000' or '#FA8800'
<code>mode</code>	either 'interpolate' or 'lookup'.
<code>default.color</code>	a String object, expressed in hexadecimal RGB, like this: '#FF0000' or '#FA8800'

Value

None.

Author(s)

Paul Shannon

See Also

setEdgeLineStyleRule setNodeColorRule

Examples

```

cw <- new.CytoscapeWindow ('setEdgeColorRule.test', graph=makeSimpleGraph())
edgeType.values = c ('phosphorylates', 'synthetic lethal', 'undefined')
colors = c ('#FF0000', '#FFFF00', '#00FF00')
setEdgeColorRule (cw, 'edgeType', edgeType.values, colors, mode='lookup')

score.values = c (-15, 0, 40);
colors = c ('#00FF00', '#FFFFFF', '#FF0000')
setEdgeColorRule (cw, 'score', score.values, colors, mode='interpolate')
# now swap the colors around
# now swap the colors
colors = c ('#FF0000', '#FFFFFF', '#00FF00')
setEdgeColorRule (cw, 'score', score.values, colors, mode='interpolate')

redraw (cw)

```

setEdgeFontSizeDirect

setEdgeFontSizeDirect

Description

In the specified CytoscapeWindow, set the opacity of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeFontSizeDirect(obj, edge.names, new.value)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.value	an integer objects, specifying font size in pixels.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeFontSizeDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeFontSizeDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]
for (i in 8:30) {
  setEdgeFontSizeDirect (cw, edge.names, i)
  redraw (cw)
}
setEdgeFontSizeDirect (cw, edge.names, 12)

```

```

setEdgeLabelColorDirect
      setEdgeLabelColorDirect

```

Description

In the specified CytoscapeWindow, set the labelColor of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeLabelColorDirect(obj, edge.names, new.value)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.value	a String object, an RGB color in '#RRGGBB' form.

Value

None.

Author(s)

Paul Shannon

Examples

```

cw <- new.CytoscapeWindow ('setEdgeLabelColorDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]
setEdgeLabelColorDirect (cw, edge.names, '#FF0000')

```

```
redraw (cw)
setEdgeLabelColorDirect (cw, edge.names, '#00FF00')
redraw (cw)
setEdgeLabelColorDirect (cw, edge.names, '#000000')
redraw (cw)
```

setEdgeLabelDirect *setEdgeLabelDirect*

Description

In the specified CytoscapeWindow, set the edgeLabel of the specified edge or edges.

Usage

```
setEdgeLabelDirect(obj, edge.names, new.value)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.value	a string object, the new label.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeEdgeLabelDirect

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLabelDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]
for (i in 1:10) {
  setEdgeLabelDirect (cw, edge.names, 255 - (i * 25))
  redraw (cw)
}
for (i in 1:10) {
  setEdgeLabelDirect (cw, edge.names, i * 25)
  redraw (cw)
}
```

```
setEdgeLabelOpacityDirect  
    setEdgeLabelOpacityDirect
```

Description

In the specified CytoscapeWindow, set the opacity of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeLabelOpacityDirect(obj, edge.names, new.value)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.value	a numeric object, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeLabelOpacityDirect

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLabelOpacityDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]  
for (i in 1:10) {  
  setEdgeLabelOpacityDirect (cw, edge.names, 255 - (i * 25))  
  redraw (cw)  
}  
for (i in 1:10) {  
  setEdgeLabelOpacityDirect (cw, edge.names, i * 25)  
  redraw (cw)  
}
```

setEdgeLabelRule *setEdgeLabelRule*

Description

Specify the edge attribute to be used as the label displayed on each edge. Non-character attributes are converted to strings before they are used.

Usage

```
setEdgeLabelRule(obj, edge.attribute.name)
```

Arguments

`obj` a CytoscapeWindowClass object.
`edge.attribute.name` the edge attribute whose values will, when this rule is applied, determine the edgeLabel on each edge.

Value

None.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLabelRule.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
setEdgeLabelRule (cw, 'edgeType')
```

setEdgeLabelWidthDirect *setEdgeLabelWidthDirect*

Description

In the specified CytoscapeWindow, set the labelWidth of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeLabelWidthDirect(obj, edge.names, new.value)
```

Arguments

obj a CytoscapeWindowClass object.
 edge.names one or more String objects, cy2-style edge names.
 new.value a integer object, pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

setEdgeColorDirect setEdgeLineStyleDirect setEdgeSourceArrowDirect setEdgeTargetArrowDirect
 setEdgeLabelDirect setEdgeFontSizeDirect setEdgeLabelColorDirect setEdgeTooltipDirect setEdge-
 LineWidthDirect setEdgeLineStyleDirect setEdgeSourceArrowShapeDirect setEdgeTargetArrow-
 ShapeDirect setEdgeSourceArrowColorDirect setEdgeTargetArrowColorDirect setEdgeLabelOpac-
 ityDirect setEdgeSourceArrowOpacityDirect setEdgeTargetArrowOpacityDirect setEdgeLabelWidthDi-
 rect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeLabelWidthDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]
for (i in 1:10) {
  setEdgeLabelWidthDirect (cw, edge.names, i)
  redraw (cw)
}
for (i in 10:1) {
  setEdgeLabelWidthDirect (cw, edge.names, i)
  redraw (cw)
}

```

setEdgeLineStyleDirect

setEdgeLineStyleDirect

Description

In the specified CytoscapeWindow, set the `lineStyle` of the specified edge or edges, bypassing all rule mapping. The `getLineStyle` method shows the possible values.

Usage

```
setEdgeLineStyleDirect(obj, edge.names, new.values)
```

Arguments

obj a CytoscapeWindowClass object.
 edge.names one or more String objects, cy2-style edge names.
 new.values one or more String object, from the supported set.

Value

None.

Author(s)

Paul Shannon

See Also

setEdgeLineStyleRule setEdgeColorDirect setEdgeFontSizeDirect setEdgeLabelColorDirect setEdgeLabelDirect setEdgeLabelOpacityDirect setEdgeLabelWidthDirect setEdgeLineStyleDirect setEdgeLineWidthDirect setEdgeOpacityDirect setEdgeSourceArrowColorDirect setEdgeSourceArrowDirect setEdgeSourceArrowOpacityDirect setEdgeSourceArrowShapeDirect setEdgeTargetArrowColorDirect setEdgeTargetArrowDirect setEdgeTargetArrowOpacityDirect setEdgeTargetArrowShapeDirect setEdgeTooltipDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeLineStyleDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
edges.of.interest <- as.character (cy2.edge.names (cw@graph))
supported.styles <- getLineStyle (cw)

# pass three edges and three styles
setEdgeLineStyleDirect (cw, edges.of.interest, supported.styles [5:7])
redraw (cw)

# pass three edges and one style
setEdgeLineStyleDirect (cw, edges.of.interest, supported.styles [8])
redraw (cw)

# now loop through all of the styles
for (style in supported.styles) {
  setEdgeLineStyleDirect (cw, edges.of.interest, style)
  redraw (cw)
}

# restore the default
setEdgeLineStyleDirect (cw, edges.of.interest, 'SOLID')
redraw (cw)

```

`setEdgeLineStyleRule`*specify the line styles to be used in drawing edges*

Description

Specify how data attributes – for the specified named attribute – are mapped to edge line style.

Usage

```
setEdgeLineStyleRule(obj, edge.attribute.name, attribute.values, line.styles, de
```

Arguments

`obj` a CytoscapeWindowClass object.

`edge.attribute.name` the edge attribute whose values will, when this rule is applied, determine the lineStyle of each edge.

`attribute.values` A list of scalar, discrete values. For instance, interaction types: 'phosphorylates', 'ubiquinates', 'represses', 'activates'

`line.styles` One line style for each of the attribute.values

`default.style` The style to use when an explicit mapping is not provided.

Value

None.

Author(s)

Paul Shannon

See Also

[getLineStylees](#)

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLineStyleRule.test', graph=makeSimpleGraph())
line.styles <- c ('SINEWAVE', 'DOT', 'PARALLEL_LINES')
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeLineStyleRule (cw, 'edgeType', edgeType.values, line.styles)
redraw (cw)
```

```
setEdgeLineWidthDirect  
    setEdgeLineWidthDirect
```

Description

In the specified CytoscapeWindow, set the lineWidth of the specified edge or edges. Width is measured in pixels.

Usage

```
setEdgeLineWidthDirect(obj, edge.names, new.value)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.value	an integer object, typically in the range of 0 to 10.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeLineWidthDirect

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLineWidthDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]  
for (i in 1:10) {  
  setEdgeLineWidthDirect (cw, edge.names, i)  
  redraw (cw)  
}  
  
setEdgeLineWidthDirect (cw, edge.names, 1)
```

```
setEdgeLineWidthRule  
    setEdgeLineWidthRule
```

Description

Specify the edge attribute which controls the thickness of the edges displayed in the graph. This is currently only a lookup mapping. An interpolated mapping will be added in the future.

Usage

```
setEdgeLineWidthRule(obj, edge.attribute.name, attribute.values, line.widths, de
```

Arguments

```
obj          a CytoscapeWindowClass object.  
edge.attribute.name  the edge attribute whose values will, when this rule is applied, determine the  
                    edgeLineWidth on each edge.  
attribute.values    observed values of the specified attribute on the edges.  
line.widths        the corresponding widths.  
default.width      use this where the rule fails to apply
```

Value

None.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('setEdgeLineWidthRule.test', graph=makeSimpleGraph())  
displayGraph (cw)  
layout (cw, 'jgraph-spring')  
redraw (cw)  
edge.attribute.values = c ('phosphorylates', 'synthetic lethal', 'undefined')  
line.widths = c (0, 8, 16)  
setEdgeLineWidthRule (cw, 'edgeType', edge.attribute.values, line.widths)
```

```
setEdgeOpacityDirect  
    setEdgeOpacityDirect
```

Description

In the specified CytoscapeWindow, set the opacity of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeOpacityDirect(obj, edge.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, cy2-style edge names.
new.values	a numeric object, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeOpacityDirect

Examples

```
cw <- new.CytoscapeWindow ('setEdgeOpacityDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
edge.names = as.character (cy2.edge.names (cw@graph)) [1:2]  
for (i in 1:10) {  
  setEdgeOpacityDirect (cw, edge.names, 255 - (i * 25))  
  redraw (cw)  
}  
for (i in 1:10) {  
  setEdgeOpacityDirect (cw, edge.names, i * 25)  
  redraw (cw)  
}
```

```
setEdgeSourceArrowColorDirect
      setEdgeSourceArrowColorDirect
```

Description

In the specified CytoscapeWindow, set the edgeSourceArrowColor of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeSourceArrowColorDirect(obj, edge.names, new.colors)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, edges in standard Cytoscape form.
new.colors	one or more String object, representing a color in a '#RRGGBB' hex format.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeEdgeSourceArrowColorDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeSourceArrowColorDirect.test', graph=makeSimpleGraph)
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')

arrows = c ('Arrow', 'Diamond', 'Circle')
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeSourceArrowRule (cw, 'edgeType', edgeType.values, arrows)
setEdgeTargetArrowRule (cw, 'edgeType', edgeType.values, arrows)

colors.1 = c ("#FFFFFF", "#FFFFFF", "#FFFFFF")
colors.2 = c ("#AA00AA", "#00AAAA", "#0000AA")

edge.names = as.character (cy2.edge.names (cw@graph)) [1:3]

for (i in 1:2) {
  setEdgeSourceArrowColorDirect (cw, edge.names, colors.1)
  redraw (cw)
  Sys.sleep (1)
}

```

```

setEdgeSourceArrowColorDirect (cw, edge.names, colors.2)
redraw (cw)
Sys.sleep (1)
} # for i

```

```

setEdgeSourceArrowColorRule

```

Specify Rule for the Source Arrow Color

Description

Specify how edge attributes – that is, data values of the specified edge attribute – control the color of the source arrow, found at the end of an edge, where it connects to the source node.

Usage

```

setEdgeSourceArrowColorRule(obj, edge.attribute.name, attribute.values, colors,

```

Arguments

obj	a CytoscapeWindowClass object.
edge.attribute.name	the edge attribute whose values will, when this ColorRule is applied, determine the color of the source arrow for each edge.
attribute.values	A list of scalar, discrete values. For instance, interaction types: 'phosphorylates', 'ubiquinates', 'represses', 'activates'
colors	A color for each of the attribute.values
default.color	The color to use when an explicit mapping is not provided. (Note: this is broken in Cytoscape 2.7)

Value

None.

Author(s)

Paul Shannon

See Also

[setEdgeSourceArrowColorRule](#)

Examples

```

cw <- new.CytoscapeWindow ('setEdgeSourceArrowColorRule.test', graph=makeSimpleGraph())
colors <- c ("#AA00AA", "#AAAA00", "#AA0000")
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeSourceArrowColorRule (cw, 'edgeType', edgeType.values, colors)

```

```
setEdgeSourceArrowOpacityDirect
    setEdgeSourceArrowOpacityDirect
```

Description

In the specified CytoscapeWindow, set the opacity of the source arrow of the specified edge or edges. Opacity is an integer between 0 (invisible) and 255 (fully rendered).

Usage

```
setEdgeSourceArrowOpacityDirect(obj, edge.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more cy2-style edge names, String objects.
new.values	one or more integer objects, between 0 and 255.

Value

None.

Author(s)

Paul Shannon

See Also

cy2.edge.names setEdgeTargetArrowOpacityDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeSourceArrowOpacityDirect.test', graph=makeSimpleGraph)
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

edges.of.interest = as.character (cy2.edge.names (cw@graph))
# make sure the source arrows are visible
setEdgeSourceArrowShapeDirect (cw, edges.of.interest, 'Circle')

# first try passing three edges and three arrow opacity values
setEdgeSourceArrowOpacityDirect (cw, edges.of.interest, c (64, 128, 255))
redraw (cw)

Sys.sleep (1)

# now try passing three edges and one opacity value
setEdgeSourceArrowOpacityDirect (cw, edges.of.interest, 32)
redraw (cw)

# now loop through all of the arrow.opacitys
```

```

for (opacity in seq (0, 255, by=45)) {
  setEdgeSourceArrowOpacityDirect (cw, edges.of.interest, opacity)
  Sys.sleep (1)
  redraw (cw)
}

# restore the default
setEdgeSourceArrowOpacityDirect (cw, edges.of.interest, 255)
redraw (cw)

```

```
setEdgeSourceArrowRule
```

specify the arrow types to be used at the end of an edge, at the 'source' node

Description

Specify how data attributes – for the specified named attribute – are mapped to the source arrow type.

Usage

```
setEdgeSourceArrowRule(obj, edge.attribute.name, attribute.values, arrows, default)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.attribute.name	the edge attribute whose values will, when this rule is applied, determine the sourceArrow of each edge.
attribute.values	A list of scalar, discrete values. For instance, interaction types: 'phosphorylates', 'ubiquinates', 'represses', 'activates'
arrows	One arrow type for each of the attribute.values
default	The arrow type to use when an explicit mapping is not provided.

Value

None.

Author(s)

Paul Shannon

See Also

[getArrowShapes](#)

Examples

```

cw <- new.CytoscapeWindow ('setEdgeSourceArrowRule.test', graph=makeSimpleGraph())
arrows <- c ('Arrow', 'Diamond', 'Circle')
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeSourceArrowRule (cw, 'edgeType', edgeType.values, arrows)
redraw (cw)

```

```

setEdgeSourceArrowShapeDirect
      setEdgeSourceArrowShapeDirect

```

Description

In the specified CytoscapeWindow, set the source arrow shape of the specified edge or edges, using one of the supported shapes.

Usage

```
setEdgeSourceArrowShapeDirect(obj, edge.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more cy2-style edge names, String objects.
new.values	one or more String objects, from the supported set.

Value

None.

Author(s)

Paul Shannon

See Also

cy2.edge.names getArrowShapes setEdgeTargetArrowRule setEdgeSourceArrowShapeDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeSourceArrowShapeDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

edges.of.interest = as.character (cy2.edge.names (cw@graph))
supported.arrow.shapes = getArrowShapes (cw)

# first try passing three edges and three arrow shapes
setEdgeSourceArrowShapeDirect (cw, edges.of.interest, supported.arrow.shapes [2:5])
redraw (cw)

```

```
    Sys.sleep (1)

    # now try passing three edges and one arrow.shapes
    setEdgeSourceArrowShapeDirect (cw, edges.of.interest, supported.arrow.shapes [6])
    redraw (cw)

    # now loop through all of the arrow.shapes

    for (shape in supported.arrow.shapes) {
      setEdgeSourceArrowShapeDirect (cw, edges.of.interest, shape)
      Sys.sleep (1)
      redraw (cw)
    }

    # restore the default
    setEdgeSourceArrowShapeDirect (cw, edges.of.interest, 'No Arrow')
    redraw (cw)
```

```
setEdgeTargetArrowColorDirect
    setEdgeTargetArrowColorDirect
```

Description

In the specified CytoscapeWindow, set the edgeTargetArrowColor of the specified edge or edges. Low numbers, near zero, are transparent. High numbers, near 255, are maximally opaque: they are fully visible.

Usage

```
setEdgeTargetArrowColorDirect(obj, edge.names, new.colors)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more String objects, edges in standard Cytoscape form.
new.colors	one or more String object, representing a color in a '#RRGGBB' hex format.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeEdgeTargetArrowColorDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeTargetArrowColorDirect.test', graph=makeSimpleGraph
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')

arrows = c ('Arrow', 'Diamond', 'Circle')
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeTargetArrowRule (cw, 'edgeType', edgeType.values, arrows)
setEdgeTargetArrowRule (cw, 'edgeType', edgeType.values, arrows)

colors.1 = c ("#FFFFFF", "#FFFFFF", "#FFFFFF")
colors.2 = c ("#AA00AA", "#00AAAA", "#0000AA")

edge.names = as.character (cy2.edge.names (cw@graph)) [1:3]

for (i in 1:2) {
  setEdgeTargetArrowColorDirect (cw, edge.names, colors.1)
  redraw (cw)
  Sys.sleep (1)
  setEdgeTargetArrowColorDirect (cw, edge.names, colors.2)
  redraw (cw)
  Sys.sleep (1)
} # for i

```

```
setEdgeTargetArrowColorRule
```

Specify Rule for the Target Arrow Color

Description

Specify how edge attributes – that is, data values of the specified edge attribute – control the color of the target arrow, found at the end of an edge, where it connects to the target node.

Usage

```
setEdgeTargetArrowColorRule(obj, edge.attribute.name, attribute.values, colors,
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>edge.attribute.name</code>	the edge attribute whose values will, when this ColorRule is applied, determine the color of the target arrow of each edge.
<code>attribute.values</code>	A list of scalar, discrete values. For instance, interaction types: 'phosphorylates', 'ubiquinates', 'represses', 'activates'
<code>colors</code>	A color for each of the attribute.values
<code>default.color</code>	The color to use when an explicit mapping is not provided. (Note: this is broken in Cytoscape 2.7)

Value

None.

Author(s)

Paul Shannon

See Also

[setEdgeSourceArrowColorRule](#)

Examples

```
cw <- new.CytoscapeWindow ('setEdgeTargetArrowColorRule.test', graph=makeSimpleGraph())
colors <- c ("#AA00AA", "#AAAA00", "#AA0000")
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeTargetArrowColorRule (cw, 'edgeType', edgeType.values, colors)
```

setEdgeTargetArrowOpacityDirect
setEdgeTargetArrowOpacityDirect

Description

In the specified CytoscapeWindow, set the opacity of the target arrow of the specified edge or edges. Opacity is an integer between 0 (invisible) and 255 (fully rendered).

Usage

```
setEdgeTargetArrowOpacityDirect(obj, edge.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more cy2-style edge names, String objects.
new.values	one or more integer objects, between 0 and 255.

Value

None.

Author(s)

Paul Shannon

See Also

cy2.edge.names setEdgeTargetArrowOpacityDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeTargetArrowOpacityDirect.test', graph=makeSimpleGraph)
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

edges.of.interest = as.character (cy2.edge.names (cw@graph))

# make sure the target arrows are visible
setEdgeTargetArrowShapeDirect (cw, edges.of.interest, 'Circle')

# first try passing three edges and three arrow opacity values
setEdgeTargetArrowOpacityDirect (cw, edges.of.interest, c (64, 128, 255))
redraw (cw)

# now try passing three edges and one opacity value
setEdgeTargetArrowOpacityDirect (cw, edges.of.interest, 32)
redraw (cw)

# now loop through all of the arrow.opacitys
for (opacity in seq (0, 255, by=45)) {
  setEdgeTargetArrowOpacityDirect (cw, edges.of.interest, opacity)
  redraw (cw)
}

# restore the default
setEdgeTargetArrowOpacityDirect (cw, edges.of.interest, 255)
redraw (cw)

```

```
setEdgeTargetArrowRule
```

specify the arrow types to be used at the end of an edge, at the 'target' node

Description

Specify how data attributes – for the specified named attribute – are mapped to the target arrow type.

Usage

```
setEdgeTargetArrowRule(obj, edge.attribute.name, attribute.values, arrows, default)
```

Arguments

`obj` a CytoscapeWindowClass object.
`edge.attribute.name` the edge attribute whose values will, when this rule is applied, determine the `targetArrow` of each edge.

attribute.values	A list of scalar, discrete values. For instance, interaction types: 'phosphorylates', 'ubiquinates', 'represses', 'activates'
arrows	One arrow type for each of the attribute.values
default	The arrow type to use when an explicit mapping is not provided.

Value

None.

Author(s)

Paul Shannon

See Also

[getArrowShapes](#)

Examples

```

cw <- new.CytoscapeWindow ('setEdgeTargetArrowRule.test', graph=makeSimpleGraph())
arrows <- c ('Arrow', 'Diamond', 'Circle')
edgeType.values <- c ('phosphorylates', 'synthetic lethal', 'undefined')
setEdgeTargetArrowRule (cw, 'edgeType', edgeType.values, arrows)
redraw (cw)

```

```

setEdgeTargetArrowShapeDirect
      setEdgeTargetArrowShapeDirect

```

Description

In the specified CytoscapeWindow, set the target arrow shape of the specified edge or edges, using one of the supported shapes.

Usage

```
setEdgeTargetArrowShapeDirect(obj, edge.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
edge.names	one or more cy2-style edge names, String objects.
new.values	one or more String objects, from the supported set.

Value

None.

Author(s)

Paul Shannon

See Also

cy2.edge.names getArrowShapes setEdgeTargetArrowRule setEdgeTargetArrowShapeDirect

Examples

```

cw <- new.CytoscapeWindow ('setEdgeTargetArrowShapeDirect.test', graph=makeSimpleGraph)
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

edges.of.interest = as.character (cy2.edge.names (cw@graph))
supported.arrow.shapes = getArrowShapes (cw)

# first try passing three edges and three arrow shapes
setEdgeTargetArrowShapeDirect (cw, edges.of.interest, supported.arrow.shapes [2:5])
redraw (cw)

Sys.sleep (1)

# now try passing three edges and one arrow.shapes
setEdgeTargetArrowShapeDirect (cw, edges.of.interest, supported.arrow.shapes [6])
redraw (cw)

# now loop through all of the arrow.shapes
for (shape in supported.arrow.shapes) {
  setEdgeTargetArrowShapeDirect (cw, edges.of.interest, shape)
  Sys.sleep (1)
  redraw (cw)
}

# restore the default
setEdgeTargetArrowShapeDirect (cw, edges.of.interest, 'No Arrow')
redraw (cw)

```

setEdgeTooltipDirect

setEdgeTooltipDirect

Description

In the specified CytoscapeWindow, set the tooltips of the specified edge or edges. The tooltips are not available until redraw is called.

Usage

```
setEdgeTooltipDirect(obj, edge.names, new.values)
```

Arguments

obj a CytoscapeWindowClass object.
edge.names one or more cy2-style edge names, String objects.
new.values one or more String objects.

Value

None.

Author(s)

Paul Shannon

See Also

cy2.edge.names setEdgeTooltipRule

Examples

```
cw <- new.CytoscapeWindow ('setEdgeTooltipDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)

edges.of.interest = as.character (cy2.edge.names (cw@graph))

# first try passing three edges and three tooltips
setEdgeTooltipDirect (cw, edges.of.interest, c ('tooltip #1', 'tooltip #2', 'tooltip #3'))
redraw (cw)

Sys.sleep (1)

# now try passing three edges and one tooltip
setEdgeTooltipDirect (cw, edges.of.interest, 'a general purpose tooltip')
redraw (cw)

setEdgeTooltipDirect (cw, edges.of.interest, '')
redraw (cw)
```

setEdgeTooltipRule *setEdgeTooltipRule*

Description

Specify the edge attribute to be used as the tooltip for each edge. Non-character attributes are converted to strings before they are used as tooltips.

Usage

```
setEdgeTooltipRule(obj, edge.attribute.name)
```

Arguments

`obj` a CytoscapeWindowClass object.
`edge.attribute.name` the edge attribute whose values will, when this rule is applied, determine the tooltip on each edge.

Value

None.

Author(s)

Paul Shannon

Examples

```

cw <- new.CytoscapeWindow ('setEdgeTooltipRule.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
setEdgeTooltipRule (cw, 'edgeType')

```

setGraph

setGraph

Description

Assigns the supplied graph object to the appropriate slot in the specified CytoscapeWindow object.

Usage

```
setGraph(obj, graph)
```

Arguments

`obj` a CytoscapeWindowClass object.
`graph` a graph object.

Value

The modified CytoscapeWindow object.

Author(s)

Paul Shannon

Examples

```

cw <- new.CytoscapeWindow ('setGraph.test') # an empty graph is created by default
graph <- makeSimpleGraph ()
setGraph (cw, graph)
print (length (nodes (getGraph (cw))))

```

```
setLayoutProperties  
    setLayoutProperties
```

Description

Sets the specified properties for the specified layout. Unmentioned properties are left unchanged.

Usage

```
setLayoutProperties(obj, layout.name, properties.list)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`layout.name` a string object.
`properties.list`
a a named list with as many entries as you wish to modify

Value

None.

Author(s)

Paul Shannon

See Also

layout getLayoutNames getLayoutNameMapping getLayoutPropertyNames getLayoutPropertyType
getLayoutPropertyValue

Examples

```
cy <- CytoscapeConnection ()  
prop.names <- getLayoutPropertyNames (cy, 'isom')  
print (prop.names)  
# "maxEpoch" "sizeFactor" "radiusConstantTime" "radius" "minRadius" "initialAdapt  
print (getLayoutPropertyValue (cy, 'isom', 'radiusConstantTime'))  
# modify just two of the eight properties; the others are unchanged  
setLayoutProperties (cy, 'isom', list (radiusConstantTime=4, radius=20))
```

`setNodeAttributes` *setNodeAttributes*

Description

Transfer the named node attribute from the the R graph (found in `obj@graph`) to Cytoscape. This method is typically called by `displayGraph`, which will suffice for most users' needs. It transfers the specified node attributes, for all nodes, from the `cw@graph` slot to Cytoscape.

Usage

```
setNodeAttributes(obj, attribute.name)
```

Arguments

`obj` a CytoscapeWindowClass object.
`attribute.name` a string one of the attributes defined on the nodes.

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeAttributesDirect` `setEdgeAttributes` `setEdgeAttributesDirect` `sendEdges` `sendNodes` `displayGraph`

Examples

```
cw <- new.CytoscapeWindow ('setNodeAttributes.test', graph=makeSimpleGraph())
attribute.names = noa.names (cw@graph)

for (attribute.name in attribute.names)
  result = setNodeAttributes (cw, attribute.name)
```

```
setNodeAttributesDirect
      setNodeAttributesDirect
```

Description

Transfer the named node attribute, for all named nodes, to Cytoscape. The attribute must be previously defined on the nodes of the graph: see `nodeDataDefaults` in the `graph` class. This method is useful if you wish to run a 'movie.' For example, if you have a timecourse experiment, with different values at successive time points of the 'lfc' (log fold change) measurements or 'pValue' of each node. With a `nodeColor` and `nodeSize` rule already specified, you can animate the display of the nodes across time in the graph by pumping new values of the attributes attributes using this method, and then asking for a redraw. An example of such node-attribute-driven animation can be found here....[todo].

Usage

```
setNodeAttributesDirect(obj, attribute.name, attribute.type, node.names, values)
```

Arguments

<code>obj</code>	a <code>CytoscapeWindowClass</code> object.
<code>attribute.name</code>	a string one of the attributes defined on the nodes.
<code>attribute.type</code>	a string from one of these three groups: (floating, numeric, double), (integer, int), (string, char, character). This parameter is required because <code>RCytoscape</code> cannot always infer the type of an attribute.
<code>node.names</code>	a list of strings, node names
<code>values</code>	a list of objects of the type specified by 'attribute.name', one per node

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeAttributes` `setEdgeAttributes` `setEdgeAttributesDirect`

Examples

```

cw <- new.CytoscapeWindow ('setNodeAttributesDirect.test', graph=makeSimpleGraph())
stopifnot ('count' %in% noa.names (cw@graph))
result = setNodeAttributesDirect (cw, 'count', 'int', c ('A', 'B', 'C'), c (4, 8, 12))

```

```
setNodeBorderColorDirect  
setNodeBorderColorDirect
```

Description

In the specified CytoscapeWindow, set the color of the border of the specified node.

Usage

```
setNodeBorderColorDirect(obj, node.names, new.color)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
new.color	a String object, in standard hex notation.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeSizeDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeBorderColorDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setNodeBorderColorDirect (cw, 'A', '#FFFF00')  
redraw (cw)
```

```
setNodeBorderColorRule  
setNodeBorderColorRule
```

Description

Specify how data attributes – for the specified named attribute – are mapped to node color. There are two modes: 'interpolate' and 'lookup'. In the former, you specify data values ('control points') and colors; when a node's corresponding data attribute value is exactly that of a control point, the specified color is used. If the node's data attribute falls between control points, then the color is interpolated. Note! In the 'interpolate' mode, you almost always want to provide two additional colors: one for node data values falling below the minimum control point, one for node data values falling above the maximum control point. If you provide an equal number of colors and control.points, the default.color is used to paint nodes above and below the specified range. A useful data exploration strategy would be to use `default.color <- '#000000'` causing all extreme nodes to be painted black.

The 'lookup' mode provides no interpolation, and is useful when you have a node attribute with a finite set of discrete values, each of which you want to display in a specific color. For example: render all receptors in yellow, all transcription factors in blue, and all kinases in dark red.

Usage

```
setNodeBorderColorRule(obj, node.attribute.name, control.points, colors, mode, d
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>node.attribute.name</code>	the node attribute whose values will, when this rule is applied, determine the color of each node.
<code>control.points</code>	a list of values. In the interpolate mode, a typical choice is the minimum, the maximum, some sensible midpoint.
<code>colors</code>	a list of colors, either two more than the number of control points (if mode='interpolate'), in which case the first color is used for all attributes values below the minimum, and the last color is used for those above the maximum. Or, if mode='lookup', the same number of colors as control.points are expected. Colors are expressed as quoted hexadecimal RGB strings, e.g., '#FF0000' or '#FA8800'
<code>mode</code>	'interpolate' or 'lookup'. This roughly corresponds to the visual mapping of continuously varying data (i.e., lfc or pValue), versus visual mapping of discrete data (i.e., molecule type, or phosphorylation status). With the interpolation mode, you must specify n+2 colors: adding a 'below' and an 'above' color. In lookup mode, specify exactly as many control.points as colors. If are data attribute values are found on the nodes which do not appear in your list, they will displayed in the default color.
<code>default.color</code>	'#000000' (black) by default, to catch your eye. Used primarily in mode=='lookup' and in mode='interpolate' if you fail to specify 'above' and 'below' values.

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeShapeRule`

Examples

```

cw <- new.CytoscapeWindow ('setNodeBorderColorRule.test', graph=makeSimpleGraph())
control.points <- c (-3.0, 0.0, 3.0) # typical range of log-fold-change ratio values
# paint negative values shades of green, positive values shades of
# red, out-of-range low values are dark green; out-of-range high
# values are dark red
colors <- c ("#00AA00", "#00FF00", "#FFFFFF", "#FF0000", "#AA0000")
setNodeBorderColorRule (cw, node.attribute.name='lfc', control.points, colors, mode='lfc')
redraw (cw)
data.values <- c ("kinase", "transcription factor", "glycoprotein")
colors <- c ("#0000AA", "#FFFF00", "#0000AA")
setNodeBorderColorRule (cw, node.attribute.name='type', data.values, colors, mode='lfc')

```

```

setNodeBorderOpacityDirect
setNodeBorderOpacityDirect

```

Description

In the specified CytoscapeWindow, set the opacity of the border of the specified node.

Usage

```
setNodeBorderOpacityDirect(obj, node.names, new.values)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.names` one or more String objects.
`new.values` a numeric object, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeFillOpacityDirect` `setNodeLabelOpacityDirect` `setNodeOpacityDirect`

Examples

```
cw <- new.CytoscapeWindow ('setNodeBorderOpacityDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeBorderOpacityDirect (cw, 'A', 220)
redraw (cw)
```

setNodeBorderWidthDirect
setNodeBorderWidthDirect

Description

In the specified CytoscapeWindow, set the width of the border of the specified node.

Usage

```
setNodeBorderWidthDirect(obj, node.names, new.sizes)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
new.sizes	an integer, in pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeSizeDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeBorderWidthDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeBorderWidthDirect (cw, 'A', 10)
redraw (cw)
```

```
setNodeBorderWidthRule  
    setNodeBorderWidthRule
```

Description

Specify the node attribute which controls the thickness of the nodes displayed in the graph. This is currently only a lookup mapping. An interpolated mapping will be added in the future.

Usage

```
setNodeBorderWidthRule(obj, node.attribute.name, attribute.values, line.widths,
```

Arguments

```
obj          a CytoscapeWindowClass object.  
node.attribute.name  
              the node attribute whose values will, when this rule is applied, determine the  
              nodeBorderWidth on each node.  
attribute.values  
              observed values of the specified attribute on the nodes.  
line.widths  the corresponding widths.  
default.width  
              use this where the rule fails to apply
```

Value

None.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('setNodeBorderWidthRule.test', graph=makeSimpleGraph())  
displayGraph (cw)  
layout (cw, 'jgraph-spring')  
redraw (cw)  
node.attribute.values = c ('kinase', 'transcription factor', 'glycoprotein')  
line.widths = c (0, 8, 16)  
setNodeBorderWidthRule (cw, 'type', node.attribute.values, line.widths)
```

`setNodeColorDirect` *setNodeColorDirect*

Description

In the specified CytoscapeWindow, set the color of the specified node or nodes. This method bypasses the vizmap, and excludes this node, for the duration of the current Cytoscape session, from further manipulation by vizmap color rules.

Usage

```
setNodeColorDirect(obj, node.names, new.color)
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>node.names</code>	a String list object.
<code>new.color</code>	an String object, using the standard hexadecimal form, eg, '#FF88AA'

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeColorRule`

Examples

```
cw <- new.CytoscapeWindow ('setNodeColorDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeColorDirect (cw, 'A', '#880000')
redraw (cw)
```

```
setNodeColorRule  setNodeColorRule
```

Description

Specify how data attributes – for the specified named attribute – are mapped to node color. There are two modes: 'interpolate' and 'lookup'. In the former, you specify data values ('control points') and colors; when a node's corresponding data attribute value is exactly that of a control point, the specified color is used. If the node's data attribute falls between control points, then the color is interpolated. Note! In the 'interpolate' mode, you almost always want to provide two additional colors: one for node data values falling below the minimum control point, one for node data values falling above the maximum control point. If you provide an equal number of colors and control.points, the default.color is used to paint nodes above and below the specified range. A useful data exploration strategy would be to use `default.color <- '#000000'` causing all extreme nodes to be painted black.

The 'lookup' mode provides no interpolation, and is useful when you have a node attribute with a finite set of discrete values, each of which you want to display in a specific color. For example: render all receptors in yellow, all transcription factors in blue, and all kinases in dark red.

Usage

```
setNodeColorRule(obj, node.attribute.name, control.points, colors, mode, default)
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>node.attribute.name</code>	the node attribute whose values will, when this rule is applied, determine the color of each node.
<code>control.points</code>	a list of values. In the interpolate mode, a typical choice is the minimum, the maximum, some sensible midpoint.
<code>colors</code>	a list of colors, either two more than the number of control points (if mode='interpolate'), in which case the first color is used for all attributes values below the minimum, and the last color is used for those above the maximum. Or, if mode='lookup', the same number of colors as control.points are expected. Colors are expressed as quoted hexadecimal RGB strings, e.g., '#FF0000' or '#FA8800'
<code>mode</code>	'interpolate' or 'lookup'. This roughly corresponds to the visual mapping of continuously varying data (i.e., lfc or pValue), versus visual mapping of discrete data (i.e., molecule type, or phosphorylation status). With the interpolation mode, you must specify n+2 colors: adding a 'below' and an 'above' color. In lookup mode, specify exactly as many control.points as colors. If are data attribute values are found on the nodes which do not appear in your list, they will displayed in the default color.
<code>default.color</code>	'#000000' (black) by default, to catch your eye. Used primarily in mode=='lookup' and in mode='interpolate' if you fail to specify 'above' and 'below' values.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeShapeRule

Examples

```

cw <- new.CytoscapeWindow ('setNodeColorRule.test', graph=makeSimpleGraph())
control.points <- c (-3.0, 0.0, 3.0) # typical range of log-fold-change ratio values
# paint negative values shades of green, positive values shades of
# red, out-of-range low values are dark green; out-of-range high
# values are dark red
node.colors <- c ("#00AA00", "#00FF00", "#FFFFFF", "#FF0000", "#AA0000")
setNodeColorRule (cw, node.attribute.name='lfc', control.points, node.colors, mode='int')
redraw (cw)
data.values <- c ("kinase", "transcription factor", "glycoprotein")
node.colors <- c ("#0000AA", "#FFFF00", "#0000AA")
setNodeColorRule (cw, node.attribute.name='type', data.values, node.colors, mode='loc')

```

```

setNodeFillOpacityDirect
      setNodeFillOpacityDirect

```

Description

In the specified CytoscapeWindow, set the opacity of the fill color of the specified node.

Usage

```
setNodeFillOpacityDirect(obj, node.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
new.values	a numeric object, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeLabelOpacityDirect setNodeOpacityDirect setNodeBorderOpacityDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeFillOpacityDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeFillOpacityDirect (cw, 'A', 220)
redraw (cw)
```

```
setNodeFontSizeDirect
      setNodeFontSizeDirect
```

Description

In the specified CytoscapeWindow, set the size of the font used in rendering the label of the specified node.

Usage

```
setNodeFontSizeDirect (obj, node.names, new.sizes)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
new.sizes	an integer, in pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeWidthDirect setNodeHeightDirect setNodeSizeDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeFontSizeDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeFontSizeDirect (cw, 'A', 32)
redraw (cw)
```

```
setNodeHeightDirect  
    setNodeHeightDirect
```

Description

In the specified CytoscapeWindow, set the height of the specified node. Not that the node dimensions (height and width) must be unlocked for this to work. If they ARE locked, then node and height change together, as specified by a node size rule, or the setNodeSizeDirect method

Usage

```
setNodeHeightDirect(obj, node.names, new.heights)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one ore more String objects.
new.heights	one or more integers, in pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeWidthDirect lockNodeDimensions setNodeSizeDirect setNodeHeightDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeHeightDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
lockNodeDimensions (cw, 'default', FALSE)  
setNodeHeightDirect (cw, 'A', 32)  
redraw (cw)
```

setNodeImageDirect *setNodeImageDirect*

Description

In the specified CytoscapeWindow, set the images of the specified nodes.

Usage

```
setNodeImageDirect(obj, node.names, image.urls)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
image.urls	one or more String objects. If just one, then this is replicated for each of the supplied node.names.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeShapeDirect

Examples

```

cw <- new.CytoscapeWindow ('setNodeImageDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeImageDirect (cw, 'C', 'http://rcytoscape.systemsbiology.net/versions/current/ima
redraw (cw)

```

setNodeLabelColorDirect
setNodeLabelColorDirect

Description

In the specified CytoscapeWindow, set the size of the font used in rendering the label of the specified node.

Usage

```
setNodeLabelColorDirect(obj, node.names, new.colors)
```

Arguments

`obj` a `CytoscapeWindowClass` object.
`node.names` one or more `String` objects.
`new.colors` an string, using standard hex notation.

Value

None.

Author(s)

Paul Shannon

See Also

`setNodeFontSizeDirect`

Examples

```
cw <- new.CytoscapeWindow ('setNodeLabelColorDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeFontSizeDirect (cw, 'A', 50)
setNodeLabelColorDirect (cw, 'A', '#FFFF00')
redraw (cw)
```

`setNodeLabelDirect` *setNodeLabelDirect*

Description

In the specified `CytoscapeWindow`, set the labels of the specified nodes.

Usage

```
setNodeLabelDirect(obj, node.names, new.labels)
```

Arguments

`obj` a `CytoscapeWindowClass` object.
`node.names` one or more `String` objects.
`new.labels` one or more `String` objects. If just one, then this is replicated for each of the supplied `node.names`.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeShapeDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeLabelDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeLabelDirect (cw, 'A', 'A new, very long label')
redraw (cw)
```

setNodeLabelOpacityDirect
setNodeLabelOpacityDirect

Description

In the specified CytoscapeWindow, set the opacity of the label of the specified node.

Usage

```
setNodeLabelOpacityDirect(obj, node.names, new.values)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	one or more String objects.
new.values	a numeric object, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeFillOpacityDirect setNodeOpacityDirect setNodeBorderOpacityDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeLabelOpacityDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeLabelOpacityDirect (cw, 'A', 220)
redraw (cw)
```

setNodeLabelRule *setNodeLabelRule*

Description

Specify the node attribute to be used as the label for each node. Non-character attributes are converted to strings before they are used as labels.

Usage

```
setNodeLabelRule(obj, node.attribute.name)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.attribute.name` the node attribute whose values will, when this rule is applied, determine the label on each node.

Value

None.

Author(s)

Paul Shannon

Examples

```
cw <- new.CytoscapeWindow ('setNodeLabelRule.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
setNodeLabelRule (cw, 'label')
redraw (cw)
setNodeLabelRule (cw, 'type')
redraw (cw)
setNodeLabelRule (cw, 'lfc')
redraw (cw)
setNodeLabelRule (cw, 'count')
redraw (cw)
setNodeLabelRule (cw, 'label')
redraw (cw)
```

```
setNodeOpacityDirect  
    setNodeOpacityDirect
```

Description

In the specified CytoscapeWindow, set the opacity of all aspects of the specified node: fill color, border, label.

Usage

```
setNodeOpacityDirect(obj, node.names, new.values)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.names` one or more String objects.
`new.values` a numeric object, one or more, ranging from 0 to 255.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeFillOpacityDirect setNodeLabelOpacityDirect setNodeBorderOpacityDirect

Examples

```
cw <- new.CytoscapeWindow ('setNodeOpacityDirect.test', graph=makeSimpleGraph())  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
setNodeOpacityDirect (cw, 'A', 220)  
redraw (cw)
```

`setNodeShapeDirect` *setNodeShapeDirect*

Description

In the specified CytoscapeWindow, set the shape of the specified node.

Usage

```
setNodeShapeDirect(obj, node.names, new.shapes)
```

Arguments

<code>obj</code>	a CytoscapeWindowClass object.
<code>node.names</code>	one or more String objects.
<code>new.shapes</code>	one or more String objects, one of the allowed values returned by <code>getNodeShape</code> .

Value

None.

Author(s)

Paul Shannon

See Also

`getNodeShapeDirects`

Examples

```
cw <- new.CytoscapeWindow ('setNodeShapeDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeShapeDirect (cw, 'A', 'triangle')
redraw (cw)
```

`setNodeShapeRule` *setNodeShapeRule*

Description

Specify how data attributes how the specified node attribute values determine the node shape.

Usage

```
setNodeShapeRule (obj, node.attribute.name=, attribute.values,
node.shapes, default.shape)
```

Arguments

`obj` a CytoscapeWindowClass object.

`node.attribute.name` the node attribute whose values will, when this rule is applied, determine the shape of each node.

`attribute.values` A list of scalar, discrete values. For instance, molecule types: 'transporter', 'receptor', 'kinase'

`node.shapes` A list of nodes selected from among those supported.

`default.shape` A single string, the shape used if no explicit mapping is provided.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeColorRule setNodeLabelRule

Examples

```

cw <- new.CytoscapeWindow ('setNodeShapeRule.test', graph=makeSimpleGraph())
shapes <- c ("trapezoid", "round_rect", "ellipse")
molecule.types <- c ("kinase", "transcription factor", "glycoprotein")
setNodeShapeRule (cw, node.attribute.name='type', molecule.types, shapes)
redraw (cw)

```

setNodeSizeDirect *setNodeSizeDirect*

Description

In the specified CytoscapeWindow, set the size of the specified node. Not that the node dimensions (size and size) must be locked (the default state) for this to work. Node height and width change together.

Usage

```
setNodeSizeDirect(obj, node.names, new.sizes)
```

Arguments

`obj` a CytoscapeWindowClass object.

`node.names` one or more String objects.

`new.sizes` one or more integers, in pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

lockNodeDimensions setNodeWidthDirect setNodeHeightDirect

Examples

```

cw <- new.CytoscapeWindow ('setNodeSizeDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setNodeSizeDirect (cw, 'A', 32)
redraw (cw)

```

setNodeSizeRule *setNodeSizeRule*

Description

Specify how data attributes how the specified node attribute values determine the node size.

Usage

```
setNodeSizeRule (obj, node.attribute.name, control.points, node.sizes, mode, default.size)
```

Arguments

`obj` a CytoscapeWindowClass object.

`node.attribute.name` the node attribute whose values will, when this rule is applied, determine the size of each node.

`control.points` A list of (currently, exactly 3) values, which specify the 'control points' to control the coloring of nodes

`node.sizes` The nodes sizes which correspond to the control points.

`mode` 'interpolate' or 'lookup'. This roughly corresponds to the visual mapping of continuously varying data (i.e., lfc or pValue), versus visual mapping of discrete data (i.e., molecule type, or phosphorylation status). With the interpolation mode, you must specify n+2 colors: adding a 'below' and an 'above' color. In lookup mode, specify exactly as many control.points as colors. If are data attribute values are found on the nodes which do not appear in your list, they will displayed in the default color.

`default.size` the size of nodes not otherwise specified. Does not work in Cytoscape 2.7.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeColorRule

Examples

```

cw <- new.CytoscapeWindow ('setNodeSizeRule.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
control.points <- c (10, 30, 80)
node.sizes <- c (20, 50, 80)
node.attribute.name <- 'count' # previously defined, has values which range between
# remind yourself of the values of count on each of the three nodes
print (noa (getGraph (cw), 'count'))
# A.A B.B C.C
# "2" "30" "100"
setNodeSizeRule (cw, node.attribute.name, control.points, node.sizes, mode='interpolat

# now make a new rule. explicitly specify below and above sizes
node.sizes <- c (1, 20, 50, 80, 200) # anything below 20 will have size of 1; and
setNodeSizeRule (cw, node.attribute.name, control.points, node.sizes, mode='interpolat

# now use a mode='lookup' rule. specify a size for two of the molecule types
# look to see that the third type, glycoprotein, gets the tiny default.size of 5

molecule.types <- c ('kinase', 'transcription factor')
node.sizes <- c (60, 80)
setNodeSizeRule (cw, 'type', molecule.types, node.sizes, default.size= 5, mode='lookup
redraw (cw)

```

setNodeTooltipRule *setNodeTooltipRule*

Description

Specify the node attribute to be used as the tooltip for each node. Non-character attributes are converted to strings before they are used as tooltips.

Usage

```
setNodeTooltipRule(obj, node.attribute.name)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.attribute.name` the node attribute whose values will, when this rule is applied, determine the tooltip on each node.

Value

None.

Author(s)

Paul Shannon

Examples

```

cw <- new.CytoscapeWindow ('setNodeTooltipRule.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
setNodeTooltipRule (cw, 'type')
setNodeTooltipRule (cw, 'lfc')
setNodeTooltipRule (cw, 'count')

```

setNodeWidthDirect *setNodeWidthDirect*

Description

In the specified CytoscapeWindow, set the width of the specified node. Not that the node dimensions (width and height) must be unlocked for this to work. If they ARE locked, then node and width change together, as specified by a node size rule, or the setNodeSize method

Usage

```
setNodeWidthDirect(obj, node.names, new.widths)
```

Arguments

`obj` a CytoscapeWindowClass object.
`node.names` one or more String objects.
`new.widths` one or more integer objects, in pixel units.

Value

None.

Author(s)

Paul Shannon

See Also

setNodeWidthRule lockNodeDimensions setNodeSizeDirect setNodeHeightDirect

Examples

```

cw <- new.CytoscapeWindow ('setNodeWidthDirect.test', graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
lockNodeDimensions (cw, 'default', FALSE)
setNodeWidthDirect (cw, 'A', 32)
redraw (cw)

```

setPosition

setPosition

Description

Set the position of the specified nodes on the CytoscapeWindow canvas. Use this for any hand-crafted layouts, or novel layout algorithms, you wish to use.

Usage

```
setPosition(obj, node.names, x.coords, y.coords)
```

Arguments

obj	a CytoscapeWindowClass object.
node.names	a list of strings, the names of nodes to select.
x.coords	a list of floating point numbers, one for each node in the node.names list.
y.coords	a list of floating point numbers, one for each node in the node.names list.

Value

None.

Author(s)

Paul Shannon

See Also

getPosition

Examples

```

cw <- new.CytoscapeWindow ('setPosition.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw)
setPosition (cw, c ('A', 'B', 'C'), c (10.0, 20.0, 500), c (0.0,
100.0, 3))

```

```
setTooltipDismissDelay  
    setTooltipDismissDelay
```

Description

Specify the number of milliseconds before the tooltip (a small lightweight window) pops up over a node or edge.

Usage

```
setTooltipDismissDelay(obj, msec)
```

Arguments

obj	a CytoscapeConnectionClass object.
msec	an integer.

Value

None.

Author(s)

Paul Shannon

See Also

setTooltipInitialDelay, setTooltip, setNodeTooltipRule, setEdgeTooltipRule, setNodeTooltipDirect, setEdgeTooltipDirect

Examples

```
window.title = 'setTooltipDismissDelay demo'  
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())  
  # use node type as the tooltip  
setNodeTooltipRule (cw, 'type')  
  # and edgeType  
setEdgeTooltipRule (cw, 'edgeType')  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
  # have the tooltips popup after 200 milliseconds, and then  
  # disappear after 3000 (3 seconds)  
setTooltipInitialDelay (cw, 200)  
setTooltipDismissDelay (cw, 3000)
```

```
setTooltipInitialDelay  
    setTooltipInitialDelay
```

Description

Specify the number of milliseconds before the tooltip (a small lightweight window) pops up over a node or edge.

Usage

```
setTooltipInitialDelay(obj, msec)
```

Arguments

obj	a CytoscapeConnectionClass object.
msec	an integer.

Value

None.

Author(s)

Paul Shannon

See Also

setTooltipDismissDelay, setTooltip, setNodeTooltipRule, setEdgeTooltipRule, setNodeTooltipDirect, setEdgeTooltipDirect

Examples

```
window.title = 'setTooltipInitialDelay demo'  
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())  
  # use node type as the tooltip  
setNodeTooltipRule (cw, 'type')  
  # and edgeType  
setEdgeTooltipRule (cw, 'edgeType')  
displayGraph (cw)  
redraw (cw)  
layout (cw, 'jgraph-spring')  
  # have the tooltips popup right away, as soon as the mouse hovers  
  # over a node or edge, and then stay up as long as the mouse  
  # remains on top of that node or edge  
setTooltipInitialDelay (cw, 0)  
setTooltipDismissDelay (cw, 0)
```

setVisualStyle	<i>setVisualStyle</i>
----------------	-----------------------

Description

Cytoscape provides a number of canned visual styles. You can also create your own. Use this method to establish an (already-defined) visual style as the style which governs the display of a network in the specified CytoscapeWindow object.

Usage

```
setVisualStyle(obj, new.style.name)
```

Arguments

obj	a CytoscapeWindowClass object.
new.style.name	a character string specifying the name of an existing style you wish to use.

Value

Nothing.

Author(s)

Paul Shannon

See Also

getVisualStyleNames copyVisualStyle

Examples

```
window.name = 'demo.setVisualStyle'
cw = new.CytoscapeWindow (window.name, graph=makeSimpleGraph ())
displayGraph (cw)
redraw (cw)
layout (cw)

styles = getVisualStyleNames (cw)
# now cycle through the currently defined styles
for (style in styles) {
  print (paste ("about to set new style:", style))
  setVisualStyle (cw, style)
}
```

setWindowSize	<i>setWindowSize</i>
---------------	----------------------

Description

Control the size of the CytoscapeWindow by specifying a width and height, On a typical screen, there may be 1200 pixels in the width of a full-size window, and 800 pixels in height.

Usage

```
setWindowSize(obj, width, height)
```

Arguments

obj	a CytoscapeWindowClass object.
width	a numeric object.
height	a numeric object.

Value

None.

Author(s)

Paul Shannon

See Also

getZoom setZoom getCenter setCenter getViewCoordinates fitContent

Examples

```
window.title = 'setWindowSize demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setWindowSize (cw, 1200, 800)
fitContent (cw)
system ('sleep 1')
setWindowSize (cw, 120, 80)
fitContent (cw)
system ('sleep 1')
setWindowSize (cw, 600, 400)
fitContent (cw)
```

setZoom	<i>setZoom</i>
---------	----------------

Description

This method expands or contracts the relative size of the objects (the graph) displayed in the CytoscapeWindow. A value of 1.0 typically renders the graph with an ample margin. A call to fitContent produces a zoom level of about 1.5.

Usage

```
setZoom(obj, new.level)
```

Arguments

obj	a CytoscapeWindowClass object.
new.level	a numeric object.

Value

None.

Author(s)

Paul Shannon

See Also

getZoom getCenter setCenter getViewCoordinates fitContent

Examples

```
window.title = 'setZoom demo'
cw <- new.CytoscapeWindow (window.title, graph=makeSimpleGraph())
displayGraph (cw)
redraw (cw)
layout (cw, 'jgraph-spring')
setZoom (cw, 0.3)
system ('sleep 1')
setZoom (cw, 3.0)
system ('sleep 1')
setZoom (cw, 1.0)
```

```
showGraphicsDetails  
    showGraphicsDetails
```

Description

For all windows, and regardless of the current zoom level, display or hide graphics details – of which node labels are the most obvious example.

Usage

```
showGraphicsDetails(obj, new.value)
```

Arguments

`obj` a CytoscapeConnectionClass object.
`new.value` a logical object, TRUE or FALSE.

Value

None.

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()  
showGraphicsDetails (cy, TRUE)
```

```
unhideAll    unhideAll
```

Description

Currently (in Cytoscape 2.7) broken. The redisplay of hidden nodes and edges does not always work...

Usage

```
unhideAll(obj)
```

Arguments

`obj` a CytoscapeWindowClass object.

Value

None.

Author(s)

Paul Shannon

See Also

selectNodes clearSelection

Examples

```
cw <- new.CytoscapeWindow ('unhideAll.test', graph=makeSimpleGraph())
displayGraph (cw)
layout (cw, 'jgraph-spring')
redraw (cw)
clearSelection (cw)
selectNodes (cw, 'A')
hideSelectedNodes (cw)
system ('sleep 2')
unhideAll (cw)
```

`validCyWin`*validCyWin*

Description

Checks all the slots of the object, printing error messages as needed, returning TRUE or FALSE. In particular, RCytoscape imposes some requirements on graphs, including the use of an 'edgeType' edge attribute, and a call to `initNodeAttribute` and `initEdgeAttribute` for every attribute. These requirements are checked here.

Usage

```
validCyWin(obj)
```

Arguments

`obj` An instance of the CytoscapeWindow class

Value

TRUE or FALSE. Error messages are written to stderr.

Author(s)

Paul Shannon

Examples

```
g <- new ('graphNEL', edgemode='directed')
cw <- new.CytoscapeWindow ('test validCyWin', graph=g)
validCyWin (cw) # should see warning about absence of the privileged edge attribute 'e
```

`version``version`

Description

Test the connection to Cytoscape.

Usage

```
version(obj)
```

Arguments

`obj` a `CytoscapeConnectionClass` object.

Value

"A string describing the current version of the CytoscapeRPC plugin."

Author(s)

Paul Shannon

Examples

```
cy <- CytoscapeConnection ()
print (version (cy))
# e.g., "1.3.2"
```

Index

*Topic classes

CytoscapeConnectionClass-class, 2

CytoscapeWindowClass-class, 4

*Topic graphs

CytoscapeConnectionClass-class, 2

CytoscapeWindowClass-class, 4

*Topic graph

addCyEdge, 5

addCyNode, 6

addGraphToGraph, 7

clearMsg, 8

clearSelection, 9

copyVisualStyle, 9

createWindow, 11

createWindowFromSelection, 11

cy2.edge.names, 12

CytoscapeConnection, 1

CytoscapeWindow, 3

deleteAllWindows, 13

deleteEdgeAttribute, 14

deleteNodeAttribute, 15

deleteSelectedEdges, 16

deleteSelectedNodes, 16

deleteWindow, 17

demoSimpleGraph, 18

displayGraph, 19

dockPanel, 19

eda, 20

eda.names, 21

existing.CytoscapeWindow, 22

fitContent, 23

fitSelectedContent, 23

floatPanel, 24

getAllEdgeAttributes, 25

getAllEdges, 26

getAllNodeAttributes, 26

getAllNodes, 27

getArrowShapes, 28

getAttributeClassNames, 28

getCenter, 29

getDefaultBackgroundColor, 30

getDefaultEdgeReverseSelectionColor, 30

getDefaultEdgeSelectionColor, 31

getDefaultNodeReverseSelectionColor, 32

getDefaultNodeSelectionColor, 32

getDirectlyModifiableVisualProperties, 33

getEdgeAttribute, 34

getEdgeAttributeNames, 35

getEdgeCount, 35

getFirstNeighbors, 36

getGraph, 37

getGraphFromCyWindow, 37

getLayoutNameMapping, 38

getLayoutNames, 39

getLayoutPropertyNames, 39

getLayoutPropertyType, 40

getLayoutPropertyValue, 41

getLineStyle, 42

getNodeAttribute, 42

getNodeAttributeNames, 43

getNodeCount, 44

getNodeShapes, 45

getPosition, 45

getSelectedEdgeCount, 46

getSelectedEdges, 47

getSelectedNodeCount, 47

getSelectedNodes, 48

getViewCoordinates, 49

getVisualStyleNames, 49

getWindowCount, 50

getWindowID, 51

getWindowList, 51

getZoom, 52

hideAllPanels, 53

hideNodes, 53

hidePanel, 54

hideSelectedEdges, 55

hideSelectedNodes, 56

initEdgeAttribute, 56

- initNodeAttribute, [57](#)
- invertEdgeSelection, [58](#)
- invertNodeSelection, [59](#)
- layout, [59](#)
- lockNodeDimensions, [60](#)
- makeRandomGraph, [61](#)
- makeSimpleGraph, [62](#)
- msg, [63](#)
- new.CytoscapeWindow, [64](#)
- noa, [65](#)
- noa.names, [65](#)
- ping, [66](#)
- raiseWindow, [67](#)
- redraw, [67](#)
- restoreLayout, [68](#)
- saveImage, [69](#)
- saveLayout, [70](#)
- saveNetwork, [70](#)
- selectEdges, [71](#)
- selectFirstNeighborsOfSelectedNodes, [72](#)
- selectNodes, [73](#)
- sendEdges, [74](#)
- sendNodes, [74](#)
- setCenter, [75](#)
- setDefaultBackgroundColor, [76](#)
- setDefaultEdgeColor, [77](#)
- setDefaultEdgeLineWidth, [78](#)
- setDefaultEdgeReverseSelectionColor, [79](#)
- setDefaultEdgeSelectionColor, [79](#)
- setDefaultNodeBorderColor, [80](#)
- setDefaultNodeBorderWidth, [81](#)
- setDefaultNodeColor, [82](#)
- setDefaultNodeFontSize, [83](#)
- setDefaultNodeLabelColor, [84](#)
- setDefaultNodeReverseSelectionColor, [85](#)
- setDefaultNodeSelectionColor, [85](#)
- setDefaultNodeShape, [86](#)
- setDefaultNodeSize, [87](#)
- setEdgeAttributes, [88](#)
- setEdgeAttributesDirect, [88](#)
- setEdgeColorDirect, [89](#)
- setEdgeColorRule, [90](#)
- setEdgeFontSizeDirect, [91](#)
- setEdgeLabelColorDirect, [92](#)
- setEdgeLabelDirect, [93](#)
- setEdgeLabelOpacityDirect, [94](#)
- setEdgeLabelRule, [95](#)
- setEdgeLabelWidthDirect, [95](#)
- setEdgeLineStyleDirect, [96](#)
- setEdgeLineStyleRule, [98](#)
- setEdgeLineWidthDirect, [99](#)
- setEdgeLineWidthRule, [100](#)
- setEdgeOpacityDirect, [101](#)
- setEdgeSourceArrowColorDirect, [102](#)
- setEdgeSourceArrowColorRule, [103](#)
- setEdgeSourceArrowOpacityDirect, [104](#)
- setEdgeSourceArrowRule, [105](#)
- setEdgeSourceArrowShapeDirect, [106](#)
- setEdgeTargetArrowColorDirect, [107](#)
- setEdgeTargetArrowColorRule, [108](#)
- setEdgeTargetArrowOpacityDirect, [109](#)
- setEdgeTargetArrowRule, [110](#)
- setEdgeTargetArrowShapeDirect, [111](#)
- setEdgeTooltipDirect, [112](#)
- setEdgeTooltipRule, [113](#)
- setGraph, [114](#)
- setLayoutProperties, [115](#)
- setNodeAttributes, [116](#)
- setNodeAttributesDirect, [117](#)
- setNodeBorderColorDirect, [118](#)
- setNodeBorderColorRule, [118](#)
- setNodeBorderOpacityDirect, [120](#)
- setNodeBorderWidthDirect, [121](#)
- setNodeBorderWidthRule, [122](#)
- setNodeColorDirect, [123](#)
- setNodeColorRule, [124](#)
- setNodeFillOpacityDirect, [125](#)
- setNodeFontSizeDirect, [126](#)
- setNodeHeightDirect, [127](#)
- setNodeImageDirect, [128](#)
- setNodeLabelColorDirect, [128](#)
- setNodeLabelDirect, [129](#)
- setNodeLabelOpacityDirect, [130](#)
- setNodeLabelRule, [131](#)
- setNodeOpacityDirect, [132](#)
- setNodeShapeDirect, [133](#)
- setNodeShapeRule, [133](#)
- setNodeSizeDirect, [134](#)
- setNodeSizeRule, [135](#)

- setNodeTooltipRule, 136
 - setNodeWidthDirect, 137
 - setPosition, 138
 - setTooltipDismissDelay, 139
 - setTooltipInitialDelay, 140
 - setVisualStyle, 141
 - setWindowSize, 142
 - setZoom, 143
 - showGraphicsDetails, 144
 - unhideAll, 144
 - validCyWin, 145
 - version, 146
- addCyEdge, 5
- addCyEdge, CytoscapeWindowClass-method
(*addCyEdge*), 5
- addCyNode, 6
- addCyNode, CytoscapeWindowClass-method
(*addCyNode*), 6
- addGraphToGraph, 7
- addGraphToGraph, CytoscapeWindowClass-method
(*addGraphToGraph*), 7
- clearMsg, 8
- clearMsg, CytoscapeConnectionClass-method
(*clearMsg*), 8
- clearSelection, 9
- clearSelection, CytoscapeWindowClass-method
(*clearSelection*), 9
- copyVisualStyle, 9
- copyVisualStyle, CytoscapeConnectionClass-method
(*copyVisualStyle*), 9
- createWindow, 11
- createWindow, CytoscapeWindowClass-method
(*createWindow*), 11
- createWindowFromSelection, 11
- createWindowFromSelection, CytoscapeWindowClass-method
(*createWindowFromSelection*), 11
- cy2.edge.names, 12
- CytoscapeConnection, 1
- CytoscapeConnectionClass-class, 2
- CytoscapeWindow, 3
- CytoscapeWindowClass-class, 4
- deleteAllWindows, 13
- deleteAllWindows, CytoscapeConnectionClass-method
(*deleteAllWindows*), 13
- deleteEdgeAttribute, 14
- deleteEdgeAttribute, CytoscapeConnectionClass-method
(*deleteEdgeAttribute*), 14
- deleteNodeAttribute, 15
- deleteNodeAttribute, CytoscapeConnectionClass-method
(*deleteNodeAttribute*), 15
- deleteSelectedEdges, 16
- deleteSelectedEdges, CytoscapeWindowClass-method
(*deleteSelectedEdges*), 16
- deleteSelectedNodes, 16
- deleteSelectedNodes, CytoscapeWindowClass-method
(*deleteSelectedNodes*), 16
- deleteWindow, 17
- deleteWindow, CytoscapeConnectionClass-method
(*deleteWindow*), 17
- demoSimpleGraph, 18
- displayGraph, 19
- displayGraph, CytoscapeWindowClass-method
(*displayGraph*), 19
- dockPanel, 19
- dockPanel, CytoscapeConnectionClass-method
(*dockPanel*), 19
- eda, 20
- edges, 21
- existing.CytoscapeWindow, 22
- fitContent, 23
- fitContent, CytoscapeWindowClass-method
(*fitContent*), 23
- fitSelectedContent, 23
- fitSelectedContent, CytoscapeWindowClass-method
(*fitSelectedContent*), 23
- floatPanel, 24
- floatPanel, CytoscapeConnectionClass-method
(*floatPanel*), 24
- getAllEdgeAttributes, 25
- getAllEdgeAttributes, CytoscapeWindowClass-method
(*getAllEdgeAttributes*), 25
- getAllEdges, 26
- getAllEdges, CytoscapeWindowClass-method
(*getAllEdges*), 26
- getAllNodeAttributes, 26
- getAllNodeAttributes, CytoscapeWindowClass-method
(*getAllNodeAttributes*), 26
- getAllNodes, 27
- getAllNodes, CytoscapeWindowClass-method
(*getAllNodes*), 27
- getArrowShapes, 28, 105, 111
- getArrowShapes, CytoscapeConnectionClass-method
(*getArrowShapes*), 28
- getAttributeClassNames, 28
- getAttributeClassNames, CytoscapeConnectionClass-method
(*getAttributeClassNames*), 28
- getCenter, 29

- getCenter, CytoscapeWindowClass-method
 (*getCenter*), 29
- getDefaultBackgroundColor, 30
- getDefaultBackgroundColor, CytoscapeConnectionClass-method
 (*getDefaultBackgroundColor*), 30
- getDefaultEdgeReverseSelectionColor, 30
- getDefaultEdgeReverseSelectionColor, CytoscapeConnectionClass-method
 (*getDefaultEdgeReverseSelectionColor*), 30
- getDefaultEdgeSelectionColor, 31
- getDefaultEdgeSelectionColor, CytoscapeConnectionClass-method
 (*getDefaultEdgeSelectionColor*), 31
- getDefaultNodeReverseSelectionColor, 32
- getDefaultNodeReverseSelectionColor, CytoscapeConnectionClass-method
 (*getDefaultNodeReverseSelectionColor*), 32
- getDefaultNodeSelectionColor, 32
- getDefaultNodeSelectionColor, CytoscapeConnectionClass-method
 (*getDefaultNodeSelectionColor*), 32
- getDirectlyModifiableVisualProperties, 33
- getDirectlyModifiableVisualProperties, CytoscapeConnectionClass-method
 (*getDirectlyModifiableVisualProperties*), 33
- getEdgeAttribute, 34
- getEdgeAttribute, CytoscapeConnectionClass-method
 (*getEdgeAttribute*), 34
- getEdgeAttributeNames, 35
- getEdgeAttributeNames, CytoscapeConnectionClass-method
 (*getEdgeAttributeNames*), 35
- getEdgeCount, 35
- getEdgeCount, CytoscapeWindowClass-method
 (*getEdgeCount*), 35
- getFirstNeighbors, 36
- getFirstNeighbors, CytoscapeWindowClass-method
 (*getFirstNeighbors*), 36
- getGraph, 37
- getGraph, CytoscapeWindowClass-method
 (*getGraph*), 37
- getGraphFromCyWindow, 37
- getGraphFromCyWindow, CytoscapeConnectionClass-method
 (*getGraphFromCyWindow*), 37
- getLayoutNameMapping, 38
- getLayoutNameMapping, CytoscapeConnectionClass-method
 (*getLayoutNameMapping*), 38
- getLayoutNames, 39
- getLayoutNames, CytoscapeConnectionClass-method
 (*getLayoutNames*), 39
- getLayoutPropertyNames, 39
- getLayoutPropertyNames, CytoscapeConnectionClass-method
 (*getLayoutPropertyNames*), 39
- getLayoutPropertyType, 40
- getLayoutPropertyType, CytoscapeConnectionClass-method
 (*getLayoutPropertyType*), 40
- getLayoutPropertyValue, 41
- getLayoutPropertyValue, CytoscapeConnectionClass-method
 (*getLayoutPropertyValue*), 41
- getLineStyle, 42
- getLineStyle, CytoscapeConnectionClass-method
 (*getLineStyle*), 42
- getNodeAttribute, 42
- getNodeAttribute, CytoscapeConnectionClass-method
 (*getNodeAttribute*), 42
- getNodeAttributeNames, 43
- getNodeAttributeNames, CytoscapeConnectionClass-method
 (*getNodeAttributeNames*), 43
- getNodeCount, 44
- getNodeCount, CytoscapeWindowClass-method
 (*getNodeCount*), 44
- getNodeShapes, 45
- getNodeShapes, CytoscapeConnectionClass-method
 (*getNodeShapes*), 45
- getOrientation, 45
- getOrientation, CytoscapeWindowClass-method
 (*getOrientation*), 45
- getSelectedEdgeCount, 46
- getSelectedEdgeCount, CytoscapeWindowClass-method
 (*getSelectedEdgeCount*), 46
- getSelectedEdges, 47
- getSelectedEdges, CytoscapeWindowClass-method
 (*getSelectedEdges*), 47
- getSelectedNodeCount, 47
- getSelectedNodeCount, CytoscapeWindowClass-method
 (*getSelectedNodeCount*), 47
- getSelectedNodes, 48
- getSelectedNodes, CytoscapeWindowClass-method
 (*getSelectedNodes*), 48
- getViewCoordinates, 49
- getViewCoordinates, CytoscapeWindowClass-method
 (*getViewCoordinates*), 49
- getWindowCount, 50
- getWindowCount, CytoscapeConnectionClass-method
 (*getWindowCount*), 50
- getWindowID, 51

- getWindowID, CytoscapeConnectionClass-method (getWindowID), 51
- getWindowList, 51
- getWindowList, CytoscapeConnectionClass-method (getWindowList), 51
- getZoom, 52
- getZoom, CytoscapeWindowClass-method (getZoom), 52
- hideAllPanels, 53
- hideAllPanels, CytoscapeConnectionClass-method (hideAllPanels), 53
- hideNodes, 53
- hideNodes, CytoscapeWindowClass-method (hideNodes), 53
- hidePanel, 54
- hidePanel, CytoscapeConnectionClass-method (hidePanel), 54
- hideSelectedEdges, 55
- hideSelectedEdges, CytoscapeWindowClass-method (hideSelectedEdges), 55
- hideSelectedNodes, 56
- hideSelectedNodes, CytoscapeWindowClass-method (hideSelectedNodes), 56
- initEdgeAttribute, 56
- initNodeAttribute, 57
- invertEdgeSelection, 58
- invertEdgeSelection, CytoscapeWindowClass-method (invertEdgeSelection), 58
- invertNodeSelection, 59
- invertNodeSelection, CytoscapeWindowClass-method (invertNodeSelection), 59
- layout, 59
- layout, CytoscapeWindowClass-method (layout), 59
- lockNodeDimensions, 60
- lockNodeDimensions, CytoscapeConnectionClass-method (lockNodeDimensions), 60
- makeRandomGraph, 61
- makeSimpleGraph, 62
- msg, 63
- msg, CytoscapeConnectionClass-method (msg), 63
- new.CytoscapeWindow, 64
- noa, 65
- noa.names, 65
- ping, 66
- ping, CytoscapeConnectionClass-method (ping), 66
- raiseWindow, 67
- raiseWindow, CytoscapeConnectionClass-method (raiseWindow), 67
- redraw, 67
- redraw, CytoscapeWindowClass-method (redraw), 67
- restoreLayout, 68
- restoreLayout, CytoscapeWindowClass-method (restoreLayout), 68
- saveImage, 69
- saveImage, CytoscapeWindowClass-method (saveImage), 69
- saveLayout, 70
- saveLayout, CytoscapeWindowClass-method (saveLayout), 70
- saveNetwork, 70
- saveNetwork, CytoscapeWindowClass-method (saveNetwork), 70
- selectEdges, 71
- selectEdges, CytoscapeWindowClass-method (selectEdges), 71
- selectFirstNeighborsOfSelectedNodes, 72
- selectFirstNeighborsOfSelectedNodes, CytoscapeWindowClass-method (selectFirstNeighborsOfSelectedNodes), 72
- selectNodes, 73
- selectNodes, CytoscapeWindowClass-method (selectNodes), 73
- sendEdges, 74
- sendEdges, CytoscapeWindowClass-method (sendEdges), 74
- sendNodes, 74
- sendNodes, CytoscapeWindowClass-method (sendNodes), 74
- setCenter, 75
- setCenter, CytoscapeWindowClass-method (setCenter), 75
- setDefaultBackgroundColor, 76
- setDefaultBackgroundColor, CytoscapeConnectionClass-method (setDefaultBackgroundColor), 76
- setDefaultEdgeColor, 77
- setDefaultEdgeColor, CytoscapeConnectionClass-method (setDefaultEdgeColor), 77
- setDefaultEdgeLineWidth, 78
- setDefaultEdgeLineWidth, CytoscapeConnectionClass-method (setDefaultEdgeLineWidth), 78
- setDefaultEdgeReverseSelectionColor, 79

- setDefaultEdgeReverseSelectionColor, CytoscapeWindowClass-method
 (*setDefaultEdgeReverseSelectionColor*), (*setEdgeColorRule*), 90
 79
- setDefaultEdgeSelectionColor, 79
- setDefaultEdgeSelectionColor, CytoscapeConnectionClass-method
 (*setDefaultEdgeSelectionColor*), (*setEdgeFontSizeDirect*), 91
 79
- setDefaultNodeBorderColor, 80
- setDefaultNodeBorderColor, CytoscapeConnectionClass-method
 (*setDefaultNodeBorderColor*), (*setEdgeLabelColorDirect*), 92
 80
- setDefaultNodeBorderWidth, 81
- setDefaultNodeBorderWidth, CytoscapeConnectionClass-method
 (*setDefaultNodeBorderWidth*), (*setEdgeLabelDirect*), 93
 81
- setDefaultNodeColor, 82
- setDefaultNodeColor, CytoscapeConnectionClass-method
 (*setDefaultNodeColor*), (*setEdgeLabelOpacityDirect*), 94
 82
- setDefaultNodeFontSize, 83
- setDefaultNodeFontSize, CytoscapeConnectionClass-method
 (*setDefaultNodeFontSize*), (*setEdgeLabelRule*), 95
 83
- setDefaultNodeLabelColor, 84
- setDefaultNodeLabelColor, CytoscapeConnectionClass-method
 (*setDefaultNodeLabelColor*), (*setEdgeLabelWidthDirect*), 95
 84
- setDefaultNodeReverseSelectionColor, 85
- setDefaultNodeReverseSelectionColor, CytoscapeConnectionClass-method
 (*setDefaultNodeReverseSelectionColor*), (*setEdgeLineStyleDirect*), 96
 85
- setDefaultNodeReverseSelectionColor, CytoscapeWindowClass-method
 (*setDefaultNodeReverseSelectionColor*), (*setEdgeLineStyleRule*), 98
 85
- setDefaultNodeSelectionColor, 85
- setDefaultNodeSelectionColor, CytoscapeConnectionClass-method
 (*setDefaultNodeSelectionColor*), (*setEdgeLineWidthDirect*), 99
 85
- setDefaultNodeShape, 86
- setDefaultNodeShape, CytoscapeConnectionClass-method
 (*setDefaultNodeShape*), (*setEdgeLineWidthRule*), 100
 86
- setDefaultNodeSize, 87
- setDefaultNodeSize, CytoscapeConnectionClass-method
 (*setDefaultNodeSize*), (*setEdgeOpacityDirect*), 101
 87
- setEdgeAttributes, 88
- setEdgeAttributes, CytoscapeWindowClass-method
 (*setEdgeAttributes*), 88
- setEdgeAttributesDirect, 88
- setEdgeAttributesDirect, CytoscapeWindowClass-method
 (*setEdgeAttributesDirect*), 88
- setEdgeColorDirect, 89
- setEdgeColorDirect, CytoscapeWindowClass-method
 (*setEdgeColorDirect*), 89
- setEdgeColorRule, 90
- setEdgeFontSizeDirect, 91
- setEdgeFontSizeDirect, CytoscapeWindowClass-method
 (*setEdgeFontSizeDirect*), 91
- setEdgeLabelColorDirect, 92
- setEdgeLabelColorDirect, CytoscapeWindowClass-method
 (*setEdgeLabelColorDirect*), 92
- setEdgeLabelDirect, 93
- setEdgeLabelDirect, CytoscapeWindowClass-method
 (*setEdgeLabelDirect*), 93
- setEdgeLabelOpacityDirect, 94
- setEdgeLabelOpacityDirect, CytoscapeWindowClass-method
 (*setEdgeLabelOpacityDirect*), 94
- setEdgeLabelRule, 95
- setEdgeLabelRule, CytoscapeWindowClass-method
 (*setEdgeLabelRule*), 95
- setEdgeLabelWidthDirect, 95
- setEdgeLabelWidthDirect, CytoscapeWindowClass-method
 (*setEdgeLabelWidthDirect*), 95
- setEdgeLineStyleDirect, 96
- setEdgeLineStyleDirect, CytoscapeWindowClass-method
 (*setEdgeLineStyleDirect*), 96
- setEdgeLineStyleRule, 98
- setEdgeLineStyleRule, CytoscapeWindowClass-method
 (*setEdgeLineStyleRule*), 98
- setEdgeLineWidthDirect, 99
- setEdgeLineWidthDirect, CytoscapeWindowClass-method
 (*setEdgeLineWidthDirect*), 99
- setEdgeLineWidthRule, 100
- setEdgeLineWidthRule, CytoscapeWindowClass-method
 (*setEdgeLineWidthRule*), 100
- setEdgeOpacityDirect, 101
- setEdgeOpacityDirect, CytoscapeWindowClass-method
 (*setEdgeOpacityDirect*), 101
- setEdgeSourceArrowColorDirect, 102
- setEdgeSourceArrowColorDirect, CytoscapeWindowClass-method
 (*setEdgeSourceArrowColorDirect*), 102
- setEdgeSourceArrowColorRule, 103, 109
- setEdgeSourceArrowColorRule, CytoscapeWindowClass-method
 (*setEdgeSourceArrowColorRule*), 103, 109
- setEdgeSourceArrowOpacityDirect, 104

- setEdgeSourceArrowOpacityDirect, CytoscapeWindowClass-method
 (setEdgeSourceArrowOpacityDirect), 117
 104 setNodeBorderColorDirect, 118
- setEdgeSourceArrowRule, 105 setNodeBorderColorDirect, CytoscapeWindowClass-
 method (setNodeBorderColorDirect),
 setEdgeSourceArrowRule, CytoscapeWindowClass-method
 (setEdgeSourceArrowRule), 118
 105 setNodeBorderColorRule, 118
- setEdgeSourceArrowShapeDirect, setNodeBorderColorRule, CytoscapeWindowClass-
 method (setNodeBorderColorRule),
 106 118
- setEdgeSourceArrowShapeDirect, CytoscapeWindowClass-method
 (setEdgeSourceArrowShapeDirect), setNodeBorderOpacityDirect, 120
 106 setNodeBorderOpacityDirect, CytoscapeWindowClass-
 method (setNodeBorderOpacityDirect),
 setEdgeTargetArrowColorDirect, 120
- setEdgeTargetArrowColorDirect, CytoscapeWindowClass-method
 (setEdgeTargetArrowColorDirect), setNodeBorderWidthDirect, CytoscapeWindowClass-
 method (setNodeBorderWidthDirect),
 107 121
- setEdgeTargetArrowColorRule, 108 121
- setEdgeTargetArrowColorRule, CytoscapeWindowClass-method
 (setEdgeTargetArrowColorRule), setNodeBorderWidthRule, CytoscapeWindowClass-
 method (setNodeBorderWidthRule),
 108 122
- setEdgeTargetArrowOpacityDirect, 122
- setEdgeTargetArrowOpacityDirect, CytoscapeWindowClass-method
 (setEdgeTargetArrowOpacityDirect), (setNodeColorDirect), 123
 109 setNodeColorDirect, 123
- setEdgeTargetArrowRule, 110 setNodeColorRule, 124
- setEdgeTargetArrowRule, CytoscapeWindowClass-method
 (setEdgeTargetArrowRule), setNodeColorRule, CytoscapeWindowClass-method
 (setNodeColorRule), 124
 110 setNodeFillOpacityDirect, 125
- setEdgeTargetArrowShapeDirect, setNodeFillOpacityDirect, CytoscapeWindowClass-
 method (setNodeFillOpacityDirect),
 111 125
- setEdgeTargetArrowShapeDirect, CytoscapeWindowClass-method
 (setEdgeTargetArrowShapeDirect), setNodeFontSizeDirect, CytoscapeWindowClass-
 method (setNodeFontSizeDirect),
 111 126
- setEdgeTooltipDirect, 112 126
- setEdgeTooltipDirect, CytoscapeWindowClass-method
 (setEdgeTooltipDirect), 112 setNodeHeightDirect, 127
- setEdgeTooltipRule, 113 (setNodeHeightDirect), 127
- setEdgeTooltipRule, CytoscapeWindowClass-method
 (setEdgeTooltipRule), 113 setNodeImageDirect, 128
- setGraph, 114 (setNodeImageDirect), 128
- setGraph, CytoscapeWindowClass-method
 (setGraph), 114 setNodeLabelColorDirect, 128
- setLayoutProperties, 115 setNodeLabelColorDirect, CytoscapeWindowClass-
 method (setNodeLabelColorDirect),
 setLayoutProperties, CytoscapeConnectionClass-method
 (setLayoutProperties), 115 128
- setNodeAttributes, 116 setNodeLabelDirect, 129
- setNodeAttributes, CytoscapeWindowClass-method
 (setNodeAttributes), 116 (setNodeLabelDirect), 129
- setNodeAttributesDirect, 117 setNodeLabelOpacityDirect, 130
- setNodeAttributesDirect, CytoscapeWindowClass-
 method (setNodeLabelOpacityDirect),
 setNodeAttributesDirect, CytoscapeWindowClass-method

130
 setNodeLabelRule, 131
 setNodeLabelRule, CytoscapeWindowClass-method
 (*setNodeLabelRule*), 131
 setNodeOpacityDirect, 132
 setNodeOpacityDirect, CytoscapeWindowClass-method
 (*setNodeOpacityDirect*), 132
 setNodeShapeDirect, 133
 setNodeShapeDirect, CytoscapeWindowClass-method
 (*setNodeShapeDirect*), 133
 setNodeShapeRule, 133
 setNodeShapeRule, CytoscapeWindowClass-method
 (*setNodeShapeRule*), 133
 setNodeSizeDirect, 134
 setNodeSizeDirect, CytoscapeWindowClass-method
 (*setNodeSizeDirect*), 134
 setNodeSizeRule, 135
 setNodeSizeRule, CytoscapeWindowClass-method
 (*setNodeSizeRule*), 135
 setNodeTooltipRule, 136
 setNodeTooltipRule, CytoscapeWindowClass-method
 (*setNodeTooltipRule*), 136
 setNodeWidthDirect, 137
 setNodeWidthDirect, CytoscapeWindowClass-method
 (*setNodeWidthDirect*), 137
 setPosition, 138
 setPosition, CytoscapeWindowClass-method
 (*setPosition*), 138
 setTooltipDismissDelay, 139
 setTooltipDismissDelay, CytoscapeConnectionClass-method
 (*setTooltipDismissDelay*),
 139
 setTooltipInitialDelay, 140
 setTooltipInitialDelay, CytoscapeConnectionClass-method
 (*setTooltipInitialDelay*),
 140
 setVisualStyle, 141
 setVisualStyle, CytoscapeConnectionClass-method
 (*setVisualStyle*), 141
 setWindowSize, 142
 setWindowSize, CytoscapeWindowClass-method
 (*setWindowSize*), 142
 setZoom, 143
 setZoom, CytoscapeWindowClass-method
 (*setZoom*), 143
 sfn
 (*selectFirstNeighborsOfSelectedNodes*),
 72
 sfn, CytoscapeWindowClass-method
 (*selectFirstNeighborsOfSelectedNodes*),
 72
 showGraphicsDetails, 144
 showGraphicsDetails, CytoscapeConnectionClass-method
 (*showGraphicsDetails*), 144
 unhideAll, 144
 unhideAll, CytoscapeWindowClass-method
 (*unhideAll*), 144
 validCyWin, 145
 version, 146
 version, CytoscapeConnectionClass-method
 (*version*), 146