

# Package ‘erccdashboard’

November 17, 2019

**Type** Package

**Title** Assess Differential Gene Expression Experiments with ERCC Controls

**Version** 1.20.0

**Author** Sarah Munro, Steve Lund

**Maintainer** Sarah Munro <sarah.munro@gmail.com>

**Description** Technical performance metrics for differential gene expression experiments using External RNA Controls Consortium (ERCC) spike-in ratio mixtures.

**URL** <https://github.com/munrosa/erccdashboard>,  
<http://tinyurl.com/erccsrn>

**BugReports** <https://github.com/munrosa/erccdashboard/issues>

**Depends** R (>= 3.2), ggplot2 (>= 2.1.0), gridExtra (>= 2.0.0)

**Imports** edgeR, gplots, grid, gtools, limma, locfit, MASS, plyr, qvalue, reshape2, ROCR, scales, stringr

**License** GPL (>=2)

**Collate** runDashboard.R initDat.R dashboardFile.R plotAdjust.R  
loadERCCInfo.R loadExpMeas.R getDesignMat.R normalizeDat.R  
prepERCCDat.R est\_r\_m.R dynRangePlot.R geneExprTest.R  
testDECount.R testDEArray.R erccROC.R estLODR.R printLODRres.R  
saveERCCPlots.R maSignal.R annotLODR.R

**biocViews** ImmunoOncology, GeneExpression, Transcription,  
AlternativeSplicing, DifferentialExpression,  
DifferentialSplicing, Genetics, Microarray, mRNAMicroarray,  
RNASeq, BatchEffect, MultipleComparison, QualityControl

**LazyData** yes

**Roxygen** list(wrap = FALSE)

**RoxygenNote** 5.0.1

**git\_url** <https://git.bioconductor.org/packages/erccdashboard>

**git\_branch** RELEASE\_3\_10

**git\_last\_commit** e2942b1

**git\_last\_commit\_date** 2019-10-29

**Date/Publication** 2019-11-16

## R topics documented:

|                                |           |
|--------------------------------|-----------|
| annotLODR . . . . .            | 2         |
| dynRangePlot . . . . .         | 3         |
| ERCC . . . . .                 | 4         |
| ERCCDef . . . . .              | 4         |
| ERCCMix1and2 . . . . .         | 5         |
| erccROC . . . . .              | 5         |
| estLODR . . . . .              | 6         |
| est_r_m . . . . .              | 7         |
| geneExprTest . . . . .         | 7         |
| initDat . . . . .              | 8         |
| maSignal . . . . .             | 9         |
| MET.CTL.countDat . . . . .     | 10        |
| MET.CTL.totalReads . . . . .   | 11        |
| runDashboard . . . . .         | 11        |
| saveERCCPlots . . . . .        | 12        |
| SEQC.Example . . . . .         | 13        |
| UHRR.HBRR.arrayDat . . . . .   | 14        |
| UHRR.HBRR.countDat . . . . .   | 14        |
| UHRR.HBRR.totalReads . . . . . | 15        |
| <b>Index</b>                   | <b>16</b> |

---

annotLODR

*Annotate signal-abundance and ratio-abundance plots with LODR*

---

### Description

Annotate signal-abundance and ratio-abundance plots with LODR

### Usage

```
annotLODR(exDat)
```

### Arguments

exDat            list, contains input data and stores analysis results

### Examples

```
data(SEQC.Example)
```

```
exDat <- initDat(datType="array", isNorm=FALSE,
  exTable=UHRR.HBRR.arrayDat,
  filenameRoot="testRun", sample1Name="UHRR",
  sample2Name="HBRR", erccmix="RatioPair",
  erccdilution = 1, spikeVol = 50,
  totalRNAmass = 2.5*10^(3), choseFDR=0.01)
```

```
exDat <- est_r_m(exDat)
```

```
exDat <- dynRangePlot(exDat)
```

```
exDat <- geneExprTest(exDat)
exDat <- estLODR(exDat, kind="ERCC", prob=0.9)
exDat <- annotLODR(exDat)
exDat$Figures$maPlot
```

---

|              |  |
|--------------|--|
| dynRangePlot | <i>Produce signal-abundance plot to evaluate dynamic range</i> |
|--------------|--|

---

### Description

Produce signal-abundance plot to evaluate dynamic range

### Usage

```
dynRangePlot(exDat, allPoints, labelReps)
```

### Arguments

|           |   |
|-----------|---|
| exDat     | list, contains input data and stores analysis results   |
| allPoints | boolean, default is false, means of replicates will be plotted. If true then all replicates will be plotted as individual points. |
| labelReps | boolean, default is false. If true then replicates will be labeled.   |

### Examples

```
data(SEQC.Example)
exDat <- initDat(datType="count", isNorm=FALSE, exTable=MET.CTL.countDat,
  filenameRoot="testRun", sample1Name="MET",
  sample2Name="CTL", erccmix="RatioPair",
  erccdilution=1/100, spikeVol=1, totalRNAmass=0.500,
  choseFDR=0.1)
exDat <- est_r_m(exDat)
exDat <- dynRangePlot(exDat, allPoints="FALSE", labelReps ="FALSE")
exDat$Figures$dynRangePlot
```

ERCC

*ERCC data*

---

**Description**

Contains 2 data frames: ERCCDef and ERCCMix1and2

**Usage**

```
data(ERCC)
```

**Examples**

```
data(ERCC)
```

---

ERCCDef

*ERCCDef dataframe*

---

**Description**

ERCC transcript lengths and GC content

**Format**

A data frame with 96 observations on the following 3 variables.

Feature a factor vector

Length a numeric vector

GC a numeric vector

**Details**

Length and GC content of all 96 ERCC controls in NIST SRM 2374

**Source**

<http://tinyurl.com/erccsrn>

---

|              |                               |
|--------------|-------------------------------|
| ERCCMix1and2 | <i>ERCCMix1and2 dataframe</i> |
|--------------|-------------------------------|

---

**Description**

Ambion RatioPair ERCC Mixtures

**Format**

A data frame with 96 observations on the following 4 variables.

ERCC.AMB.Expected a factor vector of all 96 ERCC control IDs

Subpool a factor vector of the ERCC Ratios in each Subpool with levels 4:1 1:1 1:1.5 1:2

Mix1Conc.Attomoles\_ul a numeric vector of the ERCC concentrations in Mix 1

Mix2Conc.Attomoles\_ul a numeric vector of the ERCC concentrations in Mix 2

**Source**

<http://www.lifetechnologies.com/order/catalog/product/4456739>

---

|         |   |
|---------|---|
| erccROC | <i>Produce Receiver Operator Characteristic (ROC) Curves and AUC statistics</i> |
|---------|---|

---

**Description**

Produce Receiver Operator Characteristic (ROC) Curves and AUC statistics

**Usage**

```
erccROC(exDat)
```

**Arguments**

exDat list, contains input data and stores analysis results

**Examples**

```
data(SEQC.Example)

exDat <- initDat(datType="array", isNorm=FALSE,
  exTable=UHRR.HBRR.arrayDat,
  filenameRoot="testRun", sample1Name="UHRR",
  sample2Name="HBRR", erccmix="RatioPair",
  erccdilution = 1, spikeVol = 50,
  totalRNAmass = 2.5*10^(3), choseFDR=0.01)

exDat <- est_r_m(exDat)
```

```

exDat <- dynRangePlot(exDat)

exDat <- geneExprTest(exDat)

exDat <- erccROC(exDat)

exDat$Figures$rocPlot

```

---

estLODR

*Estimate Limit of Detection of Ratios (LODR)*


---

## Description

Estimate Limit of Detection of Ratios (LODR)

## Usage

```
estLODR(exDat, kind = "ERCC", prob = 0.9)
```

## Arguments

|       |   |
|-------|---|
| exDat | list, contains input data and stores analysis results |
| kind  | "ERCC" or "Sim"                                       |
| prob  | probability, ranging from 0 - 1, default is 0.9       |

## Details

This is the function to estimate a limit of detection of ratios (LODR) for a chosen probability and threshold p-value for the fold changes in the ERCC control ratio mixtures.

## Examples

```

data(SEQC.Example)

exDat <- initDat(datType="array", isNorm=FALSE,
  exTable=UHRR.HBRR.arrayDat,
  filenameRoot="testRun", sample1Name="UHRR",
  sample2Name="HBRR", erccmix="RatioPair",
  erccdilution = 1, spikeVol = 50,
  totalRNAmass = 2.5*10^(3), choseFDR=0.01)

exDat <- est_r_m(exDat)

exDat <- dynRangePlot(exDat)

exDat <- geneExprTest(exDat)

exDat <- estLODR(exDat, kind = "ERCC", prob = 0.9)

exDat$Figures$lodrERCCPlot

```

---

|         |  |
|---------|--|
| est_r_m | <i>Estimate the mRNA fraction differences for the pair of samples using replicate data</i> |
|---------|--|

---

**Description**

Estimate the mRNA fraction differences for the pair of samples using replicate data

**Usage**

```
est_r_m(exDat)
```

**Arguments**

exDat            list, contains input data and stores analysis results

**Details**

This is the first function to run after an exDat structure is initialized using initDat, because it is needed for all additional analysis. An r\_m of 1 indicates that the two sample types under comparison have similar mRNA fractions of total RNA. The r\_m estimate is used to adjusted the expected ERCC mixture ratios in this analysis and may indicate a need for a different sample normalization approach.

**Examples**

```
data(SEQC.Example)

exDat <- initDat(datType="count", isNorm = FALSE, exTable=MET.CTL.countDat,
  filenameRoot = "testRun", sample1Name = "MET",
  sample2Name = "CTL", erccmix = "RatioPair",
  erccdilution = 1/100, spikeVol = 1, totalRNAmass = 0.500,
  choseFDR = 0.1)

exDat <- est_r_m(exDat)
```

---

|              |  |
|--------------|--|
| geneExprTest | <i>Prepare differential expression testing results for spike-in analysis</i> |
|--------------|--|

---

**Description**

Prepare differential expression testing results for spike-in analysis

**Usage**

```
geneExprTest(exDat)
```

**Arguments**

exDat            list, contains input data and stores analysis results

## Details

This function wraps the QuasiSeq differential expression testing package for `datType = "count"` or uses the limma package for differential expression testing if `datType = "array"`. Alternatively, for count data only, if correctly formatted DE test results are provided, then `geneExprTest` will bypass DE testing (with reduced runtime).

## Examples

```
data(SEQC.Example)

exDat <- initDat(datType="array", isNorm=FALSE,
                exTable=UHRR.HBRR.arrayDat,
                filenameRoot="testRun", sample1Name="UHRR",
                sample2Name="HBRR", erccmix="RatioPair",
                erccdilution = 1, spikeVol = 50,
                totalRNAmass = 2.5*10^(3), choseFDR=0.01)

exDat <- est_r_m(exDat)

exDat <- dynRangePlot(exDat)

exDat <- geneExprTest(exDat)
```

---

|                      |                                  |
|----------------------|----------------------------------|
| <code>initDat</code> | <i>Initialize the exDat list</i> |
|----------------------|----------------------------------|

---

## Description

Initialize the exDat list

## Usage

```
initDat(datType = NULL, isNorm = FALSE, exTable = NULL,
        repNormFactor = NULL, filenameRoot = NULL, sample1Name = NULL,
        sample2Name = NULL, erccmix = "RatioPair", erccdilution = 1,
        spikeVol = 1, totalRNAmass = 1, choseFDR = 0.05, ratioLim = c(-4, 4),
        signalLim = c(-14, 14), userMixFile = NULL)
```

## Arguments

|                      |  |
|----------------------|--|
| <code>datType</code> | type is "count" or "array", unnormalized data is expected (normalized data may be accepted in future version of the package). Default is "count" (integer count data), "array" is unnormalized fluorescent intensities from microarray fluorescent intensities (not log transformed or normalized) |
| <code>isNorm</code>  | default is FALSE, if FALSE then the unnormalized input data will be normalized in erccdashboard analysis. If TRUE then it is expected that the data is already normalized  |
| <code>exTable</code> | data frame, the first column contains names of genes or transcripts (Feature) and the remaining columns are counts for sample replicates spiked with ERCC controls   |



|               |  |
|---------------|--|
| repNormFactor | optional vector of normalization factors for each replicate, default value is NULL and 75th percentile normalization will be applied to replicates               |
| filenameRoot  | string root name for output files  |
| sample1Name   | string name for sample 1 in the gene expression experiment   |
| sample2Name   | string name for sample 2 in the gene expression experiment   |
| erccmix       | Name of ERCC mixture design, "RatioPair" is default, the other option is "Single"  |
| erccdilution  | unitless dilution factor used in dilution of the Ambion ERCC spike-in mixture solutions  |
| spikeVol      | volume in microliters of diluted ERCC mix spiked into the total RNA samples  |
| totalRNAmass  | mass in micrograms of total RNA spiked with diluted ERCC mixtures  |
| choseFDR      | False Discovery Rate for differential expression testing , default is 0.05   |
| ratioLim      | Limits for ratio axis on MA plot, default is c(-4,4)   |
| signalLim     | Limits for signal axis on dynamic range plot, default is c(-14,14)   |
| userMixFile   | optional filename input, default is NULL, if ERCC control ratio mixtures other than the Ambion product were used then a userMixFile can be used for the analysis |

## Examples

```
data(SEQC.Example)

exDat <- initDat(datType="count", isNorm = FALSE, exTable=MET.CTL.countDat,
                filenameRoot = "testRun", sample1Name = "MET",
                sample2Name = "CTL", erccmix = "RatioPair",
                erccdilution = 1/100, spikeVol = 1, totalRNAmass = 0.500,
                choseFDR = 0.1)

summary(exDat)
```

---

|          |  |
|----------|--|
| maSignal | <i>Generate MA plots with or without annotation using LODR estimates</i> |
|----------|--|

---

## Description

Generate MA plots with or without annotation using LODR estimates

## Usage

```
maSignal(exDat, alphaPoint = 0.8, r_mAdjust = TRUE, replicate = TRUE)
```

## Arguments

|            |   |
|------------|---|
| exDat      | list, contains input data and stores analysis results   |
| alphaPoint | numeric value, for alpha (transparency) for plotted points, range is 0 - 1  |
| r_mAdjust  | default is TRUE, if FALSE then the r_m estimate will not used to offset dashed lines for empirical ratios on figure |
| replicate  | default is TRUE, if FALSE then error bars will not be produced  |

**Examples**

```

data(SEQC.Example)

exDat <- initDat(datType="array", isNorm=FALSE,
                exTable=UHRR.HBRR.arrayDat,
                filenameRoot="testRun", sample1Name="UHRR",
                sample2Name="HBRR", erccmix="RatioPair",
                erccdilution = 1, spikeVol = 50,
                totalRNAmass = 2.5*10^(3), choseFDR=0.01)

exDat <- est_r_m(exDat)

exDat <- dynRangePlot(exDat)

exDat <- geneExprTest(exDat)
# generate MA plot without LODR annotation
exDat <- maSignal(exDat)

exDat$Figures$maPlot

exDat <- estLODR(exDat, kind = "ERCC", prob = 0.9)

# Include LODR annotation
exDat <- annotLODR(exDat)

exDat$Figures$maPlot

```

---

MET.CTL.countDat

*Rat toxicogenomics count data*


---

**Description**

RNA-Seq count data from Methimazole and Control rat biological replicates

**Format**

A data frame with 16590 observations of the following 7 variables.

Feature a factor vector of all Endogenous and ERCC transcripts in the experiment

MET\_1 a numeric vector of counts from Methimazole treatment biological replicate 1

MET\_2 a numeric vector of counts from Methimazole treatment biological replicate 2

MET\_3 a numeric vector of counts from Methimazole treatment biological replicate 3

CTL\_1 a numeric vector of counts from Control biological replicate 1

CTL\_2 a numeric vector of counts from Control biological replicate 2

CTL\_3 a numeric vector of counts from Control biological replicate 3

---

|                    |   |
|--------------------|---|
| MET.CTL.totalReads | <i>Rat toxicogenomics total read data</i> |
|--------------------|---|

---

**Description**

Total reads per biological replicate from FASTQ files

**Format**

The format is: int [1:6] 41423502 46016148 44320280 38400362 47511484 33910098

---

|              |  |
|--------------|--|
| runDashboard | <i>Run default erccdashboard analysis of ERCC control ratio mixtures</i> |
|--------------|--|

---

**Description**

Run default erccdashboard analysis of ERCC control ratio mixtures

**Usage**

```
runDashboard(datType = NULL, isNorm = FALSE, exTable = NULL,
  repNormFactor = NULL, filenameRoot = NULL, sample1Name = NULL,
  sample2Name = NULL, erccmix = "RatioPair", erccdilution = 1,
  spikeVol = 1, totalRNAmass = 1, choseFDR = 0.05, ratioLim = c(-4, 4),
  signalLim = c(-14, 14), userMixFile = NULL)
```

**Arguments**

|               |  |
|---------------|--|
| datType       | type is "count" (RNA-Seq) or "array" (microarray), "count" is unnormalized integer count data (normalized RNA-Seq data will be accepted in an updated version of the package), "array" can be normalized or unnormalized fluorescent intensities from a microarray experiment. |
| isNorm        | default is FALSE, if FALSE then the unnormalized input data will be normalized in erccdashboard analysis. If TRUE then it is expected that the data is already normalized  |
| exTable       | data frame, the first column contains names of genes or transcripts (Feature) and the remaining columns are expression measures for sample replicates spiked with ERCC controls  |
| repNormFactor | optional vector of normalization factors for each replicate, default value is NULL and 75th percentile normalization will be applied to replicates   |
| filenameRoot  | string root name for output files  |
| sample1Name   | string name for sample 1 in the gene expression experiment   |
| sample2Name   | string name for sample 2 in the gene expression experiment   |
| erccmix       | Name of ERCC mixture design, "RatioPair" is default, the other option is "Single"  |
| erccdilution  | unitless dilution factor used in dilution of the Ambion ERCC spike-in mixture solutions  |

|              |  |
|--------------|--|
| spikeVol     | volume in microliters of diluted ERCC mix spiked into the total RNA samples  |
| totalRNAmass | mass in micrograms of total RNA spiked with diluted ERCC mixtures  |
| choseFDR     | False Discovery Rate for differential expression testing   |
| ratioLim     | Limits for ratio axis on MA plot, default is c(-4,4)   |
| signalLim    | Limits for ratio axis on MA plot, default is c(-14,14)   |
| userMixFile  | optional filename input, default is NULL, if ERCC control ratio mixtures other than the Ambion product were used then a userMixFile can be used for the analysis |

## Examples

```
data(SEQC.Example)

exDat <- runDashboard(datType = "count", isNorm = FALSE,
                     exTable = MET.CTL.countDat,
                     filenameRoot = "COH.ILM",
                     sample1Name = "MET", sample2Name = "CTL",
                     erccmix = "RatioPair", erccdilution = 1/100,
                     spikeVol = 1, totalRNAmass = 0.500, choseFDR = 0.1)

summary(exDat)
```

---

|               |   |
|---------------|---|
| saveERCCPlots | <i>Save erccdashboard plots to a pdf file</i> |
|---------------|---|

---

## Description

The function savePlots will save selected figures to a pdf file. The default is the 4 manuscript figures to a single page (plotsPerPg = "manuscript"). If plotsPerPg = "single" then each plot is placed on an individual page. If plotlist is not defined (plotlist = NULL) or if plotlist = exDat\$Figures then all plots in exDat\$Figures are printed to a PDF file.

## Usage

```
saveERCCPlots(exDat, plotsPerPg = "main", saveas = "pdf", outName, plotlist,
              res)
```

## Arguments

|            |  |
|------------|--|
| exDat      | list, contains input data and stores analysis results  |
| plotsPerPg | string, if "main" then the 4 main plots are printed to one page, if "single" then a single plot is printed per page from the plotlist argument |
| saveas     | Choose file format from "pdf", "jpeg" or "png"   |
| outName    | Choose output file name, default will be fileName from exDat   |
| plotlist   | list, contains plots to print  |
| res        | Choose the file resolution   |

**Examples**

```

data(SEQC.Example)

exDat <- initDat(datType="count", isNorm=FALSE, exTable=MET.CTL.countDat,
                filenameRoot="testRun", sample1Name="MET",
                sample2Name="CTL", erccmix="RatioPair",
                erccdilution=1/100, spikeVol=1, totalRNAmass=0.500,
                choseFDR=0.1)

exDat <- est_r_m(exDat)

exDat <- dynRangePlot(exDat)

exDat <- geneExprTest(exDat)

exDat <- erccROC(exDat)

exDat <- estLODR(exDat, kind="ERCC", prob=0.9)

exDat <- annotLODR(exDat)

#to print 4 main plots to a single page pdf file
saveERCCPlots(exDat, plotsPerPg = "manuscript", saveas = "pdf")

#to print 4 plots to a jpeg file
saveERCCPlots(exDat, plotsPerPg = "manuscript", saveas = "jpeg")

# or to create a multiple page pdf of all plots produced
saveERCCPlots(exDat, plotsPerPg = "single", plotlist = exDat$Figures)

# or to create a multiple page pdf of just 2 plots
saveERCCPlots(exDat, plotsPerPg = "single",
              plotlist = list(exDat$Figures$lodrPlot, exDat$Figures$maPlot))

```

---

SEQC.Example

*Example data from SEQC project for erccdashboard analysis*

---

**Description**

Contains the following 5 items

- MET.CTL.countDat - Rat toxicogenomics count data
- MET.CTL.totalReads - Rat toxicogenomics total read data
- UHRR.HBRR.arrayDat - UHRR and HBRR Illumina BeadArray data
- UHRR.HBRR.countDat - UHRR and HBRR RNA-Seq Illumina count data
- UHRR.HBRR.totalReads - UHRR and HBRR sample total read data

**Usage**

```
data(SEQC.Example)
```

**Examples**

```
data(SEQC.Example)
```

---

```
UHRR.HBRR.arrayDat    UHRR and HBRR Illumina BeadArray data
```

---

**Description**

Unnormalized microarray data from Lab 13 of reference sample interlaboratory study

**Format**

A data frame with 17627 observations of the following 7 variables.

Feature a factor vector of all Endogenous and ERCC transcripts in the experiment

UHRR\_3 a numeric vector of fluorescence intensities from UHRR microarray technical replicate 1

UHRR\_2 a numeric vector of fluorescence intensities from UHRR microarray technical replicate 2

UHRR\_1 a numeric vector of fluorescence intensities from UHRR microarray technical replicate 3

HBRR\_3 a numeric vector of fluorescence intensities from HBRR microarray technical replicate 1

HBRR\_2 a numeric vector of fluorescence intensities from HBRR microarray technical replicate 2

HBRR\_1 a numeric vector of fluorescence intensities from HBRR microarray technical replicate 3

---

```
UHRR.HBRR.countDat    UHRR and HBRR RNA-Seq Illumina count data
```

---

**Description**

RNA-Seq count data from UHRR and HBRR interlaboratory study library replicates

**Format**

A data frame with 43919 observations of the following 9 variables.

Feature a character vector of all Endogenous and ERCC transcripts in the experiment

UHRR\_1 a numeric vector of counts from UHRR library preparation replicate 1

UHRR\_2 a numeric vector of counts from UHRR library preparation replicate 2

UHRR\_3 a numeric vector of counts from UHRR library preparation replicate 3

UHRR\_4 a numeric vector of counts from UHRR library preparation replicate 4

HBRR\_1 a numeric vector of counts from HBRR library preparation replicate 1

HBRR\_2 a numeric vector of counts from HBRR library preparation replicate 2

HBRR\_3 a numeric vector of counts from HBRR library preparation replicate 3

HBRR\_4 a numeric vector of counts from HBRR library preparation replicate 4

---

UHRR.HBRR.totalReads *UHRR and HBRR sample total read data*

---

**Description**

Total reads per library replicate from FASTQ files

**Format**

The format is: int [1:8] 138786892 256006510 199468322 431933806 247985592 219383270  
251265814 257508210

# Index

## \*Topic **datasets**

- ERCC, [4](#)
- ERCCDef, [4](#)
- ERCCMix1and2, [5](#)
- SEQC.Example, [13](#)
- UHRR.HBRR.arrayDat, [14](#)
- UHRR.HBRR.countDat, [14](#)

annotLODR, [2](#)

dynRangePlot, [3](#)

- ERCC, [4](#)
- ERCCDef, [4](#)
- ERCCMix1and2, [5](#)
- erccROC, [5](#)
- est\_r\_m, [7](#)
- estLODR, [6](#)

geneExprTest, [7](#)

initDat, [8](#)

- maSignal, [9](#)
- MET.CTL.countDat, [10](#)
- MET.CTL.totalReads, [11](#)

runDashboard, [11](#)

- saveERCCPlots, [12](#)
- SEQC.Example, [13](#)

- UHRR.HBRR.arrayDat, [14](#)
- UHRR.HBRR.countDat, [14](#)
- UHRR.HBRR.totalReads, [15](#)