

Package ‘DAPAR’

March 30, 2021

Type Package

Title Tools for the Differential Analysis of Proteins Abundance with R

Version 1.22.6

Date 2021-03-23

Author Samuel Wieczorek [cre,aut],
Florence Combes [aut],
Thomas Burger [aut],
Cosmin Lazar [ctb],
Alexia Dorffer [ctb],
Anais Courtier [ctb],
Helene Borges [ctb],
Enora Fremy [ctb]

Maintainer Samuel Wieczorek <samuel.wieczorek@cea.fr>

Description This package contains a collection of functions for the visualisation and the statistical analysis of proteomic data.

License Artistic-2.0

VignetteBuilder knitr

Depends R (>= 4.0.3)

Suggests BiocGenerics, testthat, BiocStyle

Imports Biobase, MSnbase, tibble, RColorBrewer, stats, preprocessCore, Cairo, png, lattice, reshape2, gplots, pcaMethods, ggplot2, limma, knitr, tmvtnorm, norm, impute, stringr, grDevices, graphics, openxlsx, utils, cp4p (>= 0.3.5), scales, Matrix, vioplot, imp4p (>= 0.8), forcats, methods, highcharter, DAPARdata (>= 1.18.0), siggenes, graph, lme4, readxl, clusterProfiler, dplyr, tidyr, AnnotationDbi, tidyverse, vsn, FactoMineR, factoextra, multcomp, purrr, visNetwork, foreach, parallel, doParallel, igraph, dendextend, Mfuzz, apcluster, diptest, cluster

biocViews Proteomics, Normalization, Preprocessing, MassSpectrometry, QualityControl, GO, DataImport

NeedsCompilation no

RoxygenNote 7.1.1

Encoding UTF-8

URL <http://www.prostar-proteomics.org/>

BugReports <https://github.com/samWieczorek/DAPAR/issues>

Collate ``agregation.R"``anova_analysis.R"``bioAnalysis.R"``
 ``clustering.R"``compute.t.tests.R"``DiffAnalysis.R"``
 ``get_pep_prot_cc.R"``inOutFiles.R"``limmaAnalysis.R"``
 ``logText.R"``missingValuesFilter.R"``
 ``missingValuesImputation_PeptideLevel.R"``
 ``missingValuesImputation_ProteinLevel.R"``missingValuesPlots.R"``
 ``normalize.R"``pepa.R"``plots_boxplot.R"``plots_compare_Norm.R"``
 ``plots_corr_matrix.R"``plots_density.R"``plots_density_CV.R"``
 ``plots_heatmaps.R"``plots_pca.R"``plots_violin.R"``utils.R"``
 ``volcanoPlot.R"``

git_url <https://git.bioconductor.org/packages/DAPAR>

git_branch RELEASE_3_12

git_last_commit 9f59cf1

git_last_commit_date 2021-03-23

Date/Publication 2021-03-29

R topics documented:

| | |
|---|----|
| addOriginOfValue | 5 |
| aggregateIter | 6 |
| aggregateIterParallel | 7 |
| aggregateMean | 8 |
| aggregateSum | 8 |
| aggregateTopn | 9 |
| averageIntensities | 10 |
| barplotEnrichGO_HC | 11 |
| barplotGroupGO_HC | 11 |
| boxPlotD_HC | 12 |
| BuildAdjacencyMatrix | 13 |
| BuildColumnToProteinDataset | 13 |
| BuildColumnToProteinDataset_par | 14 |
| buildGraph | 15 |
| BuildPalette | 16 |
| check.conditions | 16 |
| check.design | 17 |
| checkClusterability | 17 |
| classic1wayAnova | 18 |
| compareNormalizationD_HC | 19 |
| compute_t_tests | 20 |
| corrMatrixD_HC | 21 |
| CountPep | 22 |
| createMSnset | 22 |
| CVDistD | 24 |
| CVDistD_HC | 25 |
| dapar_hc_chart | 25 |
| dapar_hc_ExportMenu | 26 |
| deleteLinesFromIndices | 27 |
| densityPlotD | 28 |
| densityPlotD_HC | 28 |

| | |
|---------------------------------------|----|
| diffAnaComputeFDR | 29 |
| diffAnaGetSignificant | 30 |
| diffAnaSave | 31 |
| diffAnaVolcanoplot | 32 |
| diffAnaVolcanoplot_rCharts | 33 |
| display.CC.visNet | 34 |
| enrich_GO | 35 |
| finalizeAggregation | 36 |
| findMECBlock | 37 |
| formatLimmaResult | 37 |
| formatPHResults | 38 |
| fudge2LRT | 39 |
| get.pep.prot.cc | 40 |
| GetDetailedNbPeptides | 41 |
| GetDetailedNbPeptidesUsed | 41 |
| getIndicesConditions | 42 |
| getIndicesOfLinesToRemove | 43 |
| getListNbValuesInLines | 43 |
| GetNbPeptidesUsed | 44 |
| getNumberOf | 44 |
| getNumberOfEmptyLines | 45 |
| getPourcentageOfMV | 46 |
| getProcessingInfo | 46 |
| getProteinsStats | 47 |
| getQuantile4Imp | 47 |
| getTextForAggregation | 48 |
| getTextForAnaDiff | 49 |
| getTextForFiltering | 49 |
| getTextForGOAnalysis | 50 |
| getTextForHypothesisTest | 50 |
| getTextForNewDataset | 51 |
| getTextForNormalization | 51 |
| getTextForpeptideImputation | 52 |
| getTextForproteinImputation | 53 |
| Get_AllComparisons | 53 |
| GlobalQuantileAlignment | 54 |
| GOAnalysisSave | 55 |
| GraphPepProt | 56 |
| group_GO | 56 |
| hc_logFC_DensityPlot | 57 |
| hc_mvTypePlot2 | 58 |
| heatmap.DAPAR | 59 |
| heatmapD | 60 |
| histPValue_HC | 61 |
| impute.detQuant | 61 |
| impute.pa2 | 62 |
| inner.aggregate.iter | 63 |
| inner.aggregate.topn | 64 |
| inner.mean | 64 |
| inner.sum | 65 |
| is.MV | 65 |
| is.OfType | 66 |

| | |
|------------------------------------|-----|
| LH0 | 67 |
| LH0.lm | 67 |
| LH1 | 68 |
| LH1.lm | 68 |
| limmaCompleteTest | 69 |
| listSheets | 69 |
| LOESS | 70 |
| make.contrast | 71 |
| make.design | 71 |
| make.design.1 | 72 |
| make.design.2 | 73 |
| make.design.3 | 73 |
| MeanCentering | 74 |
| mvFilter | 75 |
| mvFilterFromIndices | 76 |
| mvFilterGetIndices | 77 |
| mvHisto_HC | 78 |
| mvImage | 79 |
| mvPerLinesHistoPerCondition_HC | 79 |
| mvPerLinesHisto_HC | 80 |
| my_hc_chart | 81 |
| my_hc_ExportMenu | 82 |
| nonzero | 82 |
| normalizeMethods.dapar | 83 |
| NumericalFiltering | 83 |
| NumericalgetIndicesOfLinesToRemove | 84 |
| pepa.test | 85 |
| plotJitter | 86 |
| plotJitter_rCharts | 86 |
| plotPCA_Eigen | 87 |
| plotPCA_Eigen_hc | 87 |
| plotPCA_Ind | 88 |
| plotPCA_Var | 89 |
| postHocTest | 89 |
| proportionConRev_HC | 90 |
| QuantileCentering | 91 |
| rbindMSnset | 92 |
| readExcel | 92 |
| reIntroduceMEC | 93 |
| removeLines | 94 |
| samLRT | 94 |
| saveParameters | 95 |
| scatterplotEnrichGO_HC | 96 |
| setMEC | 97 |
| splitAdjacencyMat | 97 |
| StringBasedFiltering | 98 |
| StringBasedFiltering2 | 99 |
| SumByColumns | 99 |
| test.design | 100 |
| translatedRandomBeta | 101 |
| univ_AnnotDbPkg | 101 |
| violinPlotD | 102 |

| | |
|--|-----|
| visualizeClusters | 103 |
| vsn | 104 |
| wrapper.compareNormalizationD_HC | 105 |
| wrapper.corrMatrixD_HC | 106 |
| wrapper.CVDistD | 107 |
| wrapper.CVDistD_HC | 107 |
| wrapper.dapar.impute.mi | 108 |
| wrapper.hc_mvTypePlot2 | 110 |
| wrapper.heatmapD | 110 |
| wrapper.impute.detQuant | 111 |
| wrapper.impute.fixedValue | 112 |
| wrapper.impute.KNN | 112 |
| wrapper.impute.mle | 113 |
| wrapper.impute.pa | 114 |
| wrapper.impute.pa2 | 114 |
| wrapper.impute.slsa | 115 |
| wrapper.mvHisto_HC | 116 |
| wrapper.mvImage | 117 |
| wrapper.mvPerLinesHistoPerCondition_HC | 117 |
| wrapper.mvPerLinesHisto_HC | 118 |
| wrapper.normalizedD | 119 |
| wrapper.pca | 120 |
| wrapper.CalibrationPlot | 120 |
| wrapperClassic1wayAnova | 121 |
| wrapperRunClustering | 122 |
| writeMSnsetToCSV | 124 |
| writeMSnsetToExcel | 124 |

Index 126

| | |
|------------------|--|
| addOriginOfValue | <i>Sets the OriginOfValues dataframe</i> |
|------------------|--|

Description

Sets the OriginOfValues dataframe in the fData table

Usage

```
addOriginOfValue(obj, names = NULL)
```

Arguments

| | |
|-------|----------------------------|
| obj | An object of class MSnSet |
| names | A list of integer xxxxxxxx |

Value

An instance of class MSnSet.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
addOriginOfValue(Exp1_R25_pept)
```

```
aggregateIter      .xxx
```

Description

Method to xxxxx

Usage

```
aggregateIter(obj.pep, X, init.method = "Sum", method = "Mean", n = NULL)
```

Arguments

```
obj.pep      xxxxx
X            xxxxx
init.method  xxxxx
method      xxxxx
n           xxxxx
```

Value

A protein object of class MSnset

Author(s)

Samuel Wieczorek

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
protID <- "Protein_group_IDs"
X <- BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], protID, FALSE)
aggregateIter(Exp1_R25_pept[1:1000],X=X)

## End(Not run)
```

`aggregateIterParallel xxxx`

Description

Method to xxxxx

Usage

```
aggregateIterParallel(  
  obj.pep,  
  X,  
  init.method = "Sum",  
  method = "Mean",  
  n = NULL  
)
```

Arguments

| | |
|--------------------------|-------|
| <code>obj.pep</code> | xxxxx |
| <code>X</code> | xxxx |
| <code>init.method</code> | xxxxx |
| <code>method</code> | xxxxx |
| <code>n</code> | xxxx |

Value

xxxxx

Author(s)

Samuel Wieczorek

Examples

```
## Not run:  
utils::data(Exp1_R25_pept, package='DAPARdata')  
protID <- "Protein_group_IDs"  
obj.pep <- Exp1_R25_pept[1:1000]  
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)  
aggregateIterParallel(obj.pep, X)  
  
## End(Not run)
```

| | |
|---------------|--|
| aggregateMean | <i>Compute the intensity of proteins as the mean of the intensities of their peptides.</i> |
|---------------|--|

Description

This function computes the intensity of proteins as the mean of the intensities of their peptides.

Usage

```
aggregateMean(obj.pep, X)
```

Arguments

| | |
|---------|--|
| obj.pep | A peptide object of class MSnset |
| X | An adjacency matrix in which lines and columns correspond respectively to peptides and proteins. |

Value

A matrix of intensities of proteins

Author(s)

Alexia Dorffer

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
obj.pep <- Exp1_R25_pept[1:1000]
protID <- "Protein_group_IDs"
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
aggregateMean(obj.pep, X)

## End(Not run)
```

| | |
|--------------|---|
| aggregateSum | <i>Compute the intensity of proteins with the sum of the intensities of their peptides.</i> |
|--------------|---|

Description

This function computes the intensity of proteins based on the sum of the intensities of their peptides.

Usage

```
aggregateSum(obj.pep, X)
```


Arguments

obj.pep A matrix of intensities of peptides
 X An adjacency matrix in which lines and columns correspond respectively to peptides and proteins.

Value

A matrix of intensities of proteins

Author(s)

Alexia Dorffer

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
protID <- "Protein_group_IDs"
obj.pep <- Exp1_R25_pept[1:1000]
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
DAPAR::aggregateSum(obj.pep, X)

## End(Not run)
```

| | |
|---------------|--|
| aggregateTopn | <i>Compute the intensity of proteins as the sum of the intensities of their n best peptides.</i> |
|---------------|--|

Description

This function computes the intensity of proteins as the sum of the intensities of their n best peptides.

Usage

```
aggregateTopn(obj.pep, X, method = "Mean", n = 10)
```

Arguments

obj.pep A matrix of intensities of peptides
 X An adjacency matrix in which lines and columns correspond respectively to peptides and proteins.
 method xxx
 n The maximum number of peptides used to aggregate a protein.

Value

A matrix of intensities of proteins

Author(s)

Alexia Dorffer, Samuel Wiczorek

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
obj.pep <- Exp1_R25_pept[1:1000]
protID <- "Protein_group_IDs"
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
DAPAR::aggregateTopn(obj.pep, X, n=3)

## End(Not run)
```

| | |
|--------------------|--|
| averageIntensities | <i>Average protein/peptide abundances for each condition studied</i> |
|--------------------|--|

Description

Calculate the average of the abundances for each protein in each condition for an ExpressionSet or MSnSet. Needs to have the array expression data ordered in the same way as the phenotype data (columns of the array data in the same order than the condition column in the phenotype data).

Usage

```
averageIntensities(ESet_obj)
```

Arguments

ESet_obj ExpressionSet object containing all the data

Value

a dataframe in wide format providing (in the case of 3 or more conditions) the means of intensities for each protein/peptide in each condition. If there are less than 3 conditions, an error message is returned.

Author(s)

Helene Borges

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
averageIntensities(obj)
```

| | |
|--------------------|--|
| barplotEnrichGO_HC | <i>A barplot that shows the result of a GO enrichment, using the package highcharter</i> |
|--------------------|--|

Description

A barplot of GO enrichment analysis

Usage

```
barplotEnrichGO_HC(ego, maxRes = 5, title = NULL)
```

Arguments

| | |
|--------|---|
| ego | The result of the GO enrichment, provides either by the function <code>enrichGO</code> in the package <code>DAPAR</code> or the function <code>enrichGO</code> of the package clusterProfiler |
| maxRes | The maximum number of categories to display in the plot |
| title | The title of the plot |

Value

A barplot

Author(s)

Samuel Wieczorek

| | |
|-------------------|---|
| barplotGroupGO_HC | <i>A barplot which shows the result of a GO classification, using the package highcharter</i> |
|-------------------|---|

Description

A barplot of GO classification analysis

Usage

```
barplotGroupGO_HC(ggo, maxRes = 5, title = "")
```

Arguments

| | |
|--------|--|
| ggo | The result of the GO classification, provides either by the function <code>group_GO</code> in the package <code>DAPAR</code> or the function <code>groupGO</code> in the package clusterProfiler |
| maxRes | An integer which is the maximum number of classes to display in the plot |
| title | The title of the plot |

Value

A barplot

Author(s)

Samuel Wiczorek

`boxPlotD_HC`*Builds a boxplot from a dataframe using the library highcharter*

Description

Boxplot for quantitative proteomics data using the library highcharter

Usage

```
boxPlotD_HC(  
  obj,  
  conds,  
  keyId = NULL,  
  legend = NULL,  
  palette = NULL,  
  subset.view = NULL  
)
```

Arguments

| | |
|--------------------------|--|
| <code>obj</code> | Numeric matrix |
| <code>conds</code> | xxx |
| <code>keyId</code> | xxxx |
| <code>legend</code> | A vector of the conditions (one condition per sample). |
| <code>palette</code> | xxx |
| <code>subset.view</code> | A vector of index indicating rows to highlight |

Value

A boxplot

Author(s)

Samuel Wiczorek, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')  
obj <- Exp1_R25_prot  
conds <- legend <- Biobase::pData(obj)$Condition  
key <- "Protein_IDs"  
boxPlotD_HC(obj, conds, key, legend, c(rep('blue',3), rep('green',3)), 1:10)
```

BuildAdjacencyMatrix *Function matrix of appartenance group*

Description

Method to create a binary matrix with proteins in columns and peptides in lines on a MSnSet object (peptides)

Usage

```
BuildAdjacencyMatrix(obj.pep, protID, unique = TRUE)
```

Arguments

| | |
|---------|---|
| obj.pep | An object (peptides) of class MSnSet. |
| protID | The name of proteins ID column |
| unique | A boolean to indicate whether only the unique peptides must be considered (TRUE) or if the shared peptides have to be integrated (FALSE). |

Value

A binary matrix

Author(s)

Florence Combes, Samuel Wiczorek, Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], "Protein_group_IDs", TRUE)
```

BuildColumnToProteinDataset

creates a column for the protein dataset after agregation by using the previous peptide dataset.

Description

This function creates a column for the protein dataset after aggregation by using the previous peptide dataset.

Usage

```
BuildColumnToProteinDataset(peptideData, matAdj, columnName, proteinNames)
```

Arguments

| | |
|--------------|---|
| peptideData | A data.frame of meta data of peptides. It is the fData of the MSnset object. |
| matAdj | The adjacency matrix used to agregate the peptides data. |
| columnName | The name of the column in fData(peptides_MSnset) that the user wants to keep in the new protein data.frame. |
| proteinNames | The names of the protein in the new dataset (i.e. rownames) |

Value

A vector

Author(s)

Samuel Wieczorek

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
protID <- "Protein_group_IDs"
obj.pep <- Exp1_R25_pept[1:1000]
M <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
data <- Biobase::fData(obj.pep)
protData <- DAPAR::aggregateMean(obj.pep, M)
name <- "Protein_group_IDs"
proteinNames <- rownames(Biobase::fData(protData))
BuildColumnToProteinDataset(data, M, name,proteinNames )

## End(Not run)
```

BuildColumnToProteinDataset_par

creates a column for the protein dataset after agregation by using the previous peptide dataset.

Description

This function creates a column for the protein dataset after agregation by using the previous peptide dataset. It is a parallel version of the function BuildColumnToProteinDataset

Usage

```
BuildColumnToProteinDataset_par(peptideData, matAdj, columnName, proteinNames)
```

Arguments

| | |
|--------------|---|
| peptideData | A data.frame of meta data of peptides. It is the fData of the MSnset object. |
| matAdj | The adjacency matrix used to agregate the peptides data. |
| columnName | The name of the column in fData(peptides_MSnset) that the user wants to keep in the new protein data.frame. |
| proteinNames | The names of the protein in the new dataset (i.e. rownames) |

Value

A vector

Author(s)

Samuel Wieczorek

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
protID <- "Protein_group_IDs"
obj.pep <- Exp1_R25_pept[1:1000]
M <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
data <- Biobase::fData(obj.pep)
protData <- DAPAR::aggregateSum(obj.pep, M)
name <- "Protein_group_IDs"
proteinNames <- rownames(Biobase::fData(protData))
BuildColumnToProteinDataset_par(data, M, name,proteinNames )

## End(Not run)
```

buildGraph

Display a CC

Description

Display a CC

Usage

```
buildGraph(The.CC, X)
```

Arguments

| | |
|--------|---------------|
| The.CC | A cc (a list) |
| X | xxxxx |

Value

A plot

Author(s)

Thomas Burger, Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
X <- BuildAdjacencyMatrix(Exp1_R25_pept, "Protein_group_IDs", FALSE)
l1 <- get.pep.prot.cc(X)
g <- buildGraph(l1[[1]], X)
```

| | |
|--------------|---|
| BuildPalette | <i>Builds a complete color palette for the conditions given in argument</i> |
|--------------|---|

Description

xxxx

Usage

```
BuildPalette(conds, base_palette = NULL)
```

Arguments

| | |
|--------------|--|
| conds | The extended vector of samples conditions |
| base_palette | The basic color (HEX code) used to build the complete palette. This vector have the same length as unique(conds). Default base palette is 'Dark2' from the package RColorBrewer. |

Value

A vector composed of HEX color code for the conditions

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conditions <- Biobase::pData(Exp1_R25_pept)$Condition
BuildPalette(conditions, c('AAAAAA', 'BBBBBB'))
```

| | |
|------------------|-------------------------------------|
| check.conditions | <i>Check if the design is valid</i> |
|------------------|-------------------------------------|

Description

This function check the validity of the conditions

Usage

```
check.conditions(conds)
```

Arguments

| | |
|-------|----------|
| conds | A vector |
|-------|----------|

Value

A list

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
check.conditions(Biobase::pData(Exp1_R25_pept)$Condition)
```

| | |
|--------------|-------------------------------------|
| check.design | <i>Check if the design is valid</i> |
|--------------|-------------------------------------|

Description

This function check the validity of the experimental design

Usage

```
check.design(sTab)
```

Arguments

sTab The data.frame which correspond to the pData function of MSnbase

Value

A boolean

Author(s)

Thomas Burger, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
check.design(Biobase::pData(Exp1_R25_pept)[,1:3])
```

| | |
|---------------------|---|
| checkClusterability | <i>Prepare the data for subsequent clustering</i> |
|---------------------|---|

Description

The first step is to standardize the data (with the Mfuzz package). Then the function checks that these data are clusterizable or not (use of [diptest::dip.test()] to determine whether the distribution is unimodal or multimodal). Finally, it determines the "optimal" k by the Gap statistic approach.

Usage

```
checkClusterability(standards, b = 500)
```

Arguments

| | |
|-----------|---|
| standards | a matrix or dataframe containing only the standardized mean intensities returned by the function [standardiseMeanIntensities()] |
| b | Parameter B of the function [gap_cluster()] |

Value

a list of 2 elements: * dip_test: the result of the clusterability of the data * gap_cluster: the gap statistic obtained with the function [cluster::clusGap()].

Author(s)

Helene Borges

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition = 'WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
averaged_means <- averageIntensities(obj)
only_means <- dplyr::select_if(averaged_means, is.numeric)
only_features <- dplyr::select_if(averaged_means, is.character)
means <- purrr::map(purrr::array_branch(as.matrix(only_means), 1), mean)
centered <- only_means - unlist(means)
centered_means <- dplyr::bind_cols(feature = dplyr::as_tibble(only_features), dplyr::as_tibble(centered))
checkClust <- checkClusterability(centered_means, b=100)
```

| | |
|------------------|--|
| classic1wayAnova | <i>Function to perform a One-way Anova statistical test on a MsnBase dataset</i> |
|------------------|--|

Description

Function to perform a One-way Anova statistical test on a MsnBase dataset

Usage

```
classic1wayAnova(current_line, conditions)
```

Arguments

| | |
|--------------|--|
| current_line | The line currently treated from the quantitative data to perform the ANOVA |
| conditions | The conditions represent the different classes of the studied factor |

Value

A named vector containing all the different values of the aov model

Author(s)

Hélène Borges

Examples

```

utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
anova_tests <- t(apply(Biobase::exprs(obj),1, classic1wayAnova, conditions=as.factor(Biobase::pData(obj)$Con

```

```
compareNormalizationD_HC
```

Builds a plot from a dataframe. Same as compareNormalizationD but uses the library highcharter

Description

Plot to compare the quantitative proteomics data before and after normalization using the library highcharter

Usage

```

compareNormalizationD_HC(
  qDataBefore,
  qDataAfter,
  keyId = NULL,
  conds = NULL,
  palette = NULL,
  subset.view = NULL,
  n = 100,
  type = "scatter"
)

```

Arguments

| | |
|-------------|---|
| qDataBefore | A dataframe that contains quantitative data before normalization. |
| qDataAfter | A dataframe that contains quantitative data after normalization. |
| keyId | xxx |
| conds | A vector of the conditions (one condition per sample). |
| palette | xxx |
| subset.view | xxx |
| n | An integer that is equal to the maximum number of displayed points. This number must be less or equal to the size of the dataset. If it is less than it, it is a random selection |
| type | scatter or line |

Value

A plot

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot
qDataBefore <- Biobase::exprs(obj)
conds <- Biobase::pData(obj)[,"Condition"]
id <- Biobase::fData(obj)[,obj@experimentData@other$proteinId]
objAfter <- wrapper.normalizeD(obj, method = "QuantileCentering", conds =conds, type = "within conditions")
compareNormalizationD_HC(qDataBefore=qDataBefore, qDataAfter=Biobase::exprs(objAfter), keyId = id, conds=conds)

compareNormalizationD_HC(qDataBefore=qDataBefore, qDataAfter=Biobase::exprs(objAfter), keyId = id, subset=vi
```

| | |
|-----------------|--------|
| compute_t_tests | xxxxxx |
|-----------------|--------|

Description

This function is xxxxxx

Usage

```
compute_t_tests(obj, contrast = "OnevsOne", type = "Student")
```

Arguments

| | |
|----------|---|
| obj | A matrix of quantitative data, without any missing values. |
| contrast | Indicates if the test consists of the comparison of each biological condition versus each of the other ones (contrast=1; for example H0:"C1=C2" vs H1:"C1!=C2", etc.) or each condition versus all others (contrast=2; e.g. H0:"C1=(C2+C3)/2" vs H1:"C1!=(C2+C3)/2", etc. if there are three conditions). |
| type | xxxxxx |

Value

A list of two items : logFC and P_Value; both are dataframe. The first one contains the logFC values of all the comparisons (one column for one comparison), the second one contains the pvalue of all the comparisons (one column for one comparison). The names of the columns for those two dataframes are identical and correspond to the description of the comparison.

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
ttest <- compute_t_tests(obj)
```

| | |
|----------------|---|
| corrMatrixD_HC | <i>Displays a correlation matrix of the quantitative data of the exprs() table.</i> |
|----------------|---|

Description

Correlation matrix based on a MSnSet object.

Usage

```
corrMatrixD_HC(object, samplesData = NULL, rate = 0.5, showValues = TRUE)
```

Arguments

| | |
|-------------|--|
| object | The result of the cor function. |
| samplesData | A dataframe in which lines correspond to samples and columns to the meta-data for those samples. |
| rate | The rate parameter to control the exponential law for the gradient of colors |
| showValues | xxx |

Value

A colored correlation matrix

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
samplesData <- Biobase::pData(Exp1_R25_pept)
res <- cor(qData, use = 'pairwise.complete.obs')
corrMatrixD_HC(res, samplesData)
```

| | |
|----------|--|
| CountPep | <i>Compute the number of peptides used to aggregate proteins</i> |
|----------|--|

Description

This function computes the number of peptides used to aggregate proteins.

Usage

```
CountPep(M)
```

Arguments

M A "valued" adjacency matrix in which lines and columns correspond respectively to peptides and proteins.

Value

A vector of boolean which is the adjacency matrix but with NA values if they exist in the intensity matrix.

Author(s)

Alexia Dorffer

Examples

```
library(DAPARdata)
utils::data(Exp1_R25_pept)
protID <- "Protein_group_IDs"
M <- BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], protID, FALSE)
CountPep(M)
```

| | |
|--------------|---|
| createMSnset | <i>Creates an object of class MSnSet from text file</i> |
|--------------|---|

Description

Builds an object of class MSnSet from a single tabulated-like file for quantitative and meta-data and a dataframe for the samples description. It differs from the original MSnSet builder which requires three separated files tabulated-like quantitative proteomic data into a MSnSet object, including meta-data.

Usage

```

createMSnset(
  file,
  metadata = NULL,
  indExpData,
  indFData,
  indiceID = NULL,
  indexForOriginOfValue = NULL,
  logData = FALSE,
  replaceZeros = FALSE,
  pep_prot_data = NULL,
  proteinId = NULL,
  versions = NULL
)

```

Arguments

| | |
|-----------------------|--|
| file | The name of a tab-separated file that contains the data. |
| metadata | A dataframe describing the samples (in lines). |
| indExpData | A vector of string where each element is the name of a column in designTable that have to be integrated in the fData() table of the MSnSet object. |
| indFData | The name of column in file that will be the name of rows for the exprs() and fData() tables |
| indiceID | The indice of the column containing the ID of entities (peptides or proteins) |
| indexForOriginOfValue | xxxxxxxxxxxx |
| logData | A boolean value to indicate if the data have to be log-transformed (Default is FALSE) |
| replaceZeros | A boolean value to indicate if the 0 and NaN values of intensity have to be replaced by NA (Default is FALSE) |
| pep_prot_data | A string that indicates whether the dataset is about |
| proteinId | xxxx |
| versions | A list of the following items: Prostar_Version, DAPAR_Version peptides or proteins. |

Value

An instance of class MSnSet.

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```

require(Matrix)
exprsFile <- system.file("extdata", "Exp1_R25_pept.txt", package="DAPARdata")
metadataFile <- system.file("extdata", "samples_Exp1_R25.txt", package="DAPARdata")
metadata = read.table(metadataFile, header=TRUE, sep="\t", as.is=TRUE)
indExpData <- c(56:61)

```

```
indFData <- c(1:55,62:71)
indiceID <- 64
createMSnset(exprsFile, metadata,indExpData, indFData, indiceID, indexForOriginOfValue = NULL, pep_prot_data
```

CVDistD

Distribution of CV of entities

Description

Builds a densityplot of the CV of entities in the `exprs()` table of a object. The CV is calculated for each condition present in the dataset (see the slot 'Condition' in the `pData()` table)

Usage

```
CVDistD(qData, conds = NULL, palette = NULL)
```

Arguments

| | |
|----------------------|--|
| <code>qData</code> | A dataframe that contains quantitative data. |
| <code>conds</code> | A vector of the conditions (one condition per sample). |
| <code>palette</code> | xxx |

Value

A density plot

Author(s)

Florence Combes, Samuel Wiczorek

See Also

[densityPlotD](#).

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
CVDistD(Biobase::exprs(Exp1_R25_pept), conds)
```

| | |
|------------|---------------------------------------|
| CVDistD_HC | <i>Distribution of CV of entities</i> |
|------------|---------------------------------------|

Description

Builds a densityplot of the CV of entities in the `exprs()` table of a object. The CV is calculated for each condition present in the dataset (see the slot 'Condition' in the `pData()` table) Same as the function `CVDistD` but uses the package `highcharter`

Usage

```
CVDistD_HC(qData, conds = NULL, palette = NULL)
```

Arguments

| | |
|----------------------|--|
| <code>qData</code> | A dataframe that contains quantitative data. |
| <code>conds</code> | A vector of the conditions (one condition per sample). |
| <code>palette</code> | xxx |

Value

A density plot

Author(s)

Samuel Wieczorek

See Also

[densityPlotD](#).

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
CVDistD_HC(Biobase::exprs(Exp1_R25_pept), conds)
```

| | |
|----------------|---|
| dapar_hc_chart | <i>Customised resetZoomButton of highcharts plots</i> |
|----------------|---|

Description

Customised `resetZoomButton` of highcharts plots

Usage

```
dapar_hc_chart(hc, chartType, zoomType = "None", width = 0, height = 0)
```

Arguments

| | |
|-----------|--|
| hc | A highcharter object |
| chartType | The type of the plot |
| zoomType | The type of the zoom (one of "x", "y", "xy", "None") |
| width | xxx |
| height | xxx |

Value

A highchart plot

Author(s)

Samuel Wiczorek

Examples

```
library("highcharter")
hc <- highchart()
hc <- dapar_hc_chart(hc, chartType='line', zoomType='x')
hc_add_series(hc, data = c(29, 71, 40))
```

dapar_hc_ExportMenu *Customised contextual menu of highcharts plots*

Description

Customised contextual menu of highcharts plots

Usage

```
dapar_hc_ExportMenu(hc, filename)
```

Arguments

| | |
|----------|---|
| hc | A highcharter object |
| filename | The filename under which the plot has to be saved |

Value

A contextual menu for highcharts plots

Author(s)

Samuel Wiczorek

Examples

```
library("highcharter")
hc <- highchart()
hc_chart(hc,type = "line")
hc_add_series(hc,data = c(29, 71, 40))
dapar_hc_ExportMenu(hc,filename='foo')
```

deleteLinesFromIndices

Delete the lines in the matrix of intensities and the metadata table given their indice.

Description

Delete the lines of `exprs()` table identified by their indice.

Usage

```
deleteLinesFromIndices(obj, deleteThat = NULL, processText = "")
```

Arguments

| | |
|--------------------------|--|
| <code>obj</code> | An object of class <code>MSnSet</code> containing quantitative data. |
| <code>deleteThat</code> | A vector of integers which are the indices of lines to delete. |
| <code>processText</code> | A string to be included in the <code>MSnSet</code> object for log. |

Value

An instance of class `MSnSet` that have been filtered.

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
deleteLinesFromIndices(Exp1_R25_pept, c(1:10))
```

| | |
|--------------|--|
| densityPlotD | <i>Builds a densityplot from a dataframe</i> |
|--------------|--|

Description

Densityplot of quantitative proteomics data over samples.

Usage

```
densityPlotD(obj, conds, legend = NULL, palette = NULL)
```

Arguments

| | |
|---------|--|
| obj | xxx |
| conds | xxx |
| legend | A vector of the conditions (one condition per sample). |
| palette | xxx |

Value

A density plot

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
densityPlotD(Exp1_R25_pept, conds)
```

| | |
|-----------------|--|
| densityPlotD_HC | <i>Builds a densityplot from a dataframe</i> |
|-----------------|--|

Description

Densityplot of quantitative proteomics data over samples. Same as the function [densityPlotD](#) but uses the package highcharter

Usage

```
densityPlotD_HC(obj, legend = NULL, palette = NULL)
```

Arguments

| | |
|---------|--|
| obj | xxx |
| legend | A vector of the conditions (one condition per sample). |
| palette | xxx |

Value

A density plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
densityPlotD_HC(Exp1_R25_pept)
```

| | |
|-------------------|--|
| diffAnaComputeFDR | <i>Computes the FDR corresponding to the p-values of the differential analysis using</i> |
|-------------------|--|

Description

This function is a wrapper to the function `adjust.p` from the `cp4p` package. It returns the FDR corresponding to the p-values of the differential analysis. The FDR is computed with the function `p.adjust{stats}`.

Usage

```
diffAnaComputeFDR(
  logFC,
  pval,
  threshold_PVal = 0,
  threshold_LogFC = 0,
  pi0Method = 1
)
```

Arguments

| | |
|------------------------------|--|
| <code>logFC</code> | The result (logFC values) of the differential analysis processed by limmaCompleteTest |
| <code>pval</code> | The result (p-values) of the differential analysis processed by limmaCompleteTest |
| <code>threshold_PVal</code> | The threshold on p-value to distinguish between differential and non-differential data |
| <code>threshold_LogFC</code> | The threshold on log(Fold Change) to distinguish between differential and non-differential data |
| <code>pi0Method</code> | The parameter <code>pi0.method</code> of the method <code>adjust.p</code> in the package <code>cp4p</code> |

Value

The computed FDR value (floating number)

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
limma <- limmaCompleteTest(qData,sTab)
diffAnaComputeFDR(limma$logFC[,1],limma$P_Value[,1])
```

`diffAnaGetSignificant` *Returns a MSnSet object with only proteins significant after differential analysis.*

Description

Returns a MSnSet object with only proteins significant after differential analysis.

Usage

```
diffAnaGetSignificant(obj)
```

Arguments

`obj` An object of class MSnSet.

Value

A MSnSet

Author(s)

Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
allComp <- limmaCompleteTest(qData,sTab)
data <- list(logFC=allComp$logFC[1], P_Value = allComp$P_Value[1])
obj <- diffAnaSave(obj, allComp, data)
signif <- diffAnaGetSignificant(obj)
```

| | |
|-------------|---|
| diffAnaSave | Returns a MSnSet object with the results of the differential analysis performed with limma package. |
|-------------|---|

Description

This method returns a class MSnSet object with the results of differential analysis.

Usage

```
diffAnaSave(obj, allComp, data = NULL, th_pval = 0, th_logFC = 0)
```

Arguments

| | |
|----------|---|
| obj | An object of class MSnSet. |
| allComp | A list of two items which is the result of the function <code>wrapper.limmaCompleteTest</code> or <code>xxxx</code> |
| data | The result of the differential analysis processed by <code>limmaCompleteTest</code> |
| th_pval | xxx |
| th_logFC | xxx |

Value

A MSnSet

Author(s)

Alexia Dorffer, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
allComp <- limmaCompleteTest(qData,sTab)
data <- list(logFC=allComp$logFC[1], P_Value = allComp$P_Value[1])
diffAnaSave(obj, allComp, data)
```

diffAnaVolcanoplot *Volcanoplot of the differential analysis*

Description

Plots a volcano plot after the differential analysis. Typically, the log of Fold Change is represented on the X-axis and the log₁₀ of the p-value is drawn on the Y-axis. When the `threshold_pVal` and the `threshold_logFC` are set, two lines are drawn respectively on the y-axis and the X-axis to visually distinguish between differential and non differential data.

Usage

```
diffAnaVolcanoplot(
  logFC = NULL,
  pVal = NULL,
  threshold_pVal = 1e-60,
  threshold_logFC = 0,
  conditions = NULL,
  colors = NULL
)
```

Arguments

| | |
|------------------------------|--|
| <code>logFC</code> | A vector of the log(fold change) values of the differential analysis. |
| <code>pVal</code> | A vector of the p-value values returned by the differential analysis. |
| <code>threshold_pVal</code> | A floating number which represents the p-value that separates differential and non-differential data. |
| <code>threshold_logFC</code> | A floating number which represents the log of the Fold Change that separates differential and non-differential data. |
| <code>conditions</code> | A list of the names of condition 1 and 2 used for the differential analysis. |
| <code>colors</code> | xxx |

Value

A volcano plot

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
limma <- limmaCompleteTest(qData,sTab)
diffAnaVolcanoplot(limma$logFC[,1], limma$P_Value[,1])
```

`diffAnaVolcanoplot_rCharts`*Volcanoplot of the differential analysis*

Description

Plots an interactive volcano plot after the differential analysis. Typically, the log of Fold Change is represented on the X-axis and the log₁₀ of the p-value is drawn on the Y-axis. When the `threshold_pVal` and the `threshold_logFC` are set, two lines are drawn respectively on the y-axis and the X-axis to visually distinguish between differential and non differential data. With the use of the package Highcharter, a customizable tooltip appears when the user put the mouse's pointer over a point of the scatter plot.

Usage

```
diffAnaVolcanoplot_rCharts(  
  df,  
  threshold_pVal = 1e-60,  
  threshold_logFC = 0,  
  conditions = NULL,  
  clickFunction = NULL,  
  palette = NULL,  
  swap = FALSE  
)
```

Arguments

| | |
|------------------------------|---|
| <code>df</code> | A dataframe which contains the following slots : <code>x</code> : a vector of the log(fold change) values of the differential analysis, <code>y</code> : a vector of the p-value values returned by the differential analysis. <code>index</code> : a vector of the rownames of the data. This dataframe must has been built with the option <code>stringsAsFactors</code> set to <code>FALSE</code> . There may be additional slots which will be used to show informations in the tooltip. The name of these slots must begin with the prefix <code>"tooltip_"</code> . It will be automatically removed in the plot. |
| <code>threshold_pVal</code> | A floating number which represents the p-value that separates differential and non-differential data. |
| <code>threshold_logFC</code> | A floating number which represents the log of the Fold Change that separates differential and non-differential data. |
| <code>conditions</code> | A list of the names of condition 1 and 2 used for the differential analysis. |
| <code>clickFunction</code> | A string that contains a JavaScript function used to show info from slots in <code>df</code> . The variable <code>this.index</code> refers to the slot named <code>index</code> and allows to retrieve the right row to show in the tooltip. |
| <code>palette</code> | <code>xxx</code> |
| <code>swap</code> | A boolean that indicates if the conditions have been swapped |

Value

An interactive volcano plot

Author(s)

Samuel Wieczorek

Examples

```

library(highcharter)
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
data <- limmaCompleteTest(qData,sTab)
df <- data.frame(x=data$logFC, y = -log10(data$P_Value), index = as.character(rownames(obj)))
colnames(df) <- c("x", "y", "index")
tooltipSlot <- c("Sequence", "Score")
df <- cbind(df,Biobase::fData(obj)[tooltipSlot])
colnames(df) <- gsub(".", "_", colnames(df), fixed=TRUE)
if (ncol(df) > 3){
  colnames(df)[4:ncol(df)] <-
    paste("tooltip_", colnames(df)[4:ncol(df)], sep="")
}
hc_clickFunction <- JS("function(event) {Shiny.onInputChange('eventPointClicked', [this.index]+'_'+ [this.se
cond <- c("25fmol", "10fmol")
diffAnaVolcanoplot_rCharts(df, 2.5, 1, cond,hc_clickFunction)

```

display.CC.visNet

*Display a CC***Description**

Display a CC

Usage

```

display.CC.visNet(
  g,
  layout = layout_nicely,
  obj = NULL,
  prot.tooltip = NULL,
  pept.tooltip = NULL
)

```

Arguments

| | |
|---------------------------|---------------|
| <code>g</code> | A cc (a list) |
| <code>layout</code> | xxxxx |
| <code>obj</code> | xxx |
| <code>prot.tooltip</code> | xxx |
| <code>pept.tooltip</code> | xxx |

Value

A plot

Author(s)

Thomas Burger, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
X <- BuildAdjacencyMatrix(Exp1_R25_pept, "Protein_group_IDs", FALSE)
ll <- get.pep.prot.cc(X)
g <- buildGraph(ll[[1]], X)
display.CC.visNet(g)
```

| | |
|-----------|---|
| enrich_GO | <i>Calculates GO enrichment classes for a given list of proteins/genes ID. It results an enrichResult instance.</i> |
|-----------|---|

Description

This function is a wrapper to the function `enrichGO` from the package `clusterProfiler`. Given a vector of genes/proteins, it returns an `enrichResult` instance.

Usage

```
enrich_GO(data, idFrom, orgdb, ont, readable = FALSE, pval, universe)
```

Arguments

| | |
|----------|--|
| data | A vector of ID (among ENSEMBL, ENTREZID, GENENAME, REFSEQ, UNIGENE, UNIPROT -can be different according to organisms) |
| idFrom | character indicating the input ID format (among ENSEMBL, ENTREZID, GENENAME, REFSEQ, UNIGENE, UNIPROT) |
| orgdb | annotation Bioconductor package to use (character format) |
| ont | One of "MF", "BP", and "CC" subontologies |
| readable | TRUE or FALSE (default FALSE) |
| pval | The qvalue cutoff (same parameter as in the function <code>enrichGO</code> of the package <code>clusterProfiler</code>) |
| universe | a list of ID to be considered as the background for enrichment calculation |

Value

A `groupGOResult` instance.

Author(s)

Florence Combes

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
univ<-univ_AnnotDbPkg("org.Sc.sgd.db") #univ is the background
ego<-enrich_GO(data=Biobase::fData(Exp1_R25_prot)$Protein.IDs, idFrom="UNIPROT",
orgdb="org.Sc.sgd.db",ont="MF", pval=0.05, universe = univ)
```

finalizeAggregation *Finalizes the aggregation process*

Description

Method to finalize the aggregation process

Usage

```
finalizeAggregation(obj.pep, pepData, protData, X, lib.loc = NULL)
```

Arguments

| | |
|----------|---|
| obj.pep | A peptide object of class MSnset |
| pepData | xxxx |
| protData | xxxxx |
| X | An adjacency matrix in which lines and columns correspond respectively to peptides and proteins. |
| lib.loc | A list of two items (lib.loc\$Prostar.loc and lib.loc\$DAPAR.loc) to provide the location of the installed packages |

Value

A protein object of class MSnset

Author(s)

Samuel Wieczorek

| | |
|--------------|--|
| findMECBlock | <i>Finds the LAPALA into a MSnSet object</i> |
|--------------|--|

Description

This method finds the LAPALA in a dataset.

Usage

```
findMECBlock(obj)
```

Arguments

obj An object of class MSnSet.

Value

A data.frame that contains the indexes of LAPALA

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
lapala <- findMECBlock(obj)
```

| | |
|-------------------|-------------|
| formatLimmaResult | <i>xxxx</i> |
|-------------------|-------------|

Description

xxxx

Usage

```
formatLimmaResult(fit, conds, contrast)
```

Arguments

fit xxxx
conds xxxx
contrast xxxx

Value

A list of two dataframes : logFC and P_Value. The first one contains the logFC values of all the comparisons (one column for one comparison), the second one contains the pvalue of all the comparisons (one column for one comparison). The names of the columns for those two dataframes are identical and correspond to the description of the comparison.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
limma <- limmaCompleteTest(qData,sTab)
```

| | |
|-----------------|--|
| formatPHResults | <i>Extract logFC and raw pvalues from multiple post-hoc models summaries</i> |
|-----------------|--|

Description

Extract logFC and raw pvalues from multiple post-hoc models summaries

Usage

```
formatPHResults(post_hoc_models_summaries)
```

Arguments

post_hoc_models_summaries
a list of summaries of post-hoc models.

Value

a list of 2 dataframes containing the logFC values and pvalues for each comparison.

Author(s)

Hélène Borges

Examples

```

utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
anova_tests <- t(apply(Biobase::exprs(obj),1, classic1wayAnova, conditions=as.factor(Biobase::pData(obj)$Con
names(anova_tests) <- rownames(Biobase::exprs(obj))
tms <- lapply(anova_tests,
              function(x) summary(multcomp::glht(x, linfct = multcomp::mcp(conditions = "Tukey")),
                                test = multcomp::adjusted("none")))
res <- formatPHResults(tms)

```

fudge2LRT

Heuristic to choose the value of the hyperparameter (fudge factor) used to regularize the variance estimator in the likelihood ratio statistic

Description

fudge2LRT: heuristic to choose the value of the hyperparameter (fudge factor) used to regularize the variance estimator in the likelihood ratio statistic (as implemented in samLRT). We follow the heuristic described in [1] and adapt the code of the fudge2 function in the siggene R package. [1] Tusher, Tibshirani and Chu, Significance analysis of microarrays applied to the ionizing radiation response, PNAS 2001 98: 5116-5121, (Apr 24).

Usage

```

fudge2LRT(
  lmm.res.h0,
  lmm.res.h1,
  cc,
  n,
  p,
  s,
  alpha = seq(0, 1, 0.05),
  include.zero = TRUE
)

```

Arguments

| | |
|------------|--|
| lmm.res.h0 | a vector of object containing the estimates (used to compute the statistic) under H0 for each connected component. If the fast version of the estimator was used (as implemented in this package), lmm.res.h0 is a vector containing averages of squared residuals. If a fixed effect model was used, it is a vector of lm objects and if a mixed effect model was used it is a vector or lmer object. |
| lmm.res.h1 | similar to lmm.res.h0, a vector of object containing the estimates (used to compute the statistic) under H1 for each protein. |
| cc | a list containing the indices of peptides and proteins belonging to each connected component. |
| n | the number of samples used in the test |

| | |
|--------------|--|
| p | the number of proteins in the experiment |
| s | a vector containing the maximum likelihood estimate of the variance for the chosen model. When using the fast version of the estimator implemented in this package, this is the same thing as the input lmm.res.h1. For other models (e.g. mixed models) it can be obtained from samLRT. |
| alpha | A vector of proportions used to build candidate values for the regularizer. We use quantiles of s with these proportions. Default to seq(0, 1, 0.05) |
| include.zero | logical value indicating if 0 should be included in the list of candidates. Default to TRUE. |

Value

(same as the fudge2 function of siggene): s.zero: the value of the fudge factor s0. alpha.hat: the optimal quantile of the 's' values. If s0=0, 'alpha.hat' will not be returned. vec.cv: the vector of the coefficients of variations. Following Tusher et al. (2001), the optimal 'alpha' quantile is given by the quantile that leads to the smallest CV of the modified test statistics. msg: a character string summarizing the most important information about the fudge factor.

Author(s)

Thomas Burger, Laurent Jacob

get.pep.prot.cc

Build the list of connex component of the adjacency matrix

Description

Method to build the list of connex component of the adjacency matrix

Usage

```
get.pep.prot.cc(X)
```

Arguments

X An adjacency matrix

Value

A list of CC

Author(s)

Thomas Burger, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
X <- BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], "Protein_group_IDs", FALSE)
ll <- get.pep.prot.cc(X)
```

GetDetailedNbPeptides *Computes the detailed number of peptides for each protein*

Description

Method to compute the detailed number of quantified peptides for each protein

Usage

```
GetDetailedNbPeptides(X)
```

Arguments

X An adjacency matrix

Value

A data.frame

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj.pep <- Exp1_R25_pept[1:1000]
protID <- "Protein_group_IDs"
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE)
GetDetailedNbPeptides(X)
```

GetDetailedNbPeptidesUsed

Computes the detailed number of peptides used for aggregating each protein

Description

Method to compute the detailed number of quantified peptides used for aggregating each protein

Usage

```
GetDetailedNbPeptidesUsed(X, pepData)
```

Arguments

X An adjacency matrix
pepData A data.frame of quantitative data

Value

A list of two items

Author(s)

Samuel Wieczorek

```
utils::data(Exp1_R25_pept, package='DAPARdata') obj.pep <- Exp1_R25_pept[1:1000] protID <-  
"Protein_group_IDs" X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE) GetDetailedNbPep-  
tidesUsed(X, obj.pep)
```

getIndicesConditions *Gets the conditions indices.*

Description

Returns a list for the two conditions where each slot is a vector of indices for the samples.

Usage

```
getIndicesConditions(conds, cond1, cond2)
```

Arguments

| | |
|-------|---|
| conds | A vector of strings containing the column "Condition" of the pData(). |
| cond1 | A vector of Conditions (a slot in the pData() table) for the condition 1. |
| cond2 | A vector of Conditions (a slot in the pData() table) for the condition 2. |

Value

A list with two slots iCond1 and iCond2 containing respectively the indices of samples in the pData() table of the dataset.

Author(s)

Florence Combes, Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]  
getIndicesConditions(conds, "25fmol", "10fmol")
```

`getIndicesOfLinesToRemove`*Get the indices of the lines to delete, based on a prefix string*

Description

This function returns the indice of the lines to delete, based on a prefix string

Usage

```
getIndicesOfLinesToRemove(obj, idLine2Delete = NULL, prefix = NULL)
```

Arguments

| | |
|----------------------------|--|
| <code>obj</code> | An object of class MSnSet. |
| <code>idLine2Delete</code> | The name of the column that correspond to the data to filter |
| <code>prefix</code> | A character string that is the prefix to find in the data |

Value

A vector of integers.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
getIndicesOfLinesToRemove(Exp1_R25_pept, "Potential_contaminant", prefix="+")
```

`getListNbValuesInLines`*Returns the possible number of values in lines in the data*

Description

Returns the possible number of values in lines in a matrix.

Usage

```
getListNbValuesInLines(obj, type = "WholeMatrix")
```

Arguments

| | |
|-------------------|---------------------------|
| <code>obj</code> | An object of class MSnSet |
| <code>type</code> | xxxxxxx |

Value

An integer

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
getListNbValuesInLines(Exp1_R25_pept)
```

| | |
|-------------------|--|
| GetNbPeptidesUsed | <i>Computes the number of peptides used for aggregating each protein</i> |
|-------------------|--|

Description

Method to compute the number of quantified peptides used for aggregating each protein

Usage

```
GetNbPeptidesUsed(X, pepData)
```

Arguments

| | |
|---------|-----------------------------------|
| X | An adjacency matrix |
| pepData | A data.frame of quantitative data |

Value

A data.frame

Author(s)

Samuel Wieczorek

| | |
|-------------|------------------------------------|
| getNumberOf | <i>Number of lines with prefix</i> |
|-------------|------------------------------------|

Description

Returns the number of lines, in a given column, where content matches the prefix.

Usage

```
getNumberOf(obj, name = NULL, prefix = NULL)
```

Arguments

| | |
|--------|----------------------------|
| obj | An object of class MSnSet. |
| name | The name of a column. |
| prefix | A string |

Value

An integer

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
getNumberOf(Exp1_R25_pept, "Potential_contaminant", "+")
```

getNumberOfEmptyLines *Returns the number of empty lines in the data*

Description

Returns the number of empty lines in a matrix.

Usage

```
getNumberOfEmptyLines(qData)
```

Arguments

| | |
|-------|--|
| qData | A matrix corresponding to the quantitative data. |
|-------|--|

Value

An integer

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
getNumberOfEmptyLines(qData)
```

getPourcentageOfMV *Percentage of missing values*

Description

Returns the percentage of missing values in the quantitative data (exprs()) table of the dataset).

Usage

```
getPourcentageOfMV(obj)
```

Arguments

obj An object of class MSnSet.

Value

A floating number

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
getPourcentageOfMV(Exp1_R25_pept)
```

getProcessingInfo *Returns the contents of the slot processing of an object of class MSnSet*

Description

Returns the contents of the slot processing of an object of class MSnSet

Usage

```
getProcessingInfo(obj)
```

Arguments

obj An object (peptides) of class MSnSet.

Value

The slot processing of obj@processingData

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
getProcessingInfo(Exp1_R25_pept)
```

| | |
|------------------|---|
| getProteinsStats | <i>Computes the number of proteins that are only defined by specific peptides, shared peptides or a mixture of two.</i> |
|------------------|---|

Description

This function computes the number of proteins that are only defined by specific peptides, shared peptides or a mixture of two.

Usage

```
getProteinsStats(matShared)
```

Arguments

matShared The adjacency matrix with both specific and shared peptides.

Value

A list

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
protID <- "Protein_group_IDs"
obj <- Exp1_R25_pept[1:1000]
MShared <- BuildAdjacencyMatrix(obj, protID, FALSE)
getProteinsStats(MShared)
```

| | |
|-----------------|---|
| getQuantile4Imp | <i>Quantile imputation value definition</i> |
|-----------------|---|

Description

This method returns the q-th quantile of each column of an expression set, up to a scaling factor

Usage

```
getQuantile4Imp(qData, qval = 0.025, factor = 1)
```

Arguments

| | |
|--------|--|
| qData | An expression set containing quantitative values of various replicates |
| qval | The quantile used to define the imputation value |
| factor | A scaling factor to multiply the imputation value with |

Value

A list of two vectors, respectively containing the imputation values and the rescaled imputation values

Author(s)

Thomas Burger

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
getQuantile4Imp(qData)
```

getTextForAggregation *Build the text information for the Aggregation process*

Description

Builds the text information for the Aggregation process

Usage

```
getTextForAggregation(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
params <- list()
getTextForAggregation(params)
```

`getTextForAnaDiff` *Build the text information for the Aggregation process*

Description

Build the text information for the differential Analysis process

Usage

```
getTextForAnaDiff(l.params)
```

Arguments

`l.params` A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
getTextForAnaDiff(list(design="OnevsOne",method="Limma"))
```

`getTextForFiltering` *Build the text information for the filtering process*

Description

Build the text information for the filtering process

Usage

```
getTextForFiltering(l.params)
```

Arguments

`l.params` A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
getTextForFiltering(list(mvFilterType="WholeMatrix",mvThNA=3, val_vs_percent='Value'))
```

```
getTextForGOAnalysis
```

Build the text information for the Aggregation process

Description

Build the text information for the Aggregation process

Usage

```
getTextForGOAnalysis(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wiczorek

Examples

```
getTextForGOAnalysis(list())
```

```
getTextForHypothesisTest
```

Build the text information for the hypothesis test process

Description

Builds the text information for the hypothesis test process

Usage

```
getTextForHypothesisTest(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
params <- list(design='OnevsOne', method='limma')
getTextForHypothesisTest(params)
```

`getTextForNewDataset` *Build the text information for a new dataset*

Description

Build the text information for a new dataset

Usage

```
getTextForNewDataset(l.params)
```

Arguments

`l.params` A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
getTextForNewDataset(list(filename="foo.msnset"))
```

`getTextForNormalization`
Build the text information for the Normalization process

Description

Build the text information for the Normalization process

Usage

```
getTextForNormalization(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
getTextForNormalization(list(method="SumByColumns"))
```

```
getTextForpeptideImputation
```

Build the text information for the peptide Imputation process

Description

Build the text information for the peptide Imputation process

Usage

```
getTextForpeptideImputation(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
params <- list()  
getTextForpeptideImputation(params)
```

getTextForproteinImputation

Build the text information for the protein Imputation process

Description

Build the text information for the Protein Imputation process

Usage

```
getTextForproteinImputation(l.params)
```

Arguments

l.params A list of parameters related to the process of the dataset

Value

A string

Author(s)

Samuel Wieczorek

Examples

```
params <- list()
getTextForproteinImputation(params)
```

Get_AllComparisons

Returns list that contains a list of the statistical tests performed with DAPAR and recorded in an object of class MSnSet.

Description

This method returns a list of the statistical tests performed with DAPAR and recorded in an object of class MSnSet.

Usage

```
Get_AllComparisons(obj)
```

Arguments

obj An object of class MSnSet.

Value

A list of two slots: logFC and P_Value

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
allComp <- limmaCompleteTest(qData,sTab)
data <- list(logFC=allComp$logFC[1], P_Value = allComp$P_Value[1])
obj <- diffAnaSave(obj, allComp, data)
ll <- Get_AllComparisons(obj)
```

GlobalQuantileAlignment

Normalisation GlobalQuantileAlignement

Description

Normalisation GlobalQuantileAlignement

Usage

```
GlobalQuantileAlignment(qData)
```

Arguments

qData xxxx

Value

A normalized numeric matrix

Author(s)

Samuel Wieczorek, Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
normalized <- GlobalQuantileAlignment(qData)
```

| | |
|----------------|---|
| GOAnalysisSave | <i>Returns an MSnSet object with the results of the GO analysis performed with the functions <code>enrichGO</code> and/or <code>groupGO</code> of the <code>clusterProfiler</code> package.</i> |
|----------------|---|

Description

This method returns an MSnSet object with the results of the Gene Ontology analysis.

Usage

```
GOAnalysisSave(
  obj,
  ggo_res = NULL,
  ego_res = NULL,
  organism,
  ontology,
  levels,
  pvalueCutoff,
  typeUniverse
)
```

Arguments

| | |
|---------------------------|---|
| <code>obj</code> | An object of the class MSnSet |
| <code>ggo_res</code> | The object returned by the function <code>group_GO</code> of the package DAPAR or the function <code>groupGO</code> of the package <code>clusterProfiler</code> |
| <code>ego_res</code> | The object returned by the function <code>enrich_GO</code> of the package DAPAR or the function <code>enrichGO</code> of the package <code>clusterProfiler</code> |
| <code>organism</code> | The parameter <code>OrgDb</code> of the functions <code>bitr</code> , <code>groupGO</code> and <code>enrichGO</code> |
| <code>ontology</code> | One of "MF", "BP", and "CC" subontologies |
| <code>levels</code> | A vector of the different GO grouping levels to save |
| <code>pvalueCutoff</code> | The qvalue cutoff (same parameter as in the function <code>enrichGO</code> of the package <code>clusterProfiler</code>) |
| <code>typeUniverse</code> | The type of background to be used. Values are 'Entire Organism', 'Entire dataset' or 'Custom'. In the latter case, a file should be uploaded by the user |

Value

An object of the class MSnSet

Author(s)

Samuel Wieczorek

| | |
|--------------|--|
| GraphPepProt | <i>Function to create a histogram that shows the repartition of peptides w.r.t. the proteins</i> |
|--------------|--|

Description

Method to create a plot with proteins and peptides on a MSnSet object (peptides)

Usage

```
GraphPepProt(mat)
```

Arguments

mat An adjacency matrix.

Value

A histogram

Author(s)

Alexia Dorffer, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
mat <- BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], "Protein_group_IDs")
GraphPepProt(mat)
```

| | |
|----------|--|
| group_GO | <i>Calculates the GO profile of a vector of genes/proteins at a given level of the Gene Ontology</i> |
|----------|--|

Description

This function is a wrapper to the function `groupGO` from the package `clusterProfiler`. Given a vector of genes/proteins, it returns the GO profile at a specific level. It returns a `groupGOResult` instance.

Usage

```
group_GO(data, idFrom, orgdb, ont, level, readable = FALSE)
```


Arguments

| | |
|----------|---|
| data | A vector of ID (among ENSEMBL, ENTREZID, GENENAME, REFSEQ, UNIGENE, UNIPROT -can be different according to organisms) |
| idFrom | character indicating the input ID format (among ENSEMBL, ENTREZID, GENENAME, REFSEQ, UNIGENE, UNIPROT) |
| orgdb | annotation Bioconductor package to use (character format) |
| ont | on which ontology to perform the analysis (MF, BP or CC) |
| level | level of the ontolofy to perform the analysis |
| readable | TRUE or FALSE (default FALSE) |

Value

GO profile at a specific level

Author(s)

Florence Combes

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
ggo<-group_GO(data=Biobase::fData(Exp1_R25_prot)$Protein.IDs, idFrom="UNIPROT",
orgdb="org.Sc.sgd.db", ont="MF", level=2)
```

hc_logFC_DensityPlot *Density plots of logFC values*

Description

This function show the density plots of Fold Change (the same as calculated by limma) for a list of the comparisons of conditions in a differnetial analysis.

Usage

```
hc_logFC_DensityPlot(df_logFC, threshold_LogFC = 0, palette = NULL)
```

Arguments

| | |
|-----------------|---|
| df_logFC | A dataframe that contains the logFC values |
| threshold_LogFC | The threshold on log(Fold Change) to distinguish between differential and non-differential data |
| palette | xxx |

Value

A highcharts density plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
res <- limmaCompleteTest(qData,sTab)
hc_logFC_DensityPlot(res$logFC, threshold_LogFC=1)
```

hc_mvTypePlot2

Distribution of Observed values with respect to intensity values

Description

This method shows density plots which represents the repartition of Partial Observed Values for each replicate in the dataset. The colors correspond to the different conditions (slot Condition in in the dataset of class MSnSet). The x-axis represent the mean of intensity for one condition and one entity in the dataset (i. e. a protein) whereas the y-axis count the number of observed values for this entity and the considered condition.

Usage

```
hc_mvTypePlot2(qData, conds, palette = NULL, typeofMV = NULL, title = NULL)
```

Arguments

| | |
|----------|--|
| qData | A dataframe that contains quantitative data. |
| conds | A vector of the conditions (one condition per sample). |
| palette | The different colors for conditions |
| typeofMV | xxx |
| title | The title of the plot |

Value

Density plots

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
hc_mvTypePlot2(qData, conds, title="POV distribution")
```

| | |
|---------------|--|
| heatmap.DAPAR | <i>This function is inspired from the function heatmap.2 that displays quantitative data in the <code>exprs()</code> table of an object of class <code>MSnSet</code>. For more information, please refer to the help of the <code>heatmap.2</code> function.</i> |
|---------------|--|

Description

Heatmap inspired by the `heatmap.2` function.

Usage

```
heatmap.DAPAR(  
  x,  
  col = heat.colors(100),  
  srtCol = NULL,  
  labCol = NULL,  
  labRow = NULL,  
  key = TRUE,  
  key.title = NULL,  
  main = NULL,  
  ylab = NULL  
)
```

Arguments

| | |
|------------------------|--|
| <code>x</code> | A dataframe that contains quantitative data. |
| <code>col</code> | colors used for the image. Defaults to heat colors (<code>heat.colors</code>). |
| <code>srtCol</code> | angle of column conds, in degrees from horizontal |
| <code>labCol</code> | character vectors with column conds to use. |
| <code>labRow</code> | character vectors with row conds to use. |
| <code>key</code> | logical indicating whether a color-key should be shown. |
| <code>key.title</code> | main title of the color key. If set to <code>NA</code> no title will be plotted. |
| <code>main</code> | main title; default to none. |
| <code>ylab</code> | y-axis title; default to none. |

Value

A heatmap

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
obj <- mvFilter(Exp1_R25_pept, "WholeMatrix", 6)  
qData <- Biobase::exprs(obj)  
heatmap.DAPAR(qData)
```

| | |
|----------|--|
| heatmapD | <i>This function is a wrapper to heatmap.2 that displays quantitative data in the <code>exprs()</code> table of an object of class <code>MSnSet</code></i> |
|----------|--|

Description

Heatmap of the quantitative proteomic data of a `MSnSet` object

Usage

```
heatmapD(  
  qData,  
  conds,  
  distance = "euclidean",  
  cluster = "complete",  
  dendro = FALSE  
)
```

Arguments

| | |
|-----------------------|---|
| <code>qData</code> | A dataframe that contains quantitative data. |
| <code>conds</code> | A vector containing the conditions |
| <code>distance</code> | The distance used by the clustering algorithm to compute the dendrogram. See <code>help(heatmap.2)</code> |
| <code>cluster</code> | the clustering algorithm used to build the dendrogram. See <code>help(heatmap.2)</code> |
| <code>dendro</code> | A boolean to indicate if the dendrogram has to be displayed |

Value

A heatmap

Author(s)

Florence Combes, Samuel Wiczorek, Enor Fremy

Examples

```
## Not run:  
utils::data(Exp1_R25_pept, package='DAPARdata')  
obj <- mvFilter(Exp1_R25_pept[1:1000], "WholeMatrix", 6)  
qData <- Biobase::exprs(obj)  
conds <- pData(obj)[['Condition']]  
heatmapD(qData, conds)  
  
## End(Not run)
```

| | |
|---------------|--------------------------------------|
| histPValue_HC | <i>Plots a histogram of p-values</i> |
|---------------|--------------------------------------|

Description

This function plots a histogram of p-values

Usage

```
histPValue_HC(pval_ll, bins = 80, pi0 = 1)
```

Arguments

| | |
|---------|-----|
| pval_ll | xxx |
| bins | xxx |
| pi0 | xxx |

Value

A plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
allComp <- limmaCompleteTest(qData,sTab)
histPValue_HC(allComp$P_Value[1])
```

| | |
|-----------------|---------------------------------|
| impute.detQuant | <i>Deterministic imputation</i> |
|-----------------|---------------------------------|

Description

This method replaces each missing value by a given value

Usage

```
impute.detQuant(qData, values)
```

Arguments

| | |
|--------|--|
| qData | An expression set containing quantitative or missing values |
| values | A vector with as many elements as the number of columns of qData |

Value

An imputed dataset

Author(s)

Thomas Burger

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
values <- getQuantile4Imp(qData)$shiftedImpVal
impute.detQuant(qData, values)
```

impute.pa2

Missing values imputation from a MSnSet object

Description

This method is a variation to the function `impute.pa` from the package `imp4p`.

Usage

```
impute.pa2(
  tab,
  conditions,
  q.min = 0,
  q.norm = 3,
  eps = 0,
  distribution = "unif"
)
```

Arguments

| | |
|------------|---|
| tab | An object of class MSnSet. |
| conditions | A vector of conditions in the dataset |
| q.min | A quantile value of the observed values allowing defining the maximal value which can be generated. This maximal value is defined by the quantile <code>q.min</code> of the observed values distribution minus <code>eps</code> . Default is 0 (the maximal value is the minimum of observed values minus <code>eps</code>). |
| q.norm | A quantile value of a normal distribution allowing defining the minimal value which can be generated. Default is 3 (the minimal value is the maximal value minus $qn * \text{median}(\text{sd}(\text{observed values}))$ where <code>sd</code> is the standard deviation of a row in a condition). |

| | |
|--------------|---|
| eps | A value allowing defining the maximal value which can be generated. This maximal value is defined by the quantile q_{\min} of the observed values distribution minus eps. Default is 0. |
| distribution | The type of distribution used. Values are unif or beta. |

Value

The object obj which has been imputed

Author(s)

Thomas Burger, Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.impute.pa2(Exp1_R25_pept[1:1000], distribution="beta")
```

```
inner.aggregate.iter  xxxx
```

Description

Method to xxxxx

Usage

```
inner.aggregate.iter(
  pepData,
  X,
  init.method = "Sum",
  method = "Mean",
  n = NULL
)
```

Arguments

| | |
|-------------|-------|
| pepData | xxxxx |
| X | xxxx |
| init.method | xxx |
| method | xxx |
| n | xxxx |

Value

xxxxx

Author(s)

Samuel Wieczorek

```
utils::data(Exp1_R25_pept, package='DAPARdata') protID <- "Protein_group_IDs" obj.pep <- Exp1_R25_pept[1:1000]
X <- BuildAdjacencyMatrix(obj.pep, protID, FALSE) DAPAR::inner.aggregate.iter(exprs(obj.pep),
X)
```

```
inner.aggregate.topn    xxxx
```

Description

xxxx

Usage

```
inner.aggregate.topn(pepData, X, method = "Mean", n = 10)
```

Arguments

| | |
|---------|-----------------------------------|
| pepData | A data.frame of quantitative data |
| X | An adjacency matrix |
| method | xxxxx |
| n | xxxxx |

Value

xxxxx

Author(s)

Samuel Wieczorek

```
inner.mean            xxxx
```

Description

xxxx

Usage

```
inner.mean(pepData, X)
```

Arguments

| | |
|---------|-----------------------------------|
| pepData | A data.frame of quantitative data |
| X | An adjacency matrix |

Value

xxxxx

Author(s)

Samuel Wieczorek

inner.sumxxxx

Description

xxxx

Usage

inner.sum(pepData, X)

Arguments

pepData A data.frame of quantitative data

X An adjacency matrix

Value

A matrix

Author(s)

Samuel Wieczorek

is.MV*Similar to the function is.na but focused on the equality with the missing values in the dataset (type 'POV' and 'MEC')*

Description

Similar to the function is.na but focused on the equality with the missing values in the dataset (type 'POV' and 'MEC')

Usage

is.MV(data)

Arguments

data A data.frame

Value

A boolean dataframe

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
data <- Biobase::fData(obj)[,obj@experimentData@other$OriginOfValues]
is.MV(data)
```

is.OfType

Similar to the function is.na but focused on the equality with the parameter 'type'.

Description

Similar to the function `is.na` but focused on the equality with the parameter 'type'.

Usage

```
is.OfType(data, type)
```

Arguments

| | |
|------|--------------------------------------|
| data | A data.frame |
| type | The value to search in the dataframe |

Value

A boolean dataframe

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
data <- Biobase::fData(obj)[,obj@experimentData@other$OriginOfValues]
is.OfType(data, "MEC")
```

| | |
|-----|--------|
| LH0 | xxxxxx |
|-----|--------|

Description

This function is xxxxxxxx

Usage

LH0(X, y1, y2)

Arguments

| | |
|----|--|
| X | an n.pep*n.prot indicator matrix. |
| y1 | n.pep*n.samples matrice giving the observed counts for |
| y2 | n.pep*n.samples matrice giving the observed counts for |

Value

xxxxxxxxxxx..

Author(s)

Thomas Burger, Laurent Jacob

| | |
|--------|--------|
| LH0.lm | xxxxxx |
|--------|--------|

Description

This function is xxxxxxxx

Usage

LH0.lm(X, y1, y2)

Arguments

| | |
|----|---|
| X | an n.pep*n.prot indicator matrix. |
| y1 | n.pep*n.samples matrice giving the observed counts for each peptide in each sample from the condition 1 |
| y2 | n.pep*n.samples matrice giving the observed counts for each peptide in each sample from the condition 2 |

Value

xxxxxxxxxxx..

Author(s)

Thomas Burger, Laurent Jacob

LH1 *xxxxxx*

Description

This function is xxxxxxxx

Usage

LH1(X, y1, y2, j)

Arguments

X an n.pep*n.prot indicator matrix.
y1 n.pep*n.samples matrice giving the observed counts for
y2 n.pep*n.samples matrice giving the observed counts for
j the index of the protein being tested, ie which has different

Value

xxxxxxxxxx..

Author(s)

Thomas Burger, Laurent Jacob

LH1.lm *xxxxxx*

Description

This function is xxxxxxxx

Usage

LH1.lm(X, y1, y2, j)

Arguments

X an n.pep*n.prot indicator matrix.
y1 n.pep*n.samples matrix giving the observed counts for
y2 n.pep*n.samples matrix giving the observed counts for
j the index of the protein being tested, ie which has different

Value

xxxxxxxxxx..

Author(s)

Thomas Burger, Laurent Jacob

| | |
|-------------------|--|
| limmaCompleteTest | <i>Computes a hierarchical differential analysis</i> |
|-------------------|--|

Description

This function is a limmaCompleteTest

Usage

```
limmaCompleteTest(qData, sTab, comp.type = "OnevsOne")
```

Arguments

| | |
|-----------|---|
| qData | A matrix of quantitative data, without any missing values. |
| sTab | A dataframe of experimental design (pData()). |
| comp.type | A string that corresponds to the type of comparison. Values are: 'anova1way', 'OnevsOne' and 'OnevsAll'; default is 'OnevsOne'. |

Value

A list of two dataframes : logFC and P_Value. The first one contains the logFC values of all the comparisons (one column for one comparison), the second one contains the pvalue of all the comparisons (one column for one comparison). The names of the columns for those two dataframes are identical and correspond to the description of the comparison.

Author(s)

Hélène Borges, Thomas Burger, Quentin Giai-Gianetto, Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
limma <- limmaCompleteTest(qData, sTab, comp.type='anova1way')
```

| | |
|------------|--|
| listSheets | <i>This function returns the list of the sheets names in a Excel file.</i> |
|------------|--|

Description

This function lists all the sheets of an Excel file.

Usage

```
listSheets(file)
```

Arguments

file The name of the Excel file.

Value

A vector

Author(s)

Samuel Wieczorek

LOESS

Normalisation LOESS

Description

Normalisation LOESS

Usage

```
LOESS(qData, conds, type = "overall", span = 0.7)
```

Arguments

qData A numeric matrix.
conds xxx
type "overall" (shift all the sample distributions at once) or "within conditions" (shift the sample distributions within each condition at a time).
span xxx

Value

A normalized numeric matrix

Author(s)

Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
qData <- Biobase::exprs(Exp1_R25_pept)  
conds <- Biobase::pData(Exp1_R25_pept)$Condition  
normalized <- LOESS(qData, conds, type="overall")
```

make.contrast *Builds the contrast matrix*

Description

This function builds the contrast matrix

Usage

```
make.contrast(design, condition, contrast = 1)
```

Arguments

| | |
|-----------|---|
| design | The data.frame which correspond to the pData function of MSnbase |
| condition | xxxxx |
| contrast | An integer that Indicates if the test consists of the comparison of each biological condition versus each of the other ones (Contrast=1; for example H0:"C1=C2" vs H1:"C1!=C2", etc.) or each condition versus all others (Contrast=2; e.g. H0:"C1=(C2+C3)/2" vs H1:"C1!=(C2+C3)/2", etc. if there are three conditions). |

Value

A constrat matrix

Author(s)

Thomas Burger, Quentin Giai-Gianetto, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
design <- make.design(Biobase::pData(Exp1_R25_pept))
conds <- Biobase::pData(Exp1_R25_pept)$Condition
make.contrast(design, conds)
```

make.design *Builds the design matrix*

Description

This function builds the design matrix

Usage

```
make.design(sTab)
```

Arguments

| | |
|------|--|
| sTab | The data.frame which correspond to the pData function of MSnbase |
|------|--|

Value

A design matrix

Author(s)

Thomas Burger, Quentin Giai-Gianetto, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
make.design(Biobase::pData(Exp1_R25_pept))
```

make.design.1

Builds the design matrix for designs of level 1

Description

This function builds the design matrix for design of level 1

Usage

```
make.design.1(sTab)
```

Arguments

sTab The data.frame which correspond to the pData function of MSnbase

Value

A design matrix

Author(s)

Thomas Burger, Quentin Giai-Gianetto, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
make.design.1(Biobase::pData(Exp1_R25_pept))
```

| | |
|---------------|--|
| make.design.2 | <i>Builds the design matrix for designs of level 2</i> |
|---------------|--|

Description

This function builds the design matrix for design of level 2

Usage

```
make.design.2(sTab)
```

Arguments

sTab The data.frame which correspond to the pData function of MSnbase

Value

A design matrix

Author(s)

Thomas Burger, Quentin Giai-Gianetto, Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
make.design.2(Biobase::pData(Exp1_R25_pept))
```

| | |
|---------------|--|
| make.design.3 | <i>Builds the design matrix for designs of level 3</i> |
|---------------|--|

Description

This function builds the design matrix for design of level 3

Usage

```
make.design.3(sTab)
```

Arguments

sTab The data.frame which correspond to the pData function of MSnbase

Value

A design matrix

Author(s)

Thomas Burger, Quentin Giai-Gianetto, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
sTab <- cbind(Biobase::pData(Exp1_R25_pept), Tech.Rep=1:6)
make.design.3(sTab)
```

MeanCentering

Normalisation MeanCentering

Description

Normalisation MeanCentering

Usage

```
MeanCentering(
  qData,
  conds,
  type = "overall",
  subset.norm = NULL,
  scaling = FALSE
)
```

Arguments

| | |
|-------------|---|
| qData | xxx |
| conds | xxx |
| type | "overall" (shift all the sample distributions at once) or "within conditions" (shift the sample distributions within each condition at a time). |
| subset.norm | A vector of index indicating rows to be used for normalization |
| scaling | A boolean that indicates if the variance of the data have to be forced to unit (variance reduction) or not. |

Value

A normalized numeric matrix

Author(s)

Samuel Wiczorek, Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
conds <- Biobase::pData(Exp1_R25_pept)$Condition
normalized <- MeanCentering(qData, conds, type="overall")
```

| | |
|----------|---|
| mvFilter | <i>Filter lines in the matrix of intensities w.r.t. some criteria</i> |
|----------|---|

Description

Filters the lines of `exprs()` table with conditions on the number of missing values. The user chooses the minimum amount of intensities that is acceptable and the filter delete lines that do not respect this condition. The condition may be on the whole line or condition by condition.

Usage

```
mvFilter(obj, type, th, processText = NULL)
```

Arguments

| | |
|--------------------------|--|
| <code>obj</code> | An object of class <code>MSnSet</code> containing quantitative data. |
| <code>type</code> | Method used to choose the lines to delete. Values are : "None", "WholeMatrix", "AllCond", "AtLeastOneCond" |
| <code>th</code> | An integer value of the threshold |
| <code>processText</code> | A string to be included in the <code>MSnSet</code> object for log. |

Details

The different methods are : "WholeMatrix": given a threshold `th`, only the lines that contain at least `th` values are kept. "AllCond": given a threshold `th`, only the lines which contain at least `th` values for each of the conditions are kept. "AtLeastOneCond": given a threshold `th`, only the lines that contain at least `th` values, and for at least one condition, are kept.

Value

An instance of class `MSnSet` that have been filtered.

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
mvFilter(Exp1_R25_pept, "WholeMatrix", 2)
```

mvFilterFromIndices *Filter lines in the matrix of intensities w.r.t. some criteria*

Description

Filters the lines of `exprs()` table with conditions on the number of missing values. The user chooses the minimum amount of intensities that is acceptable and the filter delete lines that do not respect this condition. The condition may be on the whole line or condition by condition.

Usage

```
mvFilterFromIndices(obj, keepThat = NULL, processText = "")
```

Arguments

| | |
|--------------------------|--|
| <code>obj</code> | An object of class <code>MSnSet</code> containing quantitative data. |
| <code>keepThat</code> | A vector of integers which are the indices of lines to keep. |
| <code>processText</code> | A string to be included in the <code>MSnSet</code> object for log. |

Details

The different methods are : "WholeMatrix": given a threshold `th`, only the lines that contain at least `th` values are kept. "AllCond": given a threshold `th`, only the lines which contain at least `th` values for each of the conditions are kept. "AtLeastOneCond": given a threshold `th`, only the lines that contain at least `th` values, and for at least one condition, are kept.

Value

An instance of class `MSnSet` that have been filtered.

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
mvFilterFromIndices(Exp1_R25_pept, c(1:10))
```

mvFilterGetIndices *Filter lines in the matrix of intensities w.r.t. some criteria*

Description

Returns the indices of the lines of `exprs()` table to delete w.r.t. the conditions on the number of missing values. The user chooses the minimum amount of intensities that is acceptable and the filter delete lines that do not respect this condition. The condition may be on the whole line or condition by condition.

Usage

```
mvFilterGetIndices(  
  obj,  
  percent = FALSE,  
  condition = "WholeMatrix",  
  threshold = NULL  
)
```

Arguments

| | |
|------------------------|--|
| <code>obj</code> | An object of class <code>MSnSet</code> containing quantitative data. |
| <code>percent</code> | TRUE or FALSE. Default is FALSE.. |
| <code>condition</code> | Method used to choose the lines to delete. Values are : "None", "EmptyLines", "WholeMatrix", "AllCond", "AtLeastOneCond" |
| <code>threshold</code> | An integer value of the threshold if <code>percent</code> is FALSE. Otherwise, a floating number between 0 and 1. |

Details

The different methods are : "WholeMatrix": given a threshold `th`, only the lines that contain at least `th` values are kept. "AllCond": given a threshold `th`, only the lines which contain at least `th` values for each of the conditions are kept. "AtLeastOneCond": given a threshold `th`, only the lines that contain at least `th` values, and for at least one condition, are kept.

Value

An vector of indices that correspond to the lines to keep.

Author(s)

Enora Fremy, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
keepThat <- mvFilterGetIndices(Exp1_R25_pept, condition = "WholeMatrix", threshold=2)  
keepThat <- mvFilterGetIndices(Exp1_R25_pept, condition = "EmptyLines")  
keepThat <- mvFilterGetIndices(Exp1_R25_pept, condition = "WholeMatrix", percent=TRUE, threshold=0.5)
```

`mvHisto_HC`*Histogram of missing values*

Description

This method plots a histogram of missing values. Same as the function `mvHisto` but uses the package `highcharter`

Usage

```
mvHisto_HC(  
  qData,  
  samplesData,  
  conds,  
  indLegend = "auto",  
  showValues = FALSE,  
  base_palette = NULL  
)
```

Arguments

| | |
|---------------------------|---|
| <code>qData</code> | A dataframe that contains quantitative data. |
| <code>samplesData</code> | A dataframe where lines correspond to samples and columns to the meta-data for those samples. |
| <code>conds</code> | A vector of the conditions (one condition per sample). |
| <code>indLegend</code> | The indices of the column name's in <code>pData()</code> tab |
| <code>showValues</code> | A logical that indicates wether numeric values should be drawn above the bars. |
| <code>base_palette</code> | xxx |

Value

A histogram

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
qData <- Biobase::exprs(Exp1_R25_pept)  
samplesData <- Biobase::pData(Exp1_R25_pept)  
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]  
mvHisto_HC(qData, samplesData, conds, indLegend="auto", showValues=TRUE)
```

| | |
|---------|----------------------------------|
| mvImage | <i>Heatmap of missing values</i> |
|---------|----------------------------------|

Description

Plots a heatmap of the quantitative data. Each column represent one of the conditions in the object of class MSnSet and the color is proportional to the mean of intensity for each line of the dataset. The lines have been sorted in order to visualize easily the different number of missing values. A white square is plotted for missing values.

Usage

```
mvImage(qData, conds)
```

Arguments

| | |
|-------|--|
| qData | A dataframe that contains quantitative data. |
| conds | A vector of the conditions (one condition per sample). |

Value

A heatmap

Author(s)

Samuel Wieczorek, Thomas Burger

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
mvImage(qData, conds)
```

| | |
|--------------------------------|---|
| mvPerLinesHistoPerCondition_HC | <i>Bar plot of missing values per lines and per condition</i> |
|--------------------------------|---|

Description

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins) and per conditions.

Usage

```
mvPerLinesHistoPerCondition_HC(
  qData,
  samplesData,
  indLegend = "auto",
  showValues = FALSE,
  palette = NULL
)
```

Arguments

| | |
|-------------|---|
| qData | A dataframe that contains quantitative data. |
| samplesData | A dataframe where lines correspond to samples and columns to the meta-data for those samples. |
| indLegend | The indice of the column name's in pData() tab |
| showValues | A logical that indicates wether numeric values should be drawn above the bars. |
| palette | xxx |

Value

A bar plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
samplesData <- Biobase::pData(Exp1_R25_pept)
mvPerLinesHistoPerCondition_HC(qData, samplesData, palette=(c('#AAAAAA', '#AAAAAA')))
```

mvPerLinesHisto_HC *Bar plot of missing values per lines using highcharter*

Description

This method plots a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins).

Usage

```
mvPerLinesHisto_HC(qData, samplesData, indLegend = "auto", showValues = FALSE)
```

Arguments

| | |
|-------------|--|
| qData | A dataframe that contains the data to plot. |
| samplesData | A dataframe which contains informations about the replicates. |
| indLegend | The indice of the column name's in pData() tab |
| showValues | A logical that indicates wether numeric values should be drawn above the bars. |

Value

A bar plot

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
samplesData <- Biobase::pData(Exp1_R25_pept)
mvPerLinesHisto_HC(qData, samplesData)
```

my_hc_chart

Customised resetZoomButton of highcharts plots

Description

Customise the resetZoomButton of highcharts plots.

Usage

```
my_hc_chart(hc, chartType, zoomType = "None")
```

Arguments

| | |
|-----------|--|
| hc | A highcharter object |
| chartType | The type of the plot |
| zoomType | The type of the zoom (one of "x", "y", "xy", "None") |

Value

A highchart plot

Author(s)

Samuel Wiczorek

Examples

```
library("highcharter")
hc <- highchart()
hc_chart(hc, type = "line")
hc_add_series(hc, data = c(29, 71, 40))
my_hc_ExportMenu(hc, filename='foo')
```

| | |
|------------------|---|
| my_hc_ExportMenu | <i>Customised contextual menu of highcharts plots</i> |
|------------------|---|

Description

Customise the contextual menu of highcharts plots.

Usage

```
my_hc_ExportMenu(hc, filename)
```

Arguments

| | |
|----------|---|
| hc | A highcharter object |
| filename | The filename under which the plot has to be saved |

Value

A contextual menu for highcharts plots

Author(s)

Samuel Wieczorek

Examples

```
library("highcharter")
hc <- highchart()
hc_chart(hc,type = "line")
hc_add_series(hc,data = c(29, 71, 40))
my_hc_ExportMenu(hc,filename='foo')
```

| | |
|---------|---|
| nonzero | <i>Retrieve the indices of non-zero elements in sparse matrices</i> |
|---------|---|

Description

This function retrieves the indices of non-zero elements in sparse matrices of class dgCMatrix from package Matrix. This function is largely inspired from the package RINGO

Usage

```
nonzero(x)
```

Arguments

| | |
|---|------------------------------------|
| x | A sparse matrix of class dgCMatrix |
|---|------------------------------------|

Value

A two-column matrix

Author(s)

Samuel Wieczorek

Examples

```
library(Matrix)
mat <- Matrix(c(0,0,0,0,0,1,0,0,1,1,0,0,0,0,1),nrow=5, byrow=TRUE, sparse=TRUE)
res <- nonzero(mat)
```

normalizeMethods.dapar

List normalization methods with tracking option

Description

List normalization methods with tracking option

Usage

```
normalizeMethods.dapar(withTracking = FALSE)
```

Arguments

withTracking xxx

NumericalFiltering *Removes lines in the dataset based on numerical conditions.*

Description

This function removes lines in the dataset based on numerical conditions.

Usage

```
NumericalFiltering(obj, name = NULL, value = NULL, operator = NULL)
```

Arguments

| | |
|----------|--|
| obj | An object of class MSnSet. |
| name | The name of the column that correspond to the line to filter |
| value | A number |
| operator | A string |

Value

An list of 2 items : obj : an object of class MSnSet in which the lines have been deleted deleted : an object of class MSnSet which contains the deleted lines

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
NumericalFiltering(Exp1_R25_pept, 'A_Count', '6', '==')
```

NumericalgetIndicesOfLinesToRemove

Get the indices of the lines to delete, based on a prefix string

Description

This function returns the indice of the lines to delete, based on a prefix string

Usage

```
NumericalgetIndicesOfLinesToRemove(
  obj,
  name = NULL,
  value = NULL,
  operator = NULL
)
```

Arguments

| | |
|----------|--|
| obj | An object of class MSnSet. |
| name | The name of the column that correspond to the data to filter |
| value | xxxx |
| operator | A xxxx |

Value

A vector of integers.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
NumericalgetIndicesOfLinesToRemove(Exp1_R25_pept, "A_Count", value="6", operator='==')
```

pepa.test

*PEptide based Protein differential Abundance test***Description**

This function is PEptide based Protein differential Abundance test

Usage

```
pepa.test(X, y, n1, n2, global = FALSE, use.lm = FALSE)
```

Arguments

| | |
|--------|--|
| X | Binary q x p design matrix for q peptides and p proteins. $X_{(ij)}=1$ if peptide i belongs to protein j, 0 otherwise. |
| y | q x n matrix representing the log intensities of q peptides among n MS samples. |
| n1 | number of samples under condition 1. It is assumed that the first n1 columns of y correspond to observations under condition 1. |
| n2 | number of samples under condition 2. |
| global | if TRUE, the test statistic for each protein uses all residues, including the ones for peptides in different connected components. Can be much faster as it does not require to compute connected components. However the p-values are not well calibrated in this case, as it amounts to adding a ridge to the test statistic. Calibrating the p-value would require knowing the amplitude of the ridge, which in turns would require computing the connected components. |
| use.lm | if TRUE (and if global=FALSE), use lm() rather than the result in Proposition 1 to compute the test statistic |

Value

A list of the following elements: llr: log likelihood ratio statistic (maximum likelihood version). llr.map: log likelihood ratio statistic (maximum a posteriori version). llr.pv: p-value for llr. llr.map.pv: p-value for llr.map. mse.h0: Mean squared error under H0 mse.h1: Mean squared error under H1 s: selected regularization hyperparameter for llr.map. wchi2: weight used to make llr.map chi2-distributed under H0.

Author(s)

Thomas Burger, Laurent Jacob

plotJitter *Jitter plot of CC*

Description

Jitter plot of CC

Usage

```
plotJitter(list.of.cc)
```

Arguments

list.of.cc List of cc such as returned by the function get.pep.prot.cc

Value

A plot

Author(s)

Thomas Burger

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
X <- BuildAdjacencyMatrix(Exp1_R25_pept[1:1000], "Protein_group_IDs", TRUE)
ll <- get.pep.prot.cc(X)
plotJitter(ll)
```

plotJitter_rCharts *Display a a jitter plot for CC*

Description

Display a jitter plot for CC

Usage

```
plotJitter_rCharts(df, clickFunction = NULL)
```

Arguments

df xxxx
clickFunction xxxx

Value

A plot

Author(s)

Thomas Burger, Samuel Wiczorek

plotPCA_Eigen *Plots the eigen values of PCA*

Description

Plots the eigen values of PCA

Usage

```
plotPCA_Eigen(res.pca)
```

Arguments

res.pca xxx

Value

A histogram

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
res.pca <- wrapper.pca(Exp1_R25_pept, ncp=6)
plotPCA_Eigen(res.pca)
```

plotPCA_Eigen_hc *Plots the eigen values of PCA with the highcharts library*

Description

Plots the eigen values of PCA with the highcharts library

Usage

```
plotPCA_Eigen_hc(res.pca)
```

Arguments

res.pca xxx

Value

A histogram

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
res.pca <- wrapper.pca(Exp1_R25_pept, ncp=6)
plotPCA_Eigen_hc(res.pca)
```

plotPCA_Ind

Plots individuals of PCA

Description

Plots individuals of PCA

Usage

```
plotPCA_Ind(res.pca, chosen.axes = c(1, 2))
```

Arguments

| | |
|-------------|------------------------|
| res.pca | xxx |
| chosen.axes | The dimensions to plot |

Value

A plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
res.pca <- wrapper.pca(Exp1_R25_pept)
plotPCA_Ind(res.pca)
```

| | |
|-------------|-------------------------------|
| plotPCA_Var | <i>Plots variables of PCA</i> |
|-------------|-------------------------------|

Description

Plots the variables of PCA

Usage

```
plotPCA_Var(res.pca, chosen.axes = c(1, 2))
```

Arguments

| | |
|-------------|------------------------|
| res.pca | xxx |
| chosen.axes | The dimensions to plot |

Value

A plot

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
res.pca <- wrapper.pca(Exp1_R25_pept)
plotPCA_Var(res.pca)
```

| | |
|-------------|---|
| postHocTest | <i>Post-hoc tests for classic 1-way ANOVA</i> |
|-------------|---|

Description

This function allows to compute a post-hoc test after a 1-way ANOVA analysis. It expects as input an object obtained with the function `classic1wayAnova`. The second parameter allows to choose between 2 different post-hoc tests: the Tukey Honest Significant Differences (specified as "TukeyHSD") and the Dunnett test (specified as "Dunnett").

Usage

```
postHocTest(aov_fits, post_hoc_test = "TukeyHSD")
```

Arguments

| | |
|---------------|--|
| aov_fits | a list containing aov fitted model objects |
| post_hoc_test | a character string indicating which post-hoc test to use. Possible values are "TukeyHSD" or "Dunnett". See details for what to choose according to your experimental design. |

Details

This is a function allowing to realise post-hoc tests for a set of proteins/peptides for which a classic 1-way anova has been performed with the function `classic1wayAnova`. Two types of tests are currently available: The Tukey HSD's test and the Dunnett's test. Default is Tukey's test. The Tukey HSD's test compares all possible pairs of means, and is based on a studentized range distribution. Here is used the `TukeyHSD()` function, which can be applied to balanced designs (same number of samples in each group), but also to midly unbalanced designs. The Dunnett's test compares a single control group to all other groups. Make sure the factor levels are properly ordered.

Value

a list of 2 dataframes: first one called "LogFC" contains all pairwise comparisons logFC values (one column for one comparison) for each analysed feature; The second one named "P_Value" contains the corresponding pvalues.

Author(s)

H  l  ne Borges

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
anova_tests <- t(apply(Biobase::exprs(obj),1, classic1wayAnova, conditions=as.factor(Biobase::pData(obj)$Con
names(anova_tests) <- rownames(Biobase::exprs(obj))
pht <- postHocTest(aov_fits = anova_tests)
```

proportionConRev_HC *Barplot of proportion of contaminants and reverse*

Description

Plots a barplot of proportion of contaminants and reverse. Same as the function `proportionConRev` but uses the package `highcharter`

Usage

```
proportionConRev_HC(nBoth = 0, nCont = 0, nRev = 0, lDataset = 0)
```

Arguments

| | |
|-----------------------|--|
| <code>nBoth</code> | The number of both contaminants and reverse identified in the dataset. |
| <code>nCont</code> | The number of contaminants identified in the dataset. |
| <code>nRev</code> | The number of reverse entities identified in the dataset. |
| <code>lDataset</code> | The total length (number of rows) of the dataset |

Value

A barplot

Author(s)

Samuel Wieczorek

Examples

```
proportionConRev_HC(10, 20, 100)
```

QuantileCentering *Normalisation QuantileCentering*

Description

Normalisation QuantileCentering

Usage

```
QuantileCentering(  
  qData,  
  conds = NULL,  
  type = "overall",  
  subset.norm = NULL,  
  quantile = 0.15  
)
```

Arguments

| | |
|-------------|---|
| qData | xxx |
| conds | xxx |
| type | "overall" (shift all the sample distributions at once) or "within conditions" (shift the sample distributions within each condition at a time). |
| subset.norm | A vector of index indicating rows to be used for normalization |
| quantile | A float that corresponds to the quantile used to align the data. |

Value

A normalized numeric matrix

Author(s)

Samuel Wieczorek, Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
obj <- Exp1_R25_pept  
conds <- Biobase::pData(Exp1_R25_pept)$Condition  
normalized <- QuantileCentering(Biobase::exprs(obj), conds, type="within conditions", subset.norm=1:10)
```

| | |
|-------------|--|
| rbindMSnset | <i>Similar to the function rbind but applies on two subsets of the same MSnSet object.</i> |
|-------------|--|

Description

Similar to the function rbind but applies on two subsets of the same MSnSet object.

Usage

```
rbindMSnset(df1 = NULL, df2)
```

Arguments

| | |
|-----|---|
| df1 | An object (or subset of) of class MSnSet. May be NULL |
| df2 | A subset of the same object as df1 |

Value

An instance of class MSnSet.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
df1 <- Exp1_R25_pept[1:100]
df2 <- Exp1_R25_pept[200:250]
rbindMSnset(df1, df2)
```

| | |
|-----------|---|
| readExcel | <i>This function reads a sheet of an Excel file and put the data into a data.frame.</i> |
|-----------|---|

Description

This function reads a sheet of an Excel file and put the data into a data.frame.

Usage

```
readExcel(file, extension, sheet)
```

Arguments

| | |
|-----------|-----------------------------|
| file | The name of the Excel file. |
| extension | The extension of the file |
| sheet | The name of the sheet |

Value

A data.frame

Author(s)

Samuel Wieczorek

reIntroduceMEC *Put back LAPALA into a MSnSet object*

Description

This method is used to put back the LAPALA that have been identified previously

Usage

```
reIntroduceMEC(obj, MECIndex)
```

Arguments

obj An object of class MSnSet.
MECIndex A data.frame that contains index of MEC (see findMECBlock).

Value

The object obj where LAPALA have been reintroduced

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
obj <- Exp1_R25_pept[1:1000]  
lapala <- findMECBlock(obj)  
obj <- wrapper.impute.detQuant(obj)  
obj <- reIntroduceMEC(obj, lapala)
```

| | |
|-------------|---|
| removeLines | <i>Removes lines in the dataset based on a prefix string.</i> |
|-------------|---|

Description

This function removes lines in the dataset based on a prefix string.

Usage

```
removeLines(obj, idLine2Delete = NULL, prefix = NULL)
```

Arguments

| | |
|---------------|--|
| obj | An object of class MSnSet. |
| idLine2Delete | The name of the column that correspond to the data to filter |
| prefix | A character string that is the prefix to find in the data |

Value

An object of class MSnSet.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
removeLines(Exp1_R25_pept, "Potential_contaminant")
removeLines(Exp1_R25_pept, "Reverse")
```

| | |
|--------|--------|
| samLRT | xxxxxx |
|--------|--------|

Description

This function computes a regularized version of the likelihood ratio statistic. The regularization adds a user-input fudge factor $s1$ to the variance estimator. This is straightforward when using a fixed effect model (cases 'numeric' and 'lm') but requires some more care when using a mixed model.

Usage

```
samLRT(lmm.res.h0, lmm.res.h1, cc, n, p, s1)
```

Arguments

| | |
|------------|--|
| lmm.res.h0 | a vector of object containing the estimates (used to compute the statistic) under H0 for each connected component. If the fast version of the estimator was used (as implemented in this package), lmm.res.h0 is a vector containing averages of squared residuals. If a fixed effect model was used, it is a vector of lm objects and if a mixed effect model was used it is a vector or lmer object. |
| lmm.res.h1 | similar to lmm.res.h0, a vector of object containing the estimates (used to compute the statistic) under H1 for each protein. |
| cc | a list containing the indices of peptides and proteins belonging to each connected component. |
| n | the number of samples used in the test |
| p | the number of proteins in the experiment |
| s1 | the fudge factor to be added to the variance estimate |

Value

llr.sam: a vector of numeric containing the regularized log likelihood ratio statistic for each protein.
s: a vector containing the maximum likelihood estimate of the variance for the chosen model. When using the fast version of the estimator implemented in this package, this is the same thing as the input lmm.res.h1.
lh1.sam: a vector of numeric containing the regularized log likelihood under H1 for each protein.
lh0.sam: a vector of numeric containing the regularized log likelihood under H0 for each connected component.
sample.sizes: a vector of numeric containing the sample size (number of biological samples times number of peptides) for each protein. This number is the same for all proteins within each connected component.

Author(s)

Thomas Burger, Laurent Jacob

| | |
|----------------|--|
| saveParameters | <i>Saves the parameters of a tool in the pipeline of Prostar</i> |
|----------------|--|

Description

Saves the parameters of a tool in the pipeline of Prostar

Usage

```
saveParameters(obj, name.dataset = NULL, name = NULL, l.params = NULL)
```

Arguments

| | |
|--------------|--|
| obj | An object of class MSnSet |
| name.dataset | The name of the dataset |
| name | The name of the tool. Available values are: "Norm, Imputation, anaDiff, GO-Analysis,Aggregation" |
| l.params | A list that contains the parameters |

Value

An instance of class MSnSet.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
l.params=list(method="Global quantile alignment", type="overall")
saveParameters(Exp1_R25_pept, "Filtered.peptide", "Imputation",l.params)
```

scatterplotEnrichGO_HC

*A dotplot that shows the result of a GO enrichment, using the package
highcharter*

Description

A scatter plot of GO enrichment analysis

Usage

```
scatterplotEnrichGO_HC(ego, maxRes = 10, title = NULL)
```

Arguments

| | |
|--------|---|
| ego | The result of the GO enrichment, provides either by the function <code>enrichGO</code> in DAPAR or the function <code>enrichGO</code> of the package <code>clusterProfiler</code> |
| maxRes | The maximum number of categories to display in the plot |
| title | The title of the plot |

Value

A dotplot

Author(s)

Samuel Wieczorek

| | |
|--------|---|
| setMEC | <i>Sets the MEC tag in the OriginOfValues</i> |
|--------|---|

Description

Sets the MEC tag in the OriginOfValues

Usage

```
setMEC(obj)
```

Arguments

obj An object of class MSnSet

Value

An instance of class MSnSet.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
setMEC(Exp1_R25_pept)
```

| | |
|-------------------|--|
| splitAdjacencyMat | <i>splits an adjacency matrix into specific and shared</i> |
|-------------------|--|

Description

Method to split an adjacency matrix into specific and shared

Usage

```
splitAdjacencyMat(X)
```

Arguments

X An adjacency matrix

Value

A list of two adjacency matrices

Author(s)

Samuel Wieczorek

StringBasedFiltering *Removes lines in the dataset based on a prefix strings (contaminants, reverse or both).*

Description

This function removes lines in the dataset based on prefix strings (contaminants, reverse or both).

Usage

```
StringBasedFiltering(  
  obj,  
  idCont2Delete = NULL,  
  prefix_Cont = NULL,  
  idRev2Delete = NULL,  
  prefix_Rev = NULL  
)
```

Arguments

| | |
|---------------|--|
| obj | An object of class MSnSet. |
| idCont2Delete | The name of the column that correspond to the contaminants to filter |
| prefix_Cont | A character string that is the prefix for the contaminants to find in the data |
| idRev2Delete | The name of the column that correspond to the reverse data to filter |
| prefix_Rev | A character string that is the prefix for the reverse to find in the data |

Value

An list of 4 items : obj : an object of class MSnSet in which the lines have been deleted deleted.both : an object of class MSnSet which contains the deleted lines corresponding to both contaminants and reverse, deleted.contaminants : n object of class MSnSet which contains the deleted lines corresponding to contaminants, deleted.reverse : an object of class MSnSet which contains the deleted lines corresponding to reverse,

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
StringBasedFiltering(Exp1_R25_pept, 'Potential_contaminant', '+', 'Reverse', '+')
```

StringBasedFiltering2 *Removes lines in the dataset based on a prefix strings.*

Description

This function removes lines in the dataset based on prefix strings.

Usage

```
StringBasedFiltering2(obj, cname = NULL, tag = NULL)
```

Arguments

| | |
|-------|--|
| obj | An object of class MSnSet. |
| cname | The name of the column that correspond to the line to filter |
| tag | A character string that is the prefix for the contaminants to find in the data |

Value

An list of 4 items : obj : an object of class MSnSet in which the lines have been deleted deleted : an object of class MSnSet which contains the deleted lines

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
StringBasedFiltering2(Exp1_R25_pept, 'Potential_contaminant', '+')
```

SumByColumns *Normalisation SumByColumns*

Description

Normalisation SumByColumns

Usage

```
SumByColumns(qData, conds = NULL, type = NULL, subset.norm = NULL)
```

Arguments

| | |
|-------------|--|
| qData | xxxx |
| conds | xxx |
| type | Available values are "overall" (shift all the sample distributions at once) or "within conditions" (shift the sample distributions within each condition at a time). |
| subset.norm | A vector of index indicating rows to be used for normalization |

Value

A normalized numeric matrix

Author(s)

Samuel Wiczorek, Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
conds <- Biobase::pData(Exp1_R25_pept)$Condition
normalized <- SumByColumns(qData, conds, type="within conditions", subset.norm=1:10)
```

test.design

Check if xxxxxx

Description

This function check xxxxx

Usage

```
test.design(tab)
```

Arguments

tab A data.frame which correspond to xxxxxx

Value

A list of two items

Author(s)

Thomas Burger, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
test.design(Biobase::pData(Exp1_R25_pept)[,1:3])
```

translatedRandomBeta *Generator of simulated values*

Description

Generator of simulated values

Usage

```
translatedRandomBeta(n, min, max, param1 = 3, param2 = 1)
```

Arguments

| | |
|--------|---|
| n | An integer which is the number of simulation (same as in rbeta) |
| min | An integer that corresponds to the lower bound of the interval |
| max | An integer that corresponds to the upper bound of the interval |
| param1 | An integer that is the first parameter of rbeta function. |
| param2 | An integer that is second parameter of rbeta function. |

Value

A vector of n simulated values

Author(s)

Thomas Burger

Examples

```
translatedRandomBeta(1000, 5, 10, 1, 1)
```

| | |
|-----------------|---|
| univ_AnnotDbPkg | <i>Returns the totality of ENTREZ ID (gene id) of an OrgDb annotation package. Careful : org.Pf.plasmo.db : no ENTREZID but ORF</i> |
|-----------------|---|

Description

Function to compute the "universe" argument for the enrich_GO function, in case this latter should be the entire organism. Returns all the ID of the OrgDb annotation package for the corresponding organism.

Usage

```
univ_AnnotDbPkg(orgdb)
```

Arguments

| | |
|-------|---|
| orgdb | a Bioconductor OrgDb annotation package |
|-------|---|

Value

A vector of ENTREZ ID

Author(s)

Florence Combes

violinPlotD

Builds a violinplot from a dataframe

Description

Builds a violinplot from a dataframe

Usage

```
violinPlotD(  
  obj,  
  conds,  
  keyId,  
  legend = NULL,  
  palette = NULL,  
  subset.view = NULL  
)
```

Arguments

| | |
|-------------|--|
| obj | xxx |
| conds | xxx |
| keyId | xxx |
| legend | A vector of the conditions (one condition per sample). |
| palette | xxx |
| subset.view | xxx |

Value

A violinplot

Author(s)

Samuel Wieczorek, Anais Courtier

See Also

[densityPlotD](#)

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot
library(vioplot)
legend <- conds <- Biobase::pData(obj)$Condition
key <- "Protein_IDs"
violinPlotD(obj, conds=legend, keyId=key, legend=legend, palette=c(rep('blue',3), rep('green',3)),subset.vie
```

| | |
|-------------------|--|
| visualizeClusters | <i>Visualize the clusters according to pvalue thresholds</i> |
|-------------------|--|

Description

Visualize the clusters according to pvalue thresholds

Usage

```
visualizeClusters(  
  dat,  
  clust_model,  
  adjusted_pValues,  
  FDR_th = NULL,  
  ttl = "",  
  subttl = ""  
)
```

Arguments

| | |
|------------------|--|
| dat | the standardize data returned by the function [checkClusterability()] |
| clust_model | the clustering model obtained with dat. |
| adjusted_pValues | vector of the adjusted pvalues obtained for each protein with a 1-way ANOVA (for example obtained with the function [wrapperClassic1wayAnova()]). |
| FDR_th | the thresholds of FDR pvalues for the coloring of the profiles. The default (NULL) creates 4 thresholds: 0.001, 0.005, 0.01, 0.05 For the sake of readability, a maximum of 4 values can be specified. |
| ttl | title for the plot. |
| subttl | subtitle for the plot. |

Value

a ggplot object

Author(s)

Helene Borges

Examples

```

library(dplyr)
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:100]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
expR25_ttest <- compute_t_tests(obj)
averaged_means <- averageIntensities(obj)
only_means <- dplyr::select_if(averaged_means, is.numeric)
only_features <- dplyr::select_if(averaged_means, is.character)
means <- purrr::map(purrr::array_branch(as.matrix(only_means), 1), mean)
centered <- only_means - unlist(means)
centered_means <- dplyr::bind_cols(feature = dplyr::as_tibble(only_features), dplyr::as_tibble(centered))
difference <- only_means[,1] - only_means[,2]
clusters <- as.data.frame(difference) %>%
  dplyr::mutate(cluster = dplyr::if_else(difference > 0, 1,2))
vizu <- visualizeClusters(dat = centered_means,
  clust_model = as.factor(clusters$cluster),
  adjusted_pValues = expR25_ttest$P_Value$`25fmol_vs_10fmol_pval`,
  FDR_th = c(0.001,0.005,0.01,0.05),
  ttl = "Clustering of protein profiles")

```

vsn

*Normalisation vsn***Description**

Normalisation vsn

Usage

vsn(qData, conds, type = NULL)

Arguments

| | |
|-------|---|
| qData | A numeric matrix. |
| conds | xxx |
| type | "overall" (shift all the sample distributions at once) or "within conditions" (shift the sample distributions within each condition at a time). |

Value

A normalized numeric matrix

Author(s)

Thomas Burger, Helene Borges, Anais Courtier, Enora Fremy

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
qData <- Biobase::exprs(Exp1_R25_pept)
conds <- Biobase::pData(Exp1_R25_pept)$Condition
normalized <- vsn(qData, conds, type="overall")
```

```
wrapper.compareNormalizationD_HC
      Builds a plot from a dataframe
```

Description

```
#' Wrapper to the function that plot to compare the quantitative proteomics #' data before and after
normalization #' #' @title Builds a plot from a dataframe #' #' @param objBefore A dataframe
that contains quantitative data before #' normalization. #' #' @param objAfter A dataframe that
contains quantitative data after #' normalization. #' #' @param conds A vector of the condi-
tions (one condition per sample). #' #' @param indData2Show A vector of the indices of the
columns to show in the #' plot. The indices are those of indices of #' the columns int the data.frame
qDataBefore. #' #' @param ... arguments for palette #' #' @return A plot #' #' @author Samuel
Wieczorek #' #' @examples #' utils::data(Exp1_R25_pept, package='DAPARdata') #' conds <-
Biobase::pData(Exp1_R25_pept)[,"Condition"] #' objAfter <- wrapper.normalizeD(obj=Exp1_R25_pept,
method="QuantileCentering",conds = conds, type="within conditions") #' wrapper.compareNormalizationD(Exp1_R25_
objAfter, conds) #' #' @importFrom Biobase exprs pData #' #' @export #' #' @importFrom
Biobase exprs fData pData #' wrapper.compareNormalizationD <- function(objBefore, objAfter,
conds=NULL, indData2Show=NULL, ...)
```

```
qDataBefore <- Biobase::exprs(objBefore) qDataAfter <- Biobase::exprs(objAfter) if (is.null(conds))
conds <- Biobase::pData(objBefore)[,"Condition"]
```

```
compareNormalizationD(qDataBefore, qDataAfter, conds, indData2Show, ...)
```

Wrapper to the function that plot to compare the quantitative proteomics data before and after normalization.

Usage

```
wrapper.compareNormalizationD_HC(
  objBefore,
  objAfter,
  condsForLegend = NULL,
  ...
)
```

Arguments

| | |
|----------------|---|
| objBefore | A dataframe that contains quantitative data before normalization. |
| objAfter | A dataframe that contains quantitative data after normalization. |
| condsForLegend | A vector of the conditions (one condition per sample). |
| ... | arguments for palette |

Value

A plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conds <- Biobase::pData(Exp1_R25_pept)[,"Condition"]
objAfter <- wrapper.normalizeD(obj = Exp1_R25_pept, method = "QuantileCentering", conds=conds, type = "within")
wrapper.compareNormalizationD_HC(Exp1_R25_pept, objAfter, conds)
```

```
wrapper.corrMatrixD_HC
```

Displays a correlation matrix of the quantitative data of the exprs() table

Description

```
#' Builds a correlation matrix based on a MSnSet object. #' #' @title Displays a correlation matrix of the quantitative data of the #' exprs() table #' #' @param obj An object of class MSnSet. #' #' @param rate A float that defines the gradient of colors. #' #' @return A colored correlation matrix #' #' @author Alexia Dorffer #' #' @examples #' #' @importFrom Biobase exprs pData #' #' @export #' wrapper.corrMatrixD <- function(obj, rate=5) qData <- Biobase::exprs(obj) samplesData <- Biobase::pData(obj) corrMatrixD(qData, samplesData, rate)
```

Builds a correlation matrix based on a MSnSet object.

Usage

```
wrapper.corrMatrixD_HC(obj, rate = 0.5, showValues = TRUE)
```

Arguments

| | |
|------------|--|
| obj | An object of class MSnSet. |
| rate | A float that defines the gradient of colors. |
| showValues | xxx |

Value

A colored correlation matrix

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.corrMatrixD_HC(Exp1_R25_pept)
```

| | |
|-----------------|---------------------------------------|
| wrapper.CVDistD | <i>Distribution of CV of entities</i> |
|-----------------|---------------------------------------|

Description

Builds a densityplot of the CV of entities in the `exprs()` table of an object `MSnSet`. The variance is calculated for each condition present in the dataset (see the slot 'Condition' in the `pData()` table).

Usage

```
wrapper.CVDistD(obj, ...)
```

Arguments

| | |
|------------------|--|
| <code>obj</code> | An object of class <code>MSnSet</code> . |
| <code>...</code> | arguments for palette |

Value

A density plot

Author(s)

Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.CVDistD(Exp1_R25_pept)
```

| | |
|--------------------|---------------------------------------|
| wrapper.CVDistD_HC | <i>Distribution of CV of entities</i> |
|--------------------|---------------------------------------|

Description

Builds a densityplot of the CV of entities in the `exprs()` table. of an object `MSnSet`. The variance is calculated for each condition present in the dataset (see the slot 'Condition' in the `pData()` table). Same as the function `wrapper.CVDistD` but uses the package `highcharter`

Usage

```
wrapper.CVDistD_HC(obj, ...)
```

Arguments

obj An object of class MSnSet
... arguments for palette.

Value

A density plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
wrapper.CVDistD_HC(Exp1_R25_pept)
```

wrapper.dapar.impute.mi

Missing values imputation using the LSImpute algorithm.

Description

This method is a wrapper to the function `impute.mi` of the package `imp4p` adapted to an object of class `MSnSet`.

Usage

```
wrapper.dapar.impute.mi(  
  obj,  
  nb.iter = 3,  
  nknn = 15,  
  selec = 600,  
  siz = 500,  
  weight = 1,  
  ind.comp = 1,  
  progress.bar = FALSE,  
  x.step.mod = 300,  
  x.step.pi = 300,  
  nb.rei = 100,  
  method = 4,  
  gridsize = 300,  
  q = 0.95,  
  q.min = 0,  
  q.norm = 3,  
  eps = 0,  
  methodi = "slsa",  
  lapala = TRUE,  
  distribution = "unif"  
)
```

Arguments

| | |
|--------------|---|
| obj | An object of class MSnSet. |
| nb.iter | Same as the function mi.mix in the package imp4p |
| nknn | Same as the function mi.mix in the package imp4p |
| selec | Same as the function mi.mix in the package imp4p |
| siz | Same as the function mi.mix in the package imp4p |
| weight | Same as the function mi.mix in the package imp4p |
| ind.comp | Same as the function mi.mix in the package imp4p |
| progress.bar | Same as the function mi.mix in the package imp4p |
| x.step.mod | Same as the function estim.mix in the package imp4p |
| x.step.pi | Same as the function estim.mix in the package imp4p |
| nb.rei | Same as the function estim.mix in the package imp4p |
| method | Same as the function estim.mix in the package imp4p |
| gridsize | Same as the function estim.mix in the package imp4p |
| q | Same as the function mi.mix in the package imp4p |
| q.min | Same as the function impute.pa in the package imp4p |
| q.norm | Same as the function impute.pa in the package imp4p |
| eps | Same as the function impute.pa in the package imp4p |
| methodi | Same as the function mi.mix in the package imp4p |
| lapala | xxxxxxxxxxx |
| distribution | The type of distribution used. Values are unif (default) or beta. |

Value

The `exprs(obj)` matrix with imputed values instead of missing values.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
dat <- mvFilter(Exp1_R25_pept[1:1000], type="AllCond", th = 1)
dat <- wrapper.dapar.impute.mi(dat, nb.iter=1)
```

```
wrapper.hc_mvTypePlot2
```

Distribution of observed values with respect to intensity values from a MSnSet object

Description

This method is a wrapper for the function [hc_mvTypePlot2](#) adapted to objects of class MSnSet).

Usage

```
wrapper.hc_mvTypePlot2(obj, ...)
```

Arguments

`obj` An object of class MSnSet.
`...` See [hc_mvTypePlot2](#)

Value

A scatter plot

Author(s)

Florence Combes, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
wrapper.hc_mvTypePlot2(Exp1_R25_pept)
```

```
wrapper.heatmapD
```

This function is a wrapper to [heatmap.2](#) that displays quantitative data in the `exprs()` table of an object of class MSnSet

Description

Builds a heatmap of the quantitative proteomic data of a MSnSet object.

Usage

```
wrapper.heatmapD(  
  obj,  
  distance = "euclidean",  
  cluster = "complete",  
  dendro = FALSE  
)
```

Arguments

| | |
|----------|---|
| obj | An object of class MSnSet. |
| distance | The distance used by the clustering algorithm to compute the dendrogram. See <code>help(heatmap.2)</code> . |
| cluster | the clustering algorithm used to build the dendrogram. See <code>help(heatmap.2)</code> |
| dendro | A boolean to indicate if the dendrogram has to be displayed |

Value

A heatmap

Author(s)

Alexia Dorffer

Examples

```
## Not run:
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- mvFilter(Exp1_R25_pept[1:1000], "WholeMatrix", 6)
wrapper.heatmapD(obj)

## End(Not run)
```

wrapper.impute.detQuant

Wrapper of the function [impute.detQuant](#) for objects of class MSnSet

Description

This method is a wrapper of the function [impute.detQuant](#) for objects of class MSnSet

Usage

```
wrapper.impute.detQuant(obj, qval = 0.025, factor = 1)
```

Arguments

| | |
|--------|--|
| obj | An instance of class MSnSet |
| qval | An expression set containing quantitative values of various replicates |
| factor | A scaling factor to multiply the imputation value with |

Value

An imputed instance of class MSnSet

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.impute.detQuant(Exp1_R25_pept)
```

```
wrapper.impute.fixedValue
```

Missing values imputation from a MSnSet object

Description

This method is a wrapper to objects of class MSnSet and imputes missing values with a fixed value.

Usage

```
wrapper.impute.fixedValue(obj, fixVal)
```

Arguments

| | |
|--------|----------------------------|
| obj | An object of class MSnSet. |
| fixVal | A float . |

Value

The object obj which has been imputed

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.impute.fixedValue(Exp1_R25_pept[1:1000], 0.001)
```

```
wrapper.impute.KNN
```

KNN missing values imputation from a MSnSet object

Description

This method is a wrapper for objects of class MSnSet and imputes missing values with a fixed value. This function imputes the missing values condition by condition.

Usage

```
wrapper.impute.KNN(obj, K)
```


Arguments

obj An object of class MSnSet.
K the number of neighbors.

Value

The object obj which has been imputed

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
wrapper.impute.KNN(Exp1_R25_pept[1:1000], 3)
```

wrapper.impute.mle *Imputation of peptides having no values in a biological condition.*

Description

This method is a wrapper to the function `impute.mle` of the package `imp4p` adapted to an object of class `MSnSet`.

Usage

```
wrapper.impute.mle(obj)
```

Arguments

obj An object of class MSnSet.

Value

The `exprs(obj)` matrix with imputed values instead of missing values.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
dat <- mvFilter(Exp1_R25_pept[1:1000,], type="AllCond", th = 1)  
dat <- wrapper.impute.mle(dat)
```

wrapper.impute.pa *Imputation of peptides having no values in a biological condition.*

Description

This method is a wrapper to the function `impute.pa` of the package `imp4p` adapted to an object of class `MSnSet`.

Usage

```
wrapper.impute.pa(obj, q.min = 0.025)
```

Arguments

`obj` An object of class `MSnSet`.
`q.min` Same as the function `impute.pa` in the package `imp4p`

Value

The `exprs(obj)` matrix with imputed values instead of missing values.

Author(s)

Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
dat <- mvFilter(Exp1_R25_pept[1:1000], type="AllCond", th = 1)  
dat <- wrapper.impute.pa(dat)
```

wrapper.impute.pa2 *Missing values imputation from a MSnSet object*

Description

This method is a wrapper to the function `impute.pa2` adapted to objects of class `MSnSet`.

Usage

```
wrapper.impute.pa2(obj, q.min = 0, q.norm = 3, eps = 0, distribution = "unif")
```

Arguments

| | |
|--------------|--|
| obj | An object of class MSnSet. |
| q.min | A quantile value of the observed values allowing defining the maximal value which can be generated. This maximal value is defined by the quantile q.min of the observed values distribution minus eps. Default is 0 (the maximal value is the minimum of observed values minus eps). |
| q.norm | A quantile value of a normal distribution allowing defining the minimal value which can be generated. Default is 3 (the minimal value is the maximal value minus $qn * \text{median}(sd(\text{observed values}))$ where sd is the standard deviation of a row in a condition). |
| eps | A value allowing defining the maximal value which can be generated. This maximal value is defined by the quantile q.min of the observed values distribution minus eps. Default is 0. |
| distribution | The type of distribution used. Values are unif (default) or beta. |

Value

The object obj which has been imputed

Author(s)

Thomas Burger, Samuel Wiczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.impute.pa2(Exp1_R25_pept[1:1000], distribution="beta")
```

wrapper.impute.slsa *Imputation of peptides having no values in a biological condition.*

Description

This method is a wrapper to the function `impute.slsa` of the package `imp4p` adapted to an object of class `MSnSet`.

Usage

```
wrapper.impute.slsa(obj)
```

Arguments

| | |
|-----|----------------------------|
| obj | An object of class MSnSet. |
|-----|----------------------------|

Value

The `exprs(obj)` matrix with imputed values instead of missing values.

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
dat <- DAPAR::mvFilter(Exp1_R25_pept[1:1000], type="AllCond", th = 1)
dat <- wrapper.impute.slsa(dat)
```

wrapper.mvHisto_HC *Histogram of missing values from a MSnSet object*

Description

This method plots from a MSnSet object a histogram of missing values.

Usage

```
wrapper.mvHisto_HC(obj, indLegend = "auto", showValues = FALSE, ...)
```

Arguments

| | |
|------------|--|
| obj | An object of class MSnSet. |
| indLegend | The indices of the column name's in pData() tab. |
| showValues | A logical that indicates wether numeric values should be drawn above the bars. |
| ... | xxx |

Value

A histogram

Author(s)

Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.mvHisto_HC(Exp1_R25_pept, showValues=TRUE)
```

wrapper.mvImage *Heatmap of missing values from a MSnSet object*

Description

Plots a heatmap of the quantitative data. Each column represent one of the conditions in the object of class MSnSet and the color is proportional to the mean of intensity for each line of the dataset. The lines have been sorted in order to visualize easily the different number of missing values. A white square is plotted for missing values.

Usage

```
wrapper.mvImage(obj)
```

Arguments

obj An object of class MSnSet.

Value

A heatmap

Author(s)

Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=1)
obj <- mvFilterFromIndices(obj, keepThat)
wrapper.mvImage(obj)
```

wrapper.mvPerLinesHistoPerCondition_HC
Bar plot of missing values per lines and per conditions from an object MSnSet

Description

This method is a wrapper to plots (using highcharts) from a MSnSet object a bar plot which represents the distribution of the number of missing values (NA) per lines (ie proteins) and per conditions.

Usage

```
wrapper.mvPerLinesHistoPerCondition_HC(obj, ...)
```

Arguments

obj An object of class MSnSet.
 ... xxx

Value

A bar plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.mvPerLinesHistoPerCondition_HC(Exp1_R25_pept)
```

```
wrapper.mvPerLinesHisto_HC
```

*Histogram of missing values per lines from an object using highchar-
 ter MSnSet*

Description

```
#' This method is a wrapper to plots from a MSnSet object a #' histogram which represents the dis-
#' tribution of the #' number of missing values (NA) per lines (ie proteins). #' #' @title Histogram of
#' missing values per lines from an object #' MSnSet #' #' @param obj An object of class MSnSet. #'
#' @param indLegend The indice of the column name's in pData() tab . #' #' @param showValues
#' A logical that indicates wether numeric values should be #' drawn above the bars. #' #' @return
#' A histogram #' #' @author Alexia Dorffer #' #' @examples #' #' #' @export #' #' @import-
#' From Biobase pData exprs fData #' wrapper.mvPerLinesHisto <- function(obj, indLegend="auto",
#' showValues=FALSE) qData <- Biobase::exprs(obj) samplesData <- Biobase::pData(obj) mvPerLi-
#' nesHisto(qData, samplesData, indLegend, showValues)
```

This method is a wrapper to plots from a MSnSet object a histogram which represents the distribution of the number of missing values (NA) per lines (ie proteins).

Usage

```
wrapper.mvPerLinesHisto_HC(obj, indLegend = "auto", showValues = FALSE)
```

Arguments

obj An object of class MSnSet.
 indLegend The indice of the column name's in pData() tab .
 showValues A logical that indicates wether numeric values should be drawn above the bars.

Value

A histogram

Author(s)

Alexia Dorffer

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
wrapper.mvPerLinesHisto_HC(Exp1_R25_pept)
```

 wrapper.normalizeD *Normalisation*

Description

Provides several methods to normalize quantitative data from a MSnSet object. They are organized in six main families : GlobalQuantileAlignment, sumByColumns, QuantileCentering, MeanCentering, LOESS, vsn For the first family, there is no type. For the five other families, two type categories are available : "Overall" which means that the value for each protein (ie line in the expression data tab) is computed over all the samples ; "within conditions" which means that the value for each protein (ie line in the exprs() data tab) is computed condition by condition.

Usage

```
wrapper.normalizeD(obj, method, withTracking = FALSE, ...)
```

Arguments

| | |
|--------------|---|
| obj | An object of class MSnSet. |
| method | One of the following : "GlobalQuantileAlignment" (for normalizations of important magnitude), "SumByColumns", "QuantileCentering", "Mean Centering", "LOESS" and "vsn". |
| withTracking | xxx |
| ... | xxx |

Author(s)

Samuel Wiczorek, Thomas Burger, Helene Borges

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
conds <- Biobase::pData(Exp1_R25_pept)$Condition
obj <- wrapper.normalizeD(obj = Exp1_R25_pept, method = "QuantileCentering", conds=conds, type = "within condi")
```

wrapper.pca *Compute the PCA*

Description

Compute the PCA

Usage

```
wrapper.pca(obj, var.scaling = TRUE, ncp = NULL)
```

Arguments

| | |
|-------------|------------------------|
| obj | xxx |
| var.scaling | The dimensions to plot |
| ncp | xxxx |

Value

A xxxxxx

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- mvFilter(Exp1_R25_pept, "WholeMatrix", 6)
res.pca <- wrapper.pca(obj)
```

wrapperCalibrationPlot

Performs a calibration plot on an MSnSet object, calling the cp4p package functions.

Description

This function is a wrapper to the calibration.plot method of the cp4p package for use with MSnSet objects.

Usage

```
wrapperCalibrationPlot(vPVal, pi0Method = "pounds")
```

Arguments

| | |
|-----------|--|
| vPVal | A dataframe that contains quantitative data. |
| pi0Method | A vector of the conditions (one condition per sample). |

Value

A plot

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R25_pept[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
qData <- Biobase::exprs(obj)
sTab <- Biobase::pData(obj)
limma <- limmaCompleteTest(qData,sTab)
wrapperCalibrationPlot(limma$P_Value[,1])
```

wrapperClassic1wayAnova

Wrapper for One-way Anova statistical test

Description

Wrapper for One-way Anova statistical test

Usage

```
wrapperClassic1wayAnova(obj, with_post_hoc = "No", post_hoc_test = "No")
```

Arguments

| | |
|---------------|--|
| obj | An object of class MSnSet. |
| with_post_hoc | a character string with 2 possible values: "Yes" and "No" (default) saying if function must perform a Post-Hoc test or not. |
| post_hoc_test | character string, possible values are "No" (for no test; default value) or TukeyHSD" or "Dunnnett". See details of postHocTest() function to choose the appropriate one. |

Details

This function allows to perform a 1-way Analysis of Variance. Also computes the post-hoc tests if the with_post_hoc parameter is set to yes. There are two possible post-hoc tests: the Tukey Honest Significant Differences (specified as "TukeyHSD") and the Dunnnett test (specified as "Dunnnett").

Value

A list of two dataframes. First one called "logFC" contains all pairwise comparisons logFC values (one column for one comparison) for each analysed feature (Except in the case without post-hoc testing, for which NAs are returned.); The second one named "P_Value" contains the corresponding p-values.

Author(s)

Hélène Borges

See Also

[postHocTest()]

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
anovatest <- wrapperClassic1wayAnova(obj)
```

wrapperRunClustering *Run a clustering pipeline of protein/peptide abundance profiles.*

Description

This function does all of the steps necessary to obtain a clustering model and its graph from average abundances of proteins/peptides. It is possible to carry out either a kmeans model or an affinity propagation model. See details for exact steps.

Usage

```
wrapperRunClustering(
  obj,
  clustering_method,
  conditions_order = NULL,
  k_clusters = NULL,
  adjusted_pvals,
  ttl = "",
  subttl = "",
  FDR_thresholds = NULL
)
```

Arguments

obj ExpressionSet or MSnSet object.

clustering_method character string. Three possible values are "kmeans", "affinityProp" and "affinityPropReduced". See the details section for more explanation.

conditions_order vector specifying the order of the Condition factor levels in the phenotype data. Default value is NULL, which means that it is the order of the condition present in the phenotype data of "obj" which is taken to create the profiles.

k_clusters integer or NULL. Number of clusters to run the kmeans algorithm. If 'clustering_method' is set to "kmeans" and this parameter is set to NULL, then a kmeans model will be realized with an optimal number of clusters 'k' estimated by the Gap statistic method. Ignored for the Affinity propagation model.

adjusted_pvals vector of adjusted pvalues returned by the [wrapperClassic1wayAnova()]

ttl the title for the final plot

subttl the subtitle for the final plot

FDR_thresholds vector containing the different threshold values to be used to color the profiles according to their adjusted pvalue. The default value (NULL) generates 4 thresholds: [0.001, 0.005, 0.01, 0.05]. Thus, there will be 5 intervals therefore 5 colors: the pvalues <0.001, those between 0.001 and 0.005, those between 0.005 and 0.01, those between 0.01 and 0.05, and those > 0.05. The highest given value will be considered as the threshold of insignificance, the profiles having a pvalue > this threshold value will then be colored in gray.

Details

The first step consists in averaging the abundances of proteins/peptides according to the different conditions defined in the phenotype data of the expressionSet / MSnSet. Then we standardize the data if there are more than 2 conditions. If the user asks to realize a kmeans model without specifying the desired number of clusters ('clustering_method = "kmeans"' and 'k_clusters = NULL'), the function checks data's clusterability and estimates a number of clusters k using the gap statistic method. It is advise however to specify a k for the kmeans, because the gap stat gives the smallest possible k, whereas in biology a small number of clusters can turn out to be uninformative. If you want to run a kmeans but you don't know what number of clusters to give, you can let the pipeline run the first time without specifying 'k_clusters', in order to view the profiles the first time and choose by the following is a more appropriate value of k. If it is assumed that the data can be structured with a large number of clusters, it is recommended to use the affinity propagation model instead. This method simultaneously considers all the data as exemplary potentials, unlike hard clustering (kmeans) which initializes with a number k of points taken at random. The "affinityProp" model will use a q parameter set to NA, meaning that exemplar preferences are set to the median of non-Inf values in the similarity matrix (set q to 0.5 will be the same). The "affinityPropReduced" model will use a q set to 0, meaning that exemplar preferences are set to the sample quantile with threshold 0 of non-Inf values. This should lead to a smaller number of final clusters.

Value

a list of 2 elements: "model" is the clustering model, "ggplot" is the ggplot of profiles clustering.

Author(s)

Helene Borges

References

Tibshirani, R., Walther, G. and Hastie, T. (2001). Estimating the number of data clusters via the Gap statistic. **Journal of the Royal Statistical Society** B, 63, 411–423.

Frey, B. J. and Dueck, D. (2007) Clustering by passing messages between data points. **Science** 315, 972-976. DOI: [10.1126/science.1136800](https://doi.org/10.1126/science.1136800)

Examples

```
utils::data(Exp1_R25_prot, package='DAPARdata')
obj <- Exp1_R25_prot[1:1000]
keepThat <- mvFilterGetIndices(obj, condition='WholeMatrix', threshold=ncol(obj))
obj <- mvFilterFromIndices(obj, keepThat)
expR25_ttest <- compute_t_tests(obj)
```

```
wrapperRunClustering(obj = obj, adjusted_pvals = expR25_ttest$P_Value$`25fmol_vs_10fmol_pval`)
```

| | |
|------------------|---|
| writeMSnsetToCSV | <i>Exports a MSnset dataset into a zip archive containing three zipped CSV files.</i> |
|------------------|---|

Description

This function exports a MSnset dataset into three csv files compressed in a zip file

Usage

```
writeMSnsetToCSV(obj, fname)
```

Arguments

| | |
|-------|-------------------------------|
| obj | An object of class MSnSet. |
| fname | The name of the archive file. |

Value

A compressed file

Author(s)

Samuel Wieczorek

Examples

```
utils::data(Exp1_R25_pept, package='DAPARdata')  
obj <- Exp1_R2_pept[1:1000]  
writeMSnsetToCSV(obj, "foo")
```

| | |
|--------------------|---|
| writeMSnsetToExcel | <i>This function exports a MSnSet object to a Excel file.</i> |
|--------------------|---|

Description

This function exports a MSnSet data object to a Excel file. Each of the three data.frames in the MSnSet object (ie experimental data, phenoData and metaData are respectively integrated into separate sheets in the Excel file). The colored cells in the experimental data correspond to the original missing values which have been imputed.

Usage

```
writeMSnsetToExcel(obj, filename)
```

Arguments

`obj` An object of class MSnSet.
`filename` A character string for the name of the Excel file.

Value

A Excel file (.xlsx)

Author(s)

Samuel Wieczorek

Examples

```
Sys.setenv("R_ZIPCMD"= Sys.which("zip"))
utils::data(Exp1_R25_pept, package='DAPARdata')
obj <- Exp1_R2_pept[1:1000]
writeMSnsetToExcel(obj, "foo")
```

Index

addOriginOfValue, 5
aggregateIter, 6
aggregateIterParallel, 7
aggregateMean, 8
aggregateSum, 8
aggregateTopn, 9
averageIntensities, 10

barplotEnrichGO_HC, 11
barplotGroupGO_HC, 11
bitr, 55
boxPlotD_HC, 12
BuildAdjacencyMatrix, 13
BuildColumnToProteinDataset, 13
BuildColumnToProteinDataset_par, 14
buildGraph, 15
BuildPalette, 16

check.conditions, 16
check.design, 17
checkClusterability, 17
classic1wayAnova, 18
clusterProfiler, 11, 35, 55, 56, 96
compareNormalizationD_HC, 19
compute_t_tests, 20
corrMatrixD_HC, 21
CountPep, 22
createMSnset, 22
CVDistD, 24
CVDistD_HC, 25

dapar_hc_chart, 25
dapar_hc_ExportMenu, 26
deleteLinesFromIndices, 27
densityPlotD, 24, 25, 28, 28, 102
densityPlotD_HC, 28
diffAnaComputeFDR, 29
diffAnaGetSignificant, 30
diffAnaSave, 31
diffAnaVolcanoplot, 32
diffAnaVolcanoplot_rCharts, 33
display.CC.visNet, 34

enrich_GO, 35

enrichGO, 55

finalizeAggregation, 36
findMECBlock, 37
formatLimmaResult, 37
formatPHResults, 38
fudge2LRT, 39

get.pep.prot.cc, 40
Get_AllComparisons, 53
GetDetailedNbPeptides, 41
GetDetailedNbPeptidesUsed, 41
getIndicesConditions, 42
getIndicesOfLinesToRemove, 43
getListNbValuesInLines, 43
GetNbPeptidesUsed, 44
getNumberOf, 44
getNumberOfEmptyLines, 45
getPercentageOfMV, 46
getProcessingInfo, 46
getProteinsStats, 47
getQuantile4Imp, 47
getTextForAggregation, 48
getTextForAnaDiff, 49
getTextForFiltering, 49
getTextForGOAnalysis, 50
getTextForHypothesisTest, 50
getTextForNewDataset, 51
getTextForNormalization, 51
getTextForpeptideImputation, 52
getTextForproteinImputation, 53
GlobalQuantileAlignment, 54
GOAnalysisSave, 55
GraphPepProt, 56
group_GO, 56
groupGO, 55

hc_logFC_DensityPlot, 57
hc_mvTypePlot2, 58, 110
heatmap.2, 59, 60, 110
heatmap.DAPAR, 59
heatmapD, 60
histPValue_HC, 61

impute.detQuant, 61, 111

- impute.pa2, 62
- inner.aggregate.iter, 63
- inner.aggregate.topn, 64
- inner.mean, 64
- inner.sum, 65
- is.MV, 65
- is.OfType, 66

- LH0, 67
- LH0.lm, 67
- LH1, 68
- LH1.lm, 68
- limma, 31
- limmaCompleteTest, 29, 31, 69
- listSheets, 69
- LOESS, 70

- make.contrast, 71
- make.design, 71
- make.design.1, 72
- make.design.2, 73
- make.design.3, 73
- MeanCentering, 74
- mvFilter, 75
- mvFilterFromIndices, 76
- mvFilterGetIndices, 77
- mvHisto_HC, 78
- mvImage, 79
- mvPerLinesHisto_HC, 80
- mvPerLinesHistoPerCondition_HC, 79
- my_hc_chart, 81
- my_hc_ExportMenu, 82

- nonzero, 82
- normalizeMethods.dapar, 83
- NumericalFiltering, 83
- NumericalgetIndicesOfLinesToRemove, 84

- pepa.test, 85
- plotJitter, 86
- plotJitter_rCharts, 86
- plotPCA_Eigen, 87
- plotPCA_Eigen_hc, 87
- plotPCA_Ind, 88
- plotPCA_Var, 89
- postHocTest, 89
- proportionConRev_HC, 90

- QuantileCentering, 91

- rbindMSnset, 92
- readExcel, 92
- reIntroduceMEC, 93
- removeLines, 94

- samlRT, 94
- saveParameters, 95
- scatterplotEnrichGO_HC, 96
- setMEC, 97
- splitAdjacencyMat, 97
- StringBasedFiltering, 98
- StringBasedFiltering2, 99
- SumByColumns, 99

- test.design, 100
- translatedRandomBeta, 101

- univ_AnnotDbPkg, 101

- violinPlotD, 102
- visualizeClusters, 103
- vsn, 104

- wrapper.compareNormalizationD_HC, 105
- wrapper.corrMatrixD_HC, 106
- wrapper.CVDistD, 107, 107
- wrapper.CVDistD_HC, 107
- wrapper.dapar.impute.mi, 108
- wrapper.hc_mvTypePlot2, 110
- wrapper.heatmapD, 110
- wrapper.impute.detQuant, 111
- wrapper.impute.fixedValue, 112
- wrapper.impute.KNN, 112
- wrapper.impute.mle, 113
- wrapper.impute.pa, 114
- wrapper.impute.pa2, 114
- wrapper.impute.slsa, 115
- wrapper.mvHisto_HC, 116
- wrapper.mvImage, 117
- wrapper.mvPerLinesHisto_HC, 118
- wrapper.mvPerLinesHistoPerCondition_HC, 117
- wrapper.normalized, 119
- wrapper.pca, 120
- wrapperCalibrationPlot, 120
- wrapperClassic1wayAnova, 121
- wrapperRunClustering, 122
- writeMSnsetToCSV, 124
- writeMSnsetToExcel, 124