

# Package ‘bacon’

October 18, 2022

**Type** Package

**Title** Controlling bias and inflation in association studies using the empirical null distribution

**Version** 1.24.0

**Author** Maarten van Iterson [aut, cre], Erik van Zwet [ctb]

**Maintainer** Maarten van Iterson <mviterson@gmail.com>

**Description** Bacon can be used to remove inflation and bias often observed in epigenome- and transcriptome-wide association studies. To this end bacon constructs an empirical null distribution using a Gibbs Sampling algorithm by fitting a three-component normal mixture on z-scores.

**License** GPL (>= 2)

**Depends** R (>= 3.3), methods, stats, ggplot2, graphics, BiocParallel, ellipse

**Suggests** BiocStyle, knitr, rmarkdown, testthat, roxygen2

**biocViews** ImmunoOncology, StatisticalMethod, Bayesian, Regression, GenomeWideAssociation, Transcriptomics, RNASeq, MethylationArray, BatchEffect, MultipleComparison

**RoxygenNote** 6.1.1

**Collate** 'BaconClass.R' 'BaconMethods.R' 'bacon.R' 'normmixture.R'

**VignetteBuilder** knitr

**NeedsCompilation** yes

**git\_url** <https://git.bioconductor.org/packages/bacon>

**git\_branch** RELEASE\_3\_15

**git\_last\_commit** 8e0c070

**git\_last\_commit\_date** 2022-04-26

**Date/Publication** 2022-10-18

**R topics documented:**

bacon	2
Bacon-class	4
bias	4
dnormmix	5
es	6
estimates	6
fit	7
inflation	8
meta	9
plot,Bacon-method	10
plotnormmix	10
posteriors	11
pval	12
rnormmix	13
se	13
topTable	14
traces	15
tstat	16
<b>Index</b>	<b>17</b>

bacon

*Gibbs sampler***Description**

Gibbs Sampler Algorithm to fit a three component normal mixture to z-scores

**Usage**

```
bacon(teststatistics = NULL, effectsizes = NULL,
      standarderrors = NULL, niter = 5000L, nburnin = 2000L,
      nbins = 1000, trim = 0.999, level = 0.05, na.exclude = FALSE,
      verbose = FALSE, priors = list(sigma = list(alpha = 1.28, beta =
      0.36), mu = list(lambda = c(0, 3, -3), tau = c(1000, 100, 100)), epsilon
      = list(gamma = c(90, 5, 5)))
```

**Arguments**

teststatistics	numeric vector or matrix of test-statistics
effectsizes	numeric vector or matrix of effect-sizes
standarderrors	numeric vector or matrix of standard errors
niter	number of iterations
nburnin	length of the burnin period
nbins	default 1000 else bin test-statistics

trim	default 0.999 trimming test-statistics
level	significance level used to determine prop. null for starting values
na.exclude	see ?na.exclude
verbose	default FALSE
priors	list of parameters of for the prior distributions

**Value**

object of class-Bacon

**Author(s)**

mvaniterson

**References**

Implementation is based on a version from Zhihui Liu <https://macsphere.mcmaster.ca/handle/11375/9368>

**Examples**

```
##simulate some test-statistic from a normal mixture
##and run bacon
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
bc <- bacon(y)
##extract all estimated mixture parameters
estimates(bc)
##extract inflation
inflation(bc)
##extract bias
bias(bc)

##extract bias and inflation corrected test-statistics
head(tstat(bc))

##inspect the Gibbs Sampling output
traces(bc)
posteriors(bc)
fit(bc)

##simulate multiple sets of test-statistic from a normal mixture
##and run bacon
y <- matrix(rnormmix(10*2000, c(0.9, 0, 1, 0, 4, 1)), ncol=10)
bc <- bacon(y)
##extract all estimated mixture parameters
estimates(bc)
##extract only the inflation
inflation(bc)
##extract only the bias
bias(bc)
##extract bias and inflation corrected P-values
```

```
head(pval(bc))
##extract bias and inflation corrected test-statistics
head(tstat(bc))
```

---

Bacon-class	<i>An S4 class container for storing Gibbs Sampler input and output</i>
-------------	---

---

### Description

An S4 class container for storing Gibbs Sampler input and output

### Slots

teststatistics numeric vector or matrix of test-statistics  
 effectsizes numeric vector or matrix of effect-sizes  
 standarderrors numeric vector or matrix of standard errors  
 traces array of Gibbs Sampler traces  
 estimates vector or matrix of parameter estimates  
 priors list of parameters of for the prior distributions  
 niter number of iterations  
 nburnin length of the burnin period

---

bias	<i>Method to extract the estimated bias from the 'bacon'-object</i>
------	---

---

### Description

Method to extract the estimated bias from the 'bacon'-object

### Usage

```
bias(object)

## S4 method for signature 'Bacon'
bias(object)
```

### Arguments

object           'bacon'-object

### Value

vector or matrix of inflation

**See Also**[bacon](#)**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
bias(bc)
```

---

**dnormmix***density of a k-component normal mixture*

---

**Description**

density of a k-component normal mixture

**Usage**

```
dnormmix(x, theta)
```

**Arguments**

x	x like dnorm(x, ...
theta	parameters of the mixture proportion, mean and sd

**Details**

details follow

**Value**

density of a k-component normal mixture

**Author(s)**

mvaniterson

**Examples**

```
n <- 2000
theta <- c(0.8, 0, 1, 0, 4, 1)
x <- rnormmix(n, theta)
hist(x, freq=FALSE, n=100)
curve(dnormmix(x, theta), add=TRUE, lwd=2)
```

---

es *Method to extract inflation- and bias-corrected effect-sizes*

---

### Description

Method to extract inflation- and bias-corrected effect-sizes

### Usage

```
es(object, corrected = TRUE)

## S4 method for signature 'Bacon'
es(object, corrected = TRUE)
```

### Arguments

object	'bacon'-object
corrected	optional return uncorrected

### Value

vector or matrix of effect-sizes

### See Also

[bacon](#)

### Examples

```
es <- replicate(6, rnormmix(2000, c(0.9, 0, 1, 0, 4, 1)))
se <- replicate(6, 0.8*sqrt(4/rchisq(2000,df=4)))
bc <- bacon(NULL, es, se)
head(es(bc))
```

---

estimates *Method to extract the estimated parameters from the 'bacon'-object*

---

### Description

Method to extract the estimated parameters from the 'bacon'-object

### Usage

```
estimates(object)

## S4 method for signature 'Bacon'
estimates(object)
```

**Arguments**

object            'bacon'-object

**Value**

vector or matrix of estimates

**See Also**

[bacon](#)

**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
estimates(bc)
```

---

fit

*Method to plot mixture fit*

---

**Description**

Method to plot mixture fit

**Usage**

```
fit(object, index = 1, ...)

## S4 method for signature 'Bacon'
fit(object, index, col = "grey75", border = "grey75",
     ...)
```

**Arguments**

object            'bacon'-object  
index            if multiple sets of test-statistics where provided  
...               additional plotting parameters  
col               line color default 'grey75'  
border            border color 'grey75'

**Value**

plot of the Gibbs Sampler mixture fit

**See Also**[bacon](#)**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
fit(bc)
```

---

**inflation***Method to extract the estimated inflation from the 'bacon'-object*

---

**Description**

Method to extract the estimated inflation from the 'bacon'-object

**Usage**

```
inflation(object)
```

```
## S4 method for signature 'Bacon'
inflation(object)
```

**Arguments**

object           'bacon'-object

**Value**

vector or matrix of inflation

**See Also**[bacon](#)**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
inflation(bc)
```



---

meta	<i>fixed meta-analysis</i>
------	----------------------------

---

## Description

Perform fixed meta-analysis using inflation and bias corrected effect-sizes and standard errors

## Usage

```
meta(object, corrected = TRUE, ...)  
  
## S4 method for signature 'Bacon'  
meta(object, corrected = TRUE, ...)
```

## Arguments

object	'bacon'-object
corrected	optional return uncorrected
...	additional arguments

## Details

TODO maybe add idea's from [http://www.netstorm.be/home/meta\\_analysis#metaAnalysisU](http://www.netstorm.be/home/meta_analysis#metaAnalysisU)

## Value

object of class 'bacon' with added fixed-effect meta-analysis test-statistics, effect-sizes and standard-errors

## See Also

[bacon](#)

## Examples

```
es <- replicate(6, rnormmix(2000, c(0.9, 0, 1, 0, 4, 1)))  
se <- replicate(6, 0.8*sqrt(4/rchisq(2000,df=4)))  
bc <- bacon(NULL, es, se)  
mbc <- meta(bc)
```

---

plot,Bacon-method      *plot hist or qq*

---

### Description

simple ggplot2 plotting function for 'bacon'-object

### Usage

```
## S4 method for signature 'Bacon'
plot(x, y, type = c("hist", "qq"))
```

### Arguments

x	'bacon'-object
y	NULL
type	hist or qq

### Value

either qq-plot of P-values or histogram of Test-statistics

---

plotnormmix      *plot normal mixtures*

---

### Description

plot normal mixtures

### Usage

```
plotnormmix(x, theta, ...)
```

### Arguments

x	vector of test statistics
theta	parameters describing the mixture components
...	arguments passed to hist

### Details

details follow

### Value

return plot with histogram of the data and mixture and individual components

**Author(s)**

mvaniterson

**Examples**

```
n <- 2000
theta <- c(0.8, 0, 1, 0, 4, 1)
x <- rnormmix(n, theta)
plotnormmix(x, theta)
```

---

posterior*Method to plot posterior distribution*


---

**Description**

Method to plot posterior distribution

**Usage**

```
posterior(object, thetas = c("sigma.0", "p.0"), index = 1,
  alphas = c(0.95, 0.9, 0.75), xlab = "", ylab = "", ...)

## S4 method for signature 'Bacon'
posterior(object, thetas = c("sigma.0", "p.0"),
  index = 1, alphas = c(0.95, 0.9, 0.75), xlab = "", ylab = "",
  ...)
```

**Arguments**

object	'bacon'-object
thetas	which thetas to plot
index	if multiple sets of test-statistics where provided
alphas	significance level confidence ellipses
xlab	optional xlab
ylab	optional ylab
...	additional plotting parameters

**Value**

plot of the Gibbs Sampler posterior probabilities

**See Also**[bacon](#)

### Examples

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
posteriors(bc)
```

---

pval

*Method to extract inflation- and bias-corrected P-values*

---

### Description

Method to extract inflation- and bias-corrected P-values

### Usage

```
pval(object, corrected = TRUE)

## S4 method for signature 'Bacon'
pval(object, corrected = TRUE)
```

### Arguments

object	'bacon'-object
corrected	optional return uncorrected

### Value

vector or matrix of P-values

### See Also

[bacon](#)

### Examples

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
bc <- bacon(y, nbins=100) #nbins = 100 to speed up the calculations
head(pval(bc))
```

---

rnormmix	<i>sample from a normal mixture</i>
----------	-------------------------------------

---

**Description**

sample from a normal mixture

**Usage**

```
rnormmix(n, theta, shuffle = TRUE)
```

**Arguments**

n	size
theta	parameters
shuffle	shuffle return vectors or keep nulls and alternative ordered (null, alts)

**Details**

details follow

**Value**

n samples from a normal mixture with parameters theta

**Author(s)**

mvaniterson

**Examples**

```
n <- 2000
theta <- c(0.8, 0, 1, 0, 4, 1)
x <- rnormmix(n, theta)
```

---

se	<i>Method to extract inflation- and bias-corrected standard errors</i>
----	--

---

**Description**

Method to extract inflation- and bias-corrected standard errors

**Usage**

```
se(object, corrected = TRUE)

## S4 method for signature 'Bacon'
se(object, corrected = TRUE)
```

**Arguments**

```
object          'bacon'-object
corrected       optional return uncorrected
```

**Value**

vector or matrix of standard-errors

**See Also**

[bacon](#)

**Examples**

```
es <- replicate(6, rnormmix(2000, c(0.9, 0, 1, 0, 4, 1)))
se <- replicate(6, 0.8*sqrt(4/rchisq(2000,df=4)))
bc <- bacon(NULL, es, se)
head(se(bc))
```

---

topTable

*topTable*

---

**Description**

Extract top features after meta analysis

**Usage**

```
topTable(object, number = 10, adjust.method = "bonf",
          sort.by = c("pval", "eff.size"))

## S4 method for signature 'Bacon'
topTable(object, number = 10, adjust.method = "bonf",
          sort.by = c("pval", "eff.size"))
```

**Arguments**

```
object          'bacon'-object
number          return specified number of top features, n=-1 return all features
adjust.method   P-value multiple testing adjustment method default bonferroni
sort.by        order results by pval or eff.size
```

**Value**

table with top features

**See Also**

[bacon](#)

**Examples**

```
es <- replicate(6, rnormmix(2000, c(0.9, 0, 1, 0, 4, 1)))
se <- replicate(6, 0.8*sqrt(4/rchisq(2000,df=4)))
bc <- bacon(NULL, es, se)
mbc <- meta(bc)
topTable(mbc)
```

---

traces

*Method to plot Gibbs sampling traces*

---

**Description**

Method to plot Gibbs sampling traces

**Usage**

```
traces(object, burnin = TRUE, index = 1)
```

```
## S4 method for signature 'Bacon'
traces(object, burnin = TRUE, index = 1)
```

**Arguments**

object	'bacon'-object
burnin	include burnin period default true
index	if multiple sets of test-statistics where provided

**Value**

plot of the Gibbs Sampler traces

**See Also**

[bacon](#)

**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))
##nbins = 100 to speed up the calculations
bc <- bacon(y, nbins=100)
traces(bc)
```

---

tstat	<i>Method to extract inflation- and bias-corrected test-statistics</i>
-------	--

---

**Description**

Method to extract inflation- and bias-corrected test-statistics

**Usage**

```
tstat(object, corrected = TRUE)
```

```
## S4 method for signature 'Bacon'  
tstat(object, corrected = TRUE)
```

**Arguments**

object	'bacon'-object
corrected	optional return uncorrected

**Value**

vector or matrix of test-statistics

**See Also**

[bacon](#)

**Examples**

```
y <- rnormmix(2000, c(0.9, 0, 1, 0, 4, 1))  
##nbins = 100 to speed up the calculations  
bc <- bacon(y, nbins=100)  
head(tstat(bc))
```



# Index

bacon, [2](#), [5–9](#), [11](#), [12](#), [14–16](#)  
Bacon-class, [4](#)  
bias, [4](#)  
bias, Bacon-method (bias), [4](#)  
  
dnormmix, [5](#)  
  
es, [6](#)  
es, Bacon-method (es), [6](#)  
estimates, [6](#)  
estimates, Bacon-method (estimates), [6](#)  
  
fit, [7](#)  
fit, Bacon-method (fit), [7](#)  
  
inflation, [8](#)  
inflation, Bacon-method (inflation), [8](#)  
  
meta, [9](#)  
meta, Bacon-method (meta), [9](#)  
  
plot, Bacon-method, [10](#)  
plotnormmix, [10](#)  
posteriors, [11](#)  
posteriors, Bacon-method (posteriors), [11](#)  
pval, [12](#)  
pval, Bacon-method (pval), [12](#)  
  
rnormmix, [13](#)  
  
se, [13](#)  
se, Bacon-method (se), [13](#)  
  
topTable, [14](#)  
topTable, Bacon-method (topTable), [14](#)  
traces, [15](#)  
traces, Bacon-method (traces), [15](#)  
tstat, [16](#)  
tstat, Bacon-method (tstat), [16](#)