

# Package ‘SMAP’

January 16, 2024

**Title** A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling

**Version** 1.67.0

**Date** 2007-08-27

**Depends** R (>= 2.10), methods

**Author** Robin Andersson <[robin.andersson@lcb.uu.se](mailto:robin.andersson@lcb.uu.se)>

**Description** Functions and classes for DNA copy number profiling of array-CGH data

**Maintainer** Robin Andersson <[robin.andersson@lcb.uu.se](mailto:robin.andersson@lcb.uu.se)>

**License** GPL-2

**LazyLoad** true

**Collate** AllClasses.R AllGenerics.R methods-SMAPHMM.R  
methods-SMAPObservations.R methods-SMAPProfile.R  
methods-GaussParam.R methods-grad.R methods-eta.R

**biocViews** Microarray, TwoChannel, CopyNumberVariation

**git\_url** <https://git.bioconductor.org/packages/SMAP>

**git\_branch** devel

**git\_last\_commit** 70650d6

**git\_last\_commit\_date** 2023-10-24

**Repository** Bioconductor 3.19

**Date/Publication** 2024-01-15

## Table of contents:

GBM . . . . .	2
smap . . . . .	3
SMAP-internal . . . . .	5
SMAPHMM . . . . .	6
SMAPHMM-class . . . . .	7
SMAPObservations . . . . .	8

SMAPObservations-class . . . . .	9
SMAPProfile-class . . . . .	10
SMAPProfiles-class . . . . .	11
<b>Index</b>	<b>13</b>

---

 GBM

*Glioblastoma multiforme array CGH data*


---

## Description

Array CGH data measurements of glioblastoma multiforme sample G24460.

## Usage

```
data(GBM)
```

## Source

Genome wide array CGH data from Diaz de Stahl, T., et al. (2005).

## References

Diaz de Stahl, T., et al. (2005) Chromosome 22 tiling-path array-CGH analysis identifies germline- and tumor-specific aberrations in patients with glioblastoma multiforme. *Genes Chromosomes Cancer* **44**(2), 161–169

## See Also

[smap](#)

## Examples

```
data(GBM)
observations <- SMAPObservations(value=as.numeric(GBM[,2]),
                                chromosome=as.character(GBM[,3]),
                                startPosition=as.numeric(GBM[,4]),
                                endPosition=as.numeric(GBM[,5]),
                                name="G24460",
                                reporterId=as.character(GBM[,1]))

plot(observations)
```

---

smap	<i>smap: A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling</i>
------	---

---

## Description

This function fits a Hidden Markov Model (HMM) to a set of observed microarray intensity ratios and outputs the most plausible state sequence in the HMM through segmental a posteriori maximization.

Briefly, given an HMM with initial parameter settings *lambda* and a set of observations *O*, the method alternates maximization of the joint posterior probability of the state sequence *Q* and *lambda* given *O*,  $p(Q, \lambda | O)$ , over *Q* (using a modified Viterbi algorithm) and *lambda* (using a gradient descent scheme with individual learning rate adaptation).

## Usage

```
smap(x, Obs, sd.min=0.05, mean.sd=0.05,
     max.iters=Inf, gd.max.iters=Inf, tau=0.05,
     eta=0.01, e.change=0.5, e.same=1.2,
     e.min=0.0001, e.max=0.5, adaptive=TRUE,
     overlap=TRUE, distance=TRUE, chrom.wise=FALSE,
     verbose=1, L=5000000)
```

## Arguments

x	An object of class <a href="#">SMAPHMM-class</a> .
Obs	An object of class <a href="#">SMAPObservations-class</a> .
sd.min	The minimum allowed standard deviation of state associated Gaussian distributions (numeric).
mean.sd	Prior standard deviation of state associated Gaussian means (numeric).
max.iters	Maximum number of iterations in the SMAP algorithm (numeric).
gd.max.iters	Maximum number of iterations in the gradient descent algorithm per SMAP iteration (numeric).
tau	Minimum log probability improvement required in the SMAP and gradient descent optimization (numeric).
eta	Initial learning rate in the gradient descent optimization (numeric).
e.change	Multiplier for individual learning rate adaptation if the sign of partial derivative changes (numeric). Only used if <code>adaptive == TRUE</code> .
e.same	Multiplier for individual learning rate adaptation if the sign of partial derivative stays the same (numeric). Only used if <code>adaptive == TRUE</code> .
e.min	Minimum allowed learning rate (numeric).
e.max	Maximum allowed learning rate (numeric).



```
                                endPosition=as.numeric(GBM[,5]),
                                name="G24460",
                                reporterId=as.character(GBM[,1]))
plot(observations, ylim=c(0,2))
## Initiate HMM
init.means <- c(0.4, 0.7, 1, 1.3, 1.6, 3)
init.sds <- rep(0.1, 6)
phi <- cbind(init.means, init.sds)
hmm <- SMAPHMM(6, phi, initTrans=0.02)
hmm
## RUN SMAP:
profile <- smap(hmm, observations, verbose=2)
## genome profile
plot(profile, ylim=c(0,2))
## chromosome 9 profile
ids <- which(chromosome(observations) == "9")
plot(profile[ids], ylim=c(0,2), main="chromosome 9")
## output results for chromosome 9
#cbind(reporterId(observations[ids]), Q(profile[ids]))
```

---

SMAP-internal

*SMAP-internal*

---

## Description

Internal methods for the **SMAP** package.

## Author(s)

Robin Andersson, <robin.andersson@lcb.uu.se>

## References

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

## See Also

[smap](#)

SMAPHMM

*Constructor for "SMAPHMM" objects***Description**

A constructor for [SMAPHMM-class](#) objects.

**Usage**

```
SMAPHMM(noStates, Phi, A=NULL,
        Pi=rep(1/noStates,noStates),
        initTrans=0.2/(noStates - 1))
```

**Arguments**

<code>noStates</code>	The number of hidden states in the HMM (numeric).
<code>Phi</code>	A Gaussian distribution parameter matrix (numeric).
<code>A</code>	A <code>noStates * noStates</code> matrix of transition probabilities between the hidden states (numeric).
<code>Pi</code>	A vector of initial probabilities of starting in a certain state (numeric).
<code>initTrans</code>	Specifies the transition probability between non-equal states (numeric).

**Details**

`Phi` is a `noStates * 2` matrix that specifies the parameters of Gaussian distributions associated with each hidden state. The first column specifies standard deviations, the second specifies means.

If `A == NULL`, `initTrans` specifies the transition probability between states `i` and `j` in `1:noStates`, such that `i != j`. Only used if `A == NULL`. `initTrans * noStates` must be smaller than (or equal to) 1.

**Value**

An object of class [SMAPHMM-class](#).

**Author(s)**

Robin Andersson, <[robin.andersson@lcb.uu.se](mailto:robin.andersson@lcb.uu.se)>

**References**

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

**See Also**

[smap](#), [SMAPHMM-class](#), [SMAPObservations-class](#)

---

SMAPHMM-class	Class "SMAPHMM": A class to manage HMMs for the SMAP package
---------------	--

---

### Description

Holds parameters for a Hidden Markov Model (HMM) used in the **SMAP** package.

### Objects from the Class

Objects should not be created directly but via the constructor function [SMAPHMM](#).

### Slots

**A:** Object of class "matrix" The transition probability matrix between states.  
**Pi:** Object of class "numeric" The initial probabilities of starting in a certain state.  
**Phi:** Object of class "matrix" A matrix that specifies the parameters of Gaussian distributions associated with each hidden state. The first column specifies standard deviations, the second specifies means.  
**noStates:** Object of class "numeric" The number of hidden states in the HMM.  
**Z:** Object of class "matrix" Matrix of transition probabilities.  
**Y:** Object of class "numeric" Vector of initial probabilities.  
**eta:** Object of class "ANY". Internal slot.  
**grad:** Object of class "ANY". Internal slot.

### Methods

**A** signature(object = "SMAPHMM"): Returns the transition matrix.  
**Pi** signature(object = "SMAPHMM"): Returns the initial probabilities.  
**Phi** signature(object = "SMAPHMM"): Returns the distribution parameter matrix.  
**noStates** signature(object = "SMAPHMM"): Returns the number of hidden states in the HMM.

### Author(s)

Robin Andersson, <[robin.andersson@lcb.uu.se](mailto:robin.andersson@lcb.uu.se)>

### References

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

### See Also

[smap](#), [SMAPHMM](#)

---

SMAPObservations      *Constructor for "SMAPObservations" objects*

---

### Description

A constructor for [SMAPObservations-class](#) objects.

### Usage

```
SMAPObservations(value, chromosome, startPosition, endPosition,  
                 name=character(0),  
                 reporterId=as.character(1:length(value)))
```

### Arguments

value	A vector of microarray intensity ratios (numeric).
chromosome	A vector of chromosome annotations (character).
startPosition	A vector of start positions (numeric).
endPosition	A vector of end positions (numeric).
name	The name of the observation set (character).
reporterId	A vector of observation identifiers, e.g., probe ids (character).

### Details

The vectors `value`, `chromosome`, `startPosition`, `endPosition`, and `reporterId` must be of equal length.

### Value

An object of class [SMAPObservations-class](#).

### Author(s)

Robin Andersson, <[robin.andersson@lcb.uu.se](mailto:robin.andersson@lcb.uu.se)>

### References

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

### See Also

[smap](#), [SMAPObservations-class](#), [SMAPHMM-class](#)

**Examples**

```
## Load Glioblastoma multiforme data
data(GBM)
observations <- SMAPObservations(value=as.numeric(GBM[,2]),
                                chromosome=as.character(GBM[,3]),
                                startPosition=as.numeric(GBM[,4]),
                                endPosition=as.numeric(GBM[,5]),
                                name="G24460",
                                reporterId=as.character(GBM[,1]))

## plot observations
plot(observations, ylim=c(0,2))
## plot subset of observations (chromosome 9)
ids <- which(chromosome(observations) == "9")
plot(observations[ids])
```

---

SMAPObservations-class

*Class "SMAPObservations": A class to manage microarray observations for the SMAP package*

---

**Description**

Holds observed microarray intensity ratios and clone annotations for the **SMAP** package.

**Objects from the Class**

Objects can be created by calls of the form `new("SMAPObservations", value, chromosome, startPosition, endPosition, name, reporterId)`. Values for internal slots (see below) are not intended to be passed upon construction. You can also use the convenience function [SMAPObservations](#).

**Slots**

**value:** Object of class "numeric" Microarray intensity ratios.  
**chromosome:** Object of class "character" Associated chromosomes for the observations.  
**startPosition:** Object of class "numeric" Associated start positions for the observations.  
**endPosition:** Object of class "numeric" Associated end positions for the observations.  
**reporterId:** Object of class "character" Identifiers of the observations, e.g., probe ids.  
**name:** Object of class "character" An identifier of the observation set.  
**noObservations:** Object of class "numeric" The number of observations in the set.  
**chrom.start:** Object of class "numeric". Internal slot.  
**chroms:** Object of class "character". Internal slot.  
**distance:** Object of class "numeric". Internal slot.  
**noOverlaps:** Object of class "numeric". Internal slot.  
**overlaps:** Object of class "numeric". Internal slot.  
**overlapIds:** Object of class "numeric". Internal slot.  
**startOverlaps:** Object of class "numeric". Internal slot.

**Methods**

- value** signature(object = "SMAPObservations"): Returns the values of the observations.
- chromosome** signature(object = "SMAPObservations"): Returns the chromosome annotations of the observations.
- startPosition** signature(object = "SMAPObservations"): Returns the start positions of the observations.
- endPosition** signature(object = "SMAPObservations"): Returns the end positions of the observations.
- reporterId** signature(object = "SMAPObservations"): Returns the identifiers of the observations.
- name** signature(object = "SMAPObservations"): Returns the name of the observation set.
- noObservations** signature(object = "SMAPObservations"): Returns the number of observations in the set.
- initialize** signature(.Object = "SMAPObservations"): Creates an instance.
- plot** signature(x = "SMAPObservations", y = "missing"): A plot method for the observations.
- [ signature(x = "SMAPPObservations"): Creates a new object of class SMAPObservations with extracted elements as specified by the indices provided.

**Author(s)**

Robin Andersson, <robin.andersson@lcb.uu.se>

**References**

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

**See Also**

[smap](#), [SMAPObservations](#)

---

SMAPPProfile-class      *Class "SMAPPProfile"*

---

**Description**

Holds results from running [smap](#).

**Objects from the Class**

Objects are not intended to be created directly but as a result from running [smap](#).

**Slots**

**HMM:** Object of class "SMAPHMM"

**observations:** Object of class "SMAPObservations"

**P:** Object of class "numeric" The log joint posterior probability of the state sequence Q and parameters of HMM given the observations.

**Q:** Object of class "numeric" The optimal state sequence (path) in the HMM.

**name:** Object of class "character" The name of the object.

**Methods**

**P** signature(object = "SMAPProfile"): Returns the log joint posterior probability.

**Q** signature(object = "SMAPProfile"): Returns the optimal state sequence.

**HMM** signature(object = "SMAPProfile"): Returns the optimized HMM.

**name** signature(object = "SMAPProfile"): Returns the name of the profile.

**observations** signature(object = "SMAPProfile"): Returns the observations.

**plot** signature(x = "SMAPProfile", y = "missing"): A plot method for the result profile.

[ signature(x = "SMAPProfile"): Creates a new object of class SMAPProfile with extracted elements as specified by the indices provided.

**Author(s)**

Robin Andersson, <robin.andersson@lcb.uu.se>

**References**

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

**See Also**

[smap](#), [SMAPProfiles-class](#)

---

SMAPProfiles-class      *Class "SMAPProfiles"*

---

**Description**

Holds results from running [smap](#).

**Objects from the Class**

Objects are not intended to be created directly but as a result from running [smap](#).

**Slots**

**.Data:** Object of class "list" A list of objects of class [SMAPPProfile-class](#).  
**name:** Object of class "character" The name of the object.

**Extends**

Class "list", from data part. Class "vector", by class "list".

**Methods**

**Q** signature(object = "SMAPPProfiles"): Returns the optimal state sequence of the list elements.  
**observations** signature(object = "SMAPPProfiles"): Returns the observations of the list elements.  
**name** signature(object = "SMAPPProfiles"): Returns the name of the profile.  
**plot** signature(x = "SMAPPProfiles", y = "missing"): A plot method for the result profiles.

**Author(s)**

Robin Andersson, <robin.andersson@lcb.uu.se>

**References**

Andersson, R., Bruder, C. E. G., Piotrowski, A., Menzel, U., Nord, H., Sandgren, J., Hvidsten, T. R., Diaz de Stahl, T., Dumanski, J. P., Komorowski, J., A Segmental Maximum A Posteriori Approach to Array-CGH Copy Number Profiling, submitted

**See Also**

[smap](#), [SMAPPProfile-class](#)

# Index

- \* **classes**
  - SMAPHMM, 6
  - SMAPHMM-class, 7
  - SMAPObservations, 8
  - SMAPObservations-class, 9
  - SMAPProfile-class, 10
  - SMAPProfiles-class, 11
- \* **datasets**
  - GBM, 2
- \* **internal**
  - SMAP-internal, 5
- \* **methods**
  - smap, 3
  - SMAP-internal, 5
- [, SMAPObservations-method (SMAP-internal), 5
- [, SMAPProfile-method (SMAP-internal), 5
- [[<- , SMAPProfiles-method (SMAP-internal), 5
  
- A (SMAPHMM-class), 7
- A, eta-method (SMAP-internal), 5
- A, grad-method (SMAP-internal), 5
- A, SMAPHMM-method (SMAP-internal), 5
  
- chromosome (SMAPObservations-class), 9
- chromosome, SMAPObservations-method (SMAP-internal), 5
  
- endPosition (SMAPObservations-class), 9
- endPosition, SMAPObservations-method (SMAP-internal), 5
  
- GBM, 2
  
- HMM (SMAPProfile-class), 10
- HMM, SMAPProfile-method (SMAP-internal), 5
  
- initialize, eta-method (SMAP-internal), 5
- initialize, gaussparam-method (SMAP-internal), 5
- initialize, grad-method (SMAP-internal), 5
- initialize, SMAPHMM-method (SMAP-internal), 5
- initialize, SMAPObservations-method (SMAP-internal), 5
- initialize, SMAPProfile-method (SMAP-internal), 5
  
- name (SMAPObservations-class), 9
- name, SMAPObservations-method (SMAP-internal), 5
- name, SMAPProfile-method (SMAP-internal), 5
- name, SMAPProfiles-method (SMAP-internal), 5
- noObservations (SMAPObservations-class), 9
- noObservations, SMAPObservations-method (SMAP-internal), 5
- noStates (SMAPHMM-class), 7
- noStates, SMAPHMM-method (SMAP-internal), 5
  
- observations (SMAPProfile-class), 10
- observations, SMAPProfile-method (SMAP-internal), 5
- observations, SMAPProfiles-method (SMAP-internal), 5
  
- P (SMAPProfile-class), 10
- P, SMAPProfile-method (SMAP-internal), 5
- Phi (SMAPHMM-class), 7
- Phi, eta-method (SMAP-internal), 5
- Phi, grad-method (SMAP-internal), 5
- Phi, SMAPHMM-method (SMAP-internal), 5
- Pi (SMAPHMM-class), 7
- Pi, eta-method (SMAP-internal), 5

Pi,grad-method (SMAP-internal), 5  
Pi,SMAPHMM-method (SMAP-internal), 5  
plot,SMAPObservations,missing-method  
    (SMAPObservations-class), 9  
plot,SMAPPProfile,missing-method  
    (SMAP-internal), 5  
plot,SMAPPProfiles,missing-method  
    (SMAP-internal), 5  
  
Q (SMAPPProfile-class), 10  
Q,SMAPPProfile-method (SMAP-internal), 5  
Q,SMAPPProfiles-method (SMAP-internal), 5  
  
reporterId (SMAPObservations-class), 9  
reporterId,SMAPObservations-method  
    (SMAP-internal), 5  
  
show,SMAPHMM-method (SMAP-internal), 5  
show,SMAPObservations-method  
    (SMAP-internal), 5  
show,SMAPPProfile-method  
    (SMAP-internal), 5  
show,SMAPPProfiles-method  
    (SMAP-internal), 5  
smap, 2, 3, 5–8, 10–12  
smap,SMAPHMM,SMAPObservations-method  
    (SMAP-internal), 5  
SMAP-internal, 5  
SMAPHMM, 4, 6, 7  
SMAPHMM-class, 7  
SMAPObservations, 4, 8, 9, 10  
SMAPObservations-class, 9  
SMAPPProfile-class, 10  
SMAPPProfiles-class, 11  
startPosition (SMAPObservations-class),  
    9  
startPosition,SMAPObservations-method  
    (SMAP-internal), 5  
  
value (SMAPObservations-class), 9  
value,eta-method (SMAP-internal), 5  
value,SMAPObservations-method  
    (SMAP-internal), 5