

Package ‘ccdata’

April 11, 2019

Title Data for Combination Connectivity Mapping (ccmap) Package

Version 1.8.0

Author Alex Pickering

Maintainer Alex Pickering <alexvpickering@gmail.com>

Description This package contains microarray gene expression data generated from the Connectivity Map build 02 and LINCS 11000. The data are used by the ccmap package to find drugs and drug combinations to mimic or reverse a gene expression signature.

Depends R (>= 3.3)

License MIT + file LICENSE

LazyData false

biocViews ExperimentData, MicroarrayData, ExpressionData

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/ccdata>

git_branch RELEASE_3_8

git_last_commit d92b4e1

git_last_commit_date 2018-10-30

Date/Publication 2019-04-11

R topics documented:

cmap_es	2
cmap_var	2
genes	3
l1000_es	3
net1	4
net2	4
xgb_mod	5
Index	6

`cmap_es`*Effect size values for Connectivity Map build 02 drugs.*

Description

Moderated unbiased effect sizes values for all 1309 drugs in the Connectivity Map build 02.

Usage

```
data(cmap_es)
```

Format

An object of class `matrix` with 13832 rows and 1309 columns.

Details

Calculated as described by Marot et al (see reference) using [toptable](#) from `limma` and [effectsize](#) from `metaMA`.

Value

A matrix where columns correspond to drugs and rows to gene symbols.

References

Marot G, Foulley JL, Mayer CD, Jaffrézic F. Moderated effect size and P-value combinations for microarray meta-analyses. *Bioinformatics*. 2009 Oct 15;25(20):2692-9. doi: 10.1093/bioinformatics/btp444.

`cmap_var`*Variance values for Connectivity Map build 02 drugs.*

Description

Variations of unbiased effect sizes values for all 1309 drugs in the Connectivity Map build 02.

Usage

```
data(cmap_var)
```

Format

An object of class `matrix` with 13832 rows and 1309 columns.

Details

Calculated as described by Marot et al (see reference) using [toptable](#) from `limma` and [effectsize](#) from `metaMA`.

Value

A matrix where columns correspond to drugs and rows to gene symbols.

References

Marot G, Foulley JL, Mayer CD, Jaffrézic F. Moderated effect size and P-value combinations for microarray meta-analyses. *Bioinformatics*. 2009 Oct 15;25(20):2692-9. doi: 10.1093/bioinformatics/btp444.

genes

HGNC symbols used for NNet predictions.

Description

Order is as required for input and produced by output of net1/net2 predictions.

Usage

data(genes)

Format

An object of class character of length 11525.

Value

A character vector of 11525 HGNC symbols.

11000_es

Effect size values for LINCS 11000 signatures.

Description

Moderated unbiased effect sizes values for all 230829 LINCS 11000 signatures.

Usage

data(11000_es)

Format

An object of class matrix with 1001 rows and 230829 columns.

Details

Calculated as described by Marot et al (see reference) using [toptable](#) from limma and [effectsize](#) from metaMA.

Value

A matrix where columns correspond to perturbagens and rows to gene symbols.

References

Marot G, Foulley JL, Mayer CD, Jaffrézic F. Moderated effect size and P-value combinations for microarray meta-analyses. *Bioinformatics*. 2009 Oct 15;25(20):2692-9. doi: 10.1093/bioinformatics/btp444.

net1

Neural network model 1 for treatment combinations.

Description

Contains weight matrices and bias vectors needed to make predictions.

Usage

#NA

Format

An object of class `list` of length 4.

Value

List with matrices `W1/W2` and vectors `b1/b2`.

net2

Neural network model 2 for treatment combinations.

Description

Contains weight matrices and bias vectors needed to make predictions.

Usage

#NA

Format

An object of class `list` of length 4.

Value

List with matrices `W1/W2` and vectors `b1/b2`.

`xgb_mod`*XGBoost model for treatment combinations.*

Description

Model stacks predictions from net1 and net2 with effect size values from cmap_es and variance values from cmap_var.

Usage

#NA

Format

An object of class `xgb.Booster` of length 2.

Value

Object of class `xgb.Booster`

Index

*Topic **datasets**

cmap_es, 2

cmap_var, 2

genes, 3

l1000_es, 3

net1, 4

net2, 4

xgb_mod, 5

cmap_es, 2

cmap_var, 2

effectsize, 2, 3

genes, 3

l1000_es, 3

net1, 4

net2, 4

toptable, 2, 3

xgb_mod, 5