

Finding trans eQTL in the Cheung data

VJ Carey

June 3, 2012

```
> options(error=recover)
> #library(chfive40)
> library(cheung2010)
> library(hgfocus.db)
> library(GenomicRanges)
> allst = as.list(hgfocusCHRLOC)
> allen = as.list(hgfocusCHRLOCEND)
> pchrs = sapply(allst, function(x)names(x)[1])
> bad = which(sapply(pchrs,length)==0)
> if (length(bad)>0) {
+ pchrs = pchrs[-bad]
+ pchrs = sapply(pchrs, function(x)x)
+ pchrs = paste("chr", pchrs, sep="")
+ allst = allst[-bad]
+ allen = allen[-bad]
+ }
> st = sapply(allst, function(x) abs(x)[1])
> en = sapply(allen, function(x) abs(x)[1])
> gra = GRanges(seqnames=pchrs, IRanges(st,en))
> names(gra) = names(allst)
> gra = split(gra, seqnames(gra))
> lkg = getSS("cheung2010", "chr5")
> fn5 = featureNames(lkg)
> gra = lapply(gra, function(x)x[ intersect(names(x), fn5) ])
> library(SNPlocs.Hsapiens.dbSNP.20100427)
> if (!exists("c1s") && file.exists("c1s.rda")) load("c1s.rda")
> if (!exists("c1s")) c1s = getSNPlocs("ch1", as.GRanges=TRUE)
> if ("ch1" %in% seqlevels(c1s)) seqlevels(c1s) = gsub("ch", "chr", seqlevels(c1s))
> if (!file.exists("c1s.rda")) save(c1s,file="c1s.rda")
> if (!exists("c2s") && file.exists("c2s.rda")) load("c2s.rda")
> if (!exists("c2s")) c2s = getSNPlocs("ch2", as.GRanges=TRUE)
> if ("ch2" %in% seqlevels(c2s)) seqlevels(c2s) = gsub("ch", "chr", seqlevels(c2s))
```

```

> if (!file.exists("c2s.rda")) save(c2s,file="c2s.rda")
> if (!exists("c3s") && file.exists("c3s.rda")) load("c3s.rda")
> if (!exists("c3s")) c3s = getSNPlocs("ch3", as.GRanges=TRUE)
> if ("ch3" %in% seqlevels(c3s)) seqlevels(c3s) = gsub("ch", "chr", seqlevels(c3s))
> if (!file.exists("c3s.rda")) save(c3s,file="c3s.rda")
> if (!exists("c4s") && file.exists("c4s.rda")) load("c4s.rda")
> if (!exists("c4s")) c4s = getSNPlocs("ch4", as.GRanges=TRUE)
> if ("ch4" %in% seqlevels(c4s)) seqlevels(c4s) = gsub("ch", "chr", seqlevels(c4s))
> if (!file.exists("c4s.rda")) save(c4s,file="c4s.rda")
> if (!exists("c17s") && !exists("c17s") && file.exists("c17s.rda")) load("c17s.rda")
> if (!exists("c17s")) c17s = getSNPlocs("ch17", as.GRanges=TRUE)
> if ("ch17" %in% seqlevels(c17s)) seqlevels(c17s) = gsub("ch", "chr", seqlevels(c17s))
> if (!file.exists("c17s.rda")) save(c17s,file="c17s.rda")
> if (!exists("c19s") && !exists("c19s") && file.exists("c19s.rda")) load("c19s.rda")
> if (!exists("c19s")) c19s = getSNPlocs("ch19", as.GRanges=TRUE)
> if ("ch19" %in% seqlevels(c19s)) seqlevels(c19s) = gsub("ch", "chr", seqlevels(c19s))
> if (!file.exists("c19s.rda")) save(c19s,file="c19s.rda")
>
> #if ("multicore" %in% installed.packages()[,1]) library(multicore)
> #system("rm -rf tsc")
> #tr1c = transScores("cheung2010", "chr1", ~sex, snpRanges=c1s, geneRanges=gra[["chr1"]])
> #save(tr1c, file="tr1c.rda")
> #tr2c = transScores("cheung2010", "chr2", ~sex, snpRanges=c2s, geneRanges=gra[["chr2"]])
> #save(tr2c, file="tr2c.rda")
> #gc()
> #tr3c = transScores("cheung2010", "chr3", ~sex, snpRanges=c3s, geneRanges=gra[["chr3"]])
> #save(tr3c, file="tr3c.rda")
> #gc()
> #tr4c = transScores("cheung2010", "chr4", ~sex, snpRanges=c4s, geneRanges=gra[["chr4"]])
> #save(tr4c, file="tr4c.rda")

```

We use the probes on chr17 identified as harboring trans regulators by Cheung.

```

> tempfolder = function ()
+ {
+   z = tempfile()
+   system(paste("mkdir", z))
+   z
+ }
> obsfold = tempfolder()
> permfold = tempfolder()
> pr17 = structure(c("209165_at", "203654_s_at", "203367_at", "201508_at",
+ "218676_s_at", "208982_at", "202148_s_at", "214552_s_at", "214299_at",

```

```

+ "219282_s_at"), .Names = c("AATF", "COIL", "DUSP14", "IGFBP4",
+ "PCTP", "PECAM1", "PYCR1", "RABEP1", "TOP3A", "TRPV2"))
> options(verbose=TRUE)
> if (!exists("mgrsave")) {
+   mgrsave = list()
+   for (i in 1:22) {
+     cat(i)
+     cc17 = getSS("cheung2010", paste("chr", i, sep=""), probesToKeep=pr17)
+     mgrsave[[i]] = eqtlTests(cc17, ~sex, targdir=obsfold, runname=paste("cc17", i, se
+     rm(cc17)
+     gc()
+   }
+   save(mgrsave, file="mgrsave.rda")
+ }

```

12345678910111213141516171819202122

```

> set.seed(12345)
> if (!exists("mgrsave_perm")) {
+   mgrsave_perm = list()
+   for (i in 1:22) {
+     cat(i)
+     cc17 = getSS("cheung2010", paste("chr", i, sep=""), probesToKeep=pr17, wrapperEnd
+     mgrsave_perm[[i]] = eqtlTests(cc17, ~sex, targdir=permfold, runname=paste("pcc17"
+     rm(cc17)
+     gc()
+   }
+   save(mgrsave_perm, file="mgrsave_perm.rda")
+ }

```

12345678910111213141516171819202122