

Package ‘MantelCorr’

October 8, 2014

Title Compute Mantel Cluster Correlations

Version 1.34.0

Date 2005-17-10

Author Brian Steinmeyer and William Shannon

Description Computes Mantel cluster correlations from a (p x n) numeric data matrix (e.g. microarray gene-expression data).

Maintainer Brian Steinmeyer <steinmeb@ilya.wustl.edu>

Depends R (>= 2.10)

Imports stats

License GPL (>= 2)

biocViews Clustering

R topics documented:

ClusterGeneList	2
ClusterList	3
DistMatrices	4
GetClusters	5
GolubTrain	6
MantelCorrs	8
PermutatonTest	9

Index	11
--------------	-----------

ClusterGeneList *Generate Genes from a Cluster List*

Description

'ClusterGeneList' produces a list of both significant and nonsignificant genes from each respective cluster type

Usage

```
ClusterGeneList(clus, clustlist.sig, x.data)
```

Arguments

clus 'clusters' object returned by 'GetClusters'
clustlist.sig 'SignificantClusters' object returned by 'ClusterList'
x.data original (p x n) numeric data matrix (e.g., gene-expression data)

Value

A list with components:

SignificantClusterGenes
 significant cluster genes returned from 'ClusterList'
NonSignificantClusterGenes
 nonsignificant cluster genes returned from 'ClusterList'

Note

argument 'x.data' should have an ID gene variable, 'probes', attached as a 'dimnames' attribute

Author(s)

Brian Steinmeyer

See Also

'GetClusters' 'ClusterList'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples
```

```
clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corr <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)

# generate both significant and non-significant gene clusters
cluster.list <- ClusterList(permutation.result, clusters.result$cluster.sizes, mantel.corr)

# significant and non-significant cluster genes (expression values)
cluster.genes <- ClusterGeneList(clusters.result$clusters, cluster.list$SignificantClusters, data)
```

ClusterList

Generate a Cluster List

Description

'ClusterList' generates a list of both significant and nonsignificant clusters, with cluster number, Mantel cluster correlation and size

Usage

```
ClusterList(p.val, clus.size, mantel.corr)
```

Arguments

p.val	permutation p-value returned from 'PermutationTest'
clus.size	vector of k cluster sizes returned from 'GetCluster'
mantel.corr	original, unpermuted k Mantel correlations returned from 'MantelCorrs'

Value

A list with components:

SignificantClusters

clusters with significant Mantel correlation, equal to or larger than the permutation p-value returned by 'PermutationTest'

NonSignificantClusters

clusters with nonsignificant Mantel correlation, smaller than the permutation p-value returned by 'PermutationTest'

Author(s)

Brian Steinmeyer

See Also

'PermutationTest'

Examples

```

# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corr <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)

# generate both significant and non-significant gene clusters
cluster.list <- ClusterList(permutation.result, clusters.result$cluster.sizes, mantel.corr)

```

DistMatrices

Compute Dissimilarity Matrices

Description

'DistMatrices' uses 'dist' to compute dissimilarity matrices for 'data' and each cluster k from 'GetClusters'

Usage

```
DistMatrices(x.data, cluster.assignment)
```

Arguments

x.data original 'data' matrix
cluster.assignment cluster assignment vector, "clusters", returned by 'GetClusters'

Value

returns a list with two components:

Dsubsets dissimilarity matrices for each cluster k
Dfull dissimilarity matrix for the original 'data'

Note

'GetClusters' should be executed prior to 'DistMatrices'

Author(s)

Brian Steinmeyer

See Also

'GetClusters'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dissimilarity.matrices <- DistMatrices(data, clusters.result$clusters)
```

GetClusters*Over-Partition a (p x n) Data Matrix using 'kmeans'*

Description

'GetClusters' uses an overly large k with the 'kmeans' function to over-partition p variables (rows = genes) from n objects (cols = samples) from a given data matrix 'x.data'

Usage

```
GetClusters(x.data, num.k, num.iters)
```

Arguments

x.data	p x n data matrix of numeric values
num.k	number of k partitions desired
num.iters	number of iterations - recommend ≥ 100

Value

'GetClusters' returns a list with the following components:

clusters	cluster assignment from 'kmeans'
cluster.sizes	size of each cluster k from 'kmeans'

Note

The input data matrix, `x.data`, must be numeric (e.g., gene-expression values). We recommend using `'num.k'` = one-half the number of genes and `'num.iters'` greater than 50

Author(s)

Brian Steinmeyer

See Also

`'kmeans'`

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
```

GolubTrain

Golub Training Set

Description

Samples were taken with Affymetrix Hgu6800 chips and expression levels measured on 7,129 genes (probes). The samples consist of 27 acute lymphoblastic leukemia (ALL) and 11 acute myeloid leukemia (AML) patients. The data values are raw (e.g. no standardization or gene filtering applied).

Usage

```
data(GolubTrain)
```

Format

A data frame of 7129 observations (genes) with the following 38 variables (samples):

X1 ALL
X2 ALL
X3 ALL
X4 ALL

- X5** ALL
- X6** ALL
- X7** ALL
- X8** ALL
- X9** ALL
- X10** ALL
- X11** ALL
- X12** ALL
- X13** ALL
- X14** ALL
- X15** ALL
- X16** ALL
- X17** ALL
- X18** ALL
- X19** ALL
- X20** ALL
- X21** ALL
- X22** ALL
- X23** ALL
- X24** ALL
- X25** ALL
- X26** ALL
- X27** ALL
- X28** AML
- X29** AML
- X30** AML
- X31** AML
- X32** AML
- X33** AML
- X34** AML
- X35** AML
- X36** AML
- X37** AML
- X38** AML

Source

<http://www.broad.mit.edu/cgi-bin/cancer/datasets.cgi>

References

Golub, T.R. Molecular Classification of Cancer: Class Discovery and Class Prediction by Gene Expression Monitoring. Science, vol 286, 531-537, 1999.

Examples

```
data(GolubTrain)
```

MantelCorrs

Compute Mantel Correlation(s)

Description

'MantelCorrs' computes the Mantel correlation between two dissimilarity matrices

Usage

```
MantelCorrs(Dfull, Dsubsets)
```

Arguments

Dfull	distance matrix returned by 'DistMatrices' using original 'data'
Dsubsets	list of distance matrices from each k cluster or partition returned by 'DistMatrices'

Value

A list with k components

where component i

Mantel correlation for cluster i, $i = 1, \dots, k$

Warning

The function is meant to be executed AFTER 'GetClustes' and 'DistMatrices' (see example)

Note

the value 'k' corresponds to the parameter 'num.k' in 'GetClusters'

Author(s)

Brian Steinmeyer

References

Mantel N: The detection of disease clustering and a generalized regression approach. Cancer Research. 27(2), 209-220 (1967).

See Also

'GetClusters' 'DistMatrices' 'kmeans'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corr <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
```

PermutatonTest

Permutation Test for Dissimilarity Matrices

Description

'PermutationTest' computes and returns an empirical p-value from a null distribution generated by permuting 'Dfull' a total of 'num.per' times.

Usage

```
PermutationTest(Dfull, Dsubsets, num.per, num.chips, alpha)
```

Arguments

Dfull	dissimilarity matrix from the original (p x n) microarray expression data
Dsubsets	dissimilarity matrices from each k disjoint clusters returned by 'GetClusters'
num.per	number of permutations
num.chips	number of samples, 'n' from the original (p x n) data matrix
alpha	desired level of significance

Details

For each permutation, k Mantel correlations are computed by correlating the permuted 'Dfull' with each dissimilarity matrix 'Dsubsets' from the 'k' clusters returned by 'GetClusters'. The absolute value of the maximum Mantel cluster correlation is retained at each permutation. These 'num.per' maximum correlations are then used to generate a null distribution for distance metric independence, with the p-value taken from the (1 - 'alpha') percentile of this permutation distribution.

Value

returns the permuted p-value for the 'alpha' selected level of significance

Warning

(p x n) data matrix should be numeric (e.g. gene-expression levels)

Note

The function is meant to be executed AFTER 'GetClusters', 'DistMatrices' and 'MantelCorr' (see example)

Author(s)

Brian Steinmeyer

See Also

'GetClusters' 'DistMatrices' 'MantelCorrs'

Examples

```
# simulate a p x n microarray expression dataset, where p = genes and n = samples
data.sep <- rbind(matrix(rnorm(1000), ncol=50), matrix(rnorm(1000, mean=5), ncol=50))
noise <- matrix(runif(40000), ncol=1000)
data <- t(cbind(data.sep, noise))
data <- data[1:200, ]
# data has p = 1,050 genes and n = 40 samples

clusters.result <- GetClusters(data, 100, 100)
dist.matrices <- DistMatrices(data, clusters.result$clusters)
mantel.corrs <- MantelCorrs(dist.matrices$Dfull, dist.matrices$Dsubsets)
permutation.result <- PermutationTest(dist.matrices$Dfull, dist.matrices$Dsubsets, 100, 40, 0.05)
```

Index

*Topic **cluster**

ClusterGeneList, [2](#)

ClusterList, [3](#)

DistMatrices, [4](#)

GetClusters, [5](#)

MantelCorrs, [8](#)

PermutatonTest, [9](#)

*Topic **datasets**

GolubTrain, [6](#)

ClusterGeneList, [2](#)

ClusterList, [3](#)

DistMatrices, [4](#)

GetClusters, [5](#)

GolubTrain, [6](#)

MantelCorrs, [8](#)

PermutationTest (PermutatonTest), [9](#)

PermutatonTest, [9](#)