

Package ‘transomics2cytoscape’

October 14, 2021

Title A tool set for 3D Trans-Omic network visualization with Cytoscape

Version 1.2.2

Description transomics2cytoscape generates a file for 3D transomics visualization by providing input that specifies the IDs of multiple KEGG pathway layers, their corresponding Z-axis heights, and an input that represents the edges between the pathway layers. The edges are used, for example, to describe the relationships between kinase on a pathway and enzyme on another pathway. This package automates creation of a transomics network as shown in the figure in Yugi.2014 (<https://doi.org/10.1016/j.celrep.2014.07.021>) using Cytoscape automation (<https://doi.org/10.1186/s13059-019-1758-4>).

License Artistic-2.0

Imports RCy3, KEGGREST, dplyr

Suggests testthat, roxygen2, knitr, BiocStyle, rmarkdown

Encoding UTF-8

LazyData true

biocViews Network, Software, Pathways, DataImport, KEGG

VignetteBuilder knitr

SystemRequirements Java 11, Cytoscape 3.8.2, Cy3D >= 1.1.3

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/transomics2cytoscape>

git_branch RELEASE_3_13

git_last_commit 724a2d6

git_last_commit_date 2021-10-08

Date/Publication 2021-10-14

Author Kozo Nishida [aut, cre] (<<https://orcid.org/0000-0001-8501-7319>>), Katsuyuki Yugi [aut] (<<https://orcid.org/0000-0002-2046-4289>>)

Maintainer Kozo Nishida <kozo.nishida@gmail.com>

R topics documented:

create3Dnetwork	2
createTransomicEdges	3
ec2reaction	3
installCyApps	4

Index	5
--------------	----------

create3Dnetwork	<i>Create 3D network view for transomics visualization.</i>
-----------------	---

Description

Import multiple KEGG pathways and integrate the pathways into Cy3D renderer

Usage

```
create3Dnetwork(networkDataDir, networkLayers, stylexml)
```

Arguments

networkDataDir	Path of a directory to put the network files of the second column of networkLayers TSV.
networkLayers	Path of a TSV file with the 3 columns (layer index, the network file name in networkDataDir, Z-height of the network).
stylexml	Path of a XML file for Cytoscape style

Value

A SUID of the 3D network.

Author(s)

Kozo Nishida

Examples

```
## Not run:
networkDataDir <- tempfile(); dir.create(networkDataDir)
networkLayers <- system.file("extdata", "yugi2014.tsv",
  package = "transomics2cytoscape")
stylexml <- system.file("extdata", "transomics.xml",
  package = "transomics2cytoscape")
suid <- create3Dnetwork(networkDataDir, networkLayers, stylexml)

## End(Not run)
```

createTransomicEdges *Create Trans-Omic edges between layers of the network.*

Description

Create Trans-Omic edges between layers of the network

Usage

```
createTransomicEdges(suid, transomicEdges)
```

Arguments

suid A SUID of Cytoscape network

transomicEdges Path of a TSV file with the 9 columns (layer index of a source node, name or KEGG object ID that the source node should have, layer index of a target node, name or KEGG object ID that the target node should have, interaction type).

Value

A SUID of the 3D network.

Author(s)

Kozo Nishida

Examples

```
## Not run:
transomicEdges <- system.file("extdata", "allosteric.tsv",
  package = "transomics2cytoscape")
createTransomicEdges(suid, transomicEdges)

## End(Not run)
```

ec2reaction *Convert KEGG enzyme IDs to KEGG reaction IDs.*

Description

Convert KEGG enzyme IDs to KEGG reaction IDs

Usage

```
ec2reaction(tsvFilePath, columnIndex, outputFilename)
```

Arguments

tsvFilePath Path of a TSV file with the 9 columns (layer index of a source node, name or KEGG object ID that the source node should have, layer index of a target node, name or KEGG object ID that the target node should have, interaction type).

columnIndex The column number

outputFilename The output filename

Value

None

Author(s)

Kozo Nishida

Examples

```
## Not run:
ec = system.file("extdata", "allosteric_ecnumber.tsv",
  package = "transomics2cytoscape")
ec2reaction(ec, 8, "allosteric.tsv")

## End(Not run)
```

installCyApps

Install the Cytoscape Apps the transomics2cytoscape depends.

Description

Install the Cytoscape Apps the transomics2cytoscape depends

Usage

```
installCyApps()
```

Value

None

Author(s)

Kozo Nishida

Examples

```
## Not run:
installCyApps()

## End(Not run)
```

Index

create3Dnetwork, [2](#)
createTransomicEdges, [3](#)
ec2reaction, [3](#)
installCyApps, [4](#)