

MyGene.info R Client

Adam Mark, Ryan Thompson, Chunlei Wu

May 19, 2021

Contents

1	Overview	2
2	Gene Annotation Service	2
2.1	<code>getGene</code>	2
2.2	<code>getGenes</code>	2
3	Gene Query Service	3
3.1	<code>query</code>	3
3.2	<code>queryMany</code>	4
4	<code>makeTxDbFromMyGene</code>	5
5	Tutorial, ID mapping	6
5.1	Mapping gene symbols to Entrez gene ids	6
5.2	Mapping gene symbols to Ensembl gene ids	7
5.3	When an input has no matching gene	8
5.4	When input ids are not just symbols	8
5.5	When an input id has multiple matching genes	9
5.6	Can I convert a very large list of ids?	11
6	References	11

1 Overview

MyGene.Info provides simple-to-use REST web services to query/retrieve gene annotation data. It's designed with simplicity and performance emphasized. *mygene* is an easy-to-use R wrapper to access MyGene.Info services.

2 Gene Annotation Service

2.1 `getGene`

- Use `getGene`, the wrapper for GET query of `"/gene/<geneid>"` service, to return the gene object for the given geneid.

```
> gene <- getGene("1017", fields="all")
> length(gene)

[1] 1

> gene["name"]

[[1]]
NULL

> gene["taxid"]

[[1]]
NULL

> gene["uniprot"]

[[1]]
NULL

> gene["refseq"]

[[1]]
NULL
```

2.2 `getGenes`

- Use `getGenes`, the wrapper for POST query of `"/gene"` service, to return the list of gene objects for the given character vector of geneids.

```
> getGenes(c("1017", "1018", "ENSG00000148795"))

DataFrame with 3 rows and 7 columns
```

	query	_id	X_version	entrezgene	name
	<character>	<character>	<integer>	<character>	<character>
1	1017	1017	4	1017 cyclin dependent kin..	
2	1018	1018	4	1018 cyclin dependent kin..	
3	ENSG00000148795	1586	3	1586 cytochrome P450 fami..	

	symbol	taxid
	<character>	<integer>
1	CDK2	9606
2	CDK3	9606
3	CYP17A1	9606

3 Gene Query Service

3.1 query

- Use `query`, a wrapper for GET query of `"/query?q=<query>"` service, to return the query result.

```
> query(q="cdk2", size=5)

$took
[1] 23

$total
[1] 1046

$max_score
[1] 440.6161

$hits
      _id  _score  entrezgene      name  symbol  taxid
1      1017 440.6161      1017  cyclin dependent kinase 2  CDK2  9606
2     12566 371.9271     12566  cyclin-dependent kinase 2  Cdk2 10090
3     362817 312.6953     362817  cyclin dependent kinase 2  Cdk2 10116
4    102929928 286.0978  102929928  cyclin dependent kinase 2  CDK2  8469
5  ENSPMAG00000003902 286.0978      <NA>  cyclin-dependent kinase 2  cdk2  7757

> query(q="NM_013993")

$took
[1] 12
```

MyGene.info R Client

```
$total
[1] 1

$max_score
[1] 3.966719

$hits
  _id  _score entrezgene          name symbol
1 780 3.966719      780 discoidin domain receptor tyrosine kinase 1  DDR1
  taxid
1 9606
```

3.2 queryMany

- Use `queryMany`, a wrapper for POST query of `"/query"` service, to return the batch query result.

```
> queryMany(c('1053_at', '117_at', '121_at', '1255_g_at', '1294_at'),
+           scopes="reporter", species="human")

Finished
Pass returnall=TRUE to return lists of duplicate or missing query terms.
DataFrame with 6 rows and 7 columns
```

	query	_id	X_score	entrezgene	name	
	<character>	<character>	<numeric>	<character>	<character>	
1	1053_at	5982	13.4877	5982	replication factor C..	
2	117_at	3310	13.4728	3310	heat shock protein f..	
3	121_at	7849	12.2298	7849	paired box 8	
4	1255_g_at	2978	12.5058	2978	guanylate cyclase ac..	
5	1294_at	100847079	14.2754	100847079	microRNA 5193	
6	1294_at	7318	13.4877	7318	ubiquitin like modif..	
	symbol	taxid				
	<character>	<integer>				
1	RFC2	9606				
2	HSPA6	9606				
3	PAX8	9606				
4	GUCA1A	9606				
5	MIR5193	9606				
6	UBA7	9606				

4 makeTxDbFromMyGene

TxDb is a container for storing transcript annotations. `makeTxDbFromMyGene` allows the user to make a TxDb object in the Genomic Features package from a mygene "exons" query using a default mygene object.

```
> xli <- c('CCDC83',
+         'MAST3',
+         'RPL11',
+         'ZDHHC20',
+         'LUC7L3',
+         'SNORD49A',
+         'CTSH',
+         'ACOT8')
> txdb <- makeTxDbFromMyGene(xli,
+                            scopes="symbol", species="human")
> transcripts(txdb)
```

GRanges object with 17 ranges and 2 metadata columns:

	seqnames	ranges	strand	tx_id	tx_name
	<Rle>	<IRanges>	<Rle>	<integer>	<character>
[1]	11	85855382-85920013	+	1	NM_001286159
[2]	11	85855382-85920013	+	2	NM_173556
[3]	19	18097777-18151686	+	3	NM_015016
[4]	1	23691805-23696835	+	4	NM_000975
[5]	1	23691778-23696426	+	5	NM_001199802
...
[13]	17	50719602-50756215	+	13	NM_016424
[14]	17	16440035-16440106	+	14	NR_002744
[15]	15	78921749-78945098	-	15	NM_001319137
[16]	15	78921059-78945046	-	16	NM_004390
[17]	20	45841720-45857392	-	17	NM_005469

seqinfo: 7 sequences from an unspecified genome; no seqlengths

`makeTxDbFromMyGene` invokes either the `query` or `queryMany` method and passes the response to construct a `TxDb` object. See `?TxDb` for methods to utilize and access transcript annotations.

5 Tutorial, ID mapping

ID mapping is a very common, often not fun, task for every bioinformatician. Supposedly you have a list of gene symbols or reporter ids from an upstream analysis, and then your next analysis requires to use gene ids (e.g. Entrez gene ids or Ensembl gene ids). So you want to convert that list of gene symbols or reporter ids to corresponding gene ids.

Here we want to show you how to do ID mapping quickly and easily.

5.1 Mapping gene symbols to Entrez gene ids

Suppose `xli` is a list of gene symbols you want to convert to entrez gene ids:

```
> xli <- c('DDX26B',
+         'CCDC83',
+         'MAST3',
+         'FLOT1',
+         'RPL11',
+         'ZDHHC20',
+         'LUC7L3',
+         'SNORD49A',
+         'CTSH',
+         'ACOT8')
```

You can then call `queryMany` method, telling it your input is `symbol`, and you want `entrezgene` (Entrez gene ids) back.

```
> queryMany(xli, scopes="symbol", fields="entrezgene", species="human")
```

Finished

Pass `returnall=TRUE` to return lists of duplicate or missing query terms.

DataFrame with 10 rows and 5 columns

	query	notfound	_id	X_score	entrezgene
	<character>	<logical>	<character>	<numeric>	<character>
1	DDX26B	TRUE	NA	NA	NA
2	CCDC83	NA	220047	89.3727	220047
3	MAST3	NA	23031	89.5705	23031
4	FLOT1	NA	10211	91.7009	10211
5	RPL11	NA	6135	83.1285	6135
6	ZDHHC20	NA	253832	90.1929	253832
7	LUC7L3	NA	51747	87.2339	51747
8	SNORD49A	NA	26800	119.3422	26800

9	CTSH	NA	1512	86.7899	1512
10	ACOT8	NA	10005	88.0760	10005

5.2 Mapping gene symbols to Ensembl gene ids

Now if you want Ensembl gene ids back:

```

> out <- queryMany(xli, scopes="symbol", fields="ensembl.gene", species="human")

Finished
Pass returnall=TRUE to return lists of duplicate or missing query terms.

> out

DataFrame with 10 rows and 5 columns
  query notfound _id X_score
<character> <logical> <character> <numeric>
1 DDX26B TRUE NA NA
2 CCDC83 NA 220047 89.3727
3 MAST3 NA 23031 89.5705
4 FLOT1 NA 10211 91.7009
5 RPL11 NA 6135 83.1285
6 ZDHHC20 NA 253832 90.1929
7 LUC7L3 NA 51747 87.2339
8 SNORD49A NA 26800 119.3422
9 CTSH NA 1512 86.7899
10 ACOT8 NA 10005 88.0760

ensembl
<list>
1
2 ENSG00000150676
3 ENSG00000099308
4 ENSG00000232280,ENSG00000206379,ENSG00000236271
5 ENSG00000142676
6 ENSG00000180776
7 ENSG00000108848
8 ENSG00000277370
9 ENSG00000103811
10 ENSG00000101473

> out$ensembl[[4]]$gene
[1] "ENSG00000232280" "ENSG00000206379" "ENSG00000236271" "ENSG00000206480"
[5] "ENSG00000230143" "ENSG00000137312" "ENSG00000224740" "ENSG00000223654"

```

5.3 When an input has no matching gene

In case that an input id has no matching gene, you will be notified from the output. The returned list for this query term contains `notfound` value as `True`.

```
> xli <- c('DDX26B',  
+         'CCDC83',  
+         'MAST3',  
+         'FLOT1',  
+         'RPL11',  
+         'Gm10494')  
> queryMany(xli, scopes="symbol", fields="entrezgene", species="human")
```

Finished

Pass `returnall=TRUE` to return lists of duplicate or missing query terms.
DataFrame with 6 rows and 5 columns

	query	notfound	_id	X_score	entrezgene
	<character>	<logical>	<character>	<numeric>	<character>
1	DDX26B	TRUE	NA	NA	NA
2	CCDC83	NA	220047	89.3738	220047
3	MAST3	NA	23031	89.5705	23031
4	FLOT1	NA	10211	91.7009	10211
5	RPL11	NA	6135	83.1285	6135
6	Gm10494	TRUE	NA	NA	NA

5.4 When input ids are not just symbols

```
> xli <- c('DDX26B',  
+         'CCDC83',  
+         'MAST3',  
+         'FLOT1',  
+         'RPL11',  
+         'Gm10494',  
+         '1007_s_at',  
+         'AK125780')  
>
```

Above id list contains symbols, reporters and accession numbers, and supposedly we want to get back both Entrez gene ids and uniprot ids. Parameters `scopes`, `fields`, `species` are all flexible enough to support multiple values, either a list or a comma-separated string:

MyGene.info R Client

```
> out <- queryMany(xli, scopes=c("symbol", "reporter", "accession"),
+                 fields=c("entrezgene", "uniprot"), species="human")
Finished
Pass returnall=TRUE to return lists of duplicate or missing query terms.
> out
DataFrame with 9 rows and 7 columns
  query      notfound      _id  X_score  entrezgene  uniprot.Swiss.Prot
<character> <logical> <character> <numeric> <character>      <character>
1  DDX26B      TRUE      NA      NA      NA      NA
2  CCDC83      NA      220047  89.3738  220047  Q8IWF9
3  MAST3      NA      23031  89.5705  23031  060307
4  FLOT1      NA      10211  91.7009  10211  075955
5  RPL11      NA      6135  83.1285  6135  P62913
6  Gm10494    TRUE      NA      NA      NA      NA
7  1007_s_at  NA      100616237  14.2013  100616237  NA
8  1007_s_at  NA      780  12.9661  780  Q08345
9  AK125780  NA      118142757  20.0761  118142757  P43080
      uniprot.TrEMBL
      <list>
1
2      H0YDV3
3      V9GYV0
4      A2ABJ5, Q5ST80, A2AB09, ...
5      Q5VVC8, Q5VVD0, A0A2R8Y447
6
7
8  A0A024RCL1, A0A024RCJ0, A0A024RCQ1, ...
9      A0A7I2V6E2, B2R9P6
> out$uniprot.Swiss.Prot[[5]]
[1] "P62913"
```

5.5 When an input id has multiple matching genes

From the previous result, you may have noticed that query term `1007_s_at` matches two genes. In that case, you will be notified from the output, and the returned result will include both matching genes.

By passing `returnall=TRUE`, you will get both duplicate or missing query terms

MyGene.info R Client

```

> queryMany(xli, scopes=c("symbol", "reporter", "accession"),
+           fields=c("entrezgene", "uniprot"), species='human', returnall=TRUE)

Finished
$response
DataFrame with 9 rows and 7 columns
  query notfound _id X_score entrezgene uniprot.Swiss.Prot
  <character> <logical> <character> <numeric> <character> <character>
1 DDX26B TRUE NA NA NA NA
2 CCDC83 NA 220047 89.3420 220047 Q8IWF9
3 MAST3 NA 23031 89.6324 23031 060307
4 FL0T1 NA 10211 91.7009 10211 075955
5 RPL11 NA 6135 83.1236 6135 P62913
6 Gm10494 TRUE NA NA NA NA
7 1007_s_at NA 100616237 14.2754 100616237 NA
8 1007_s_at NA 780 12.9661 780 Q08345
9 AK125780 NA 118142757 19.6592 118142757 P43080
  uniprot.TrEMBL
  <list>
1
2 H0YDV3
3 V9GYV0
4 A2ABJ5, Q5ST80, A2AB09, ...
5 Q5VVC8, Q5VVD0, A0A2R8Y447
6
7
8 A0A024RCL1, A0A024RCJ0, A0A024RCQ1, ...
9 A0A7I2V6E2, B2R9P6

$duplicates
  X1007_s_at
1 2

$missing
[1] "DDX26B" "Gm10494"

```

The returned result above contains `out` for mapping output, `missing` for missing query terms (a list), and `dup` for query terms with multiple matches (including the number of matches).

5.6 Can I convert a very large list of ids?

Yes, you can. If you pass an id list (i.e., `xli` above) larger than 1000 ids, we will do the id mapping in-batch with 1000 ids at a time, and then concatenate the results all together for you. So, from the user-end, it's exactly the same as passing a shorter list. You don't need to worry about saturating our backend servers. Large lists, however, may take a while longer to query, so please wait patiently.

6 References

Wu C, MacLeod I, Su AI (2013) BioGPS and MyGene.info: organizing online, gene-centric information. *Nucl. Acids Res.* 41(D1): D561-D565. help@mygene.info