

Package ‘benchmarkfdrData2019’

October 16, 2021

Title Data and Benchmarking Results from Korthauer and Kimes et al.
(2019)

Version 1.6.0

BugReports <https://github.com/stephaniehicks/benchmarkfdrData2019/issues>

Description Benchmarking results for experimental and simulated data sets used
in Korthauer and Kimes et al. (2019) to compare methods for controlling
the false discovery rate.

Depends R (>= 3.6.0), SummarizedExperiment, ExperimentHub

Imports utils

Suggests knitr, BiocStyle, testthat, SummarizedBenchmark, dplyr,
ggplot2, rlang

License MIT + file LICENSE

Encoding UTF-8

LazyData true

biocViews SingleCellData, ExperimentData, RNASeqData, ExpressionData,
ExperimentData, ExperimentHub

VignetteBuilder knitr

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/benchmarkfdrData2019>

git_branch RELEASE_3_13

git_last_commit a560f98

git_last_commit_date 2021-05-19

Date/Publication 2021-10-16

Author Stephanie Hicks [aut, cre] (<<https://orcid.org/0000-0002-7858-0231>>),
Keegan Korthauer [aut] (<<https://orcid.org/0000-0002-4565-1654>>),
Patrick Kimes [aut] (<<https://orcid.org/0000-0001-6819-9077>>)

Maintainer Stephanie Hicks <shicks19@jhu.edu>

R topics documented:

chipseq-cbp	2
chipseq-h3k4me3	3
gsa-human	4

gsa-mouse	4
gwas-bmi	5
microbiome-baxter	6
microbiome-enigma	7
microbiome-goodrich	8
microbiome-papa	9
microbiome-schubert	10
polyester-insilico	11
rnaseq-brain	12
rnaseq-mir200c	13
scrnaseq-human	13
scrnaseq-mouse	14
sims-informative-cosine	16
sims-informative-cubic	16
sims-informative-sine	17
sims-informative-step	18
sims-null	19
sims-uasettings	19
sims-uasettings-25	20
sims-uasettings-t	21
sims-varyinginfo-discrete	22
sims-varyinginfo-smooth	23
sims-varyingntests	24
sims-varyingpi0	25
sims-varyingpi0-t	26
yeast-insilico	27
Index	30

chipseq-cbp	<i>ChIP-seq, CBP dataset results</i>
-------------	--------------------------------------

Description

Results for case study on differential peak calling in CREB-binding protein (CBP) knockout and wild-type mice described in Korthauer and Kimes et al. (2019). Analyses were performed using the csaw package.

Arguments

metadata	logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)
----------	---

Details

Results for this case study include:

- cbp-csaw-benchmark: using csaw with region width as covariate.
- cbp-csaw-uninf-benchmark: using csaw with uninformative covariate.
- cbp-csaw-cov-benchmark: using csaw with mean coverage as covariate.

See Also[chipseq-h3k4me3](#)**Examples**

```
`cbp-csaw-benchmark`(metadata = TRUE)

## Not run:
`cbp-csaw-benchmark`()
`cbp-csaw-uninf-benchmark`()
`cbp-csaw-cov-benchmark`()

## End(Not run)
```

`chipseq-h3k4me3`*ChIP-seq, H3K4me3 dataset results*

Description

Results for case study on differential peak calling in human H3K4me3 ChIP-seq data from ENCODE described in Korthauer and Kimes et al. (2019). Analyses were performed using either DESeq2 applied to predefined regions or with the csaw package.

Arguments

`metadata` logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- `h3k4me3-promoters-benchmark`: using predefined regions with mean coverage as covariate.
- `h3k4me3-csaw-benchmark`: using csaw with region width as covariate.
- `h3k4me3-csaw-uninf-benchmark`: using csaw with uninformative covariate.
- `h3k4me3-csaw-cov-benchmark`: using csaw with mean coverage as covariate.

See Also[chipseq-cbp](#)**Examples**

```
`h3k4me3-promoters-benchmark`(metadata = TRUE)

## Not run:
`h3k4me3-promoters-benchmark`()
`h3k4me3-csaw-benchmark`()
`h3k4me3-csaw-uninf-benchmark`()
`h3k4me3-csaw-cov-benchmark`()

## End(Not run)
```

gsa-human

Gene Set Analysis, human dataset results

Description

Results for case study on gene set analysis using human dataset described in Korthauer and Kimes et al. (2019). Analyses were performed using GSEA.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- human-benchmark: using gene set size as covariate.
- human-uninf-benchmark: using uninformative covariate.

See Also

[gsa-human](#)

Examples

```
`human-benchmark`(metadata = TRUE)

## Not run:
`human-benchmark`()
`human-uninf-benchmark`()

## End(Not run)
```

gsa-mouse

Gene Set Analysis, mouse dataset results

Description

Results for case study on gene set analysis using mouse dataset described in Korthauer and Kimes et al. (2019). Analyses were performed using GSEA.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- mouse-benchmark: using gene set size as covariate.
- mouse-uninf-benchmark: using uninformative covariate.

See Also

[gsa-human](#)

Examples

```
`mouse-benchmark`(metadata = TRUE)

## Not run:
`mouse-benchmark`()
`mouse-uninf-benchmark`()

## End(Not run)
```

gwas-bmi

Genome-wide Association Study, BMI dataset results

Description

Results for case study on genome-wide associate study meta-analysis using a BMI dataset from the GIANT Consortium described in Korthauer and Kimes et al. (2019).

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- bmi-maf-benchmark: using minor allele frequency as covariate.
- bmi-uninf-benchmark: using uninformative covariate.
- bmi-samplesize-benchmark: using sample size as covariate.

Examples

```
`bmi-maf-benchmark`(metadata = TRUE)

## Not run:
`bmi-maf-benchmark`()
`bmi-uninf-benchmark`()
`bmi-samplesize-benchmark`()

## End(Not run)
```

microbiome-baxter *Microbiome, Baxter dataset results*

Description

Results for case study on 16S microbiome differential testing of Baxter et al. (2016) dataset described in Korthauer and Kimes et al. (2019). Wilcoxon rank-sum test was used to test for differential abundance between samples from patients with colorectal cancer and patients with no colonic lesions.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- `baxter-genus-benchmark`: testing at genus-level using ubiquity as covariate.
- `baxter-genus-log-ubiquity-benchmark`: testing at genus-level using log-ubiquity as covariate.
- `baxter-genus-mean-abun-benchmark`: testing at genus-level using mean abundance as covariate.
- `baxter-genus-mean-uninf-benchmark`: testing at genus-level using uninformative covariate.
- `baxter-otus-benchmark`: testing at OTU-level using ubiquity as covariate.
- `baxter-otus-log-ubiquity-benchmark`: testing at OTU-level using log-ubiquity as covariate.

References

- Baxter, N. T., Ruffin, M. T., Rogers, M. A., & Schloss, P. D. (2016). Microbiota-based model improves the sensitivity of fecal immunochemical test for detecting colonic lesions. *Genome Medicine*, 8(1), 37.

See Also

[microbiome-schubert](#), [microbiome-goodrich](#), [microbiome-papa](#), [microbiome-enigma](#)

Examples

```
`baxter-genus-benchmark`(metadata = TRUE)

## Not run:
`baxter-genus-benchmark`()
`baxter-genus-log-ubiquity-benchmark`()
`baxter-genus-mean-abun-benchmark`()
`baxter-genus-mean-uninf-benchmark`()
`baxter-otus-benchmark`()
`baxter-otus-log-ubiquity-benchmark`()
```

```
## End(Not run)
```

microbiome-enigma *Microbiome, ENIGMA dataset results*

Description

Results for case study on 16S microbiome Spearman correlation testing of ENIGMA dataset described in Korthauer and Kimes et al. (2019). Spearman correlation test was used to test for correlation between OTU-level microbial abundances and various geochemical and physical measurements.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- `enigma-al-otus-benchmark`: testing for correlation with Al measurements using ubiquity as covariate.
- `enigma-al-otus-abun-benchmark`: testing for correlation with Al measurements using mean abundance as covariate.
- `enigma-al-otus-uninf-benchmark`: testing for correlation with Al measurements using uninformative covariate.
- `enigma-ph-otus-benchmark`: testing for correlation with pH measurements using ubiquity as covariate.
- `enigma-ph-otus-abun-benchmark`: testing for correlation with pH measurements using mean abundance as covariate.
- `enigma-ph-otus-uninf-benchmark`: testing for correlation with pH measurements using uninformative covariate.
- `enigma-so4-otus-benchmark`: testing for correlation with SO4 measurements using ubiquity as covariate.
- `enigma-so4-otus-abun-benchmark`: testing for correlation with SO4 measurements using mean abundance as covariate.
- `enigma-so4-otus-uninf-benchmark`: testing for correlation with SO4 measurements using uninformative covariate.

See Also

[microbiome-schubert](#), [microbiome-baxter](#), [microbiome-goodrich](#), [microbiome-papa](#)

Examples

```
`enigma-al-otus-benchmark`(metadata = TRUE)

## Not run:
`enigma-al-otus-benchmark`()
`enigma-al-otus-abun-benchmark`()
`enigma-al-otus-uninf-benchmark`()
`enigma-ph-otus-benchmark`()
`enigma-ph-otus-abun-benchmark`()
`enigma-ph-otus-uninf-benchmark`()
`enigma-so4-otus-benchmark`()
`enigma-so4-otus-abun-benchmark`()
`enigma-so4-otus-uninf-benchmark`()

## End(Not run)
```

microbiome-goodrich *Microbiome, Goodrich dataset results*

Description

Results for case study on 16S microbiome differential testing of Goodrich et al. (2014) dataset described in Korthauer and Kimes et al. (2019). Wilcoxon rank-sum test was used to test for differential abundance between samples from lean (body mass index, BMI < 25) and obese (BMI > 30) individuals.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- goodrich-genus-benchmark: testing at genus-level using ubiquity as covariate.
- goodrich-genus-abun-benchmark: testing at genus-level using mean abundance as covariate.
- goodrich-genus-uninf-benchmark: testing at genus-level using uninformative covariate.
- goodrich-otus-benchmark: testing at OTU-level using ubiquity as covariate.

References

- Goodrich, J. K. et al. (2014). Human genetics shape the gut microbiome. *Cell*, 159(4), 789-799.

See Also

[microbiome-schubert](#), [microbiome-baxter](#), [microbiome-papa](#), [microbiome-enigma](#)

Examples

```
`goodrich-genus-benchmark`(metadata = TRUE)

## Not run:
`goodrich-genus-benchmark`()
`goodrich-genus-abun-benchmark`()
`goodrich-genus-uninf-benchmark`()
`goodrich-otus-benchmark`()

## End(Not run)
```

microbiome-papa

Microbiome, Papa dataset results

Description

Results for case study on 16S microbiome differential testing of Papa et al. (2012) dataset described in Korthauer and Kimes et al. (2019). Wilcoxon rank-sum test was used to test for differential abundance between samples from patients with GI symptoms but not IBD, and IBD patients.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- papa-genus-benchmark: testing at genus-level using ubiquity as covariate.
- papa-genus-abun-benchmark: testing at genus-level using mean abundance as covariate.
- papa-genus-log-ubiquity-benchmark: testing at genus-level using log-ubiquity as covariate.
- papa-genus-uninf-benchmark: testing at genus-level using uninformative covariate.
- papa-otus-benchmark: testing at OTU-level using ubiquity as covariate.

References

- Papa, E. et al. (2012). Non-invasive mapping of the gastrointestinal microbiota identifies children with inflammatory bowel disease. *PloS One*, 7(6), e39242.

See Also

[microbiome-schubert](#), [microbiome-baxter](#), [microbiome-goodrich](#), [microbiome-enigma](#)

Examples

```
`papa-genus-benchmark`(metadata = TRUE)

## Not run:
`papa-genus-benchmark`()
`papa-genus-abun-benchmark`()
`papa-genus-log-ubiquity-benchmark`()
`papa-genus-uninf-benchmark`()
`papa-otus-benchmark`()

## End(Not run)
```

microbiome-schubert *Microbiome, Schubert dataset results*

Description

Results for case study on 16S microbiome differential testing of Schubert et al. (2014) dataset described in Korthauer and Kimes et al. (2019). Wilcoxon rank-sum test was used to test for differential abundance between samples from healthy patients and patients with diarrheal stool samples (including both *C. difficile* infection, CDI, and non-CDI samples).

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- schubert-otus-benchmark: testing at OTU-level using ubiquity as covariate.
- schubert-otus-abun-benchmark: testing at OTU-level using mean abundance as covariate.
- schubert-otus-uninf-benchmark: testing at OTU-level using uninformative covariate.

References

- Schubert, A. M. et al. (2014). Microbiome data distinguish patients with *Clostridium difficile* infection and non-*C. difficile*-associated diarrhea from healthy controls. *MBio*, 5(3), e01021-14.

See Also

[microbiome-baxter](#), [microbiome-goodrich](#), [microbiome-papa](#), [microbiome-enigma](#)

Examples

```
`schubert-otus-benchmark`(metadata = TRUE)

## Not run:
`schtubert-otus-benchmark`()
`schtubert-otus-abun-benchmark`()
`schtubert-otus-uninf-benchmark`()

## End(Not run)
```

polyester-insilico *Polyester simulated dataset results*

Description

Results for differential gene expression analysis using RNA-seq data simulated with the **Polyester** package from yeast data obtained from Schurch et al. (2016) as described in Korthauer and Kimes et al. (2019). Differential expression was tested using **DESeq2**.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- polyester-results-null5: null 5 vs. 5 comparison.
- polyester-results-de5: using unimodal alternative, 2000 DE genes, strong informative covariate, 5 vs. 5 comparison.
- polyester-results-de5-uninfCov: using unimodal alternative, 2000 DE genes, uninformative covariate, 5 vs. 5 comparison.
- polyesterW-results-de5: using unimodal alternative, 2000 DE genes, weak informative covariate, 5 vs. 5 comparison.
- polyester-results-null10: null 10 vs. 10 comparison.
- polyester-results-de10: using unimodal alternative, 2000 DE genes, strong informative covariate, 10 vs. 10 comparison.
- polyester-results-de10-uninfCov: using unimodal alternative, 2000 DE genes, uninformative covariate, 10 vs. 10 comparison.
- polyesterW-results-de10: using unimodal alternative, 2000 DE genes, weak informative covariate, 10 vs. 10 comparison.

References

- Schurch, N. J. et al. (2016). How many biological replicates are needed in an RNA-seq experiment and which differential expression tool should you use?. *RNA*, 22(6), 839-851.

See Also[yeast-insilico](#)**Examples**

```

`polyester-results-de5`(metadata = TRUE)

## Not run:
`polyester-results-de5`()
`polyester-results-de5-uninfCov`()
`polyester-results-de10`()
`polyester-results-de10-uninfCov`()
`polyester-results-null15`()
`polyester-results-null10`()
`polyesterW-results-de5`()
`polyesterW-results-de10`()

## End(Not run)

```

rnaseq-brain

*RNA-seq, brain dataset results***Description**

Results for case study on differential gene expression analysis between two brain regions (nucleus accumbens and putamen) using data from the GTEx project described in Korthauer and Kimes et al. (2019). Differential expression was tested using **DESeq2**.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- brain-benchmark: using mean counts as covariate.
- brain-uninf-benchmark: using uninformative covariate.

See Also[rnaseq-mir200c](#)**Examples**

```

`brain-benchmark`(metadata = TRUE)

## Not run:
`brain-benchmark`()
`brain-uninf-benchmark`()

## End(Not run)

```

 rnaseq-mir200c

RNA-seq, mir200c dataset results

Description

Results for case study on differential gene expression analysis between mir200c knockdown cells and untreated cells described in Korthauer and Kimes et al. (2019). Differential expression was tested using **DESeq2**.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- mir200c-benchmark: using mean counts as covariate.
- mir200c-uninf-benchmark: using uninformative covariate.

See Also

[rnaseq-brain](#)

Examples

```
`mir200c-benchmark`(metadata = TRUE)

## Not run:
`mir200c-benchmark`()
`mir200c-uninf-benchmark`()

## End(Not run)
```

 scrnaseq-human

scRNA-seq, human dataset results

Description

Results for case study on single-cell RNA-seq differential expression analysis using data from diffuse neoplastic infiltrating cells at the migrating front of human glioblastoma as described in Korthauer and Kimes et al. (2019). Differential expression was testing using either the **MAST** package, **scDD** package, or Wilcoxon rank-sum test.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- human-benchmark-mast-det: testing with **MAST**, using detection rate as covariate.
- human-benchmark-mast-mean: testing with **MAST**, using mean counts as covariate.
- human-benchmark-mast-uninf: testing with **MAST**, using uninformative covariate.
- human-benchmark-scdd-det: testing with **scDD**, using detection rate as covariate.
- human-benchmark-scdd-mean: testing with **scDD**, using mean counts as covariate.
- human-benchmark-scdd-uninf: testing with **scDD**, using uninformative covariate.
- human-benchmark-wilcox-det: testing with Wilcoxon rank-sum, using detection rate as covariate.
- human-benchmark-wilcox-mean: testing with Wilcoxon rank-sum, using mean counts as covariate.
- human-benchmark-wilcox-uninf: testing with Wilcoxon rank-sum, using uninformative covariate.

See Also

[scrnaseq-mouse](#)

Examples

```

`human-benchmark-mast-det`(metadata = TRUE)

## Not run:
`human-benchmark-mast-det`()
`human-benchmark-mast-mean`()
`human-benchmark-mast-uninf`()
`human-benchmark-scdd-det`()
`human-benchmark-scdd-mean`()
`human-benchmark-scdd-uninf`()
`human-benchmark-wilcox-det`()
`human-benchmark-wilcox-mean`()
`human-benchmark-wilcox-uninf`()

## End(Not run)

```

scrnaseq-mouse

scRNA-seq, mouse dataset results

Description

Results for case study on single-cell RNA-seq differential expression analysis using data from mouse cells at NF-kappa-beta activation as described in Korthauer and Kimes et al. (2019). Differential expression was testing using either the **MAST** package, **scDD** package, or Wilcoxon rank-sum test.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- mouse-benchmark-mast-det: testing with **MAST**, using detection rate as covariate.
- mouse-benchmark-mast-mean: testing with **MAST**, using mean counts as covariate.
- mouse-benchmark-mast-uninf: testing with **MAST**, using uninformative covariate.
- mouse-benchmark-scdd-det: testing with **scDD**, using detection rate as covariate.
- mouse-benchmark-scdd-mean: testing with **scDD**, using mean counts as covariate.
- mouse-benchmark-scdd-uninf: testing with **scDD**, using uninformative covariate.
- mouse-benchmark-wilcox-det: testing with Wilcoxon rank-sum, using detection rate as covariate.
- mouse-benchmark-wilcox-mean: testing with Wilcoxon rank-sum, using mean counts as covariate.
- mouse-benchmark-wilcox-uninf: testing with Wilcoxon rank-sum, using uninformative covariate.

See Also

[scrnaseq-human](#)

Examples

```
`mouse-benchmark-mast-det`(metadata = TRUE)

## Not run:
`mouse-benchmark-mast-det`()
`mouse-benchmark-mast-mean`()
`mouse-benchmark-mast-uninf`()
`mouse-benchmark-scdd-det`()
`mouse-benchmark-scdd-mean`()
`mouse-benchmark-scdd-uninf`()
`mouse-benchmark-wilcox-det`()
`mouse-benchmark-wilcox-mean`()
`mouse-benchmark-wilcox-uninf`()

## End(Not run)
```

```
sims-informative-cosine
```

Simulation study results (cosine covariate)

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with ‘cosine’ informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with standard Gaussian, t_5 , t_{11} , and χ_4 distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```
`informative-cosine-benchmark-gaussian`(metadata = TRUE)

## Not run:
`informative-cosine-benchmark-gaussian`()
`informative-cosine-benchmark-t11`()
`informative-cosine-benchmark-t5`()
`informative-cosine-benchmark-chisq4`()

res <- `informative-cosine-benchmark-chisq4`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

```
sims-informative-cubic
```

Simulation study results (cubic covariate)

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with ‘cubic’ informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with standard Gaussian, t_5 , t_{11} , and χ_4 distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```
`informative-cubic-benchmark-gaussian`(metadata = TRUE)

## Not run:
`informative-cubic-benchmark-gaussian`()
`informative-cubic-benchmark-t11`()
`informative-cubic-benchmark-t5`()
`informative-cubic-benchmark-chisq4`()

res <- `informative-cubic-benchmark-chisq4`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-informative-sine *Simulation study results (sine covariate)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with 'sine' informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with standard Gaussian, t_5 , t_{11} , and χ_4 distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```
`informative-sine-benchmark-gaussian`(metadata = TRUE)

## Not run:
`informative-sine-benchmark-gaussian`()
`informative-sine-benchmark-t11`()
`informative-sine-benchmark-t5`()
`informative-sine-benchmark-chisq4`()

res <- `informative-sine-benchmark-chisq4`()
```

```

res[[1]]$informative
res[[1]]$uninformative

## End(Not run)

```

sims-informative-step *Simulation study results (step covariate)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with ‘step’ informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with standard Gaussian, t_5 , t_{11} , and χ_4 distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```

`informative-step-benchmark-gaussian`(metadata = TRUE)

## Not run:
`informative-step-benchmark-gaussian`()
`informative-step-benchmark-t11`()
`informative-step-benchmark-t5`()
`informative-step-benchmark-chisq4`()

res <- `informative-step-benchmark-chisq4`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)

```

sims-null

*Simulation study results (null settings)***Description**

Results for null simulations used in Korthauer and Kimes et al. (2019) stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with standard Gaussian, t_5 , t_{11} , and χ_4 distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```
`null-benchmark-gaussian`(metadata = TRUE)

## Not run:
`null-benchmark-gaussian`()
`null-benchmark-t11`()
`null-benchmark-t5`()
`null-benchmark-chisq4`()

res <- `null-benchmark-chisq4`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-uasettings

*Simulation study results (unimodal, Gaussian-distributed)***Description**

Results for simulations used in Korthauer and Kimes et al. (2019) with 'unimodal' series of effect size distributions (Stephens, 2017) with standard Gaussian distributed test statistics, and 'cubic' informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. In each simulation, 10% of tests were non-null, i.e. had non-zero effect sizes. Simulations were performed with 'bimodal', 'flat top', 'skew' and 'spiky' effect size distributions (see corresponding reference for details).

In [sims-uasettings-t](#) and [sims-uasettings-25](#), similar settings were considered, but with t_{11} distributed test statistics and 25% of tests being non-null, respectively.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

References

- Stephens, M. (2017). False discovery rates: a new deal. *Biostatistics*, 18(2), 275-294.

See Also

[sims-uasettings-t](#), [sims-uasettings-25](#)

Examples

```
`uasettings-benchmark-bimodal`(metadata = TRUE)

## Not run:
`uasettings-benchmark-bimodal`()
`uasettings-benchmark-flattop`()
`uasettings-benchmark-skew`()
`uasettings-benchmark-spiky`()

res <- `uasettings-benchmark-spiky`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-uasettings-25 *Simulation study results (unimodal, 25% non-null)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with 'unimodal' series of effect size distributions (Stephens, 2017) with standard Gaussian distributed test statistics, and 'cubic' informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. In each simulation, 25% of tests were non-null, i.e. had non-zero effect sizes. Simulations were performed with 'bimodal', 'flat top', 'skew' and 'spiky' effect size distributions (see corresponding reference for details).

In [sims-uasettings](#), similar settings were considered, but with 10% of tests being non-null.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

References

- Stephens, M. (2017). False discovery rates: a new deal. *Biostatistics*, 18(2), 275-294.

See Also

[sims-uasettings](#)

Examples

```
`uasettings-25-benchmark-bimodal`(metadata = TRUE)

## Not run:
`uasettings-25-benchmark-bimodal`()
`uasettings-25-benchmark-flattop`()
`uasettings-25-benchmark-skew`()
`uasettings-25-benchmark-spiky`()

res <- `uasettings-25-benchmark-spiky`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-uasettings-t *Simulation study results (unimodal, t-distributed)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) with 'unimodal' series of effect size distributions (Stephens, 2017) with t_{11} distributed test statistics, and 'cubic' informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. In each simulation, 10% of tests were non-null, i.e. had non-zero effect sizes. Simulations were performed with 'bimodal', 'flat top', 'skew' and 'spiky' effect size distributions (see corresponding reference for details).

In [sims-uasettings](#) and [sims-uasettings-25](#), similar settings were considered, but with standard Gaussian distributed test statistics and 25% of tests being non-null, respectively.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

References

- Stephens, M. (2017). False discovery rates: a new deal. *Biostatistics*, 18(2), 275-294.

See Also

[sims-uasettings](#), [sims-uasettings-25](#)

Examples

```
`uasettings-t-benchmark-bimodal`(metadata = TRUE)

## Not run:
`uasettings-t-benchmark-bimodal`()
`uasettings-t-benchmark-flattop`()
`uasettings-t-benchmark-skew`()
`uasettings-t-benchmark-spiky`()

res <- `uasettings-t-benchmark-spiky`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-varyinginfo-discrete

Simulation study results (varying information, discrete)

Description

Results for simulations used in Korthauer and Kimes et al. (2019) across varying covariate informativeness, using standard Gaussian distributed test statistics, and informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. An informative covariate with tunable informativeness was defined with a rough informativeness parameter, delta, defined between 0 and 100. Simulations were performed with delta values of 0, 20, 40, 60, 80, and 100. The conditional probability of a test being null was defined by a discrete, non-smooth, function of the informative covariate.

In [sims-varyinginfo-smooth](#), similar settings were considered, but using a smooth relationship between the condition probability of a test being null and the informative covariate.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

See Also

[sims-varyinginfo-smooth](#)

Examples

```
`varyinginfo-discrete-benchmark-level100`(metadata = TRUE)

## Not run:
`varyinginfo-discrete-benchmark-level100`()
`varyinginfo-discrete-benchmark-level120`()
`varyinginfo-discrete-benchmark-level140`()
`varyinginfo-discrete-benchmark-level160`()
`varyinginfo-discrete-benchmark-level180`()
`varyinginfo-discrete-benchmark-level1100`()

res <- `varyinginfo-discrete-benchmark-level1100`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-varyinginfo-smooth

Simulation study results (varying information, smooth)

Description

Results for simulations used in Korthauer and Kimes et al. (2019) across varying covariate informativeness, using standard Gaussian distributed test statistics, and informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. An informative covariate with tunable informativeness was defined with a rough informativeness parameter, delta, defined between 0 and 100. Simulations were performed with delta values of 0, 20, 40, 60, 80, and 100. The conditional probability of a test being null was defined by a smooth function of the informative covariate.

In [sims-varyinginfo-discrete](#), similar settings were considered, but using a discrete, non-smooth, relationship between the condition probability of a test being null and the informative covariate.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

See Also

[sims-varyinginfo-discrete](#)

Examples

```
`varyinginfo-smooth-benchmark-level100`(metadata = TRUE)

## Not run:
`varyinginfo-smooth-benchmark-level100`()
`varyinginfo-smooth-benchmark-level120`()
`varyinginfo-smooth-benchmark-level140`()
`varyinginfo-smooth-benchmark-level160`()
`varyinginfo-smooth-benchmark-level180`()
`varyinginfo-smooth-benchmark-level100`()

res <- `varyinginfo-smooth-benchmark-level100`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)
```

sims-varyingntests *Simulation study results (varying number of tests)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) across varying number of hypotheses tested, using standard Gaussian distributed test statistics, and 'sine' informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with 100, 500, 1000, 5000, 10000, and 50000 tests.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as "informative" and "uninformative", respectively.

Examples

```

`varyingntests-benchmark-n100`(metadata = TRUE)

## Not run:
`varyingntests-benchmark-n100`()
`varyingntests-benchmark-n500`()
`varyingntests-benchmark-n1000`()
`varyingntests-benchmark-n5000`()
`varyingntests-benchmark-n10000`()
`varyingntests-benchmark-n50000`()

res <- `varyingntests-benchmark-n100`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)

```

sims-varyingpi0	<i>Simulation study results (varying null proportion, Gaussian-distributed)</i>
-----------------	---

Description

Results for simulations used in Korthauer and Kimes et al. (2019) across varying null proportion of hypotheses with 20000 tests, standard Gaussian distributed test statistics, and ‘sine’ informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, and 99% null tests.

In [sims-varyingpi0-t](#), similar settings were considered, but t_{11} distributed test statistics.

Arguments

metadata	logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)
----------	---

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as “informative” and “uninformative”, respectively.

See Also

[sims-varyingpi0-t](#)

Examples

```

`varyingpi0-benchmark-nullprop05`(metadata = TRUE)

## Not run:
`varyingpi0-benchmark-nullprop05`()

```

```

`varyingpi0-benchmark-nullprop10`()
`varyingpi0-benchmark-nullprop20`()
`varyingpi0-benchmark-nullprop30`()
`varyingpi0-benchmark-nullprop40`()
`varyingpi0-benchmark-nullprop50`()
`varyingpi0-benchmark-nullprop60`()
`varyingpi0-benchmark-nullprop70`()
`varyingpi0-benchmark-nullprop80`()
`varyingpi0-benchmark-nullprop90`()
`varyingpi0-benchmark-nullprop95`()
`varyingpi0-benchmark-nullprop99`()

res <- `varyingpi0-benchmark-nullprop99`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)

```

sims-varyingpi0-t *Simulation study results (varying null proportion, t-distributed)*

Description

Results for simulations used in Korthauer and Kimes et al. (2019) across varying null proportion of hypotheses with 20000 tests, t_{11} distributed test statistics, and ‘sine’ informative and paired uninformative covariates stored as a list of SummarizedBenchmark objects from 100 replications. Simulations were performed with 5%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, 95%, and 99% null tests.

In [sims-varyingpi0](#), similar settings were considered, but standard Gaussian distributed test statistics.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

The object is a list of length 100 corresponding to the 100 replications. Each entry in the list is a named list of two SummarizedBenchmark objects. The results based on using an informative and uninformative covariate are stored as “informative” and “uninformative”, respectively.

See Also

[sims-varyingpi0](#)

Examples

```

`varyingpi0-t-benchmark-nullprop05`(metadata = TRUE)

## Not run:
`varyingpi0-t-benchmark-nullprop05`()

```

```

`varyingpi0-t-benchmark-nullprop10`()
`varyingpi0-t-benchmark-nullprop20`()
`varyingpi0-t-benchmark-nullprop30`()
`varyingpi0-t-benchmark-nullprop40`()
`varyingpi0-t-benchmark-nullprop50`()
`varyingpi0-t-benchmark-nullprop60`()
`varyingpi0-t-benchmark-nullprop70`()
`varyingpi0-t-benchmark-nullprop80`()
`varyingpi0-t-benchmark-nullprop90`()
`varyingpi0-t-benchmark-nullprop95`()
`varyingpi0-t-benchmark-nullprop99`()

res <- `varyingpi0-t-benchmark-nullprop99`()
res[[1]]$informative
res[[1]]$uninformative

## End(Not run)

```

yeast-*insilico*
Yeast in silico dataset results

Description

Results for differential gene expression analysis using *in silico* (computationally) spiked-in data generated from yeast data obtained from Schurch et al. (2016) as described in Korthauer and Kimes et al. (2019). Differential expression was tested using **DESeq2**.

Arguments

metadata logical whether to load metadata (TRUE) or full resource (FALSE). (default = FALSE)

Details

Results for this case study include:

- yeast-results-null15: null 5 vs. 5 comparison.
- yeast-results-de5: using unimodal alternative, 2000 DE genes, strong informative covariate, 5 vs. 5 comparison.
- yeastH-results-de5: using unimodal alternative, 500 DE genes, strong informative covariate, 5 vs. 5 comparison.
- yeastII-results-de5: using bimodal alternative, 2000 DE genes, strong informative covariate, 5 vs. 5 comparison.
- yeastIIH-results-de5: using bimodal alternative, 500 DE genes, strong informative covariate, 5 vs. 5 comparison.
- yeastW-results-de5: using unimodal alternative, 2000 DE genes, weak informative covariate, 5 vs. 5 comparison.
- yeastHW-results-de5: using unimodal alternative, 500 DE genes, weak informative covariate, 5 vs. 5 comparison.

- yeastIIW-results-de5: using bimodal alternative, 2000 DE genes, weak informative covariate, 5 vs. 5 comparison.
- yeastIIHW-results-de5: using bimodal alternative, 500 DE genes, weak informative covariate, 5 vs. 5 comparison.
- yeast-results-de5-uninfCov: using unimodal alternative, 2000 DE genes, uninformative covariate, 5 vs. 5 comparison.
- yeastH-results-de5-uninfCov: using unimodal alternative, 500 DE genes, uninformative covariate, 5 vs. 5 comparison.
- yeastII-results-de5-uninfCov: using bimodal alternative, 2000 DE genes, uninformative covariate, 5 vs. 5 comparison.
- yeastIIH-results-de5-uninfCov: using bimodal alternative, 500 DE genes, uninformative covariate, 5 vs. 5 comparison.
- yeast-results-null10: null 10 vs. 10 comparison.
- yeast-results-de10: using unimodal alternative, 2000 DE genes, strong informative covariate, 10 vs. 10 comparison.
- yeastH-results-de10: using unimodal alternative, 500 DE genes, strong informative covariate, 10 vs. 10 comparison.
- yeastII-results-de10: using bimodal alternative, 2000 DE genes, strong informative covariate, 10 vs. 10 comparison.
- yeastIIH-results-de10: using bimodal alternative, 500 DE genes, strong informative covariate, 10 vs. 10 comparison.
- yeastW-results-de10: using unimodal alternative, 2000 DE genes, weak informative covariate, 10 vs. 10 comparison.
- yeastHW-results-de10: using unimodal alternative, 500 DE genes, weak informative covariate, 10 vs. 10 comparison.
- yeastIIW-results-de10: using bimodal alternative, 2000 DE genes, weak informative covariate, 10 vs. 10 comparison.
- yeastIIHW-results-de10: using bimodal alternative, 500 DE genes, weak informative covariate, 10 vs. 10 comparison.
- yeast-results-de10-uninfCov: using unimodal alternative, 2000 DE genes, uninformative covariate, 10 vs. 10 comparison.
- yeastH-results-de10-uninfCov: using unimodal alternative, 500 DE genes, uninformative covariate, 10 vs. 10 comparison.
- yeastII-results-de10-uninfCov: using bimodal alternative, 2000 DE genes, uninformative covariate, 10 vs. 10 comparison.
- yeastIIH-results-de10-uninfCov: using bimodal alternative, 500 DE genes, uninformative covariate, 10 vs. 10 comparison.

References

- Schurch, N. J. et al. (2016). How many biological replicates are needed in an RNA-seq experiment and which differential expression tool should you use?. *RNA*, 22(6), 839-851.

See Also

[polyester-insilico](#)

Examples

```
`yeast-results-de5`(metadata = TRUE)

## Not run:
`yeast-results-de5`()
`yeast-results-de5-uninfCov`()
`yeast-results-de10`()
`yeast-results-de10-uninfCov`()
`yeast-results-null5`()
`yeast-results-null10`()
`yeastH-results-de5`()
`yeastH-results-de5-uninfCov`()
`yeastH-results-de10`()
`yeastH-results-de10-uninfCov`()
`yeastHW-results-de5`()
`yeastHW-results-de10`()
`yeastII-results-de5`()
`yeastII-results-de5-uninfCov`()
`yeastII-results-de10`()
`yeastII-results-de10-uninfCov`()
`yeastIIH-results-de5`()
`yeastIIH-results-de5-uninfCov`()
`yeastIIH-results-de10`()
`yeastIIH-results-de10-uninfCov`()
`yeastIIHW-results-de5`()
`yeastIIHW-results-de10`()
`yeastIIW-results-de5`()
`yeastIIW-results-de10`()
`yeastW-results-de5`()
`yeastW-results-de10`()

## End(Not run)
```

Index

- baxter-genus-benchmark
 - (microbiome-baxter), 6
- baxter-genus-log-ubiquity-benchmark
 - (microbiome-baxter), 6
- baxter-genus-mean-abun-benchmark
 - (microbiome-baxter), 6
- baxter-genus-mean-uninf-benchmark
 - (microbiome-baxter), 6
- baxter-otus-benchmark
 - (microbiome-baxter), 6
- baxter-otus-log-ubiquity-benchmark
 - (microbiome-baxter), 6
- bmi-maf-benchmark (gwas-bmi), 5
- bmi-samplesize-benchmark (gwas-bmi), 5
- bmi-uninf-benchmark (gwas-bmi), 5
- brain-benchmark (rnaseq-brain), 12
- brain-uninf-benchmark (rnaseq-brain), 12

- cbp-csaw-benchmark (chipseq-cbp), 2
- cbp-csaw-cov-benchmark (chipseq-cbp), 2
- cbp-csaw-uninf-benchmark (chipseq-cbp), 2
- chipseq-cbp, 2
- chipseq-h3k4me3, 3

- enigma-al-otus-abun-benchmark
 - (microbiome-enigma), 7
- enigma-al-otus-benchmark
 - (microbiome-enigma), 7
- enigma-al-otus-uninf-benchmark
 - (microbiome-enigma), 7
- enigma-ph-otus-abun-benchmark
 - (microbiome-enigma), 7
- enigma-ph-otus-benchmark
 - (microbiome-enigma), 7
- enigma-ph-otus-uninf-benchmark
 - (microbiome-enigma), 7
- enigma-so4-otus-abun-benchmark
 - (microbiome-enigma), 7
- enigma-so4-otus-benchmark
 - (microbiome-enigma), 7
- enigma-so4-otus-uninf-benchmark
 - (microbiome-enigma), 7

- goodrich-genus-abun-benchmark
 - (microbiome-goodrich), 8
- goodrich-genus-benchmark
 - (microbiome-goodrich), 8
- goodrich-genus-uninf-benchmark
 - (microbiome-goodrich), 8
- goodrich-otus-benchmark
 - (microbiome-goodrich), 8
- gsa-human, 4
- gsa-mouse, 4
- gwas-bmi, 5

- h3k4me3-csaw-benchmark
 - (chipseq-h3k4me3), 3
- h3k4me3-csaw-cov-benchmark
 - (chipseq-h3k4me3), 3
- h3k4me3-csaw-uninf-benchmark
 - (chipseq-h3k4me3), 3
- h3k4me3-promoters-benchmark
 - (chipseq-h3k4me3), 3
- human-benchmark (gsa-human), 4
- human-benchmark-mast-det
 - (scrnaseq-human), 13
- human-benchmark-mast-mean
 - (scrnaseq-human), 13
- human-benchmark-mast-uninf
 - (scrnaseq-human), 13
- human-benchmark-scdd-det
 - (scrnaseq-human), 13
- human-benchmark-scdd-mean
 - (scrnaseq-human), 13
- human-benchmark-scdd-uninf
 - (scrnaseq-human), 13
- human-benchmark-wilcox-det
 - (scrnaseq-human), 13
- human-benchmark-wilcox-mean
 - (scrnaseq-human), 13
- human-benchmark-wilcox-uninf
 - (scrnaseq-human), 13
- human-uninf-benchmark (gsa-human), 4

- informative-cosine-benchmark-chisq4
 - (sims-informative-cosine), 16

- informative-cosine-benchmark-gaussian
(sims-informative-cosine), 16
- informative-cosine-benchmark-t11
(sims-informative-cosine), 16
- informative-cosine-benchmark-t5
(sims-informative-cosine), 16
- informative-cubic-benchmark-chisq4
(sims-informative-cubic), 16
- informative-cubic-benchmark-gaussian
(sims-informative-cubic), 16
- informative-cubic-benchmark-t11
(sims-informative-cubic), 16
- informative-cubic-benchmark-t5
(sims-informative-cubic), 16
- informative-sine-benchmark-chisq4
(sims-informative-sine), 17
- informative-sine-benchmark-gaussian
(sims-informative-sine), 17
- informative-sine-benchmark-t11
(sims-informative-sine), 17
- informative-sine-benchmark-t5
(sims-informative-sine), 17
- informative-step-benchmark-chisq4
(sims-informative-step), 18
- informative-step-benchmark-gaussian
(sims-informative-step), 18
- informative-step-benchmark-t11
(sims-informative-step), 18
- informative-step-benchmark-t5
(sims-informative-step), 18

- microbiome-baxter, 6
- microbiome-enigma, 7
- microbiome-goodrich, 8
- microbiome-papa, 9
- microbiome-schubert, 10
- mir200c-benchmark (rnaseq-mir200c), 13
- mir200c-uninf-benchmark
(rnaseq-mir200c), 13
- mouse-benchmark (gsa-mouse), 4
- mouse-benchmark-mast-det
(scrnaseq-mouse), 14
- mouse-benchmark-mast-mean
(scrnaseq-mouse), 14
- mouse-benchmark-mast-uninf
(scrnaseq-mouse), 14
- mouse-benchmark-scdd-det
(scrnaseq-mouse), 14
- mouse-benchmark-scdd-mean
(scrnaseq-mouse), 14
- mouse-benchmark-scdd-uninf
(scrnaseq-mouse), 14

- mouse-benchmark-wilcox-det
(scrnaseq-mouse), 14
- mouse-benchmark-wilcox-mean
(scrnaseq-mouse), 14
- mouse-benchmark-wilcox-uninf
(scrnaseq-mouse), 14
- mouse-uninf-benchmark (gsa-mouse), 4

- null-benchmark-chisq4 (sims-null), 19
- null-benchmark-gaussian (sims-null), 19
- null-benchmark-t11 (sims-null), 19
- null-benchmark-t5 (sims-null), 19

- papa-genus-abun-benchmark
(microbiome-papa), 9
- papa-genus-benchmark (microbiome-papa),
9
- papa-genus-log-ubiquity-benchmark
(microbiome-papa), 9
- papa-genus-uninf-benchmark
(microbiome-papa), 9
- papa-otus-benchmark (microbiome-papa), 9
- polyester-insilico, 11
- polyester-results-de10
(polyester-insilico), 11
- polyester-results-de10-uninfCov
(polyester-insilico), 11
- polyester-results-de5
(polyester-insilico), 11
- polyester-results-de5-uninfCov
(polyester-insilico), 11
- polyester-results-null10
(polyester-insilico), 11
- polyester-results-null5
(polyester-insilico), 11
- polyesterW-results-de10
(polyester-insilico), 11
- polyesterW-results-de5
(polyester-insilico), 11

- rnaseq-brain, 12
- rnaseq-mir200c, 13

- schubert-otus-abun-benchmark
(microbiome-schubert), 10
- schubert-otus-benchmark
(microbiome-schubert), 10
- schubert-otus-uninf-benchmark
(microbiome-schubert), 10
- scrnaseq-human, 13
- scrnaseq-mouse, 14
- sims-informative-cosine, 16
- sims-informative-cubic, 16

- sims-informative-sine, 17
- sims-informative-step, 18
- sims-null, 19
- sims-uasettings, 19
- sims-uasettings-25, 20
- sims-uasettings-t, 21
- sims-varyinginfo-discrete, 22
- sims-varyinginfo-smooth, 23
- sims-varyingntests, 24
- sims-varyingpi0, 25
- sims-varyingpi0-t, 26

- uasettings-25-benchmark-bimodal
(sims-uasettings-25), 20
- uasettings-25-benchmark-flattop
(sims-uasettings-25), 20
- uasettings-25-benchmark-skew
(sims-uasettings-25), 20
- uasettings-25-benchmark-spiky
(sims-uasettings-25), 20
- uasettings-benchmark-bimodal
(sims-uasettings), 19
- uasettings-benchmark-flattop
(sims-uasettings), 19
- uasettings-benchmark-skew
(sims-uasettings), 19
- uasettings-benchmark-spiky
(sims-uasettings), 19
- uasettings-t-benchmark-bimodal
(sims-uasettings-t), 21
- uasettings-t-benchmark-flattop
(sims-uasettings-t), 21
- uasettings-t-benchmark-skew
(sims-uasettings-t), 21
- uasettings-t-benchmark-spiky
(sims-uasettings-t), 21

- varyinginfo-discrete-benchmark-level100
(sims-varyinginfo-discrete), 22
- varyinginfo-discrete-benchmark-level1100
(sims-varyinginfo-discrete), 22
- varyinginfo-discrete-benchmark-level120
(sims-varyinginfo-discrete), 22
- varyinginfo-discrete-benchmark-level140
(sims-varyinginfo-discrete), 22
- varyinginfo-discrete-benchmark-level160
(sims-varyinginfo-discrete), 22
- varyinginfo-discrete-benchmark-level180
(sims-varyinginfo-discrete), 22
- varyinginfo-smooth-benchmark-level100
(sims-varyinginfo-smooth), 23
- varyinginfo-smooth-benchmark-level1100
(sims-varyinginfo-smooth), 23

- varyinginfo-smooth-benchmark-level120
(sims-varyinginfo-smooth), 23
- varyinginfo-smooth-benchmark-level40
(sims-varyinginfo-smooth), 23
- varyinginfo-smooth-benchmark-level60
(sims-varyinginfo-smooth), 23
- varyinginfo-smooth-benchmark-level80
(sims-varyinginfo-smooth), 23
- varyingntests-benchmark-n100
(sims-varyingntests), 24
- varyingntests-benchmark-n1000
(sims-varyingntests), 24
- varyingntests-benchmark-n10000
(sims-varyingntests), 24
- varyingntests-benchmark-n500
(sims-varyingntests), 24
- varyingntests-benchmark-n5000
(sims-varyingntests), 24
- varyingntests-benchmark-n50000
(sims-varyingntests), 24
- varyingpi0-benchmark-nullprop05
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop10
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop20
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop30
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop40
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop50
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop60
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop70
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop80
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop90
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop95
(sims-varyingpi0), 25
- varyingpi0-benchmark-nullprop99
(sims-varyingpi0), 25
- varyingpi0-t-benchmark-nullprop05
(sims-varyingpi0-t), 26
- varyingpi0-t-benchmark-nullprop10
(sims-varyingpi0-t), 26
- varyingpi0-t-benchmark-nullprop20
(sims-varyingpi0-t), 26
- varyingpi0-t-benchmark-nullprop30
(sims-varyingpi0-t), 26

- varyingpi0-t-benchmark-nullprop40
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop50
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop60
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop70
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop80
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop90
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop95
(sims-varyingpi0-t), [26](#)
- varyingpi0-t-benchmark-nullprop99
(sims-varyingpi0-t), [26](#)

- yeast-insilico, [27](#)
- yeast-results-de10 (yeast-insilico), [27](#)
- yeast-results-de10-uninfCov
(yeast-insilico), [27](#)
- yeast-results-de5 (yeast-insilico), [27](#)
- yeast-results-de5-uninfCov
(yeast-insilico), [27](#)
- yeast-results-null10 (yeast-insilico),
[27](#)
- yeast-results-null15 (yeast-insilico), [27](#)
- yeastH-results-de10 (yeast-insilico), [27](#)
- yeastH-results-de10-uninfCov
(yeast-insilico), [27](#)
- yeastH-results-de5 (yeast-insilico), [27](#)
- yeastH-results-de5-uninfCov
(yeast-insilico), [27](#)
- yeastHW-results-de10 (yeast-insilico),
[27](#)
- yeastHW-results-de5 (yeast-insilico), [27](#)
- yeastII-results-de10 (yeast-insilico),
[27](#)
- yeastII-results-de10-uninfCov
(yeast-insilico), [27](#)
- yeastII-results-de5 (yeast-insilico), [27](#)
- yeastII-results-de5-uninfCov
(yeast-insilico), [27](#)
- yeastIIH-results-de10 (yeast-insilico),
[27](#)
- yeastIIH-results-de10-uninfCov
(yeast-insilico), [27](#)
- yeastIIH-results-de5 (yeast-insilico),
[27](#)
- yeastIIH-results-de5-uninfCov
(yeast-insilico), [27](#)
- yeastIIHW-results-de10
(yeast-insilico), [27](#)
- yeastIIHW-results-de5 (yeast-insilico),
[27](#)
- yeastIIW-results-de10 (yeast-insilico), [27](#)
- yeastIIW-results-de5 (yeast-insilico),
[27](#)
- yeastW-results-de10 (yeast-insilico), [27](#)
- yeastW-results-de5 (yeast-insilico), [27](#)