Package 'BHC'

March 25, 2024

Type Package

Title Bayesian Hierarchical Clustering

Version 1.54.0

Date 2011-09-07

Author Rich Savage, Emma Cooke, Robert Darkins, Yang Xu

Maintainer Rich Savage <r.s.savage@warwick.ac.uk>

Description The method performs bottom-up hierarchical clustering, using a Dirichlet Process (infinite mixture) to model uncertainty in the data and Bayesian model selection to decide at each step which clusters to merge. This avoids several limitations of traditional methods, for example how many clusters there should be and how to choose a principled distance metric. This implementation accepts multinomial (i.e. discrete, with 2+ categories) or time-series data. This version also includes a randomised algorithm which is more efficient for larger data sets.

License GPL-3

biocViews Microarray, Clustering

git_url https://git.bioconductor.org/packages/BHC

git_branch RELEASE_3_18

git_last_commit 79f82ca

git_last_commit_date 2023-10-24

Repository Bioconductor 3.18

Date/Publication 2024-03-25

R topics documented:

5

Index

Function to perform Bayesian Hierarchical Clustering on a 2D array of discretised (i.e. multinomial) data

Description

bhc

The method performs bottom-up hierarchical clustering, using a Dirichlet Process (infinite mixture) to model uncertainty in the data and Bayesian model selection to decide at each step which clusters to merge. This avoids several limitations of traditional methods, for example how many clusters there should be and how to choose a principled distance metric. This implementation accepts multinomial (i.e. discrete, with 2+ categories) or time-series data. This version also includes a randomised algorithm which is more efficient for larger data sets.

Usage

Arguments

data	A 2D array containing discretised data. The dimensions of data should be nDataItems \star nFeatures, and the algorithm will cluster the data items.
itemLabels	A character array containing nDataItems entries, one for each data item in the analysis. The leaf nodes of the output dendrogram will be labelled with these labels.
nFeatureValues	Deprecated. This is a legacy argument, retained for backwards compatibility. Any value passed to it will have no effect.
timePoints	An array of length nFeatures, containing the time points of the measurements.
data⊤ype	A string specifying the data type. Either ``multinomial'', ``time-course'', or ``cubicspline''.
noise	Noise term for each gene, required only if noiseMode=2. The noise term for each gene is calculated as
	\sum (residuals ²)
	$\overline{(\text{number of observations for gene} - 1)(\text{number of replicates})}$
	where (number of observations for gene) is typically (number of time points * number of replicates).
numReps	Number of replicates per observation.
noiseMode	Noise mode. If 0 then fitted noise; 2 estimated noise from replicates.
robust	0 to use single Gaussian likelihood, 1 to use mixture likelihood.
numThroado	
nummeaus	The BHC library has been parallelised using OpenMP (currently on UN*X systems only). Specify here the number of threads to use (the default value is 1).
randomised	The BHC library has been parallelised using OpenMP (currently on UN*X systems only). Specify here the number of threads to use (the default value is 1). Set to TRUE if you wish to use the randomised algorithm.
randomised m	The BHC library has been parallelised using OpenMP (currently on UN*X sys- tems only). Specify here the number of threads to use (the default value is 1). Set to TRUE if you wish to use the randomised algorithm. If randomised is set to TRUE, then this is the dimension of the randomly chosen subset D_m in the randomised algorithm.

2

bhc

Details

Typical usage for the multinomial case:

bhc(data, itemLabels).

To use the squared-exponential covariance:

```
bhc(data, itemLabels, 0, timePoints, "time-course",
    noise, numReps, noiseMode),
```

and the cubic spline covariance:

```
bhc(data, itemLabels, 0, timePoints, "cubicspline",
    noise, numReps, noiseMode).
```

To use the randomised algorithm, simply include the following two arguments:

```
bhc(data, itemLabels, 0, timePoints, "time-course",
    noise, numReps, noiseMode, randomised=TRUE, m=10)
```

Value

A DENDROGRAM object (see the R stats package for details).

Author(s)

Rich Savage, Emma Cooke, Robert Darkins, and Yang Xu

References

Bayesian Hierarchical Clustering, Heller + Ghahramani, Gatsby Unit Technical Report GCNU-TR 2005-002 (2005); also see shorter version in ICML-2005; *R/BHC:fast Bayesian hierarchical clustering for microarray data*, Savage et al, BMC Bioinformatics 10:242 (2009); *Bayesian hierarchical clustering for microarray time series data with replicates and outlier measurements*, Cooke et al, currently under review

See Also

hclust

Examples

bhc

```
##DATA DIMENSIONS
nDataItems <- nrow(data)</pre>
nFeatures <- ncol(data)</pre>
##RUN MULTINOMIAL CLUSTERING
hc1 <- bhc(data, itemLabels, verbose=TRUE)</pre>
plot(hc1, axes=FALSE)
##RUN TIME-COURSE CLUSTERING
hc2 <- bhc(data, itemLabels, 0, timePoints, "time-course",</pre>
          numReps=1, noiseMode=0, numThreads=2, verbose=TRUE)
plot(hc2, axes=FALSE)
##OUTPUT CLUSTER LABELS TO FILE
WriteOutClusterLabels(hc1, "labels.txt", verbose=TRUE)
##FOR THE MULTINOMIAL CASE, THE DATA CAN BE DISCRETISED
newData
            <- data[] + rnorm(150, 0, 0.1);
percentiles <- FindOptimalBinning(newData, itemLabels, transposeData=TRUE, verbose=TRUE)</pre>
discreteData <- DiscretiseData(t(newData), percentiles=percentiles)</pre>
discreteData <- t(discreteData)</pre>
             <- bhc(discreteData, itemLabels, verbose=TRUE)
hc3
plot(hc3, axes=FALSE)
```

4

Index

* cluster bhc, 2 bhc, 2 DiscretiseData(bhc), 2 FindOptimalBinning(bhc), 2 hclust, 3

WriteOutClusterLabels(bhc), 2