

# Package ‘PWMEnrich.Hsapiens.background’

March 28, 2024

**Maintainer** Diego Diez <diego10ruiz@gmail.com>

**License** GPL-3

**Title** H. sapiens background for PWMEnrich

**Type** Package

**LazyLoad** yes

**Author** Robert Stojnic

**Description** PWMEnrich pre-compiled background objects for H. sapiens (human) and MotifDb H. sapiens motifs.

**Version** 4.36.0

**biocViews** Homo\_sapiens\_Data, CGHData

**Date** 2015-09-30

**Depends** R (>= 2.10), methods, PWMEnrich

**git\_url** <https://git.bioconductor.org/packages/PWMEnrich.Hsapiens.background>

**git\_branch** RELEASE\_3\_18

**git\_last\_commit** 6cee4b8

**git\_last\_commit\_date** 2023-10-24

**Repository** Bioconductor 3.18

**Date/Publication** 2024-03-28

## R topics documented:

PWMEnrich.Hsapiens.background-package . . . . .	2
<b>Index</b>	<b>4</b>

---

PWMEnrich.Hsapiens.background-package

*PWMEnrich.Hsapiens.background package overview*

---

## Description

This package provides a set of pre-compiled genomic background files for the PWMEnrich package and H. sapiens (human). The backgrounds were pre-compiled using unique 2kb promoters in human.

- MotifDb.Hsap.PFM - a list of position frequency matrices (PFMs) from MotifDb
- MotifDb.Hsap - the corresponding PWMs generated by using the background frequencies of A,C,G,T in a set of 2kb human (hg19) promoters.
- PWMLogn.hg19.MotifDb.Hsap - pre-compiled threshold-free lognormal background for MotifDb human PWMs. The lognormal distribution is fitted to 500bp chunks of 2kb human (hg19) promoters.
- PWMCutoff4.hg19.MotifDb.Hsap, PWMCutoff5.hg19.MotifDb.Hsap - pre-compiled Z-score background with cutoff of 4 and 5 (base e) for MotifDb human PWMs. The number of hits is counted in 2kb human (hg19) promoters.
- PPWMPvalueCutoff1e2.hg19.MotifDb.Hsap, PPWMPvalueCutoff1e3.hg19.MotifDb.Hsap, PPWMPvalueCutoff1e4.hg19.MotifDb.Hsap - pre-compiled Z-score background with P-value cutoff of 0.01, 0.001, and 0.0001 for MotifDb human PWMs. The number of hits with smaller P-value than cutoff is counted in 2kb human (hg19) promoters.

## Usage

```
data(MotifDb.Hsap.PFM)
data(MotifDb.Hsap)
data(PWMLogn.hg19.MotifDb.Hsap)
data(PWMCutoff4.hg19.MotifDb.Hsap)
data(PWMCutoff5.hg19.MotifDb.Hsap)
data(PPWMPvalueCutoff1e2.hg19.MotifDb.Hsap)
data(PPWMPvalueCutoff1e3.hg19.MotifDb.Hsap)
data(PPWMPvalueCutoff1e4.hg19.MotifDb.Hsap)
```

## Details

All of these objects were created with the appropriate functions available in the PWMEnrich package (see Section 'See also'). We recommend using these functions to generate backgrounds for a custom set of background sequences and/or DNA motifs.

This package also contains the 2kb upstream sequences for human genes (hg19.upstream2000) which were removed from the BSgenome.Hsapiens.UCSC.hg19 package starting from Bioconductor version 3.0.

**Author(s)**

Robert Stojnic  
Cambridge Systems Biology Centre  
University of Cambridge, UK  
Maintainer: Robert Stojnic <robert.stojnic@gmail.com>

**See Also**

[makeBackground](#), [makePWMLognBackground](#), [makePWMCutoffBackground](#), [makePWMEmpiricalBackground](#).

**Examples**

```
data(PWMLogn.hg19.MotifDb.Hsap)

res = motifEnrichment(DNAString("TGCATCAAGTGTAGTGCAAGTGAGTGATGAGTAGAAGTTGAGTGAGGTAGATGC"),
  PWMLogn.hg19.MotifDb.Hsap)

groupReport(res)[1:10]
```

# Index

\* **package**  
    PWMErich.Hsapiens.background-package, [2](#)  
    PWMPvalueCutoff1e4.hg19.MotifDb.Hsap (PWMErich.Hsapiens.background-package), [2](#)

hg19.upstream2000  
    (PWMErich.Hsapiens.background-package), [2](#)

makeBackground, [3](#)  
makePWMCutoffBackground, [3](#)  
makePWMEmpiricalBackground, [3](#)  
makePWMLognBackground, [3](#)  
MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMCutoff4.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMCutoff5.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMErich.Hsapiens.background  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMErich.Hsapiens.background-package, [2](#)

PWMGEV.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMLogn.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMPvalueCutoff1e2.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)

PWMPvalueCutoff1e3.hg19.MotifDb.Hsap  
    (PWMErich.Hsapiens.background-package), [2](#)