

Package ‘gDRtestData’

March 28, 2024

Title gDRtestData - R data package with testing dose reponse data

Version 1.0.0

Date 2023-09-18

Description R package with internal dose-response test data. Package provides functions to generate input testing data that can be used as the input for gDR pipeline. It also contains RDS files with MAE data processed by gDR.

Depends R (>= 4.2)

Imports checkmate

Suggests BiocStyle, data.table, gDRstyle (>= 0.99.16), knitr, qs, reshape2, rmarkdown, SummarizedExperiment, testthat

Enhanced

biocViews ExperimentData, TechnologyData

VignetteBuilder knitr

License Artistic-2.0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/gDRtestData>

git_branch RELEASE_3_18

git_last_commit 1ad7f03

git_last_commit_date 2023-10-24

Repository Bioconductor 3.18

Date/Publication 2024-03-28

Author Aleksander Chlebowski [aut],
Bartosz Czech [aut],
Arkadiusz Gladki [cre, aut],
Marc Hafner [aut],
Marcin Kamianowski [aut],

Sergiu Mocanu [aut],
 Natalia Potocka [aut],
 Dariusz Scigocki [aut],
 Allison Young [aut]

Maintainer Arkadiusz Gladki <gladki.arkadiusz@gmail.com>

R topics documented:

| | |
|---------------------------------------|---|
| gDRtestData-package | 2 |
| add_concentration | 3 |
| add_data_replicates | 4 |
| add_day0_data | 4 |
| cell_lines | 5 |
| create_synthetic_cell_lines | 5 |
| create_synthetic_drugs | 6 |
| drugs | 6 |
| generate_ec50 | 7 |
| generate_e_inf | 7 |
| generate_hill_coef | 8 |
| generate_response_data | 8 |
| get_test_dataset_paths | 9 |

| | |
|--------------|-----------|
| Index | 10 |
|--------------|-----------|

| | |
|---------------------|----------------------------------------------------------------------------------|
| gDRtestData-package | <i>gDRtestData: gDRtestData - R data package with testing dose response data</i> |
|---------------------|----------------------------------------------------------------------------------|

Description

R package with internal dose-response test data. Package provides functions to generate input testing data that can be used as the input for gDR pipeline. It also contains RDS files with MAE data processed by gDR.

Value

package help page

Note

To learn more about functions start with `help(package = "gDRtestData")`

Author(s)

Maintainer: Arkadiusz Gladki <gladki.arkadiusz@gmail.com>

Authors:

- Aleksander Chlebowski
- Bartosz Czech
- Marc Hafner
- Marcin Kamianowski
- Sergiu Mocanu
- Natalia Potocka
- Dariusz Scigocki
- Allison Voung

| | |
|-------------------|---------------------------|
| add_concentration | <i>Add concentrations</i> |
|-------------------|---------------------------|

Description

Add concentrations

Usage

```
add_concentration(df_layout, concentrations = 10^(seq(-3, 1, 0.5)))
```

Arguments

`df_layout` data.table that should contains the cell line, drug, concentration, and replicate columns along with the annotations that needs to be propagated

`concentrations` vector of numeric concentrations that will be added to `df_layout`

Value

data.table with concentrations

Examples

```
cell_lines <- create_synthetic_cell_lines()
add_concentration(cell_lines)
```

add_data_replicates *Add data replicates*

Description

Add data replicates

Usage

```
add_data_replicates(df_layout)
```

Arguments

df_layout data.table that should contains the cell line, drug, concentration, and replicate columns along with the annotations that needs to be propagated

Value

data.table with replicates

Examples

```
cell_lines <- create_synthetic_cell_lines()
add_data_replicates(cell_lines)
```

add_day0_data *Add data with day 0*

Description

Add data with day 0

Usage

```
add_day0_data(df_merged, noise_level = 0.05)
```

Arguments

df_merged data.table with merged data
noise_level numeric scalar with the level of noise added to the data

Value

data.table with day0 data

Examples

```
cell_lines <- create_synthetic_cell_lines()
drugs <- create_synthetic_drugs()
data <- gDRtestData::prepareData(cell_lines[seq_len(2), ], drugs[seq_len(4), ])
data$Duration <- 72
data$ReadoutValue <- 0
add_day0_data(data)
```

| | |
|------------|-------------------|
| cell_lines | <i>Cell lines</i> |
|------------|-------------------|

Description

Cell lines

Value

data.table

Examples

```
path <- system.file("annotation_data", "cell_lines.csv", package = "gDRtestData")
data.table::fread(file = path)
```

| | |
|-----------------------------|----------------------------------------------------|
| create_synthetic_cell_lines | <i>Create data.table with synthetic cell lines</i> |
|-----------------------------|----------------------------------------------------|

Description

Create data.table with synthetic cell lines

Usage

```
create_synthetic_cell_lines()
```

Value

data.table with synthetic cell lines

Examples

```
create_synthetic_cell_lines()
```

`create_synthetic_drugs`*Create data.table with synthetic drugs*

Description

Create data.table with synthetic drugs

Usage

```
create_synthetic_drugs()
```

Value

data.table with synthetic drugs

Examples

```
create_synthetic_drugs()
```

`drugs`*Drugs*

Description

Drugs

Value

data.table

Examples

```
path <- system.file("annotation_data", "drugs.csv", package = "gDRtestData")
data.table::fread(file = path)
```

| | |
|---------------|------------------------------|
| generate_ec50 | <i>Calculate EC50 metric</i> |
|---------------|------------------------------|

Description

Calculate EC50 metric

Usage

```
generate_ec50(drugs, cell_lines)
```

Arguments

| | |
|------------|----------------------------|
| drugs | data.table with drugs |
| cell_lines | data.table with cell lines |

Value

matrix with random EC50

Examples

```
generate_ec50(create_synthetic_drugs(), create_synthetic_cell_lines())
```

| | |
|----------------|-------------------------------|
| generate_e_inf | <i>Calculate E inf metric</i> |
|----------------|-------------------------------|

Description

Calculate E inf metric

Usage

```
generate_e_inf(drugs, cell_lines)
```

Arguments

| | |
|------------|----------------------------|
| drugs | data.table with drugs |
| cell_lines | data.table with cell lines |

Value

matrix with random E inf

Examples

```
generate_e_inf(create_synthetic_drugs(), create_synthetic_cell_lines())
```

```
generate_hill_coef
```

Generate hill coefficient

Description

Generate hill coefficient

Usage

```
generate_hill_coef(drugs, cell_lines)
```

Arguments

| | |
|------------|----------------------------|
| drugs | data.table with drugs |
| cell_lines | data.table with cell lines |

Value

matrix with random hill coefficient

Examples

```
generate_hill_coef(create_synthetic_drugs(), create_synthetic_cell_lines())
```

```
generate_response_data
```

Generate response data

Description

Generate response data

Usage

```
generate_response_data(df_layout, noise_level = 0.1)
```

Arguments

| | |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| df_layout | data.table that should contains the cell line, drug, concentration, and replicate columns along with the annotations that needs to be propagated |
| noise_level | numeric scalar with the level of noise added to the data |

Value

data.table with response data

Examples

```
cell_lines <- create_synthetic_cell_lines()
drugs <- create_synthetic_drugs()
gDRtestData::prepareData(cell_lines[seq_len(2), ], drugs[seq_len(4), ])
```

get_test_dataset_paths
get_test_dataset_paths

Description

Returns named vector of absolute paths to test datasets.

Usage

```
get_test_dataset_paths(datasets_dir = NULL, pattern = "finalMAE_")
```

Arguments

datasets_dir path to directory with datasets (default NULL). If NULL, then inst/testdata directory from gDRtestData will be used.

pattern used to: (1) filter to qs files from the dataset_dir path and (2) prettify the labels of the files

Value

named vector of absolute paths

Author(s)

Kamil Foltynski <kamil.foltynski@contractors.roche.com>

Examples

```
get_test_dataset_paths()
path <- system.file("testdata", package = "gDRtestData", mustWork = TRUE)
get_test_dataset_paths(path)
```

Index

* data

cell_lines, 5

drugs, 6

* internal

cell_lines, 5

drugs, 6

gDRtestData-package, 2

add_concentration, 3

add_data_replicates, 4

add_day0_data, 4

cell_lines, 5

create_synthetic_cell_lines, 5

create_synthetic_drugs, 6

drugs, 6

gDRtestData (gDRtestData-package), 2

gDRtestData-package, 2

generate_e_inf, 7

generate_ec50, 7

generate_hill_coef, 8

generate_response_data, 8

get_test_dataset_paths, 9