

An Introduction to *GenomeInfoDb*

Martin Morgan, Herve Pages, Marc Carlson, Sonali Arora

Modified: 17 January, 2014. Compiled: January 25, 2016

Contents

1 Introduction

The *GenomeInfoDb* provides an interface to access seqlevelsStyles (such as UCSC, NCBI, Ensembl) and their supported mappings for organisms. For instance, for Homo sapiens, seqlevelsStyle "UCSC" maps to "chr1", "chr2", ..., "chrX", "chrY". The section below introduces these functions with examples.

2 Functionality for all existing organisms

2.1 genomeStyles

The genomeStyles lists out for each organism, the seqlevelsStyles and their mappings.

```
seqmap <- genomeStyles()
head(seqmap,n=2)

## $Arabidopsis_thaliana
##   circular  auto   sex NCBI  TAIR9  Ensembl
## 1    FALSE   TRUE  FALSE   1   Chr1     1
## 2    FALSE   TRUE  FALSE   2   Chr2     2
## 3    FALSE   TRUE  FALSE   3   Chr3     3
## 4    FALSE   TRUE  FALSE   4   Chr4     4
## 5    FALSE   TRUE  FALSE   5   Chr5     5
## 6     TRUE   FALSE FALSE   MT   ChrM     Mt
## 7     TRUE   FALSE  TRUE  Pltd  ChrC     Pt
##
## $Caenorhabditis_elegans
##   circular  auto   sex NCBI   UCSC  Ensembl
## 1    FALSE   TRUE  FALSE   I   chrI     I
## 2    FALSE   TRUE  FALSE  II  chrII    II
## 3    FALSE   TRUE  FALSE III chrIII   III
## 4    FALSE   TRUE  FALSE  IV  chrIV   IV
## 5    FALSE   TRUE  FALSE   V   chrV     V
## 6    FALSE   FALSE  TRUE   X   chrX     X
## 7     TRUE   TRUE  FALSE  MT  chrM   MtDNA
```

Organism's supported by GenomeInfoDb can be found by :

```
names(genomeStyles())
## [1] "Arabidopsis_thaliana"      "Caenorhabditis_elegans"   "Canis_familiaris"
## [4] "Cyanidioschyzon_merolae"   "Drosophila_melanogaster"  "Homo_sapiens"
## [7] "Mus_musculus"              "Oryza_sativa"             "Populus_trichocarpa"
## [10] "Rattus_norvegicus"         "Saccharomyces_cerevisiae" "Zea_mays"
```

If one knows the organism one is interested in, then we can directly access the information for the given organism along. Each function accepts an argument called `species` which as "genus species", the default is "Homo sapiens". In the following example we list out only the first five entries returned by the code snippet.

```
head(genomeStyles("Homo_sapiens"),5)
##   circular auto   sex NCBI UCSC dbSNP Ensembl
## 1   FALSE TRUE FALSE   1 chr1  ch1      1
## 2   FALSE TRUE FALSE   2 chr2  ch2      2
## 3   FALSE TRUE FALSE   3 chr3  ch3      3
## 4   FALSE TRUE FALSE   4 chr4  ch4      4
## 5   FALSE TRUE FALSE   5 chr5  ch5      5
```

We can also check if a given style is supported by *GenomeInfoDb* for a given species. For example, if we want to know if "UCSC" mapping is supported for "Homo sapiens" we can ask :

```
"UCSC" %in% names(genomeStyles("Homo_sapiens"))
## [1] TRUE
```

2.2 extractSeqlevels

We can also extract the desired `seqlevelsStyle` from a given organism using the `extractSeqlevels`

```
extractSeqlevels(species="Arabidopsis_thaliana", style="NCBI")
## [1] "1" "2" "3" "4" "5" "MT" "Pltd"
```

2.3 extractSeqlevelsByGroup

We can also extract the desired `seqlevelsStyle` from a given organism based on a group (Group - 'auto' denotes autosomes, 'circular' denotes circular chromosomes and 'sex' denotes sex chromosomes; the default is all chromosomes are returned).

```
extractSeqlevelsByGroup(species="Arabidopsis_thaliana", style="NCBI",
                        group="auto")
## [1] "1" "2" "3" "4" "5"
```

2.4 seqlevelsStyle

We can find the `seqname Style` for a given character vector by using the `seqlevelsStyle`

```
seqlevelsStyle(paste0("chr",c(1:30)))
## [1] "UCSC"
seqlevelsStyle(c("2L","2R","X","Xhet"))
## [1] "NCBI"
```

2.5 seqlevelsInGroup

We can also subset a given character vector containing seqnames using the `seqlevelsInGroup`. We currently support 3 groups: 'auto' for autosomes, 'sex' for allosomes/sex chromosomes and circular for 'circular' chromosomes. The user can also provide the style and species they are working with. In the following examples, we extract the sex, auto and circular chromosomes for *Homo sapiens* :

```
newchr <- paste0("chr",c(1:22,"X","Y","M","1_g1000192_random","4_ctg9_hap1"))
seqlevelsInGroup(newchr, group="sex")
## [1] "chrX" "chrY"

seqlevelsInGroup(newchr, group="auto")
## [1] "chr1" "chr2" "chr3" "chr4" "chr5" "chr6" "chr7" "chr8" "chr9" "chr10"
## [11] "chr11" "chr12" "chr13" "chr14" "chr15" "chr16" "chr17" "chr18" "chr19" "chr20"
## [21] "chr21" "chr22"

seqlevelsInGroup(newchr, group="circular")
## [1] "chrM"

seqlevelsInGroup(newchr, group="sex", "Homo_sapiens", "UCSC")
## [1] "chrX" "chrY"
```

if we have a vector containing seqnames and we want to verify the species and style for them , we can use:

```
seqnames <- c("chr1", "chr9", "chr2", "chr3", "chr10")
all(seqnames %in% extractSeqlevels("Homo_sapiens", "UCSC"))
## [1] TRUE
```

2.6 orderSeqlevels

The `orderSeqlevels` can return the order of a given character vector which contains seqnames. In the following example, we show how you can find the order for a given seqnames character vector.

```
seqnames <- c("chr1", "chr9", "chr2", "chr3", "chr10")
orderSeqlevels(seqnames)
## [1] 1 3 4 2 5

seqnames[orderSeqlevels(seqnames)]
## [1] "chr1" "chr2" "chr3" "chr9" "chr10"
```

2.7 rankSeqlevels

The `rankSeqlevels` can return the rank of a given character vector which contains seqnames. In the following example, we show how you can find the rank for a given seqnames character vector.

```
seqnames <- c("chr1", "chr9", "chr2", "chr3", "chr10")
rankSeqlevels(seqnames)
## [1] 1 4 2 3 5
```

2.8 mapSeqlevels

Returns a matrix with 1 column per supplied sequence name and 1 row per sequence renaming map compatible with the specified style. If `best.only` is `TRUE` (the default), only the "best" renaming maps (i.e. the rows with less NAs) are returned.

```
mapSeqlevels(c("chrII", "chrIII", "chrM"), "NCBI")

## chrII chrIII chrM
## "II" "III" "MT"
```

We also have several seqlevel utility functions. Let us construct a basic `GRanges` and show how these functions can be used. .

```
gr <- GRanges(paste0("ch",1:35), IRanges(1:35, width=5))
gr

## GRanges object with 35 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]      ch1      [1, 5]      *
##      [2]      ch2      [2, 6]      *
##      [3]      ch3      [3, 7]      *
##      [4]      ch4      [4, 8]      *
##      [5]      ch5      [5, 9]      *
##      ...      ...      ...      ...
##      [31]     ch31     [31, 35]     *
##      [32]     ch32     [32, 36]     *
##      [33]     ch33     [33, 37]     *
##      [34]     ch34     [34, 38]     *
##      [35]     ch35     [35, 39]     *
##      -----
##      seqinfo: 35 sequences from an unspecified genome; no seqlengths
```

As you can see, we have "ch" instead of "chr" for chromosome names. We can use `renameSeqlevels` to change the "ch" to "chr"

2.9 renameSeqlevels

As the first argument - it takes the object whose seqlevels we need to change, and as the second argument it takes a named vector which has the changes.

```
newnames <- paste0("chr",1:35)
names(newnames) <- paste0("ch",1:35)
head(newnames)

##      ch1      ch2      ch3      ch4      ch5      ch6
## "chr1" "chr2" "chr3" "chr4" "chr5" "chr6"

gr <- renameSeqlevels(gr,newnames)
gr

## GRanges object with 35 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]      chr1      [1, 5]      *
##      [2]      chr2      [2, 6]      *
##      [3]      chr3      [3, 7]      *
```

```
##      [4]      chr4      [4, 8]      *
##      [5]      chr5      [5, 9]      *
##      ...      ...      ...      ...
##     [31]     chr31     [31, 35]      *
##     [32]     chr32     [32, 36]      *
##     [33]     chr33     [33, 37]      *
##     [34]     chr34     [34, 38]      *
##     [35]     chr35     [35, 39]      *
## -----
## seqinfo: 35 sequences from an unspecified genome; no seqlengths
```

Humans have just 22 primary chromosomes - but here we have some extra seqlevels which we want to remove - there are several ways we can achieve this:

2.10 dropSeqlevels

Here the second argument is the seqlevels that you want to drop.

```
dropSeqlevels(gr, paste0("chr", 23:35))

## GRanges object with 22 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]      chr1      [1, 5]      *
##      [2]      chr2      [2, 6]      *
##      [3]      chr3      [3, 7]      *
##      [4]      chr4      [4, 8]      *
##      [5]      chr5      [5, 9]      *
##      ...      ...      ...      ...
##     [18]     chr18     [18, 22]      *
##     [19]     chr19     [19, 23]      *
##     [20]     chr20     [20, 24]      *
##     [21]     chr21     [21, 25]      *
##     [22]     chr22     [22, 26]      *
## -----
## seqinfo: 22 sequences from an unspecified genome; no seqlengths
```

2.11 keepSeqlevels

Here the second argument is the seqlevels that you want to keep.

```
keepSeqlevels(gr, paste0("chr", 1:22))

## GRanges object with 22 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]      chr1      [1, 5]      *
##      [2]      chr2      [2, 6]      *
##      [3]      chr3      [3, 7]      *
##      [4]      chr4      [4, 8]      *
##      [5]      chr5      [5, 9]      *
##      ...      ...      ...      ...
##     [18]     chr18     [18, 22]      *
##     [19]     chr19     [19, 23]      *
```

```
##      [20]      chr20 [20, 24]      *
##      [21]      chr21 [21, 25]      *
##      [22]      chr22 [22, 26]      *
##      -----
##      seqinfo: 22 sequences from an unspecified genome; no seqlengths
```

2.12 keepStandardChromosomes

This function internally uses the pre-defined tables inside *GenomeInfoDb* to find the correct seqlevels according to the style of the object.

```
keepStandardChromosomes(gr)

## GRanges object with 35 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]      chr1      [1, 5]      *
##      [2]      chr2      [2, 6]      *
##      [3]      chr3      [3, 7]      *
##      [4]      chr4      [4, 8]      *
##      [5]      chr5      [5, 9]      *
##      ...      ...      ...      ...
##      [31]     chr31     [31, 35]     *
##      [32]     chr32     [32, 36]     *
##      [33]     chr33     [33, 37]     *
##      [34]     chr34     [34, 38]     *
##      [35]     chr35     [35, 39]     *
##      -----
##      seqinfo: 35 sequences from an unspecified genome; no seqlengths
```

One can also specify the optional species argument to be more precise.

```
plantgr <- GRanges(c(1:5,"MT","Pltd"), IRanges(1:7,width=5))
keepStandardChromosomes(plantgr, species="Arabidopsis thaliana")

## GRanges object with 7 ranges and 0 metadata columns:
##      seqnames      ranges strand
##      <Rle> <IRanges> <Rle>
##      [1]          1 [1, 5]      *
##      [2]          2 [2, 6]      *
##      [3]          3 [3, 7]      *
##      [4]          4 [4, 8]      *
##      [5]          5 [5, 9]      *
##      [6]         MT [6, 10]     *
##      [7]        Pltd [7, 11]     *
##      -----
##      seqinfo: 7 sequences from an unspecified genome; no seqlengths
```

3 Classes inside GenomeInfoDb package

3.1 Genome-Description class

We also provide a Genome Description class which can be used in the following way:

```
library(BSgenome.Celegans.UCSC.ce2)
class(Celegans)

## [1] "BSgenome"
## attr(,"package")
## [1] "BSgenome"

is(Celegans, "GenomeDescription")
## [1] TRUE

provider(Celegans)
## [1] "UCSC"

seqinfo(Celegans)
## Seqinfo object with 7 sequences (1 circular) from ce2 genome:
##   seqnames seqlengths isCircular genome
##   chrI      15080483      FALSE    ce2
##   chrII      15279308      FALSE    ce2
##   chrIII     13783313      FALSE    ce2
##   chrIV      17493791      FALSE    ce2
##   chrV       20922231      FALSE    ce2
##   chrX       17718849      FALSE    ce2
##   chrM        13794         TRUE     ce2

gendesc <- as(Celegans, "GenomeDescription")
class(gendesc)

## [1] "GenomeDescription"
## attr(,"package")
## [1] "GenomeInfoDb"

gendesc
## | organism: Caenorhabditis elegans (Worm)
## | provider: UCSC
## | provider version: ce2
## | release date: Mar. 2004
## | release name: WormBase v. WS120
## | ---
## | seqlengths:
## |      chrI   chrII   chrIII   chrIV   chrV   chrX   chrM
## | 15080483 15279308 13783313 17493791 20922231 17718849 13794

provider(gendesc)
## [1] "UCSC"

seqinfo(gendesc)
## Seqinfo object with 7 sequences (1 circular) from ce2 genome:
##   seqnames seqlengths isCircular genome
##   chrI      15080483      FALSE    ce2
##   chrII      15279308      FALSE    ce2
##   chrIII     13783313      FALSE    ce2
##   chrIV      17493791      FALSE    ce2
```

```
## chrV      20922231    FALSE    ce2
## chrX      17718849    FALSE    ce2
## chrM       13794      TRUE     ce2

bsgenomeName(gendesc)

## [1] "BSgenome.Celegans.UCSC.ce2"
```

3.2 SeqInfo class

```
## Note that all the arguments (except 'genome') must have the
## same length. 'genome' can be of length 1, whatever the lengths
## of the other arguments are.
x <- Seqinfo(seqnames=c("chr1", "chr2", "chr3", "chrM"),
             seqlengths=c(100, 200, NA, 15),
             isCircular=c(NA, FALSE, FALSE, TRUE),
             genome="toy")

length(x)

## [1] 4

seqnames(x)

## [1] "chr1" "chr2" "chr3" "chrM"

names(x)

## [1] "chr1" "chr2" "chr3" "chrM"

seqlevels(x)

## [1] "chr1" "chr2" "chr3" "chrM"

seqlengths(x)

## chr1 chr2 chr3 chrM
## 100 200 NA 15

isCircular(x)

## chr1 chr2 chr3 chrM
## NA FALSE FALSE TRUE

genome(x)

## chr1 chr2 chr3 chrM
## "toy" "toy" "toy" "toy"

x[c("chrY", "chr3", "chr1")] # subset by names

## Seqinfo object with 3 sequences from 2 genomes (NA, toy):
##   seqnames seqlengths isCircular genome
##   chrY      NA        NA    <NA>
##   chr3      NA        FALSE    toy
##   chr1     100        NA      toy

## Rename, drop, add and/or reorder the sequence levels:
xx <- x
seqlevels(xx) <- sub("chr", "ch", seqlevels(xx)) # rename
xx
```



```
## Seqinfo object with 4 sequences (1 circular) from toy genome:
##   seqnames seqlengths isCircular genome
##   ch1      100        NA      toy
##   ch2      200       FALSE    toy
##   ch3      NA        FALSE    toy
##   chM      15        TRUE     toy

seqlevels(xx) <- rev(seqlevels(xx)) # reorder
xx

## Seqinfo object with 4 sequences (1 circular) from toy genome:
##   seqnames seqlengths isCircular genome
##   chM      15        TRUE     toy
##   ch3      NA        FALSE    toy
##   ch2      200       FALSE    toy
##   ch1      100        NA      toy

seqlevels(xx) <- c("ch1", "ch2", "chY") # drop/add/reorder
xx

## Seqinfo object with 3 sequences from 2 genomes (toy, NA):
##   seqnames seqlengths isCircular genome
##   ch1      100        NA      toy
##   ch2      200       FALSE    toy
##   chY      NA        NA      <NA>

seqlevels(xx) <- c(chY="Y", ch1="1", "22") # rename/reorder/drop/add
xx

## Seqinfo object with 3 sequences from 2 genomes (NA, toy):
##   seqnames seqlengths isCircular genome
##   Y        NA        NA      <NA>
##   1        100       NA      toy
##   22       NA        NA      <NA>

y <- Seqinfo(seqnames=c("chr3", "chr4", "chrM"),
             seqlengths=c(300, NA, 15))
y

## Seqinfo object with 3 sequences from an unspecified genome:
##   seqnames seqlengths isCircular genome
##   chr3      300        NA      <NA>
##   chr4      NA        NA      <NA>
##   chrM      15        NA      <NA>

merge(x, y) # rows for chr3 and chrM are merged

## Warning in .Seqinfo.mergexy(x, y): Each of the 2 combined objects has sequence levels not in
## the other:
## - in 'x': chr1, chr2
## - in 'y': chr4
## Make sure to always combine/compare objects based on the same reference
## genome (use suppressWarnings() to suppress this warning).

## Seqinfo object with 5 sequences (1 circular) from 2 genomes (toy, NA):
##   seqnames seqlengths isCircular genome
##   chr1      100        NA      toy
##   chr2      200       FALSE    toy
##   chr3      300       FALSE    toy
```

```
##   chrM           15      TRUE   toy
##   chr4           NA       NA   <NA>

suppressWarnings(merge(x, y))

## Seqinfo object with 5 sequences (1 circular) from 2 genomes (toy, NA):
##   seqnames seqlengths isCircular genome
##   chr1      100       NA      toy
##   chr2      200      FALSE   toy
##   chr3      300      FALSE   toy
##   chrM       15       TRUE   toy
##   chr4       NA       NA     <NA>

## Note that, strictly speaking, merging 2 Seqinfo objects is not
## a commutative operation, i.e., in general 'z1 <- merge(x, y)'
## is not identical to 'z2 <- merge(y, x)'. However 'z1' and 'z2'
## are guaranteed to contain the same information (i.e. the same
## rows, but typically not in the same order):
suppressWarnings(merge(y, x))

## Seqinfo object with 5 sequences (1 circular) from 2 genomes (toy, NA):
##   seqnames seqlengths isCircular genome
##   chr3      300       FALSE   toy
##   chr4       NA       NA     <NA>
##   chrM       15       TRUE   toy
##   chr1      100       NA      toy
##   chr2      200      FALSE   toy

## This contradicts what 'x' says about circularity of chr3 and chrM:
isCircular(y)[c("chr3", "chrM")] <- c(TRUE, FALSE)
y

## Seqinfo object with 3 sequences (1 circular) from an unspecified genome:
##   seqnames seqlengths isCircular genome
##   chr3      300       TRUE   <NA>
##   chr4       NA       NA     <NA>
##   chrM       15      FALSE   <NA>

if (interactive()) {
  merge(x, y) # raises an error
}
```

4 Examples

4.1 converting seqlevel styles (eg:UCSC to NCBI)

A quick example using *Drosophila Melanogaster*. The txdb object contains seqlevels in UCSC style, we want to convert them to NCBI

```
txdb <- TxDb.Dmelanogaster.UCSC.dm3.ensGene
seqlevels(txdb)

## [1] "chr2L"      "chr2R"      "chr3L"      "chr3R"      "chr4"      "chrX"      "chrU"
## [8] "chrM"       "chr2LHet"   "chr2RHet"   "chr3LHet"   "chr3RHet"   "chrXHet"   "chrYHet"
## [15] "chrUextra"
```

```
genomeStyles("Drosophila melanogaster")
```

	circular	sex	auto	NCBI	UCSC	Ensembl
## 1	FALSE	FALSE	TRUE	2L	chr2L	2L
## 2	FALSE	FALSE	TRUE	2R	chr2R	2R
## 3	FALSE	FALSE	TRUE	3L	chr3L	3L
## 4	FALSE	FALSE	TRUE	3R	chr3R	3R
## 5	FALSE	FALSE	TRUE	4	chr4	4
## 6	FALSE	TRUE	FALSE	X	chrX	X
## 7	TRUE	FALSE	FALSE	MT	chrM	dmel_mitochondrion_genome
## 8	FALSE	FALSE	FALSE	2LHet	chr2LHet	2LHet
## 9	FALSE	FALSE	FALSE	2Rhet	chr2RHet	2RHet
## 10	FALSE	FALSE	FALSE	3LHet	chr3LHet	3LHet
## 11	FALSE	FALSE	FALSE	3RHet	chr3RHet	3RHet
## 12	FALSE	FALSE	FALSE	Xhet	chrXHet	XHet
## 13	FALSE	FALSE	FALSE	Yhet	chrYHet	YHet
## 14	FALSE	FALSE	FALSE	Un	chrU	U
## 15	FALSE	FALSE	FALSE	<NA>	chrUextra	Uextra

```
mapSeqlevels(seqlevels(txdb), "NCBI")
```

	chr2L	chr2R	chr3L	chr3R	chr4	chrX	chrU	chrM	chr2LHet
##	"2L"	"2R"	"3L"	"3R"	"4"	"X"	"Un"	"MT"	"2LHet"
##	chr2RHet	chr3LHet	chr3RHet	chrXHet	chrYHet	chrUextra			
##	"2Rhet"	"3LHet"	"3RHet"	"Xhet"	"Yhet"	NA			

4.2 converting styles and removing unwanted seqlevels

Suppose we read in a Bam file or a BED file and the resulting GRanges have a lot of seqlevels which are not required by your analysis or you want to rename the seqlevels from the current style to your own style (eg:UCSC to NCBI), we can use the functionality provided by GenomeInfoDb to do that.

Let us say that we have extracted the seqlevels of the Seqinfo object(say GRanges from a BED file) in a variable called "sequence".

```
sequence <- seqlevels(x)

## sequence is in UCSC format and we want NCBI style
newStyle <- mapSeqlevels(sequence, "NCBI")
newStyle <- newStyle[complete.cases(newStyle)] # removing NA cases.

## rename the seqlevels
x <- renameSeqlevels(x, newStyle)

## keep only the seqlevels you want (say autosomes)
auto <- extractSeqlevelsByGroup(species="Homo sapiens", style="NCBI",
                               group="auto")
x <- keepSeqlevels(x, auto)
```

5 Session Information

Here is the output of sessionInfo on the system on which this document was compiled:

```
toLatex(sessionInfo())
```

- R version 3.2.3 (2015-12-10), x86_64-apple-darwin13.4.0
- Locale: C/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, stats4, utils
- Other packages: AnnotationDbi 1.32.3, BSgenome 1.38.0, BSgenome.Celegans.UCSC.ce2 1.4.0, Biobase 2.30.0, BiocGenerics 0.16.1, Biostrings 2.38.3, GenomeInfoDb 1.6.3, GenomicFeatures 1.22.9, GenomicRanges 1.22.3, IRanges 2.4.6, S4Vectors 0.8.9, TxDb.Dmelanogaster.UCSC.dm3.ensGene 3.2.2, XVector 0.10.0, rtracklayer 1.30.1
- Loaded via a namespace (and not attached): BiocParallel 1.4.3, BiocStyle 1.8.0, DBI 0.3.1, GenomicAlignments 1.6.3, RCurl 1.95-4.7, RSQLite 1.0.0, Rsamtools 1.22.0, SummarizedExperiment 1.0.2, XML 3.98-1.3, biomaRt 2.26.1, bitops 1.0-6, evaluate 0.8, formatR 1.2.1, futile.logger 1.4.1, futile.options 1.0.0, highr 0.5.1, knitr 1.12.3, lambda.r 1.1.7, magrittr 1.5, stringi 1.0-1, stringr 1.0.0, tools 3.2.3, zlibbioc 1.16.0