

Package ‘Doscheda’

September 11, 2024

Type Package

Title A DownStream Chemo-Proteomics Analysis Pipeline

Version 1.27.0

Author Bruno Contrino, Piero Ricchiuto

Maintainer Bruno Contrino <br1contrino@yahoo.co.uk>

Description Doscheda focuses on quantitative chemoproteomics used to determine protein interaction profiles of small molecules from whole cell or tissue lysates using Mass Spectrometry data. The package provides a shiny application to run the pipeline, several visualisations and a downloadable report of an experiment.

License GPL-3

Depends R (>= 3.4)

Imports methods, drc, stats, httr, jsonlite, reshape2, vsn, affy, limma, stringr, ggplot2, graphics, grDevices, calibrate, corrgram, gridExtra, DT, shiny, shinydashboard, readxl, prodlim, matrixStats

biocViews Proteomics, Normalization, Preprocessing, MassSpectrometry, QualityControl, DataImport, Regression

Suggests BiocStyle, knitr, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/Doscheda>

git_branch devel

git_last_commit 34b085c

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-09-11

Contents

| | |
|---------------------------------------|-----------|
| boxplot,ChemoProtSet-method | 2 |
| ChemoProtSet-class | 3 |
| corrPlot | 3 |
| densityPlot | 4 |
| doscheda | 5 |
| doschedaApp | 5 |
| doschedaData | 5 |
| fitModel | 6 |
| getDatasets | 7 |
| getFinal | 8 |
| getInput | 8 |
| getNorm | 9 |
| getParameters | 10 |
| makeReport | 10 |
| meanSdPlot | 11 |
| pcaPlot | 12 |
| plot.ChemoProtSet | 13 |
| processedExample | 13 |
| removePeptides | 14 |
| replicatePlot | 15 |
| runDoscheda | 16 |
| runNormalisation | 18 |
| setData | 18 |
| setParameters | 20 |
| volcanoPlot | 22 |
| Index | 23 |

boxplot,ChemoProtSet-method

Default boxplot for objects of class ChemoProtSet

Description

Description

Usage

```
## S4 method for signature 'ChemoProtSet'
boxplot(x, ...)
```

Arguments

| | |
|-----|--------------------------------|
| x | object of class 'ChemoProtSet' |
| ... | other plotting options |

Value

boxplot for objects of class ChemoProtSet

ChemoProtSet-class *An S4 class to run the doscheda pipeline*

Description

An S4 class to run the doscheda pipeline

Slots

input A data.frame containing the input data
normData A data.frame containin a processed and standardised version of the input data
finalData A data.frame containing the final data produced by the pipeline
parameters A list containing all the parameters required to make the pipeline run successfully
datasets A list containing other potentially useful datasets

corrPlot *Plot showing correlation between all channels across replicates*

Description

Plot of the correlation between all the channels in the data.

Usage

```
corrPlot(x, ...)  
  
## S4 method for signature 'ChemoProtSet'  
corrPlot(x, ...)
```

Arguments

x object of class 'ChemoProtSet'
... corrplot options

Value

correlation plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample
ex <- runNormalisation(ex)
ex <- fitModel(ex)
corrPlot(ex)
```

| | |
|-------------|---|
| densityPlot | <i>Density plot for objects of class ChemoProtSet</i> |
|-------------|---|

Description

Description

Usage

```
densityPlot(x, rankProteins = FALSE, ...)

## S4 method for signature 'ChemoProtSet'
densityPlot(x, rankProteins = FALSE, ...)
```

Arguments

| | |
|--------------|---|
| x | object of class 'ChemoProtSet' |
| rankProteins | plot a the set of ranked proteins or plot the density of the channels |
| ... | other plot options |

Value

density plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample
ex <- runNormalisation(ex)
ex <- fitModel(ex)
densityPlot(ex)
```

| | |
|----------|---|
| doscheda | <i>Doscheda: A package for Down Stream Chemo-Proteomics Data Analysis</i> |
|----------|---|

Description

The Doscheda package provides three categories of important functions: foo, bar and baz.

Foo functions

The foo functions ...

| | |
|-------------|---|
| doschedaApp | <i>Run shiny application for DOSCHEDA</i> |
|-------------|---|

Description

Run a version of the pipeline with some extra features and a simple user experience. The application is documented in detail at [here](#)

Usage

```
doschedaApp()
```

Value

Launches shiny application

| | |
|--------------|--|
| doschedaData | <i>Peptide Intensity data set for Doscheda</i> |
|--------------|--|

Description

A fabricated data set to run the Doscheda pipeline from peptide intensity.

Usage

```
data(doschedaData)
```

Format

An object of class `data.frame` with 21140 rows and 15 columns.

Examples

```
data(doschedaData)
head(doschedaData)
```

fitModel

Method to fit a model to an object of class 'ChemoProtSet'

Description

Method to fit a model to an object of class 'ChemoProtSet'

Usage

```
fitModel(x)
```

```
## S4 method for signature 'ChemoProtSet'
fitModel(x)
```

Arguments

x object of class 'ChemoProtSet'

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
'Abundance..F2..131..Sample..REP_2')
ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
modelTypeStr = 'linear',PDBool = FALSE,removePepsBool = FALSE,
incPDofPDBool = FALSE,incGeneFileBool = FALSE,organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
ex<- setData(x = ex, dataFrame = doschedaData, dataChannels = channelNames,
accessionChannel = 'Master.Protein.Accessions',
sequenceChannel = 'Sequence', qualityChannel = 'Quality.PEP' )
ex <- removePeptides(ex,removePeps = FALSE)
ex <- runNormalisation(ex)
ex <- fitModel(ex)
ex
ex <- processedExample
ex <- runNormalisation(ex)
```

```
ex <- fitModel(ex)
ex
```

getDatasets *Accessor function for the datasets slot.*

Description

Accessor function for the datasets slot of a ChemoProtSet object.

Usage

```
getDatasets(x)

## S4 method for signature 'ChemoProtSet'
getDatasets(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getDatasets(ex)
```

getFinal *Accessor function for the finalData slot.*

Description

Accessor function for the finalData slot of a ChemoProtSet object.

Usage

```
getFinal(x)

## S4 method for signature 'ChemoProtSet'
getFinal(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getParameters(ex)
```

getInput *Accessor function for the Input*

Description

Accessor function for the Input slot of a ChemoProtSet object.

Usage

```
getInput(x)

## S4 method for signature 'ChemoProtSet'
getInput(x)
```


Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getInput(ex)
```

getNorm *Accessor function for the normData*

Description

Accessor function for the normData slot of a ChemoProtSet object.

Usage

```
getNorm(x)

## S4 method for signature 'ChemoProtSet'
getNorm(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getNorm(ex)
```


Value

html report of processed 'ChemoProtSet' object

Examples

```
## Not run:  
ex<- new('ChemoProtSet')  
makeReport(ex)  
  
## End(Not run)
```

meanSdPlot

MeanSd plot for objects of class ChemoProtSet

Description

Shows the ranked means with a running median calculated with a window size of 10

Usage

```
meanSdPlot(x, ...)  
  
## S4 method for signature 'ChemoProtSet'  
meanSdPlot(x, ...)
```

Arguments

x object of class 'ChemoProtSet'
... other plot options

Value

meanSd plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
meanSdPlot(ex)
```

pcaPlot

PCA of the main data sets contained in a object of class ChemoProtSet

Description

Plot of Principal Component Analysis for the first two principal components of the experimental data.

Usage

```
pcaPlot(x, ...)  
  
## S4 method for signature 'ChemoProtSet'  
pcaPlot(x, ...)
```

Arguments

| | |
|-----|--------------------------------|
| x | object of class 'ChemoProtSet' |
| ... | other plot options |

Value

PCA plot for objects of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
pcaPlot(ex)  
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
pcaPlot(ex)
```

plot.ChemoProtSet *Default plot for objects of class ChemoProtSet*

Description

Description

Usage

```
## S3 method for class 'ChemoProtSet'  
plot(x, sigmoidCoef = "rb50", ...)
```

Arguments

| | |
|-------------|--|
| x | object of class 'ChemoProtSet' |
| sigmoidCoef | the sigmoidal coefficient, one of ('difference', 'slope', 'rb50'). Obsolete if modelType is 'linear' |
| ... | other plotting options |

Value

plot for objects of class ChemoProtSet

processedExample *Processed Peptide Intensity data set for Doscheda*

Description

A processed fabricated data set to run the Doscheda pipeline from peptide intensity.

Usage

```
data(processedExample)
```

Format

An object of class ChemoProtSet of length 1.

Examples

```
data(processedExample)  
str(processedExample)
```

| | |
|----------------|---|
| removePeptides | <i>Method to remove peptides from input data of an object of class 'ChemoProtSet'</i> |
|----------------|---|

Description

Method to remove peptides from input data of an object of class 'ChemoProtSet'

Usage

```
removePeptides(x, changePearson = NA, removePeps = TRUE)
```

```
## S4 method for signature 'ChemoProtSet'
removePeptides(x, changePearson = NA,
  removePeps = TRUE)
```

Arguments

| | |
|---------------|--|
| x | object of class 'ChemoProtSet' |
| changePearson | option to change the pearson threshold cut-off parameter |
| removePeps | boolean value indicating whether peptide removal should take place |

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
## Not run:
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,
  dataTypeStr = 'intensity', modelTypeStr = 'linear',
  PDBool = FALSE,removePepsBool = FALSE,incPDofPDBool = FALSE,
  incGeneFileBool = FALSE,organismStr = 'H.sapiens',
  pearsonThrshVal = 0.4)

ex<- setData(x = ex, dataFrame = doschedaData,
```

```
dataChannels = channelNames,  
accessionChannel = 'Master.Protein.Accessions',  
sequenceChannel = 'Sequence',  
qualityChannel = 'Quality.PEP' )  
ex <- removePeptides(ex,removePeps = FALSE)  
ex  
  
## End(Not run)
```

replicatePlot

Plot replicates between concentrations

Description

Plot of Fold Change between replicate i and replicate j at a given concentration

Usage

```
replicatePlot(x, conc, repIndex1, repIndex2, ...)
```

```
## S4 method for signature 'ChemoProtSet'  
replicatePlot(x, conc, repIndex1, repIndex2, ...)
```

Arguments

| | |
|-----------|--------------------------------|
| x | object of class 'ChemoProtSet' |
| conc | concentration of channel |
| repIndex1 | index of replicate on x axis |
| repIndex2 | index of replicate on y axis |
| ... | options |

Value

Replicate plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
replicatePlot(ex,0,1,2)
```

| | |
|-------------|---|
| runDoscheda | <i>Wrapper Function to run the entire Doscheda pipeline</i> |
|-------------|---|

Description

A wrapper for the whole Doscheda pipeline, if users want to avoid using the separate steps.

Usage

```
runDoscheda(dataFrame, dataChannels, accessionChannel, chansVal, repsVal,
  dataTypeStr, modelTypeStr, PDBool = TRUE, removePepsBool = NA,
  incPDofPDBool = FALSE, PDofPDname = NA, incGeneFileBool = FALSE,
  organismStr = "h.sapiens", sigmoidConc = NA, pearsonThrshVal = 0.4,
  uniquePeps = NA, sequenceChannel = NA, qualityChannel = NA,
  pdofpdChannel = NA, incGeneID = FALSE, geneIDFile = NA,
  normType = "loess")
```

Arguments

| | |
|------------------|---|
| dataFrame | data.frame of the input data set |
| dataChannels | column names of dataFrame that correspond to data channels. These should be ordered in the format: rep1_concentration_0, ..., rep1_concentration_n, rep2_concentration_0, ... |
| accessionChannel | string that is the same as the column name for the protein accessions in dataFrame |
| chansVal | number of channels / concentrations in experiment |
| repsVal | number of replicates in experiment |
| dataTypeStr | string describing the data type of input data set. This can be 'LFC' for log fold-changes, 'FC' for fold-changes and 'intensity' for peptide intensities |
| modelTypeStr | string describing the type of model applied. This can be 'linear' for a linear model or 'sigmoid' for a sigmoidal model |
| PDBool | boolean value indicating if the input data is from Proteome Discoverer 2.1 or not |
| removePepsBool | boolean value indicating if peptide removal will take place. Only valid if input data is peptide intensities |
| incPDofPDBool | boolean value indicating if the input data contains a pull-down of pull-down column |
| PDofPDname | string with the same name as column containing pull-down of pull-down data. NA if this is not applicable |
| incGeneFileBool | boolean value indicating if the data requires a protein accession to gene ID conversion file |

| | |
|-----------------|---|
| organismStr | string giving the name of organism. the options are: 'H.sapiens', 'D. melanogaster', 'C. elegans', 'R. norvegicus', 'M. musculus'. This is only needed if PDbool is FALSE |
| sigmoidConc | vector of numerical values for concentrations of channels in the case of a sigmoidal fit |
| pearsonThrshVal | numerical value between -1 and 1 which determines the cut-off used to discard peptides during peptide removal |
| uniquePeps | string that is the same as the column name for the number of unique peptides in dataframe |
| sequenceChannel | string that is the same as the column name for the peptide sequences in dataframe |
| qualityChannel | string that is the same as the column name for the peptide quality score in dataframe |
| pdofpdChannel | string that is the same as the column name for the pull-down of pull-down data in dataframe |
| incGeneID | boolean value indicating if a protein accession to gene ID file is supplied |
| geneIDFile | data.frame containing a protein accession to gene ID conversion file |
| normType | string indicating the type of normalisation that should take place ('loess', 'median', 'none') |

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
```

```
ex <- runDoscheda(dataFrame = doschedaData, dataChannels = channelNames,
  chansVal = 6, repsVal = 2, dataTypeStr = 'intensity',
  modelTypeStr = 'linear', PDBool = FALSE, removePepsBool = FALSE,
  accessionChannel = 'Master.Protein.Accessions',
  sequenceChannel = 'Sequence', qualityChannel = 'Quality.PEP',
  incPDofPDBool = FALSE, incGeneFileBool = FALSE,
  organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
```

| | |
|------------------|---|
| runNormalisation | <i>Method to remove peptides from input data of an object of class 'ChemoProtSet'</i> |
|------------------|---|

Description

Method to remove peptides from input data of an object of class 'ChemoProtSet'

Usage

```
runNormalisation(x, normalise = "loess")  
  
## S4 method for signature 'ChemoProtSet'  
runNormalisation(x, normalise = "loess")
```

Arguments

| | |
|-----------|--|
| x | object of class 'ChemoProtSet' |
| normalise | string indicating the type of normalisation that should take place ('loess', 'median', 'none') |

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex
```

| | |
|---------|--|
| setData | <i>Method for attaching and standardising data for objects of class 'ChemoProtSet'</i> |
|---------|--|

Description

This method will subset the original data set into the required columns, standardising column names in the process.

Usage

```
setData(x, dataFrame, dataChannels, accessionChannel, uniquePeps = NA,
        sequenceChannel = NA, qualityChannel = NA, pdofpdChannel = NA,
        incGeneID = FALSE, geneIDFile = NA)
```

```
## S4 method for signature 'ChemoProtSet'
setData(x, dataFrame, dataChannels, accessionChannel,
        uniquePeps = NA, sequenceChannel = NA, qualityChannel = NA,
        pdofpdChannel = NA, incGeneID = FALSE, geneIDFile = NA)
```

Arguments

| | |
|------------------|---|
| x | object of class 'ChemoProtSet' |
| dataFrame | data.frame of the input data set |
| dataChannels | column names of dataFrame that correspond to data channels. These should be ordered in the format: rep1_concentration_0, ..., rep1_concentration_n, rep2_concentration_0, ... |
| accessionChannel | string that is the same as the column name for the protein accessions in dataFrame |
| uniquePeps | string that is the same as the column name for the number of unique peptides in dataFrame |
| sequenceChannel | string that is the same as the column name for the peptide sequences in dataFrame |
| qualityChannel | string that is the same as the column name for the peptide quality score in dataFrame |
| pdofpdChannel | string that is the same as the column name for the pull-down of pull-down data in dataFrame |
| incGeneID | boolean value indicating if a protein accession to gene ID file is supplied |
| geneIDFile | data.frame containing a protein accession to gene ID conversion file |

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
```

```

ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
modelTypeStr = 'linear',PDBool = FALSE,removePepsBool = FALSE,
incPDofPDBool = FALSE,incGeneFileBool = FALSE,organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
ex<- setData(x = ex, dataFrame = doschedaData, dataChannels = channelNames,
accessionChannel = 'Master.Protein.Accessions',
sequenceChannel = 'Sequence',qualityChannel = 'Quality.PEP')

ex

```

setParameters

Method to set parameters for a ChemoProtSet

Description

Give the ChemoProtSet object the correct parameters for a given experiment in order to successfully run the pipeline

Usage

```

setParameters(x, chansVal, repsVal, dataTypeStr, modelTypeStr, PDBool = TRUE,
removePepsBool = NA, incPDofPDBool = FALSE, PDofPDname = NA,
incGeneFileBool = FALSE, organismStr = "h.sapiens", sigmoidConc = NA,
pearsonThrshVal = 0.4)

```

```

## S4 method for signature 'ChemoProtSet'
setParameters(x, chansVal, repsVal, dataTypeStr,
modelTypeStr, PDBool = TRUE, removePepsBool = NA, incPDofPDBool = FALSE,
PDofPDname = NA, incGeneFileBool = FALSE, organismStr = "h.sapiens",
sigmoidConc = NA, pearsonThrshVal = 0.4)

```

Arguments

| | |
|----------------|--|
| x | object of class 'ChemoProtSet' |
| chansVal | number of channels / concentrations in experiment |
| repsVal | number of replicates in experiment |
| dataTypeStr | string describing the data type of input data set. This can be 'LFC' for log fold-changes, 'FC' for fold-changes and 'intensity' for peptide intensities |
| modelTypeStr | string describing the type of model applied. This can be 'linear' for a linear model or 'sigmoid' for a sigmoidal model |
| PDBool | boolean value indicating if the input data is from Proteome Discoverer 2.1 or not |
| removePepsBool | boolean value indicating if peptide removal will take place. Only valid if input data is peptide intensities |

| | |
|-----------------|---|
| incPDofPDBool | boolean value indicating if the input data contains a pull-down of pull-down column |
| PDofPDname | string with the same name as column containing pull-down of pull-down data. NA if this is not applicable |
| incGeneFileBool | boolean value indicating if the data requires a protein accession to gene ID conversion file |
| organismStr | string giving the name of organism. the options are: 'H.sapiens', 'D. melanogaster', 'C. elegans', 'R. norvegicus', 'M. musculus'. This is only needed if PDbool is FALSE |
| sigmoidConc | vector of numerical values for concentrations of channels in the case of a sigmoidal fit |
| pearsonThrshVal | numerical value between -1 and 1 which determines the cut-off used to discard peptides during peptide removal |

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')

ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
  modelTypeStr = 'linear',PDBool = FALSE, removePepsBool = FALSE,
  incPDofPDBool = FALSE, incGeneFileBool = FALSE,
  organismStr = 'H.sapiens', pearsonThrshVal = 0.4)

ex
```

`volcanoPlot`*Volcano plot for objects of class ChemoProtSet*

Description

Volcano plots designed to be run on objects of class 'ChemoProtSet' when a linear model has been applied.

Usage

```
volcanoPlot(x, coefficient = "slope", avExprs = 0.2, pVal = 0.05, ...)
```

```
## S4 method for signature 'ChemoProtSet'  
volcanoPlot(x, coefficient = "slope",  
  avExprs = 0.2, pVal = 0.05, ...)
```

Arguments

| | |
|--------------------------|---|
| <code>x</code> | object of class 'ChemoProtSet' |
| <code>coefficient</code> | coefficient of linear model to be plotted ('slope','intercept','quadratic') |
| <code>avExprs</code> | average expression cutoff |
| <code>pVal</code> | p-value cut-off |
| <code>...</code> | other plotting options |

Value

volcano plot for objects of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
volcanoPlot(ex)
```

Index

- * **datasets**
 - doschedaData, 5
 - processedExample, 13
- boxplot, ChemoProtSet-method, 2
- ChemoProtSet-class, 3
- corrPlot, 3
- corrPlot, ANY, ANY-method (corrPlot), 3
- corrPlot, ChemoProtSet-method (corrPlot), 3
- densityPlot, 4
- densityPlot, ANY, ANY-method (densityPlot), 4
- densityPlot, ChemoProtSet-method (densityPlot), 4
- doscheda, 5
- doscheda-package (doscheda), 5
- doschedaApp, 5
- doschedaData, 5
- DoschedaSet, 6–10, 12, 14, 17–19, 21, 22
- DoschedaSet (ChemoProtSet-class), 3
- fitModel, 6
- fitModel, ANY, ANY-method (fitModel), 6
- fitModel, ChemoProtSet-method (fitModel), 6
- getDatasets, 7
- getDatasets, ANY, ANY-method (getDatasets), 7
- getDatasets, ChemoProtSet-method (getDatasets), 7
- getFinal, 8
- getFinal, ANY, ANY-method (getFinal), 8
- getFinal, ChemoProtSet-method (getFinal), 8
- getInput, 8
- getInput, ANY, ANY-method (getInput), 8
- getInput, ChemoProtSet-method (getInput), 8
- getNorm, 9
- getNorm, ANY, ANY-method (getNorm), 9
- getNorm, ChemoProtSet-method (getNorm), 9
- getParameters, 10
- getParameters, ANY, ANY-method (getParameters), 10
- getParameters, ChemoProtSet-method (getParameters), 10
- makeReport, 10
- meanSdPlot, 11
- meanSdPlot, ANY, ANY-method (meanSdPlot), 11
- meanSdPlot, ChemoProtSet-method (meanSdPlot), 11
- pcaPlot, 12
- pcaPlot, ANY, ANY-method (pcaPlot), 12
- pcaPlot, ChemoProtSet-method (pcaPlot), 12
- plot.ChemoProtSet, 13
- processedExample, 13
- removePeptides, 14
- removePeptides, ANY, ANY-method (removePeptides), 14
- removePeptides, ChemoProtSet-method (removePeptides), 14
- replicatePlot, 15
- replicatePlot, ANY, ANY-method (replicatePlot), 15
- replicatePlot, ChemoProtSet-method (replicatePlot), 15
- runDoscheda, 16
- runNormalisation, 18
- runNormalisation, ANY, ANY-method (runNormalisation), 18

runNormalisation,ChemoProtSet-method
(runNormalisation), [18](#)

setData, [18](#)

setData,ANY,ANY-method (setData), [18](#)

setData,ChemoProtSet-method (setData),
[18](#)

setParameters, [20](#)

setParameters,ANY,ANY-method
(setParameters), [20](#)

setParameters,ChemoProtSet-method
(setParameters), [20](#)

volcanoPlot, [22](#)

volcanoPlot,ANY,ANY-method
(volcanoPlot), [22](#)

volcanoPlot,ChemoProtSet-method
(volcanoPlot), [22](#)