

Package ‘MGFM’

February 20, 2025

Type Package

Title Marker Gene Finder in Microarray gene expression data

Version 1.41.0

Date 2014-09-21

Author Khadija El Amrani

Maintainer Khadija El Amrani <khadija.el-amrani@charite.de>

Description The package is designed to detect marker genes from
Microarray gene expression data sets

Depends AnnotationDbi,annotate

Suggests hgu133a.db

biocViews Genetics, GeneExpression, Microarray

License GPL-3

LazyData yes

git_url <https://git.bioconductor.org/packages/MGFM>

git_branch devel

git_last_commit b6b997c

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2025-02-20

Contents

MGFM-package	2
ds2.mat	2
getHtmlpage	3
getMarkerGenes	4
grid-internal	5

Index	6
--------------	----------

MGFM-package

Marker Gene Finder in Microarray gene expression data

Description

The package is designed to detect marker genes from microarray gene expression data sets

Details

Package: MGFM
Type: Package
Version: 1.2.0
Date: 2014-08-13
License: GPL-3

Author(s)

Khadija El Amrani Maintainer: Khadija El Amrani <khadija.el-amrani@charite.de>

ds2.mat

Microarray gene expression data set

Description

microarray expression data set derived from 5 tissue types (lung, liver, heart, kidney, and brain) from two GEO Series GSE1133 and GSE2361. Each tissue type is represented by 3 replicates.

Usage

```
data(ds2.mat)
```

Format

A [matrix](#) with 22283 probe sets and 15 samples.

Details

The data consist of the following samples: GSM44702, GSM18953, GSM18954, GSM44704, GSM18949, GSM18950, GSM44690, GSM18921, GSM18922, GSM44675, GSM18955, GSM18956, GSM44671, GSM18951, GSM18952

Value

microarray data matrix

Examples

```
data(ds2.mat)
```

getHtmlpage

Function to build HTML pages to show marker genes

Description

Function to build HTML pages to show marker genes

Usage

```
getHtmlpage(markers.list,chip, directory=getwd())
```

Arguments

markers.list List of marker genes, returned by the function [getMarkerGenes](#).
chip Chip name.
directory Path to the directory where to save the html pages.

Details

This function is based on the function [htmlpage](#) from the R-package 'annotate'.

Value

This function is used only for the side effect of creating HTML tables.

Author(s)

Khadija El Amrani <khadija.el-amrani@charite.de>

Examples

```
data("ds2.mat")  
res.list <- getMarkerGenes(ds2.mat, samples2compare="all", annotate=TRUE, chip="hgu133a",  
score.cutoff=1)  
getHtmlpage(res.list, chip="hgu133a",directory=getwd())
```

getMarkerGenes *Marker Gene Detection*

Description

Function to detect marker genes using microarray gene expression data sets

Usage

```
getMarkerGenes(data.mat, samples2compare="all", annotate=TRUE, chip=NULL,
score.cutoff=1)
```

Arguments

data.mat	The microarray data matrix with probe sets corresponding to rows and samples corresponding to columns.
samples2compare	A character vector with the sample names to be compared (e.g. c("liver", "lung", "brain")). By default all samples are used.
annotate	A boolean value. If TRUE the gene symbol and the entrez gene id are shown.
chip	Chip name.
score.cutoff	A value in the interval [0,1] to filter the markers according to the specificity score. The default value is 1 (no filtering).

Details

For each marker in the output list, the probe set and the corresponding score are shown. If annotate is TRUE, the gene symbol and the entrez gene id are shown. The score is used to rank the markers according to their specificity. The score values range from 0 to 1. Values near 0 would indicate high specificity and large values closer to 1 would indicate low specificity.

Value

A list with marker genes associated with each sample type.

Author(s)

Khadija El Amrani <khadija.el-amrani@charite.de>

Examples

```
data("ds2.mat")
res.list <- getMarkerGenes(ds2.mat, samples2compare="all", annotate=TRUE,
chip="hgu133a", score.cutoff=1)
names(res.list)
## show the first 20 markers of liver
res.list[["liver_markers"]][1:20]
```

grid-internal *Internal MGFM Functions*

Description

Internal MGFM functions

Details

These are not intended to be called by the user.

Index

- * **dataset**
 - ds2.mat, [2](#)
- * **internal**
 - grid-internal, [5](#)
- * **marker genes**
 - getHtmlpage, [3](#)
 - getMarkerGenes, [4](#)
- * **microarray data**
 - getHtmlpage, [3](#)
 - getMarkerGenes, [4](#)
- * **package**
 - MGFM-package, [2](#)
 - .checkIfPkgInstalled (grid-internal), [5](#)
 - .get.annotation (grid-internal), [5](#)
 - .isMarker (grid-internal), [5](#)

ds2.mat, [2](#)

getHtmlpage, [3](#)
getMarkerGenes, [3](#), [4](#)
grid-internal, [5](#)

htmlpage, [3](#)

matrix, [2](#)
MGFM (MGFM-package), [2](#)
MGFM-package, [2](#)