

# Package ‘cytolib’

February 20, 2025

**Type** Package

**Title** C++ infrastructure for representing and interacting with the gated cytometry data

**Version** 2.19.3

**Date** 2017-08-07

**Author** Mike Jiang

**Maintainer** Mike Jiang <mike@ozette.com>

**Description** This package provides the core data structure and API to represent and interact with the gated cytometry data.

**License** AGPL-3.0-only

**License\_restricts\_use** no

**LazyLoad** yes

**Imports** RProtoBufLib

**Depends** R (>= 3.4)

**Suggests** knitr, rmarkdown

**LinkingTo** BH(>= 1.84.0.0), RProtoBufLib(>= 2.13.1), Rhdf5lib

**biocViews** ImmunoOncology, FlowCytometry, DataImport, Preprocessing, DataRepresentation

**VignetteBuilder** knitr

**SystemRequirements** GNU make, C++11

**RoxygenNote** 7.1.2

**Biarch** TRUE

**git\_url** <https://git.bioconductor.org/packages/cytolib>

**git\_branch** devel

**git\_last\_commit** 1f886d9

**git\_last\_commit\_date** 2025-01-29

**Repository** Bioconductor 3.21

**Date/Publication** 2025-02-20

## Contents

cytolib\_LdFlags . . . . . 2

**Index** . . . . . **3**

---

cytolib\_LdFlags      *Output the LD flags for building against cytolib. These flags are propagated to sourceCxx via the inlineCxxPlugin (defined below) and to packages via a line in Makevars[.win] like this:*

---

### Description

```
PKG_LIBS += $(shell "$R_HOME/bin/$R_ARCH_BIN/Rscript.exe" -e "cytolib::cytolib_LdFlags()")
```

### Usage

```
cytolib_LdFlags()
```

# Index

cytolib\_LdFlags, [2](#)