

# Package ‘DelayedDataFrame’

January 29, 2026

**Title** Delayed operation on DataFrame using standard DataFrame metaphor

**Version** 1.26.0

**Description** Based on the standard DataFrame metaphor, we are trying to implement the feature of delayed operation on the DelayedDataFrame, with a slot of lazyIndex, which saves the mapping indexes for each column of DelayedDataFrame. Methods like show, validity check, [/[[ subsetting, rbind/cbind are implemented for DelayedDataFrame to be operated around lazyIndex. The listData slot stays untouched until a realization call e.g., DataFrame constructor OR as.list() is invoked.

**biocViews** Infrastructure, DataRepresentation

**Depends** R (>= 3.6), S4Vectors (>= 0.23.19), DelayedArray (>= 0.7.5)

**License** GPL-3

**Encoding** UTF-8

**URL** <https://github.com/Bioconductor/DelayedDataFrame>

**BugReports** <https://github.com/Bioconductor/DelayedDataFrame/issues>

**Imports** methods, stats, BiocGenerics

**RoxygenNote** 7.0.2

**Suggests** testthat, knitr, rmarkdown, BiocStyle, SeqArray, GDSArray

**Collate** LazyIndex-class.R DelayedDataFrame-class.R  
DelayedDataFrame-method.R

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/DelayedDataFrame>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 27e048f

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-29

**Author** Qian Liu [aut, cre],  
Hervé Pagès [aut],  
Martin Morgan [aut]

**Maintainer** Qian Liu <Qian.Liu@roswellpark.org>

## Contents

|                                           |   |
|-------------------------------------------|---|
| as.list,DelayedDataFrame-method . . . . . | 2 |
| DelayedDataFrame . . . . .                | 3 |
| LazyIndex-class . . . . .                 | 4 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>6</b> |
|--------------|----------|

---

as.list,DelayedDataFrame-method

*DelayedDataFrame related methods.*

---

## Description

as.list, rbind would incur realization of the lazyIndex slot in DelayedDataFrame object.

cbind for DelayedDataFrame inherits the lazyIndex's if inputs have any DelayedDataFrame objects. Otherwise, return a new DelayedDataFrame with NULL lazyIndexes.

## Usage

```
## S4 method for signature 'DelayedDataFrame'
as.list(x, use.names = TRUE)

## S4 method for signature 'DelayedDataFrame'
names(x)

## S4 method for signature 'DelayedDataFrame'
cbind(..., deparse.level = 1)

## S4 method for signature 'DelayedDataFrame'
bindROWS(
  x,
  objects = list(),
  use.names = TRUE,
  ignore.mcols = FALSE,
  check = TRUE
)

## S4 method for signature 'DelayedDataFrame,ANY'
extractROWS(x, i)

## S4 method for signature 'DelayedDataFrame'
extractCOLS(x, i)

## S4 method for signature 'DelayedDataFrame'
replaceCOLS(x, i, value)

## S4 method for signature 'DelayedDataFrame'
mergeROWS(x, i, value)

## S4 method for signature 'DelayedDataFrame,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]
```

**Arguments**

|                            |                                                                                                                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>             | <code>as.list,DelayedDataFrame</code> : a <code>DelayedDataFrame</code> object. OR, <code>[,DelayedDataFrame</code> : <code>DelayedDataFrame</code> object to be subsetted.                                                                                          |
| <code>use.names</code>     | <code>as.list,DelayedDataFrame</code> : whether to use the colnames of <code>DelayedDataFrame</code> as the names for the returned list. OR, <code>bindROWS,DelayedDataFrame</code> : whether to use rownames of the input arguments. Default is <code>TRUE</code> . |
| <code>...</code>           | <code>cbind,DelayedDataFrame</code> : One or more vector-like or matrix-like objects. These can be given as named arguments. OR, <code>[,DelayedDataFrame</code> : other arguments to pass.                                                                          |
| <code>deparse.level</code> | See ‘ <code>?base::cbind</code> ’ for a description of this argument.                                                                                                                                                                                                |
| <code>objects</code>       | the <code>DelayedDataFrame</code> objects to be passed into <code>bindROWS</code> .                                                                                                                                                                                  |
| <code>ignore.mcols</code>  | Logical. This argument is ignored for <code>bindROWS,DelayedDataFrame</code> .                                                                                                                                                                                       |
| <code>check</code>         | Logical. This argument is ignored for <code>bindROWS,DelayedDataFrame</code> .                                                                                                                                                                                       |
| <code>i</code>             | row subscript                                                                                                                                                                                                                                                        |
| <code>value</code>         | the new values in the <code>i, j</code> subscripts of <code>DelayedDataFrame</code> object.                                                                                                                                                                          |
| <code>j</code>             | col subscript                                                                                                                                                                                                                                                        |
| <code>drop</code>          | if drop with reduced dimension, default is <code>TRUE</code> .                                                                                                                                                                                                       |

**Value**

colnames of `DelayedDataFrame`

---

|                               |                               |
|-------------------------------|-------------------------------|
| <code>DelayedDataFrame</code> | <i>DelayedDataFrame-class</i> |
|-------------------------------|-------------------------------|

---

**Description**

The `DelayedDataFrame` class extends the `DataFrame` class and supports the storage of any type of object (with ‘`length`’ and ‘`[]`’ methods) as columns.

the `lazyIndex` slot getter and setter for `DelayedDataFrame` object.

the coercion method between `DataFrame` and `DelayedDataFrame` objects.

**Usage**

```
DelayedDataFrame(..., row.names = NULL, check.names = TRUE)

## S4 method for signature 'DelayedDataFrame'
lazyIndex(x)

.from_DataFrame_to_DelayedDataFrame(from)

.from_DelayedDataFrame_to_DFrame(from, to = "DFrame", strict = TRUE)

lazyIndex(x) <- value

## S4 replacement method for signature 'DelayedDataFrame'
lazyIndex(x) <- value
```

**Arguments**

|                          |                                                                                                                                                                                                                                                           |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>...</code>         | the arguments to pass into construction of a new <code>DelayedDataFrame</code> .                                                                                                                                                                          |
| <code>row.names</code>   | the rownames for the newly constructed <code>DelayedDataFrame</code> object.                                                                                                                                                                              |
| <code>check.names</code> | logical. If 'TRUE' then the names of the variables in the <code>DelayedDataFrame</code> are checked to ensure that they are syntactically valid variable names and are not duplicated. If necessary they are adjusted (by 'make.names') so that they are. |
| <code>x</code>           | the <code>DelayedDataFrame</code> object.                                                                                                                                                                                                                 |
| <code>from</code>        | the object to be converted.                                                                                                                                                                                                                               |
| <code>to</code>          | the class of object to be returned by coercion.                                                                                                                                                                                                           |
| <code>strict</code>      | Logical. Whether to force return a <code>DataFrame</code> .                                                                                                                                                                                               |
| <code>value</code>       | the new value of <code>lazyIndex</code> slot for <code>DelayedDataFrame</code> object.                                                                                                                                                                    |

**Details**

The `DelayedDataFrame` inherits from `DataFrame` and behaves very similarly in terms of construction, subsetting, splitting, combining, etc. The most notable exception is that The additional slot of `lazyIndex`, enables `DelayedArray` (with different back-ends) columns to share indexes when possible.

Please be very careful to use this `replace` method for `lazyIndex` slot. Because it only replace the `lazyIndex` slot, but not necessarily the `nrow` and `rownames` slots. If you want to have synchronized subsetting for all slots, the `[]` method should be used.

**Value**

`lazyIndex<-`: the `DelayedDataFrame` object with new value of `lazyIndex` slot.

**Examples**

```
DDF <- DelayedDataFrame(letters, LETTERS)
DDF1 <- DDF[1:10,]
DDF1
lazyIndex(DDF1)
as(DDF1, "DataFrame")
```

---

LazyIndex-class

*The LazyIndex class and methods.*

---

**Description**

The `LazyIndex` class is designed to carry mapping indexes for `DelayedDataFrame` columns. So that some operations (e.g., subsetting) on `DelayedDataFrame` are delayed until a realization call is incurred. (e.g., `as.list()`, `DataFrame()`, ...)

`LazyIndex` constructor.

the subsetting method for `LazyIndex` object.

**Usage**

```

LazyIndex(listData = list(), index = integer())

## S4 method for signature 'LazyIndex'
cbind(..., deparse.level = 1)

## S4 method for signature 'LazyIndex,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

```

**Arguments**

|                            |                                                                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>listData</code>      | the list data for all mapping indexes that are used in corresponding <code>DelayedDataFrame</code> object.                          |
| <code>index</code>         | the position of mapping indexes in <code>listData</code> for each column of the corresponding <code>DelayedDataFrame</code> object. |
| <code>...</code>           | <code>LazyIndex</code> objects.                                                                                                     |
| <code>deparse.level</code> | See <code>?base::cbind</code> for a description of this argument.                                                                   |
| <code>x</code>             | <code>LazyIndex</code> object.                                                                                                      |
| <code>i</code>             | row subscript for <code>LazyIndex</code> , which will subset the <code>listData</code> slot.                                        |
| <code>j</code>             | column subscript for <code>LazyIndex</code> , which will subset the <code>index</code> slot.                                        |
| <code>drop</code>          | Logical. Whether to drop the dimension if any of the dimensions has length 1. Default is <code>TRUE</code> .                        |

**Details**

the `cbind, LazyIndex` method is defined to bind the `LazyIndexes` column-wise when `cbind, DelayedDataFrame` function is called.

**Value**

a `LazyIndex` object.

# Index

`.DelayedDataFrame (DelayedDataFrame)`, [3](#)  
`.LazyIndex (LazyIndex-class)`, [4](#)  
`.from_DataFrame_to_DelayedDataFrame`  
    (`DelayedDataFrame`), [3](#)  
`.from_DelayedDataFrame_to_DFrame`  
    (`DelayedDataFrame`), [3](#)  
`[,DelayedDataFrame,ANY,ANY,ANY-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
`[,LazyIndex,ANY,ANY,ANY-method`  
    (`LazyIndex-class`), [4](#)  
`[,LazyIndex-method (LazyIndex-class)`, [4](#)  
  
`as.list`,`DelayedDataFrame-method`, [2](#)  
  
`bindROWS`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
  
`cbind`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
`cbind`,`LazyIndex-method`  
    (`LazyIndex-class`), [4](#)  
`coerce (DelayedDataFrame)`, [3](#)  
`coerce,ANY,DelayedDataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
`coerce,DataFrame,DelayedDataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
`coerce,DelayedDataFrame,DataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
`coerce,DelayedDataFrame,DFrame-method`  
    (`DelayedDataFrame`), [3](#)  
`coerce,DFrame,DelayedDataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
  
`DelayedDataFrame`, [3](#)  
`DelayedDataFrame-class`  
    (`DelayedDataFrame`), [3](#)  
  
`extractCOLS`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
  
`extractROWS`,`DelayedDataFrame,ANY-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
`extractROWS`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
  
`LazyIndex (LazyIndex-class)`, [4](#)  
`lazyIndex (DelayedDataFrame)`, [3](#)  
`lazyIndex,DelayedDataFrame`  
    (`DelayedDataFrame`), [3](#)  
`lazyIndex,DelayedDataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
`LazyIndex-class`, [4](#)  
`lazyIndex<- (DelayedDataFrame)`, [3](#)  
`lazyIndex<- , (DelayedDataFrame)`, [3](#)  
`lazyIndex<- ,DelayedDataFrame-method`  
    (`DelayedDataFrame`), [3](#)  
  
`mergeROWS`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
  
`names`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)  
  
`replaceCOLS`,`DelayedDataFrame-method`  
    (`as.list`,`DelayedDataFrame-method`),  
    [2](#)