

# Package ‘TDbasedUFEadv’

January 30, 2026

**Type** Package

**Title** Advanced package of tensor decomposition based unsupervised  
feature extraction

**Version** 1.10.0

**Language** en-US

**Description** This is an advanced version of TDbasedUFE, which is a comprehensive package to perform Tensor decomposition based unsupervised feature extraction. In contrast to TDbasedUFE which can perform simple the feature selection and the multiomics analyses, this package can perform more complicated and advanced features, but they are not so popularly required. Only users who require more specific features can make use of its functionality.

**biocViews** GeneExpression, FeatureExtraction, MethylationArray,  
SingleCell, Software

**License** GPL-3

**Encoding** UTF-8

**Imports** TDbasedUFE, Biobase, GenomicRanges, utils, rTensor, methods,  
graphics, RTCGA, stats, enrichplot, DOSE, STRINGdb, enrichR,  
hash, shiny

**RoxygenNote** 7.2.3

**BugReports** <https://github.com/tagtag/TDbasedUFEadv/issues>

**URL** <https://github.com/tagtag/TDbasedUFEadv>

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0), RTCGA.rnaseq,  
RTCGA.clinical, BiocStyle, MOFAdat

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/TDbasedUFEadv>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 3045ab4

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-29

**Author** Y-h. Taguchi [aut, cre] (ORCID:  
<https://orcid.org/0000-0003-0867-8986>)

**Maintainer** Y-h. Taguchi <tag@granular.com>

## Contents

TDbasedUFEadv-package	2
computeSVD	3
prepareCondDrugandDisease	3
prepareCondTCGA	4
prepareexpDrugandDisease	5
prepareTensorfromList	5
prepareTensorfromMatrix	6
prepareTensorRect	6
selectFeatureProj	7
selectFeatureRect	8
selectFeatureTransRect	9
TensorRect-class	10
transSVD	10

## Index

11

---

TDbasedUFEadv-package *TDbasedUFEadv: Advanced package of tensor decomposition based unsupervised feature extraction*

---

## Description

This is an advanced version of TDbasedUFE, which is a comprehensive package to perform Tensor decomposition based unsupervised feature extraction. In contrast to TDbasedUFE which can perform simple the feature selection and the multiomics analyses, this package can perform more complicated and advanced features, but they are not so popularly required. Only users who require more specific features can make use of its functionality.

## Author(s)

**Maintainer:** Y-h. Taguchi <tag@granular.com> ([ORCID](#))

## See Also

Useful links:

- <https://github.com/tagtag/TDbasedUFEadv>
- Report bugs at <https://github.com/tagtag/TDbasedUFEadv/issues>

---

computeSVD	<i>Title</i> Perform SVD toward reduced matrix generated from a tensor with partial summation
------------	---

---

## Description

Title Perform SVD toward reduced matrix generated from a tensor with partial summation

## Usage

```
computeSVD(matrix1, matrix2, dim = 10L, scale = TRUE)
```

## Arguments

matrix1	The first original matrix that generates a tensor
matrix2	The second original matrix that generates a tensor
dim	The number of singular value vectors to be computed
scale	If matrix should be scaled or not

## Value

Singular value vectors attributed to two sets of objects associated with singular value vectors attributed to features, by multiplying

## Examples

```
matrix1 <- matrix(runif(200),20)
matrix2 <- matrix(runif(400),20)
SVD <- computeSVD(matrix1,matrix2)
```

---

prepareCondDrugandDisease	<i>Prepare condition matrix for expDrug</i>
---------------------------	---

---

## Description

Prepare condition matrix for expDrug

## Usage

```
prepareCondDrugandDisease(expDrug)
```

## Arguments

expDrug	input gene expression profile
---------	-------------------------------

## Value

Condition matrix for expDrug

## Examples

```
library(RTCGA.rnaseq)
Cancer_cell_lines <- list(ACC.rnaseq,BLCA.rnaseq,BRCA.rnaseq)
Drug_and_Disease <- prepareexpDrugandDisease(Cancer_cell_lines)
Cond <- prepareCondDrugandDisease(Drug_and_Disease$expDrug)
```

---

prepareCondTCGA	<i>Prepare Sample label for TCGA data</i>
-----------------	---

---

## Description

Prepare Sample label for TCGA data

## Usage

```
prepareCondTCGA(
  Multi_sample,
  Clinical,
  ID_column_of_Multi_sample,
  ID_column_of_Clinical
)
```

## Arguments

Multi_sample	list of sample ids
Clinical	List of clinical data matrix from RTCGA.clinical
ID_column_of_Multi_sample	Column numbers used for conditions
ID_column_of_Clinical	Column numbers that include corresponding sample ids in clinical data

## Value

list of sample labels

## Examples

```
library(RTCGA.clinical)
library(RTCGA.rnaseq)
Clinical <- list(BLCA.clinical, BRCA.clinical, CESC.clinical, COAD.clinical)
Multi_sample <- list(
  BLCA.rnaseq[seq_len(100), 1, drop = FALSE],
  BRCA.rnaseq[seq_len(100), 1, drop = FALSE],
  CESC.rnaseq[seq_len(100), 1, drop = FALSE],
  COAD.rnaseq[seq_len(100), 1, drop = FALSE]
)
ID_column_of_Multi_sample <- c(770, 1482, 773, 791)
ID_column_of_Clinical <- c(20, 20, 12, 14)
cond <- prepareCondTCGA(
  Multi_sample, Clinical,
  ID_column_of_Multi_sample, ID_column_of_Clinical
)
```

---

```
prepareexpDrugandDisease
```

*Generating gene expression of drug treated cell lines and a disease cell line*

---

### Description

Generating gene expression of drug treated cell lines and a disease cell line

### Usage

```
prepareexpDrugandDisease(Cancer_cell_lines)
```

### Arguments

`Cancer_cell_lines`  
  <- list(ACC.rnaseq,BLCA.rnaseq,BRCA.rnaseq) list that includes individual data set from RTCGA.rnaseq

### Value

list of expDrug and expDisease

### Examples

```
library(RTCGA.rnaseq)
Cancer_cell_lines <- list(ACC.rnaseq,BLCA.rnaseq,BRCA.rnaseq)
Drug_and_Disease <- prepareexpDrugandDisease(Cancer_cell_lines)
```

---

```
prepareTensorfromList
```

*Prepare tensor from a list that includes multiple profiles*

---

### Description

Prepare tensor from a list that includes multiple profiles

### Usage

```
prepareTensorfromList(Multi, proj_dim)
```

### Arguments

`Multi`            a list that includes multiple profiles  
`proj_dim`        the number of projection dimensions

### Value

a tensor as a bundle of singular value vectors obtained by applying SVD to individual omics

**Examples**

```
library(MOFAdata)
data("CLL_data")
data("CLL_covariates")
Z <- prepareTensorfromList(CLЛ_data,10L)
```

**prepareTensorfromMatrix**

*Generate tensor from two matrices*

**Description**

Generate tensor from two matrices

**Usage**

```
prepareTensorfromMatrix(matrix1, matrix2)
```

**Arguments**

matrix1	the first input matrix
matrix2	the second input matrix

**Value**

A tensor generated from the first and second matrices

**Examples**

```
Z <- prepareTensorfromMatrix(matrix(runif(100),10),matrix(runif(100),10))
```

**prepareTensorRect**

*Prepare tensor generated from two matrices that share samples*

**Description**

Prepare tensor generated from two matrices that share samples

**Usage**

```
prepareTensorRect(
  sample,
  feature,
  value,
  featureRange = GRanges(NULL),
  sampleData = list(NULL)
)
```

**Arguments**

sample	Character vector of sample names
feature	list of features from two matrices
value	array, contents of
featureRange	Genomic Ranges to be associated with features
sampleData	List of conditional labeling associated with samples

**Value**

Tensor generated from two matrices that share samples

**Examples**

```
matrix1 <- matrix(runif(1000),200) #row features, column samples
matrix2 <- matrix(runif(2000),400) #row features, column samples
Z <- prepareTensorfromMatrix(t(matrix1),t(matrix2))
Z <- prepareTensorRect(sample=as.character(seq_len(50)),
feature=list(as.character(seq_len(200)),as.character(seq_len(400))),
sampleData=list(rep(seq_len(2),each=25)),value=Z)
```

selectFeatureProj

*Select feature when projection strategy is employed for the case where features are shared with multiple omics profiles*

**Description**

Select feature when projection strategy is employed for the case where features are shared with multiple omics profiles

**Usage**

```
selectFeatureProj(
  HOSVD,
  Multi,
  cond,
  de = 1e-04,
  p0 = 0.01,
  breaks = 100L,
  input_all = NULL
)
```

**Arguments**

HOSVD	HOSVD
Multi	list of omics profiles, row: sample, column: feature
cond	list of conditions for individual omics profiles
de	initial value for optimization of standard deviation
p0	Threshold P-value
breaks	The number of bins of histogram of P-values
input_all	The number of selected feature. if null, interactive mode is activated

**Value**

list composed of logical vector that represent which features are selected and p-values

**Examples**

```
library(TDbasedUFE)
Multi <- list(matrix(runif(1000),10),matrix(runif(1000),10),
  matrix(runif(1000),10),matrix(runif(1000),10))
Z <- prepareTensorfromList(Multi,10L)
Z <- aperm(Z,c(2,1,3))
Z <- PrepareSummarizedExperimentTensor(feature =as.character(1:10),
  sample=array("",1),value=Z)
HOSVD <- computeHosvd(Z)
cond <- rep(list(rep(1:2,each=5)),4)
index <- selectFeatureProj(HOSVD,Multi,cond,de=0.1,input_all=2)
```

**selectFeatureRect**

*Select features through the selection of singular value vectors*

**Description**

Select features through the selection of singular value vectors

**Usage**

```
selectFeatureRect(
  SVD,
  cond,
  de = rep(1e-04, 2),
  p0 = 0.01,
  breaks = 100L,
  input_all = NULL
)
```

**Arguments**

SVD	SVD computed from matrix generated by partial summation of a tensor
cond	Condition to select singular value vectors
de	Initial values to be used for optimization of standard deviation
p0	Threshold value for the significance
breaks	Number of bins of histogram of P-values
input_all	The ID of selected singular value vectors. If it is null, interactive mode is activated.

**Value**

List of lists that includes P-vales as well as if individual features selected.

## Examples

```
set.seed(0)
matrix1 <- matrix(runif(2000),200)
matrix2 <- matrix(runif(4000),200)
SVD <- computeSVD(matrix1,matrix2)
index_all <- selectFeatureTransRect(SVD,
list(NULL,rep(seq_len(2),each=5),rep(seq_len(2),each=10)),de=rep(0.5,2),
input_all=1)
```

### selectFeatureTransRect

*Select features for a tensor generated from two matrices that share samples.*

## Description

Select features for a tensor generated from two matrices that share samples.

## Usage

```
selectFeatureTransRect(
  HOSVD,
  cond,
  de = rep(1e-04, 2),
  p0 = 0.01,
  breaks = 100L,
  input_all = NULL
)
```

## Arguments

HOSVD	HOSVD
cond	list of conditions
de	initial values for optimization of standard deviation
p0	threshold value for the significance
breaks	number of bins of the histogram of P-values
input_all	The selected singular value vectors attributed to samples. if NULL, interactive mode

## Value

list of logical vector that represent if the individual features are selected and P-values.

## Examples

```
library(TDbasedUFE)
set.seed(0)
matrix1 <- matrix(runif(1000),20) #row features, column samples
matrix2 <- matrix(runif(2000),40) #row features, column samples
Z <- prepareTensorfromMatrix(t(matrix1),t(matrix2))
```

```

Z <- prepareTensorRect(sample=as.character(seq_len(50)),
feature=list(as.character(seq_len(20)),as.character(seq_len(40))),
sampleData=list(rep(seq_len(2),each=25)),value=Z)
HOSVD <- computeHosvd(Z)
cond <- list(attr(Z,"sampleData")[[1]],NULL,NULL)
index_all <- selectFeatureTransRect(HOSVD,cond,de=c(0.1,0.1),
input_all=2,p0=1e-10)

```

TensorRect-class *Class definitions*

## Description

Class definitions

## Slots

sample character.  
 feature list.  
 value array.  
 featureRange GRanges.  
 sampleData list.

transSVD *Convert SVD to that for the case where samples are shared between two matrices*

## Description

Convert SVD to that for the case where samples are shared between two matrices

## Usage

transSVD(SVD)

## Arguments

SVD input SVD object generated from computeSVD function

## Value

converted SVD objects

## Examples

```

matrix1 <- matrix(runif(200),20)
matrix2 <- matrix(runif(400),20)
SVD <- computeSVD(matrix1,matrix2)
SVD <- transSVD(SVD)

```

# Index

## \* **internal**

    TDbasedUFEadv-package, [2](#)  
    computeSVD, [3](#)  
    prepareCondDrugandDisease, [3](#)  
    prepareCondTCGA, [4](#)  
    prepareexpDrugandDisease, [5](#)  
    prepareTensorfromList, [5](#)  
    prepareTensorfromMatrix, [6](#)  
    prepareTensorRect, [6](#)  
    selectFeatureProj, [7](#)  
    selectFeatureRect, [8](#)  
    selectFeatureTransRect, [9](#)  
    TDbasedUFEadv (TDbasedUFEadv-package), [2](#)  
    TDbasedUFEadv-package, [2](#)  
    TensorRect-class, [10](#)  
    transSVD, [10](#)