

Package ‘BindingSiteFinder’

February 1, 2026

Type Package

Title Binding site defintion based on iCLIP data

Version 2.9.0

Description Precise knowledge on the binding sites of an RNA-binding protein (RBP) is key to understand (post-) transcriptional regulatory processes. Here we present a workflow that describes how exact binding sites can be defined from iCLIP data. The package provides functions for binding site definition and result visualization. For details please see the vignette.

License Artistic-2.0

Encoding UTF-8

VignetteBuilder knitr

Imports tidyverse, tibble, plyr, matrixStats, stats, ggplot2, methods, rtracklayer, S4Vectors, ggforce, GenomeInfoDb, ComplexHeatmap, RColorBrewer, lifecycle, rlang,forcats, dplyr, GenomicFeatures, IRanges, kableExtra, ggdist

Depends GenomicRanges, R (>= 4.2)

Suggests testthat, BiocStyle, knitr, rmarkdown, GenomicAlignments, scales, Gviz, xlsx, GGally, patchwork, viridis, ggplotify, SummarizedExperiment, DESeq2, ggpointdensity, ggrastr, ash, txdbmaker, ggrepel, stringr

RoxygenNote 7.3.2

Collate 'AllClasses.R' 'AllGenerics.R' 'Functions.R' 'methods.R'
'bindingsites.R' 'helper.R' 'PlotFunction.R'
'CoverageFunctions.R' 'workflow.R' 'helperSpecific.R'
'exports.R' 'coveragePlots.R' 'bsfind.R' 'helperPlots.R'
'differentialFunctions.R' 'differentialPlots.R'

biocViews Sequencing, GeneExpression, GeneRegulation,
FunctionalGenomics, Coverage, DataImport

BugReports <https://github.com/ZarnackGroup/BindingSiteFinder/issues>

git_url <https://git.bioconductor.org/packages/BindingSiteFinder>

git_branch devel
git_last_commit 885c4f6
git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-02-01

Author Mirko Brüggemann [aut, cre] (ORCID:
[<https://orcid.org/0000-0002-1778-0248>](https://orcid.org/0000-0002-1778-0248)),
 Melina Klostermann [aut] (ORCID:
[<https://orcid.org/0000-0003-3122-1095>](https://orcid.org/0000-0003-3122-1095)),
 Kathi Zarnack [aut] (ORCID: <<https://orcid.org/0000-0003-3527-3378>>)

Maintainer Mirko Brüggemann <mirko.brueggemann@mail.de>

Contents

add-BSFDataSet	3
annotateWithScore	5
assignToGenes	6
assignToTranscriptRegions	8
bindingSiteCoveragePlot	9
bindingSiteDefinednessPlot	11
BSFDataSet	12
BSFind	13
calculateBsBackground	18
calculateBsFoldChange	20
calculateSignalToFlankScore	23
clipCoverage	24
collapseReplicates	26
combineBSF	27
coverageOverRanges	29
duplicatedSitesPlot	30
estimateBsWidth	31
estimateBsWidthPlot	34
exportTargetGenes	34
exportToBED	35
filterBsBackground	36
geneOverlapsPlot	39
geneRegulationPlot	40
getMeta	42
getName	42
getRanges	43
getSignal	44
getSummary	45
globalScorePlot	46
imputeBsDifferencesForTestdata	46
makeBindingSites	47
makeBsSummaryPlot	49

mergeCrosslinkDiagnosticsPlot	50
mergeSummaryPlot	51
plotBsBackgroundFilter	52
plotBsMA	53
plotBsVolcano	54
processingStepsFlowChart	55
processingStepsTable	56
pureClipGeneWiseFilter	57
pureClipGlobalFilter	58
pureClipGlobalFilterPlot	59
quickFigure	60
rangeCoveragePlot	61
reproducibilityCutoffPlot	63
reproducibilityFilter	64
reproducibilityFilterPlot	65
reproducibilitySamplesPlot	66
reproducibilityScatterPlot	67
setMeta	68
setName	69
setRanges	70
setSignal	71
setSummary	72
show	73
subset-BSFDataSet	73
summary	74
supportRatio	75
supportRatioPlot	76
targetGeneSpectrumPlot	77
transcriptRegionOverlapsPlot	78
transcriptRegionSpectrumPlot	79

Index**81**

add-BSFDataSet	<i>Add two BSFDataSet objects</i>
----------------	---

Description

Use '+' to add two objects of type [BSFDataSet](#) to each other.

Usage

```
## S4 method for signature 'BSFDataSet,BSFDataSet'  
e1 + e2
```

Arguments

e1	BSFDataSet; the first dataset
e2	BSFDataSet; the second dataset

Details

Meta data is extended by binding both input tables together. Ranges are added by re-centering partially overlapping ranges according to their combined coverage maximum.

Input ranges must be of the same size. Differently size objects cannot be added. For this and other usecases please see [combineBSF](#).

Value

A [BSFDataSet](#) object with ranges, signal and meta data from both inputs.

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)

# split ranges in two groups
allRanges = getRanges(bds)
set.seed(1234)
idx = sample(1:length(allRanges), size = length(allRanges)/2, replace = FALSE)
r1 = allRanges[idx]
r2 = allRanges[-idx]

# split meta data
allMeta = getMeta(bds)
m1 = allMeta[1:2,]
m2 = allMeta[3:4,]

# create new objects
bds1 = setRanges(bds, r1)
bds2 = setRanges(bds, r2)
bds1 = setMeta(bds1, m1)
bds2 = setMeta(bds2, m2)
bds1 = setName(bds1, "test1")
bds2 = setName(bds2, "test2")

# merge two objects with '+' operator
c1 = bds1 + bds2
```

annotateWithScore *Annotation function for BSFDataSet object*

Description

This function can be used to annotate a BSFDataSet object with merged binding sites with scores from the initial ranges (eg. PureCLIP scores).

Usage

```
annotateWithScore(  
  object,  
  match.ranges = NULL,  
  match.score = "score",  
  match.option = c("max", "sum", "mean"),  
  scoreRanges = lifecycle::deprecated(),  
  MatchColScore = lifecycle::deprecated(),  
  quiet = FALSE  
)
```

Arguments

object	a BSFDataSet object
match.ranges	a GRanges object, with numeric column for the score to match
match.score	character; meta column name of the crosslink site GenomicRanges object that holds the score to match
match.option	character; option how score should be matched
scoreRanges	deprecated -> use match.ranges instead
MatchColScore	deprecated -> use match.score instead
quiet	logical; whether to print messages

Details

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class BSFDataSet with updated meta columns of the ranges

See Also

[BSFind](#), [globalScorePlot](#)

Examples

```

if (.Platform$OS.type != "windows") {
  # load data
  csFile <- system.file("extdata", "PureCLIP_crosslink_sites_examples.bed",
                        package="BindingSiteFinder")
  cs = rtracklayer::import(con = csFile, format = "BED",
                           extraCols=c("additionalScores" = "character"))
  cs$additionalScores = NULL
  clipFiles <- system.file("extdata", package="BindingSiteFinder")
  # two experimental conditions
  meta = data.frame(
    id = c(1,2,3,4),
    condition = factor(c("WT", "WT", "KD", "KD"),
                        levels = c("KD", "WT")),
    clPlus = list.files(clipFiles, pattern = "plus.bw$", full.names = TRUE),
    clMinus = list.files(clipFiles, pattern = "minus.bw$",
                        full.names = TRUE))
  bds = BSFDataSetFromBigWig(ranges = cs, meta = meta, silent = TRUE)

  # merge binding sites
  bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
                           minCrosslinks = 2, minClSites = 1)

  # annotate with original pureCLIP score
  bdsRe = annotateWithScore(bds, cs)
}

```

assignToGenes

Assign binding sites to their hosting genes

Description

Function that assigns each binding site in the [BSFDataSet](#) to its hosting gene given a gene annotation (anno.annoDB, anno.genes).

Usage

```

assignToGenes(
  object,
  overlaps = c("frequency", "hierarchy", "remove", "keep"),
  overlaps.rule = NULL,
  anno.annoDB = NULL,
  anno.genes = NULL,
  match.geneID = "gene_id",
  match.geneName = "gene_name",
  match.geneType = "gene_type",
  quiet = FALSE
)

```

Arguments

object	a BSFDataSet object with stored binding sites. This means that ranges should be > 1
overlaps	character; how overlapping gene loci should be handled.
overlaps.rule	character vector; a vector of gene type that should be used to handle overlapping cases in a hierarchical manor. The order of the vector is the order of the hierarchy.
anno.annoDB	an object of class OrganismDbi that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class GenomicRanges that represents the gene ranges directly
match.geneID	character; meta column name of the gene ID
match.geneName	character; meta column name of the gene name
match.geneType	character; meta column name of the gene type
quiet	logical; whether to print messages

Details

Regardless of the annotation source that is being used, the respective meta information about the genes have to be present. They can be set by the `match.geneID`, `match.geneName` and `match.geneType` arguments.

In the case of overlapping gene annotation, a single binding site will be associated with multiple genes. The `overlaps` parameter allows to decide in these cases. Option ‘frequency’ will take the most frequently observed gene type, option ‘hierarchy’ works in conjunction with a user defined rule (`overlaps.rule`). Options ‘remove’ and ‘keep’ will remove or keep all overlapping cases, respectively.

Note that if an overlaps exists, but gene types are identical options ‘frequency’ and ‘hierarchy’ will cause the gene that was seen first to be selected as representative.

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSFDataSet](#) with binding sites having hosting gene information added to their meta columns.

See Also

[BSFind](#), [geneOverlapsPlot](#), [targetGeneSpectrumPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
```

```
bds = assignToGenes(bds, anno.genes = gns)
```

assignToTranscriptRegions

Assign binding sites to their hosting transcript regions

Description

Function that assigns each binding site in the [BSFDataSet](#) to its hosting transcript region given an annotation database (anno.annoDB), or a GRanges list / [CompressedGRangesList](#) (anno.transcriptRegionList) that holds the ranges for the transcript regions of interest.

Usage

```
assignToTranscriptRegions(
  object,
  overlaps = c("frequency", "hierarchy", "flag", "remove"),
  overlaps.rule = NULL,
  anno.annoDB = NULL,
  anno.transcriptRegionList = NULL,
  normalize.exclude.upper = 0.02,
  normalize.exclude.lower = 0.02,
  quiet = FALSE
)
```

Arguments

object	a BSFDataSet object with stored binding sites. This means that ranges should be > 1
overlaps	character; how overlapping transcript regions should be handled.
overlaps.rule	character vector; a vector of transcript region names that should be used to handle overlapping cases in a hierarchical manor. The order of the vector is the order of the hierarchy.
anno.annoDB	an object of class OrganismDbi that contains the transcript region annotation (!!! Experimental !!!).
anno.transcriptRegionList	an object of class CompressedGRangesList that holds an ranges for each transcript region
normalize.exclude.upper	numeric; percentage value that indicates the upper boundary for transcript region length to be considered when calculating normalization factors for regions.
normalize.exclude.lower	numeric; percentage value that indicates the lower boundary for transcript region length to be considered when calculating normalization factors for regions.
quiet	logical; whether to print messages

Details

Since the assignment is based on the overlaps of annotated transcript ranges and binding sites, no matching meta data is needed.

In the case of transcript regions overlaps are very frequent. To resolve these cases the [overlaps](#) argument can be used. Option ‘frequency’ will take the most frequently observed transcript region, option ‘hierarchy’ works in conjunction with a user defined rule ([overlaps.rule](#)). Options ‘flag’ and ‘remove’ will label binding sites with an ambiguous tag or remove all overlapping cases, respectively.

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSFDataSet](#) with binding sites having hosting transcript region information added to their meta columns.

See Also

[BSFind](#), [transcriptRegionOverlapsPlot](#), [transcriptRegionSpectrumPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])

bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
```

bindingSiteCoveragePlot

Plot signal coverage of selected ranges

Description

Function plots the coverage of the CLIP data in the signal slot and plots it as coverage. The plot is centered around a given binding site, which can be selected by an index.

Usage

```
bindingSiteCoveragePlot(
  object,
  plotIdx,
  flankPos,
```

```

  shiftPos = NULL,
  mergeReplicates = FALSE,
  autoscale = FALSE,
  highlight = TRUE,
  showCentralRange = TRUE,
  customRange = NULL,
  customRange.name = "custom",
  customAnnotation = NULL,
  customAnnotation.name = "anno",
  title = NULL,
  colorPalette = NULL
)

```

Arguments

object	a BSFDataSet object
plotIdx	integer, index of the range to plot
flankPos	numeric, number of nucleotides by which the plotting frame is symmetrically extended
shiftPos	numeric, nucleotide positions by which the current plotting range should be shifted
mergeReplicates	logical, if replicates should be merge per condition (TRUE) or if every replicates should be shown separately (FALSE)
autoscale	logical, if y-axis should be scaled to the maximum for all replicates (TRUE), or not (FALSE)
highlight	logical, if the central range should be highlighted (TRUE), or not (FALSE)
showCentralRange	logical, if the central range should be shown (TRUE), or not (FALSE)
customRange	GenomicRanges, a custom range object to be shown underneath the coverage tracks
customRange.name	character, the name of the customRange track
customAnnotation	GenomicRanges or TxDb, a custom annotation for eg. gene, exons, etc. to be shown underneath the coverage tracks
customAnnotation.name	character, the name of the customAnnotation track
title	character, set plotting title
colorPalette	vector, hex colors used for the conditions

Value

an object of class `GVIZ`

See Also[BSFDataSet](#), [BSFind](#)**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bindingSiteCoveragePlot(bds, plotIdx = 3, flankPos = 10)
```

bindingSiteDefinednessPlot

*Binding site definedness plot***Description**

Binding site definedness is given by the percent of crosslinks that fall directly inside the binding site compare to those around the binding site. This plotting function shows the distribution of those percentage values grouped by what is indicated in the `by` argument.

Usage

```
bindingSiteDefinednessPlot(
  object,
  by = c("all", "transcript_region", "gene_type"),
  showN.genes = 5,
  show.others = FALSE
)
```

Arguments

<code>object</code>	a BSFDataSet object
<code>by</code>	character; the option by which the plot should be grouped by. Options are: "all", "transcript_region", "gene_type"
<code>showN.genes</code>	numeric; if <code>by</code> is 'gene_type', then this argument set the maximum number of groups to be shown in the plot
<code>show.others</code>	logical; whether to show 'others' category.

Details

If `by` = 'all', then all binding site are grouped into one distribution. For options 'transcript_region' and 'gene_type' binding sites are split into groups according to the respective assignment. This requires that the respective assignment function was executed on the dataset prior to calling this plot function.

Value

a plot of type `ggplot`

See Also

[BSFind](#), [calculateSignalToFlankScore](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,
  est.subsetChromosome = "chr22")
bds = calculateSignalToFlankScore(bds)
bindingSiteDefinednessPlot(bds)
```

BSFDataSet

BSFDataSet object and constructors

Description

BSFDataSet contains the class GenomicRanges, which is used to store input ranges. Alongside with the iCLIP signal in list structure and additional meta data as `data.frame`.

Usage

```
BSFDataSet(ranges, meta, signal, dropSeqlevels = TRUE, silent = FALSE)
```

```
BSFDataSet(ranges, meta, signal, dropSeqlevels = TRUE, silent = FALSE)
```

```
BSFDataSetFromBigWig(ranges, meta, silent = FALSE, dropSeqlevels = TRUE)
```

Arguments

<code>ranges</code>	a <code>GenomicRanges</code> with the desired ranges to process. The strand slot must be either <code>+</code> or <code>-</code> .
<code>meta</code>	a <code>data.frame</code> with at least two columns. The first column should be a unique numeric id. The second column holds sample type information, such as the condition.
<code>signal</code>	a list with the two entries <code>'signalPlus'</code> and <code>'signalMinus'</code> , following a special representation of <code>SimpleRleList</code> for counts per replicates (see details for more information).
<code>dropSeqlevels</code>	enforce seqnames to be the same in <code>ranges</code> and <code>signal</code> , by dropping unused seqlevels which is required for most downstream functions such as <code>coverageOverRanges</code>
<code>silent</code>	suppress messages but not warnings (TRUE/ FALSE)

Details

The ranges are enforced to have to have a "+" or "-" strand annotation, "*" is not allowed. They are expected to be of the same width and a warning is thrown otherwise.

The meta information is stored as `data.frame` with at least two required columns, 'id' and 'condition'. They are used to build the unique identifier for each replicate split by '_' (eg. id = 1 and condition = WT will result in 1_WT).

The meta data needs to have the additional columns 'clPlus' and 'clMinus' to be present if `BSFDataSetFromBigWig` is called. It is used to provide the location to the iCLIP coverage files to the import function. On object initialization these files are loaded and internally represented in the signal slot of the object (see `BSFDataSet`).

The iCLIP signal is stored in a special list structure. At the lowest level crosslink counts per nucleotide are stored as Rle per chromosome summarized as a `SimpleRleList`. Such a list exists for each replicate and must be named by the replicate identifier (eg. 1_WT). Therefore this list contains always exactly the same number of entries as the number of replicates in the dataset. Since we handle strands initially separated from each other this list must be given twice, once for each strand. The strand specific entries must be named 'signalPlus' and 'signalMinus'.

The option `dropSeqlevels` forces the seqnames of the ranges and the signal to be the same. If for a specific chromosome in the ranges no respective entry in the signal list can be found, then entries with that chromosome are dropped. This behavior is needed to keep the `BSFDataSet` object in sync, which is required for downstream functions such as `coverageOverRanges`

Value

A `BSFDataSet` object.

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
rng = getRanges(bds)
sgn = getSignal(bds)
mta = getMeta(bds)
bdsNew = BSFDataSet(ranges = rng, signal = sgn, meta = mta)
```

Description

This is the main function that performs the binding site definition analysis through the following steps:

1. Filter PureCLIP sites by their score distribution: `pureClipGlobalFilter`

2. Estimate the appropriate binding site width together with the optimal gene-wise filter level: [estimateBsWidth](#)
3. Filter PureCLIP sites by their score distribution per gene: [pureClipGeneWiseFilter](#)
4. Define equally sized binding sites: [makeBindingSites](#)
5. Perform replicate reproducibility filter: [reproducibilityFilter](#)
6. Assign binding sites to their hosting genes: [assignToGenes](#)
7. Assign binding sites to their hosting transcript regions: [assignToTranscriptRegions](#)
8. Re-assign PureCLIP scores to binding sites: [annotateWithScore](#)
9. Calculation of signal-to-flank ratio: [calculateSignalToFlankScore](#)

Usage

```
BSFind(
  object,
  bsSize = NULL,
  cutoff.geneWiseFilter = NULL,
  cutoff.globalFilter = 0.01,
  est.bsResolution = "medium",
  est.geneResolution = "medium",
  est.maxBsWidth = 13,
  est.minimumStepGain = 0.02,
  est.maxSites = Inf,
  est.subsetChromosome = "chr1",
  est.minLength = 2,
  est.offset = 1,
  est.sensitive = FALSE,
  est.sensitive.size = 5,
  est.sensitive.minLength = 2,
  merge.minLength = 2,
  merge.minCrosslinks = 2,
  merge.minC1Sites = 1,
  merge.CenterIsC1Site = TRUE,
  merge.CenterIsSummit = TRUE,
  repro.cutoff = NULL,
  repro.nReps = NULL,
  repro.minLength = 1,
  overlaps.geneWiseFilter = "keepSingle",
  overlaps.geneAssignment = "frequency",
  overlaps.rule.geneAssignment = NULL,
  overlaps.TranscriptRegions = "frequency",
  overlaps.rule.TranscriptRegions = NULL,
  stf.flank = "bs",
  stf.flank.size = NULL,
  match.score = "score",
  match.geneID = "gene_id",
  match.geneName = "gene_name",
  match.geneType = "gene_type",
```

```

  match.ranges.score = NULL,
  match.option.score = "max",
  anno.annoDB = NULL,
  anno.genes = NULL,
  anno.transcriptRegionList = NULL,
  quiet = FALSE,
  veryQuiet = FALSE,
  ...
)

```

Arguments

object	a BSFDataSet object with stored ranges
bsSize	an odd integer value specifying the size of the output binding sites
cutoff.geneWiseFilter	numeric; defines the cutoff for which sites to remove in in function pureClipGeneWiseFilter . The smallest step is 1% (0.01). A cutoff of 5% will remove the lowest 5% sites, given their score, on each gene, thus keeping the strongest 95%.
cutoff.globalFilter	numeric; defines the cutoff for which sites to keep, the smallest step is 1% (0.01) in function pureClipGlobalFilter
est.bsResolution	character; level of resolution of the binding site width in function estimateBsWidth
est.geneResolution	character; level of resolution of the gene-wise filtering in function estimateBsWidth
est.maxBsWidth	numeric; the largest binding site width which should be considered in the testing
est.minimumStepGain	numeric; the minimum additional gain in the score in percent the next binding site width has to have, to be selected as best option
est.maxSites	numeric; maximum number of PureCLIP sites that are used
est.subsetChromosome	character; define on which chromosome the estimation should be done in function estimateBsWidth
est.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
est.offset	constant added to the flanking count in the signal-to-flank ratio calculation to avoid division by Zero
est.sensitive	logical; whether to enable sensitive pre-filtering before binding site merging or not
est.sensitive.size	numeric; the size (in nucleotides) of the merged sensitive region
est.sensitive.minLength	numeric; the minimum size (in nucleotides) of the merged sensitive region
merge.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.

```

merge.minCrosslinks
  the minimal number of positions to overlap with at least one crosslink event in
  the final binding sites

merge.minC1Sites
  the minimal number of crosslink sites that have to overlap a final binding site

merge.CenterIsC1Site
  logical, whether the center of a final binding site must be covered by an initial
  crosslink site

merge.CenterIsSummit
  logical, whether the center of a final binding site must exhibit the highest number
  of crosslink events

repro.cutoff  numeric; percentage cutoff to be used for the reproducibility quantile filtering

repro.nReps   numeric; number of replicates that must meet the cutoff defined in repro.cutoff
  for a binding site to be called reproducible. Defaults to N-1.

repro.minCrosslinks
  numeric; minimal number of crosslinks a binding site needs to have to be called
  reproducible. Acts as a lower boundary for repro.cutoff. Defaults to 1.

overlaps.geneWiseFilter
  character; how overlaps should be handled in pureClipGeneWiseFilter

overlaps.geneAssignment
  character; how overlaps should be handled in assignToGenes

overlaps.rule.geneAssignment
  character vector; a vector of gene types that should be used to handle overlaps if
  option 'hierarchy' is selected for assignToGenes. The order of the vector is the
  order of the hierarchy.

overlaps.TranscriptRegions
  character; how overlaps should be handled in assignToTranscriptRegions

overlaps.rule.TranscriptRegions
  character vector; a vector of gene types that should be used to handle overlaps if
  option 'hierarchy' is selected for assignToTranscriptRegions. The order of
  the vector is the order of the hierarchy.

stf.flank      character; how the flanking region shoule be set. Options are 'bs', 'manual'

stf.flank.size numeric; if flank='manual' provide the desired flanking size

match.score    character; meta column name of the crosslink site

match.geneID   character; meta column name of the genes

match.geneName character; meta column name of the gene name

match.geneType character; meta column name of the gene type

match.ranges.score
  a GRanges object, with numeric column for the score to match in function
  annotateWithScore

match.option.score
  character; meta column name of the crosslink site in function annotateWithScore

anno.annoDB    an object of class OrganismDbi that contains the gene annotation !!! Experimental !!!

```

anno.genes	an object of class <code>GenomicRanges</code> that represents the gene ranges directly
anno.transcriptRegionList	an object of class <code>CompressedGRangesList</code> that holds an ranges for each transcript region
quiet	logical; whether to print messages
veryQuiet	logical; whether to suppress all messages
...	additional arguments passed to <code>estimateBsWidth</code> , <code>makeBindingSites</code> and <code>reproducibilityFilter</code>

Details

If only the annotation is provided (anno.genes and anno.transcriptRegionList), then binding sites size (bsSize) and gene-wise cutoff (cutoff.geneWiseFilter) are estimated using `estimateBsWidth`. To avoid this behavior one has to provide input values for the arguments bsSize and cutoff.geneWiseFilter.

If no binding site size is provided through bsSize, then `estimateBsWidth` is called to estimate the optimal size for the given data-set. The result of this estimation can be looked at with `estimateBsWidthPlot` and arguments can be adjusted if needed.

Use the `processingStepsFlowChart` function to get an overview of all steps carried out by the function.

For complete details on each step, see the manual pages of the respective functions. The BSFind function returns a `BSFDataSet` with ranges merged into binding sites. A full flowchart for the entire process can be visualized with `processingStepsFlowChart`. For each of the individual steps dedicated diagnostic plots exists. Further information can be found in our Bioconductor vignette: <https://www.bioconductor.org/packages/release/bioc/html/BindingSiteFinder.html>

Value

an object of class `BSFDataSet` with ranges merged into binding sites given the inputs.

See Also

`BSFDataSet`, `estimateBsWidth`, `pureClipGlobalFilter`, `pureClipGeneWiseFilter`, `assignToGenes`, `assignToTranscriptRegions`, `annotateWithScore`, `reproducibilityFilter`, `calculateSignalToFlankScore`, `processingStepsFlowChart`

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# load transcript regions
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
BSFind(object = bds, bsSize = 9, anno.genes = gns,
       anno.transcriptRegionList = regions, est.subsetChromosome = "chr22")
```

calculateBsBackground *Compute background coverage for binding sites per gene*

Description

This function computes the background coverage used for the differential binding analysis to correct for transcript level changes. Essentially, the crosslink signal on each gene is split into crosslinks that can be attributed to the binding sites and all other signal that can be attributed to the background.

Usage

```
calculateBsBackground(
  object,
  anno.annoDB = NULL,
  anno.genes = NULL,
  blacklist = NULL,
  use.offset = TRUE,
  ranges.offset = NULL,
  match.geneID.gene = "gene_id",
  match.geneID.bs = "geneID",
  match.geneID.blacklist = "geneID",
  generate.geneID.bs = FALSE,
  generate.geneID.blacklist = FALSE,
  uniqueID.gene = "gene_id",
  uniqueID.bs = "bsID",
  uniqueID.blacklist = "bsID",
  force.unequalSites = FALSE,
  quiet = FALSE,
  veryQuiet = TRUE,
  ...
)
```

Arguments

object	a BSFDataSet object with two conditions
anno.annoDB	an object of class OrganismDbi that contains the gene annotation.
anno.genes	an object of class GenomicRanges that represents the gene ranges directly
blacklist	GRanges; genomic ranges where the signal should be excluded from the background
use.offset	logical; if an offset region around the binding sites should be used on which the signal is excluded from the background
ranges.offset	numeric; number of nucleotides the offset window around each binding site should be wide (defaults to 1/2 binding site width - NULL)
match.geneID.gene	character; the name of the column with the gene ID in the genes meta columns used for matching binding sites to genes

```

match.geneID.bs
  character; the name of the column with the gene ID in the binding sites meta
  columns used for matching binding sites to genes

match.geneID.blacklist
  character; the name of the column with the gene ID in the blacklist meta columns
  used for matching the blacklist regions with the genes

generate.geneID.bs
  logical; if the binding site to gene matching should be performed if no matching
  gene ID is provided

generate.geneID.blacklist
  logical; if the blacklist to gene matching should be performed if no matching
  gene ID is provided

uniqueID.gene  character; column name of a unique ID for all genes
uniqueID.bs    character; column name of a unique ID for all binding sites
uniqueID.blacklist
  character; column name of a unique ID for all blacklist regions

force.unequalSites
  logical; if binding sites of not identical width should be allowed or not

quiet
  logical; whether to print messages or not

veryQuiet
  logical; whether to print messages or not

...
  additional arguments; passed to assignToGenes

```

Details

To avoid that crosslinks from binding sites contaminate the background counts a protective region around each binding sites can be spanned with `use.offset` the default width of the offset region is half of the binding site width, but can also be changed with the `ranges.offset` parameter.

Additional region that one wants to exclude from contributing to the background signal can be incorporated as GRanges objects through the `blacklist` option.

It is expected that binding sites are assigned to hosting genes prior to running this function (see [BSFind](#)). This means a unique gene ID is present in the meta columns of each binding site ranges. If this is not the case one can invoke the binding site to gene assignment with `generate.geneID.bs`. The same is true for the blacklist regions with option `generate.geneID.blacklist`.

It is expected that all binding sites are of the same size (See [BSFind](#) on how to achieve this). If this is however not the case and one wants to keep binding sites of different width then option `force.unequalSites` can be used.

This function is intended to be used for the generation of the count matrix used for the differential binding analysis. It is usually preceded by `combineBSF` and followed by `filterBsBackground`.

Value

an object of class [BSFDataSet](#) with counts for binding sites, background and total gene added to the meta column of the ranges

See Also

[combineBSF](#), [filterBsBackground](#)

Examples

```

# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)

# change meta data
m = getMeta(bds)
m$condition = factor(c("WT", "WT", "KO", "KO"), levels = c("WT", "KO"))
bds = setMeta(bds, m)

# change signal
s = getSignal(bds)
names(s$signalPlus) = paste0(m$id, "_", m$condition)
names(s$signalMinus) = paste0(m$id, "_", m$condition)
bds = setSignal(bds, s)

# make example blacklist region
myBlacklist = getRanges(bds)
set.seed(1234)
myBlacklist = sample(myBlacklist, size = 500) + 4

# make background
bds.b1 = calculateBsBackground(bds, anno.genes = gns)

# make background - no offset
bds.b2 = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# make background - use blacklist
bds.b3 = calculateBsBackground(bds, anno.genes = gns, blacklist = myBlacklist)

```

calculateBsFoldChange *Compute fold-changes per binding site*

Description

Given count data for binding sites and background regions this function will compute fold-changes between two condition for each binding site. Computation is based on [DESeq](#) using the Likelihood ratio test to disentangle transcription level changes from binding site level changes.

Usage

```
calculateBsFoldChange(
  object,
  fitType = "local",
  sfType = "ratio",
  minReplicatesForReplace = 10,
  independentFiltering = TRUE,
  alpha = 0.05,
  pAdjustMethod = "BH",
  minmu = 0.5,
  filterFun = NULL,
  use.lfc.shrinkage = FALSE,
  type = c("ashr", "apeglm", "normal"),
  svalue = FALSE,
  apeAdapt = TRUE,
  apeMethod = "nbinomCR",
  match.geneID = "geneID",
  quiet = TRUE,
  veryQuiet = FALSE,
  replaceNegative = FALSE,
  removeNA = FALSE
)
```

Arguments

object	a BSFDataSet object
fitType	either "parametric", "local", "mean", or "glmGamPoi" for the type of fitting of dispersions to the mean intensity. See DESeq for more details.
sfType	either "ratio", "poscounts", or "iterate" for the type of size factor estimation. See DESeq for more details.
minReplicatesForReplace	the minimum number of replicates required in order to use replaceOutliers on a sample. See DESeq for more details.
independentFiltering	logical, whether independent filtering should be applied automatically. See results for more details.
alpha	the significance cutoff used for optimizing the independent filtering. See results for more details.
pAdjustMethod	the method to use for adjusting p-values. See results for more details.
minmu	lower bound on the estimated count. See results for more details.
filterFun	an optional custom function for performing independent filtering and p-value adjustment. See results for more details.
use.lfc.shrinkage	logical; whether to compute shrunken log2 fold changes for the DESeq results. See lfcShrink for more details.

type	if 'ashr', 'apeglm' or 'normal' should be used for fold change shrinkage. See lfcShrink for more details.
svalue	logical, should p-values and adjusted p-values be replaced with s-values when using apeglm or ash. See lfcShrink for more details.
apeAdapt	logical, should apeglm use the MLE estimates of LFC to adapt the prior. See lfcShrink for more details.
apeMethod	what method to run apeglm, which can differ in terms of speed. See lfcShrink for more details.
match.geneID	character; the name of the column with the gene ID in the binding sites meta columns used for matching binding sites to genes
quiet	logical; whether to print messages or not
veryQuiet	logical; whether to print messages or not
replaceNegative	logical; force negative counts to be replaced by 0. Be careful when using this, having negative counts can point towards problems with the gene annotation in use.
removeNA	logical; force binding sites with any NA value to be removed. Be careful when using this, having negative counts can point towards problems with the gene annotation in use.

Details

Fold-changes per binding sites are corrected for transcript level changes. Essentially, background counts are used to model transcript level changes, which are then used to compute fold-changes per binding site, which are corrected for the observed transcript level changes. This is done by using a Likelihood ratio test comparing the full model (~condition + type + condition:type) to the reduced model (~condition + type).

Fold-changes for the transcript level changes are modeled explicitly in a second round of the [DESeq](#) workflow, using the default Wald test to compare changes between the conditions (~condition). Counts attributed to binding sites are removed from the gene level counts.

Results from both calculation rounds can be filtered and further manipulated with parameters given in the DESeq2 framework (see [results](#), [lfcShrink](#)).

This function is intended to be used right after a call of [filterBsBackground](#).

Value

a [BSFDataSet](#) object, with results from the [DESeq](#) analysis added to the meta columns of the binding site ranges.

See Also

[calculateBsBackground](#), [filterBsBackground](#), [plotBsBackgroundFilter](#), [DESeq](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make example dataset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns)

# calculate fold changes - no shrinkage
bds = calculateBsFoldChange(bds)

# calculate fold changes - with shrinkage
bds = calculateBsFoldChange(bds, use.lfc.shrinkage = TRUE)
```

calculateSignalToFlankScore

Calculate signal-to-flank score

Description

This function calculates the signal-to-flank ratio for all present binding sites.

Usage

```
calculateSignalToFlankScore(
  object,
  flank = c("bs", "manual"),
  flank.size = NULL,
  quiet = FALSE
)
```

Arguments

object	a BSFDataSet object
flank	character; how the flanking region shoule be set. Options are 'bs', 'manual'
flank.size	numeric; if flank='manual' provide the desired flanking size
quiet	logical; whether to print messages

Details

Each input range is treated as a binding site. For a particular binding site all overlapping crosslinks are summed up and divided by the normalized sum of the crosslinks in the two adjecent regions of the same size. This is done for all bining sites and the ratio is reported as a score.

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSFDataSet](#) with signal-to-flank ratios added to the meta column of the ranges.

See Also

[BSFind](#), [bindingSiteDefinednessPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(bds, bsSize = 5)
bds = calculateSignalToFlankScore(bds)
```

clipCoverage

Coverage function for BSFDataSet objects

Description

Function that computes a crosslink coverage with all samples over all ranges given in the [BSFDataSet](#). The coverage can be summarized over all combinations of the three dimension (samples, ranges, positions).

Usage

```
clipCoverage(
  object,
  ranges.merge = FALSE,
  ranges.merge.method = c("sum", "mean"),
  positions.merge = FALSE,
  positions.merge.method = c("sum", "mean"),
  samples.merge = TRUE,
  samples.group = c("all", "condition"),
  samples.merge.method = c("sum", "mean"),
  out.format = c("granges", "data.frame"),
  out.format.overwrite = FALSE,
  match.rangeID = "bsID",
  quiet = FALSE
)
```

Arguments

object	a BSFDataSet object
ranges.merge	logical; whether to merge ranges

```

ranges.merge.method
  character; how to combine ranges ('sum' or 'mean')
positions.merge
  logical; whether to merge positions
positions.merge.method
  character; how to combine positions ('sum' or 'mean')
samples.merge
  logical: whether to merge samples
samples.group
  character; how samples should be grouped when combining ('all', 'condition')
samples.merge.method
  character; how to combine positions ('sum' or 'mean')
out.format
  character; how the coverage should be returned ('data.frame' or 'granges'). Note
  that option 'granges' only exists if the output coverage is of the same rows as
  the input ranges.
out.format.overwrite
  logical; if out.format='granges', then decide whether the meta columns should
  be extended by the coverage information or be overwritten
match.rangeID
  character; unique internal identifier. Name of the meta column of the input
  ranges that should be used as identifier to match the coverage back to the input
  ranges. Is 'bsID' as default, since that ID exists for all binding sites after
  makeBindingSites was called.
quiet
  logical; whether to print messages

```

Details

When summarizing the crosslink coverage over samples (`samples.merge=TRUE`) one can decide whether to summarize all samples or whether to keep conditions separate (`samples.group`). This either reduces the samples dimension to a single matrix, or a list. For a binding site set with 100 binding sites of width=7 and 4 replicates with 2 conditions, the following options are possible. With merging enabled and `samples.group='all'` the coverage of all samples is combined. With `samples.group='condition'` only samples of the same condition are grouped.

When summarizing the crosslink coverage over ranges, all ranges are combined which reduces the ranges dimension to a single vector. This turns eg. a binding site set of 100 binding sites with width=7 into a vector of length 100 with exactly one column. Depending on how the samples were summarized, the result can be a single such vector, or a list.

When summarizing the crosslink coverage over positions, all positions are combined which reduces the positions dimension to a single vector. This turns eg. a binding site set of 100 binding sites with width=7 into a vector of length 1 with 7 columns. Depending on how the samples were summarized, the result can be a single such vector, or a list.

For all summarizing operations options `sum` and `mean` exists. This allows for normalization by the eg. the number of binding sites, size of the range, number of sample, etc..

If the resulting object does have a dimension that fits to the number of input ranges the result can be directly attached to them. Basically extending the GRanges object (`out.format`).

Value

an object of class specified in `out.format`

See Also[BSFDataSet](#), [BSFind](#)**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bds = makeBindingSites(bds, bsSize = 7)
# sum of each replicate over each binding site position
c1 = clipCoverage(bds, out.format = "data.frame", positions.merge = TRUE,
  ranges.merge = FALSE, samples.merge = FALSE)
# total signal per binding site from all samples
c2 = clipCoverage(bds, out.format = "granges", positions.merge = FALSE,
  ranges.merge = TRUE, samples.merge = TRUE, samples.group = "all")
# total signal per binding site from all samples - split by condition
c3 = clipCoverage(bds, out.format = "granges", positions.merge = FALSE,
  ranges.merge = TRUE, samples.merge = TRUE, samples.group = "condition")
```

collapseReplicates *Collapse signal from replicates***Description**

Collapses all replicates merges all samples from a [BSFDataSet](#) object into a single signal stream, only split by minus and plus strand.

Usage

```
collapseReplicates(object, collapseAll = FALSE)
```

Arguments

object	a BSFDataSet object
collapseAll	TRUE/FALSE, if all samples should be collapsed (TRUE), or if samples should be kept separate by condition (FALSE)

Value

object of type [BSFDataSet](#) with updated signal

See Also[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = collapseReplicates(bds)
```

combineBSF

Combine multiple BSFDataSet objects

Description

This function combines all [BSFDataSet](#) objects from the input list into a single [BSFDataSet](#) object.

Usage

```
combineBSF(
  list,
  overlaps.fix = TRUE,
  combine.bsSize = NULL,
  combine.name = NULL,
  force.reload = FALSE,
  quiet = TRUE,
  veryQuiet = FALSE
)
```

Arguments

list	list; a list of objects from class BSFDataSet that should be combined
overlaps.fix	logical; if partially overlapping binding sites should be re-centered
combine.bsSize	numeric; the binding site size that the merged sites should have. Default=NULL, then bsSize is taken from the input objects in list.
combine.name	character; meta table name of the combined object. Default=NULL; then name is set to 'combined'
force.reload	logical; whether the signal should be derived from the merge of the input objects given in list or if the signal should be re-loaded from the path given in the meta data.
quiet	logical; whether to print messages or not
veryQuiet	logical; whether to print status messages or not

Details

Meta-data tables are added to each other by performing a row-wise bind, basically adding all meta data tables underneath each other.

The default way of signal combination is merging all signal lists on the level of the individual samples. One can also force a re-load of the signal list component by using `force.reload=TRUE`. The signal can be combined by

The ranges are combined by adding both granges objects together. With option `overlaps.fix` one can decide if partially overlapping ranges should be combined into a single range or not. If this option is `FALSE` one is likely to have overlapping binding sites after the merge. If this option is `TRUE`, then the combined coverage is used to guide the new center point for these cases.

The `combine.bsSize` option allows one to set a unique `bsSize` for all objects that should be combined. Although it is recommended to combine only objects with the same `bsSize` this option can be used to ensure that the merged result has the same `bsSize` for all ranges.

This function is usually used to combine two datasets in the context of a differential testing analysis.

Value

an object of class [BSFDataSet](#) with ranges, signal and meta data resulting from the merge of the input objects.

See Also

[processingStepsFlowChart](#), [calculateBsBackground](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)

# split ranges in two groups
allRanges = getRanges(bds)
set.seed(1234)
idx = sample(1:length(allRanges), size = length(allRanges)/2, replace = FALSE)
r1 = allRanges[idx]
r2 = allRanges[-idx]

# split meta data
allMeta = getMeta(bds)
m1 = allMeta[1:2,]
m2 = allMeta[3:4,]

# create new objects
bds1 = setRanges(bds, r1)
bds2 = setRanges(bds, r2)
bds1 = setMeta(bds1, m1)
```

```

bds2 = setMeta(bds2, m2)
bds1 = setName(bds1, "test1")
bds2 = setName(bds2, "test2")

# merge two objects with '+' operator
c1 = bds1 + bds2

# merge two objects from list
list = list(bds1, bds2)
c1 = combineBSF(list = list, overlaps.fix = TRUE,
combine.bsSize = NULL, combine.name = NULL, quiet = TRUE)

```

coverageOverRanges *Coverage function for BSFDataSet objects*

Description

The crosslink coverage is computed for all ranges in the the given BSFDataSet object (see [BSFDataSet](#) for details). Depending on the `returnOptions` the resulting coverage information is summarized, suitable for diverse computation and plotting tasks. The coverage can only be compute for objects with identical ranges.

Usage

```

coverageOverRanges(
  object,
  returnOptions = c("merge_ranges_keep_positions", "merge_replicates_per_condition",
    "merge_all_replicates", "merge_positions_keep_replicates"),
  method = "sum",
  allowNA = FALSE,
  quiet = TRUE
)

```

Arguments

<code>object</code>	a BSFDataSet object
<code>returnOptions</code>	one of <code>merge_ranges_keep_positions</code> , <code>merge_replicates_per_condition</code> , <code>merge_all_replicates</code> , <code>merge_positions_keep_replicates</code>
<code>method</code>	<code>sum</code> / <code>mean</code> , select how replicates/ ranges should be summarized
<code>allowNA</code>	<code>TRUE</code> / <code>FALSE</code> , allow NA values in the output if input ranges are of different width
<code>quiet</code>	logical, whether to print messages

Details

If `returnOptions` is set to `merge_ranges_keep_positions`: Returns a matrix with `ncol` being the nucleotides of the ranges (equal to the width of the input ranges) and `nrow` being the number of replicates in the meta information.

If `returnOptions` is set to `merge_replicates_per_condition`: Returns a list of matrices. Each list corresponds to one condition set in the meta information. The matrix in each entry has `ncols` equal to the ranges width and `nrow` equal to the number of ranges. Counts per ranges and position are summed.

If `returnOptions` is set to `merge_all_replicates`: Returns a matrix with `ncols` equal to the range width and `nrow` equal to the number of ranges. Counts per range and position are summed.

If `returnOptions` is set to `merge_positions_keep_replicates`: Returns a `GRanges` object where the counts are summed for each replicate and added to the original granges object.

Value

an object of class specified in `returnOptions`

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

rng = coverageOverRanges(bds, returnOptions = "merge_ranges_keep_positions")
rng = coverageOverRanges(bds, returnOptions = "merge_replicates_per_condition")
rng = coverageOverRanges(bds, returnOptions = "merge_all_replicates")
rng = coverageOverRanges(bds, returnOptions = "merge_positions_keep_replicates")
```

duplicatedSitesPlot *Plot the number of overlaps when assigning crosslink sites to genes*

Description

A diagnostic function that plots the number of crosslink sites with their respective overlapping rate. The function `pureClipGeneWiseFilter` is expected to be executed prior to calling this plot function.

Usage

```
duplicatedSitesPlot(object)
```

Arguments

object	a <code>BSFDataSet</code> object
--------	----------------------------------

Value

a plot of type `ggplot`

See Also

`pureClipGeneWiseFilter`

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# apply 5% gene-wise filter
bds = pureClipGeneWiseFilter(object = bds, anno.genes = gns, cutoff = 0.5,
  overlaps = "keepSingle")
duplicatedSitesPlot(bds)
```

`estimateBsWidth`

Function to estimate the appropriate binding site width together with the optimal gene-wise filter level.

Description

This function tests different width of binding sites for different gene-wise filtering steps. For each test the signal-to-score ratio is calculated. The mean over all gene-wise filterings at each binding site width is used to extract the optimal width, which serves as anchor to select the optimal gene-wise filter.

Usage

```
estimateBsWidth(
  object,
  bsResolution = c("medium", "fine", "coarse"),
  geneResolution = c("medium", "coarse", "fine", "finest"),
  est.maxBsWidth = 13,
  est.minimumStepGain = 0.02,
  est.maxSites = Inf,
  est.subsetChromosome = "chr1",
  est.minLength = 2,
  est.offset = 1,
  sensitive = FALSE,
  sensitive.size = 5,
  sensitive.minLength = 2,
  anno.annoDB = NULL,
  anno.genes = NULL,
```

```

  bsResolution.steps = NULL,
  geneResolution.steps = NULL,
  quiet = TRUE,
  veryQuiet = FALSE,
  reportScoresPerBindingSite = FALSE,
  ...
)

```

Arguments

object	a BSFDataSet object with stored crosslink sites. This means that ranges should have a width = 1.
bsResolution	character; level of resolution at which different binding site width should be tested
geneResolution	character; level of resolution at which gene-wise filtering steps should be tested
est.maxBsWidth	numeric; the largest binding site width which should be considered in the testing
est.minimumStepGain	numeric; the minimum additional gain in the score in percent the next binding site width has to have, to be selected as best option
est.maxSites	numeric; maximum number of PureCLIP sites that are used;
est.subsetChromosome	character; define on which chromosome the estimation should be done in function estimateBsWidth
est.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
est.offset	constant added to the flanking count in the signal-to-flank ratio calculation to avoid division by Zero
sensitive	logical; whether to enable sensitive pre-filtering before binding site merging or not
sensitive.size	numeric; the size (in nucleotides) of the merged sensitive region
sensitive.minLength	numeric; the minimum size (in nucleotides) of the merged sensitive region
anno.annoDB	an object of class <code>OrganismDbi</code> that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class GenomicRanges that represents the gene ranges directly
bsResolution.steps	numeric vector; option to use a user defined threshold for binding site width directly. Overwrites bsResolution
geneResolution.steps	numeric vector; option to use a user defined threshold vector for gene-wise filtering resolution. Overwrites geneResolution
quiet	logical; whether to print messages
veryQuiet	logical; whether to suppress all messages

```

reportScoresPerBindingSite
  report the ratio score for each binding site separately. Warning! This is for
  debugging and testing only. Downstream functions can be impaired.
...
  additional arguments passed to pureClipGeneWiseFilter

```

Details

Parameter estimation is done on a subset of all crosslink sites (`est.subsetChromosome`).

Gene-level filter can be tested with varying levels of accuracy ranging from ‘finest’ to ‘coarse’, representing 1 20

Binding site computation at each step can be done on three different accuracy level (`bsResolution`). Option ‘fine’ is equal to a normal run of the `makeBindingSites` function. ‘medium’ will perform a shorter version of the binding site computation, skipping some of the refinement steps. Option ‘coarse’ will approximate binding sites by merged crosslinks regions, aligning the center at the site with the highest score.

For each binding site in each set given the defined resolutions a signal-to- flank score ratio is calculated and the mean of this score per set is returned. Next a mean of means is created which results in a single score for each binding site width that was tested. The width that yielded the highest score is selected as optimal. In addition the `minimumStepGain` option allows control over the minimum additional gain in the score that a tested width has to have to be selected as the best option.

To enhance the sensitivity of the binding site estimation, the sensitivity mode exists. In this mode crosslink sites undergo a pre-filtering and merging step, to exclude potential artificial peaks (experimental-, mapping-biases). If sensitivity mode is activated the `est.minLength` option should be set to 1.

The optimal geneFilter is selected as the first one that passes the merged mean of the selected optimal binding site width.

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSDataSet](#) with binding sites with the ‘params’ slots ‘bsSize’ and ‘geneFilter’ being filled

See Also

[BSFind](#), [estimateBsWidthPlot](#)

Examples

```

# load clip data
files <- system.file("exdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
estimateBsWidth(bds, anno.genes = gns, est.maxBsWidth = 19,
  geneResolution = "coarse", bsResolution = "coarse", est.subsetChromosome = "chr22")

```

<code>estimateBsWidthPlot</code>	<i>Plot the signal-to-flank score for varying gene-wise filter and binding site width</i>
----------------------------------	---

Description

A diagnostic function that plots the the signal-to-flank score as a mean for each binding site width and gene-wise filter as indicated when executing `estimateBsWidth`. Additionally a mean of means visualizes the overall trend and a red line indicates the suggested optimal binding site width. The function `estimateBsWidth` is expected to be executed prior to calling this plot function.

Usage

```
estimateBsWidthPlot(object)
```

Arguments

<code>object</code>	a <code>BSFDataSet</code> object
---------------------	----------------------------------

Value

a plot of type `ggplot`

See Also

`estimateBsWidth`

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = estimateBsWidth(bds, anno.genes = gns, est.maxBsWidth = 19,
  geneResolution = "coarse", bsResolution = "coarse", est.subsetChromosome = "chr22")
estimateBsWidthPlot(bds)
```

<code>exportTargetGenes</code>	<i>Function to export sorted RBP target genes</i>
--------------------------------	---

Description

Genes with binding sites are target genes of the RBP. They can be exported as 'csv' or 'xlsx' file. Genes can be sorted by the sum of the individual binding sites score, or by the number of binding sites per gene.

Usage

```
exportTargetGenes(  
  object,  
  path = "./",  
  format = c("csv", "xlsx"),  
  sort = c("score", "bs"),  
  split = c("none", "geneType", "transcriptRegion")  
)
```

Arguments

object	a BSFDataSet object with stored ranges
path	A path to where the output should be stored
format	output file format
sort	sorting rule for genes
split	if and how the output file should be split

Details

As output option, one can either output all genes in a single file, or split by either gene-type or transcript-region. This options requires that either [BSFind](#) or the individual functions [assignToGenes](#), and [assignToTranscriptRegions](#) were run.

Value

a file of the type specified in [format](#)

Examples

```
# load data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
## Not run:  
# export  
# exportTargetGenes(bds)  
  
## End(Not run)
```

exportToBED

Wrapper function to export binding sites as BED files

Description

Function that serves as a wrapper function for [rtracklayer::export](#).

Usage

```
exportToBED(object, con)
```

Arguments

object	a BSDataSet object with stored ranges
con	A path or URL

Value

a .bed file

See Also

[BSFind](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
## Not run:
# export
# exportToBED(bds, con = "./myfile.bed")

## End(Not run)
```

filterBsBackground *Filter for genes not suitable for differential testing*

Description

This function removes genes where the differential testing protocol can not be applied to, using count coverage information on the binding sites and background regions per gene, through the following steps:

1. Remove genes with overall not enough crosslinks: `minCounts`
2. Remove genes with a disproportion of counts in binding sites vs. the background: `balanceBackground`
3. Remove genes where the expression between conditions is too much off balance: `balanceCondition`

Usage

```
filterBsBackground(  
  object,  
  minCounts = TRUE,  
  minCounts.cutoff = 100,  
  balanceBackground = TRUE,  
  balanceBackground.cutoff.bs = 0.3,  
  balanceBackground.cutoff.bg = 0.7,  
  balanceCondition = TRUE,  
  balanceCondition.cutoff = 0.05,  
  match.geneID = "geneID",  
  flag = FALSE,  
  quiet = FALSE,  
  veryQuiet = FALSE  
)
```

Arguments

object a [BSFDataSet](#) object with computed count data for binding sites and background regions

minCounts logical; whether to use the minimum count filter

minCounts.cutoff numeric; the minimal number of crosslink per gene over all samples for the gene to be retained (default = 100)

balanceBackground logical; whether to use the counts balancing filter between binding sites and background

balanceBackground.cutoff.bs numeric; the maximum fraction of the total signal per gene that can be within binding sites (default = 0.2)

balanceBackground.cutoff.bg numeric; the minimum fraction of the total signal per gene that can be within the background (default = 0.8)

balanceCondition logical; whether to use the counts balancing filter between conditions

balanceCondition.cutoff numeric; the maximum fraction of the total signal that can be attributed to only one condition

match.geneID character; the name of the column with the gene ID in the binding sites meta columns used for matching binding sites to genes

flag logical; whether to remove or flag binding sites from genes that do not pass any of the filters

quiet logical; whether to print messages or not

veryQuiet logical; whether to print messages or not

Details

To remove genes with overall not enough crosslinks (`minCounts`) all counts are summed up per gene across all samples and compared to the minimal count threshold (`minCounts.cutoff`).

To remove genes with a count disproportion between binding sites and background regions crosslinks are summed up for binding sites and background per gene. These sums are combined in a ratio. Genes where eg. 50% of all counts are within binding sites would be removed (see `balanceBackground.cutoff.bs` and `balanceBackground.cutoff.bg`).

To remove genes with very large expression differences between conditions, crosslinks are summed up per gene for each condition. If now eg. the total number of crosslinks is for 98% in one condition and only 2% of the combined signal is in the second condition, expression levels are too different for a reliable comparison (see `balanceCondition.cutoff`).

This function is intended to be used right after a call of [calculateBsBackground](#).

Value

an object of class [BSFDataSet](#) with binding sites filtered or flagged by the above filter options

See Also

[calculateBsBackground](#), [plotBsBackgroundFilter](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
f0 = filterBsBackground(bds)

# do not use the condition balancing filter
f1 = filterBsBackground(bds, balanceCondition = FALSE)

# use only the minimum count filter and flag binding sites instead of
# removing them
f3 = filterBsBackground(bds, flag = TRUE, balanceCondition = FALSE,
balanceBackground = FALSE)
```

geneOverlapsPlot *UpSet-plot to that shows the gene type overlaps*

Description

A diagnostic function that plots the gene types of binding sites on overlapping loci genes. The function [assignToGenes](#) is expected to be executed prior to calling this plot function.

Usage

```
geneOverlapsPlot(object, text.size = NULL, show.title = TRUE)
```

Arguments

object	a BSFDataSet object
text.size	numeric; fontsize of all numbers on axis
show.title	logical; if plot title should be visible

Value

a plot of type [ggplot](#)

See Also

[assignToGenes](#) [targetGeneSpectrumPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
geneOverlapsPlot(bds)
```

geneRegulationPlot *Gene Regulation Plot*

Description

Display the fold-change of all binding sites from a given gene on a relative per-nucleotide scale. Binding sites are displayed as dots and with increasing log2 fold-change, they deviate stronger from the center line.

Usage

```
geneRegulationPlot(
  object,
  plot.geneID = NULL,
  anno.annoDB = NULL,
  anno.genes = NULL,
  match.geneID = "gene_id",
  match.geneName = "gene_name",
  plot.gene.n.tiles = 100,
  alpha = 0.05,
  lfc.cutoff = 2,
  transcript.regions.outlier.handle = c("first", "second", "both", "remove"),
  quiet = FALSE
)
```

Arguments

object	object; a BSFDataSet object
plot.geneID	character; the gene id of the gene to display. The id must match with the gene ids given in the annotation object.
anno.annoDB	object; an object of class <code>OrganismDbi</code> that contains the gene annotation (!!! Experimental !!!).
anno.genes	object; an object of class GenomicRanges that represents the gene ranges directly.
match.geneID	character; meta column name of the gene ID
match.geneName	character; meta column name of the gene name
plot.gene.n.tiles	numeric; number of tiles the gene should be split in
alpha	numeric; the alpha value to show significantly regulated binding sites. This should match the alpha value used in calculateBsFoldChange .
lfc.cutoff	numeric; log2 fold-change cutoff to show significantly regulated binding sites. This should match the lfc.cutoff value used in calculateBsFoldChange .
transcript.regions.outlier.handle	character; the option how to handle multiple transcript region annotations being present for the same binding site.
quiet	logical; whether to print messages

Details

For this function to work, binding sites must be assigned to hosting genes using [assignToGenes](#). It is also recommended to assign binding sites to transcript regions with [assignToTranscriptRegions](#).

It is also necessary to calculate the log2 fold-change of binding sites between two conditions using the differential binding workflow [calculateBsFoldChange](#).

If in addition the transcript regions of the binding sites are given, then shapes are changed accordingly. An edge case can arise from the merging of two [BSFDataSet](#) objects. If binding sites are overlapping and slightly offset close to the end of a particular transcript region annotation, they might be assigned to different regions in both objects. This results in some ambiguity after the merge, where for instance a binding site can be assigned to CDS and 3'UTR. To handle how such edge cases are displayed, the `transcript.regions.outlier.handle` exists. As default, simply the region of the object that was merged first is shown. If one is interested in showing all regions, then the options both displays both annotations at the same time and labels them accordingly.

Value

an object of class `ggplot2`

See Also

[BSFind](#), [calculateBsFoldChange](#) [assignToGenes](#) [assignToTranscriptRegions](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make example plot
exampleGeneId = "ENSG00000253352.10"
geneRegulationPlot(bds, plot.geneID = exampleGeneId, anno.genes = gns)
```

getMeta*Accessor method for the meta data of the BSFDataSet object*

Description

Meta data is stored as a `data.frame` and must contain the columns "condition", "clPlus" and "clMinus".

Usage

```
getMeta(object)

## S4 method for signature 'BSFDataSet'
getMeta(object)
```

Arguments

`object` a BSFDataSet object

Value

returns the meta data `data.frame` with the columns "condition", "clPlus" and "clMinus".

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getMeta(bds)
```

getName*Accessor method for the name of the BSFDataSet object*

Description

The name slot holds the name of the dataset

Usage

```
getName(object)

## S4 method for signature 'BSFDataSet'
getName(object)
```

Arguments

object a BSFDataSet object

Value

returns the name of the dataset

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getName(bds)
```

getRanges

Accessor method for the ranges of the BSFDataSet object

Description

The ranges slot holds the genomic ranges information of the sites currently in the object. They are encoded as a GRanges object with each binding site having a single ranges entry.

Usage

```
getRanges(object)

## S4 method for signature 'BSFDataSet'
getRanges(object)
```

Arguments

object a BSFDataSet object

Value

returns the genomic ranges (GRanges) of the associated ranges

See Also[BSFDataSet](#)**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getRanges(bds)
```

getSignal*Accessor method for the signal data of the BSFDataSet object***Description**

Signal data is loaded from the path specified in [getMeta](#) columns "clPlus" and "clMinus" and stored as a list of RLE lists.

Usage

```
getSignal(object)

## S4 method for signature 'BSFDataSet'
getSignal(object)
```

Arguments

object a BSFDataSet object

Value

returns the signal data, as list of RLE list for each strand, named after the meta data columns "clPlus" and "clMinus"

See Also[getMeta BSFDataSet](#)**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getSignal(bds)
```

getSummary

Accessor method for the summary slot of the BSFDataSet object

Description

The summary slot is used to track information of the filtering steps applied in the [makeBindingSites](#) function

Usage

```
getSummary(object, ...)

## S4 method for signature 'BSFDataSet'
getSummary(object)
```

Arguments

object	a BSFDataSet object
...	additional arguments

Value

returns the summary information stored in the summary slot after [makeBindingSites](#) was run

See Also

[BSFDataSet](#) [makeBindingSites](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minCISites = 1)

getSummary(bds)
```

globalScorePlot*Plot the PureCLIP score distribution after re-assignment*

Description

A diagnostic function that plots the PureCLIP score distribution on a log2 scale after the re-assignment on binding site level. The function [annotateWithScore](#) is expected to be executed prior to calling this plot function.

Usage

```
globalScorePlot(object)
```

Arguments

object a [BSFDataSet](#) object

Value

a plot of type [ggplot](#)

See Also

[annotateWithScore](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds1 = makeBindingSites(object = bds, bsSize = 9)
bds1 = annotateWithScore(bds1, match.ranges = getRanges(bds))
globalScorePlot(bds1)
```

imputeBsDifferencesForTestdata*Impute artificial differences in the example data set*

Description

A function that works only on the test data set provided with the package. It is used for internal testing and the making of examples to showcase the differential binding functions.

Usage

```
imputeBsDifferencesForTestdata(object, size = 5, change.per = 0.1)
```

Arguments

object	a <code>BSFDataSet</code> object; explicitly the test data set from the extdata folder
size	numeric; the number of positions on which signal should be deleted, counting from the start
change.per	numeric; the percentage of ranges that should be effected by the change.

Details

Differences between samples are artificially introduced by removing the signal on a random set of binding sites of the input.

Value

object a `BSFDataSet` object with the signal slot adapted to reflect changes in binding between two artificial conditions

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)

bds = imputeBsDifferencesForTestdata(bds)
```

<code>makeBindingSites</code>	<i>Define equally sized binding sites from peak calling results and iCLIP crosslink events.</i>
-------------------------------	---

Description

This function performs the merging of single nucleotide crosslink sites into binding sites of a user defined width (bsSize). Depending on the desired output width crosslink sites with a distance closer than bsSize - 1 are concatenated. Initially all input regions are concatenated and then imperatively merged and extended. Concatenated regions smaller than minWidth are removed prior to the merge and extension routine. This prevents outlier crosslink pileup, eg. mapping artifacts to be integrated into the final binding sites. All remaining regions are further processed and regions larger than the desired output width are interactively split up by setting always the position with the highest number of crosslinks as center. Regions smaller than the desired width are symmetrically extended. Resulting binding sites are then filtered by the defined constraints.

Usage

```
makeBindingSites(
  object,
  bsSize = NULL,
  minWidth = 2,
  minCrosslinks = 2,
  minC1Sites = 1,
  centerIsC1Site = TRUE,
  centerIsSummit = TRUE,
  sub.chr = NA,
  quiet = FALSE
)
```

Arguments

object	a BSFDataSet object (see BSFDataSet)
bsSize	an odd integer value specifying the size of the output binding sites
minWidth	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
minCrosslinks	the minimal number of positions to overlap with at least one crosslink event in the final binding sites
minC1Sites	the minimal number of crosslink sites that have to overlap a final binding site
centerIsC1Site	logical, whether the center of a final binding site must be covered by an initial crosslink site
centerIsSummit	logical, whether the center of a final binding site must exhibit the highest number of crosslink events
sub.chr	chromosome identifier (eg, chr1, chr2) used for subsetting the BSFDataSet object. This option can be used for testing different parameter options
quiet	logical, whether to print info messages

Details

The `bsSize` argument defines the final output width of the merged binding sites. It has to be an odd number, to ensure that a binding site has a distinct center.

The `minWidth` parameter is used to describe the minimum width a ranges has to be after the initial concatenation step. For example: Consider `bsSize = 9` and `minWidth = 3`. Then all initial crosslink sites that are closer to each other than 8 nucleotides (`bsSize - 1`) will be concatenated. Any of these ranges with less than 3 nucleotides of width will be removed, which reflects about 1/3 of the desired binding site width.

The argument `minCrosslinks` defines how many positions of the binding sites are covered with at least one crosslink event. This threshold has to be defined in conjunction with the binding site width. A default value of 3 with a binding site width of 9 means that 1/3 of all positions in the final binding site must be covered by a crosslink event. Setting this filter to 0 deactivates it.

The `minC1Sites` argument defines how many positions of the binding site must have been covered by the original crosslink site input. If the input was based on the single nucleotide crosslink positions computed by PureCLIP than this filter checks for the number of positions originally identified

by PureCLIP in the computed binding sites. The default of `minC1Sites = 1` essentially deactivates this filter. Setting this filter to 0 deactivates it.

The options `centerIsC1Site` and `centerIsSummit` ensure that the center of each binding site is covered by an initial crosslink site and represents the summit of crosslink events in the binding site, respectively.

The option `sub.chr` allows to run the binding site merging on a smaller subset (eg. "chr1") for improved computational speed when testing the effect of various binding site width and filtering options.

Value

an object of type `BSFDataSet` with modified ranges

See Also

`BSFDataSet`, `BSFind`, `mergeCrosslinkDiagnosticsPlot`, `makeBsSummaryPlot`

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# standard options, no subsetting
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minC1Sites = 1)

# standard options, with subsetting
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minC1Sites = 1, sub.chr = "chr22")
```

`makeBsSummaryPlot` *Plot binding site filter diagnostics*

Description

A diagnostic function that plots the number of binding sites retained after each filtering step calculated in `makeBindingSites`. The function `makeBindingSites` is expected to be executed prior to calling this plot function.

Usage

```
makeBsSummaryPlot(object)
```

Arguments

`object` a `BSFDataSet` object

Value

a plot of type `ggplot`

See Also

[makeBindingSites](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
makeBsSummaryPlot(bds)
```

`mergeCrosslinkDiagnosticsPlot`

Plot binding site merging diagnostics

Description

A diagnostic function that plots the number of regions to merge over the width of these regions for each merging iteration calculated in [makeBindingSites](#). The function `makeBindingSites` is expected to be executed prior to calling this plot function.

Usage

```
mergeCrosslinkDiagnosticsPlot(object)
```

Arguments

`object` a [BSFDataSet](#) object

Value

a plot of type `ggplot`

See Also

[makeBindingSites](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
mergeCrosslinkDiagnosticsPlot(bds)
```

`mergeSummaryPlot` *Plot summarized results of the different binding site merging and filtering steps*

Description

Bar charts produced for the different filter steps in the binding site merging routine. Depending on the selected option (select) all or only a user defined filter can be shown.

Usage

```
mergeSummaryPlot(  
  object,  
  select = c("all", "filter", "inputRanges", "minClSites", "mergeCrosslinkSites",  
  "minCrosslinks", "centerIsClSite", "centerIsSummit"),  
  ...  
)
```

Arguments

object	a BSFDataObject, with the makeBindingSites function already run
select	one of "all", "filter", "inputRanges", "minCLSSites", "mergeCrosslinkSites", "minCrosslinks", "centerIsCLSite" or "centerIsSummit". Defines which parameter is selected for plotting.
...	further arguments passed to ggplot

Details

If object is a single BSFDataObject a single coverage plot will be drawn, whereas if it is a list of BSFDataObjects, then faceting is used to make a plot for each list element.

Value

a plot of type `ggplot` after the `makeBindingSites` function was run

See Also

makeBindingSites

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# plotting a single object
bds0 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minC1Sites = 1)
```

```

mergeSummaryPlot(bds0)

# plotting mulitple obejcts
bds1 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
bds2 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 3, sub.chr = "chr22")
l = list(`1. bsSize = 3` = bds1, `2. bsSize = 9` = bds2)
mergeSummaryPlot(l, width = 20)

```

plotBsBackgroundFilter

Diagnostic plots for the differential binding background

Description

To perform differential binding analysis between two conditions the [calculateBsBackground](#) function groups crosslinks per gene into those from binding sites and those from background regions. The [filterBsBackground](#) function perfrroms certain filtering operations on that background to ensure that it's suitable for differential testing. This function visually displays the effect of these filtering operations.

Usage

```

plotBsBackgroundFilter(
  object,
  filter = c("minCounts", "balanceBackground", "balanceCondition")
)

```

Arguments

object	a BSFDataSet object with background counts filtered by filterBsBackground
filter	character; which filter to display in the plot (one of: 'minCounts', 'balanceBackground', 'balanceCondition')

Value

a plot of type [ggplot](#)

See Also

[calculateBsBackground](#)
[filterBsBackground](#)

Examples

```

# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# display minCount filter
plotBsBackgroundFilter(bds, filter = "minCounts")

# display balance background filter
plotBsBackgroundFilter(bds, filter = "balanceBackground")

# display balance condition filter
plotBsBackgroundFilter(bds, filter = "balanceCondition")

```

plotBsMA

MA style plot

Description

Wrapper that plots differential binding results as MA plot. For each binding site the estimated baseMean (log2) is shown on X and the fold-change (log2) is shown on Y.

Usage

```
plotBsMA(object, what = c("bs", "bg"), sig.threshold = 0.05)
```

Arguments

object	a BSFDataSet object with results calculated by calculateBsFoldChange
what	character; whether to show results for binding sites or the background (one of: 'bs', 'bg')
sig.threshold	numeric; what P value significance level to use (default = 0.05)

Value

a plot of type [ggplot](#)

See Also[calculateBsFoldChange](#)**Examples**

```

# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make MA plot
plotBsMA(bds)

```

plotBsVolcano*Volcano style plot*

Description

Wrapper that plots differential binding results as volcano plot. For each binding site the estimated fold-change (log2) is shown on X and the adjusted P value (-log10) is shown on Y.

Usage

```
plotBsVolcano(object, what = c("bs", "bg"), sig.threshold = 0.05)
```

Arguments

object	a <code>BSFDataSet</code> object with results calculated by calculateBsFoldChange
what	character; whether to show results for binding sites or the background (one of: 'bs', 'bg')
sig.threshold	numeric; what P value significance level to use (default = 0.05)

Value

a plot of type [ggplot](#)

See Also[calculateBsFoldChange](#)**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make volcano plot
plotBsVolcano(bds)
```

processingStepsFlowChart*Step-wise flowchart plot*

Description

An overview plot that shows all workflow functions that were executed on the current object, with all input and output binding site numbers and major options that were used. The function can be called at any time in the analysis. Most optimal usage is after a full run of the wrapper function [BSFind](#).

Usage

```
processingStepsFlowChart(object, size.all = 3)
```

Arguments

object	a BSDataSet object
size.all	numeric; size of all numbers

Value

a plot of type [ggplot](#)

See Also[BSFind](#)**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,
  est.subsetChromosome = "chr22")
processingStepsFlowChart(bds)
```

processingStepsTable *Create a table of all workflow steps for reporting*

Description

Function that creates a printable table with all steps and numbers for each of the workflow steps that were carried out.

Usage

```
processingStepsTable(object, option = c("reduced", "full", "extended"))
```

Arguments

object	a BSFDataSet object with stored ranges
option	character; how detailed the table should be

Details

If `option` is set to 'reduced', only the most necessary information are collected. Option 'full' contains a full list of all options and parameters that were set in any of the workflow functions. Option 'extended' contains extra information about the binding site merging step.

Value

a `kableExtra` table

See Also[BSFind](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# apply 5% filter
bds = pureClipGlobalFilter(object = bds, cutoff = 0.05)
processingStepsTable(bds)
```

pureClipGeneWiseFilter

Filter PureCLIP sites by their score distribution per gene

Description

Function that applies a filter on the crosslink site score distribution at gene level. This allows to filter for those sites with the strongest signal on each gene. Since scores are tied to the expression level of the hosting transcript this function allows a fair filter for all genes partially independent of the expression level.

Usage

```
pureClipGeneWiseFilter(
  object,
  cutoff = 0.05,
  overlaps = c("keepSingle", "removeAll", "keepAll"),
  anno.annoDB = NULL,
  anno.genes = NULL,
  match.score = "score",
  match.geneID = "gene_id",
  quiet = FALSE
)
```

Arguments

object	a BSFDataSet object with stored crosslink ranges of width=1
cutoff	numeric; defines the cutoff for which sites to remove, the smallest step is 1% (0.01). A cutoff of 5% will remove the lowest 5% sites, given their score, on each gene, thus keeping the strongest 95%.
overlaps	character; how overlapping gene loci should be handled.
anno.annoDB	an object of class OrganismDbi that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class GenomicRanges that represents the gene ranges directly
match.score	character; meta column name of the crosslink site GenomicRanges object that holds the score which is used for sub-setting

match.geneID	character; meta column name of the genes GenomicRanges object that holds a unique geneID
quiet	logical; whether to print messages

Details

The [GenomicRanges](#) contained in the [BSFDataSet](#) need to have a meta-column that holds a numeric score value, which is used for filtering. The name of the column can be set with `scoreCol`.

In the case of overlapping gene annotation, a single crosslink site will be attributed to multiple genes. The `overlaps` parameter allows to control these cases. Option ‘keepSingle’ will only keep a single instance of the site; ‘removeAll’ will remove both sites; ‘keepAll’ will keep both sites.

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSFDataSet](#) with its ranges filtered by those that passed the gene-wise threshold set with `cutoff`

See Also

[BSFind](#), [estimateBsWidthPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# apply 5% gene-wise filter
pureClipGeneWiseFilter(object = bds, anno.genes = gns, cutoff = 0.5, overlaps = "keepSingle")
```

`pureClipGlobalFilter` *Filter PureCLIP sites by their score distribution*

Description

Function that applies a filter on the global crosslink site score distribution. The [GenomicRanges](#) contained in the [BSFDataSet](#) need to have a meta-column that holds a numeric score value, which is used for filtering. The name of the column can be set with `match.score`.

Usage

```
pureClipGlobalFilter(  
  object,  
  cutoff = 0.01,  
  match.score = "score",  
  quiet = FALSE  
)
```

Arguments

object	a BSFDataSet object with stored crosslink ranges of width=1
cutoff	numeric; defines the cutoff for which sites to keep, the smallest step is 1% (0.01)
match.score	character; meta column name of the crosslink site GenomicRanges object that holds the score which is used for sub-setting
quiet	logical; whether to print messages

Details

The function is part of the standard workflow performed by [BSFind](#).

Value

an object of class [BSFDataSet](#) with its ranges filtered by those that passed the threshold set with cutoff

See Also

[BSFind](#), [pureClipGlobalFilterPlot](#)

Examples

```
# load data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
# apply 5% filter  
pureClipGlobalFilter(object = bds, cutoff = 0.05)
```

pureClipGlobalFilterPlot

Plot the PureCLIP score distribution with global cutoff indicator

Description

A diagnostic function that plots the PureCLIP score distribution on a log2 scale. The function [pureClipGlobalFilter](#) is expected to be executed prior to calling this plot function.

Usage

```
pureClipGlobalFilterPlot(object)
```

Arguments

object a [BSFDataSet](#) object

Value

a plot of type [ggplot](#)

See Also

[pureClipGlobalFilter](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# apply 5% filter
bds = pureClipGlobalFilter(object = bds, cutoff = 0.05)
pureClipGlobalFilterPlot(bds)
```

quickFigure

Quick figures

Description

Summarize all results in a set of quick figures. Depending on how the function is called a different set of analytic plots are arranged into either a 'main' or 'supplementary' type multi-panel figure.

Usage

```
quickFigure(
  object,
  what = c("main", "supp"),
  save.filename = NULL,
  save.width = 10,
  save.height = 12,
  save.device = "pdf",
  quiet = TRUE,
  ...
)
```

Arguments

object	a BSFDataSet object
what	character; the plotting option. One of: 'main', 'supp'
save.filename	File name to create on the disc
save.width	numeric; plot size width
save.height	numeric; plot size height
save.device	charcter; Device to use. One of: 'pdf', 'png', ...
quiet	whether to print messages
...	further arguments passed to ggsave

Value

a plot

See Also

[BSFind](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,
  est.subsetChromosome = "chr22")
quickFigure(bds)
```

rangeCoveragePlot *Plot crosslink event coverage over binding site range*

Description

A diagnostic plot function that allows to check the coverage of crosslink events over different merged regions. The coverage is shown as mean over all replicates and conditions, with a standard deviation corridor.

Usage

```
rangeCoveragePlot(
  object,
  width = 20,
  show.samples = FALSE,
  subset.chromosome = "chr1",
  quiet = TRUE
)
```

Arguments

object	a BSFDataSet, or a list of BSFDataSet
width	numeric; set the plotting range to show (in nt)
show.samples	logical; to show individual samples as lines
subset.chromosome	character; subset by all ranges on the indicated chromosome. Can also be a vector with multiple chromosomes. If NULL then all ranges are being used.
quiet	logical; whether to print messages

Details

If object is a single BSFDataObject a single coverage plot will be drawn, whereas if it is a list of BSFDataObjects, then faceting is used to make a plot for each list element.

Value

a plot of type ggplot2 displaying the crosslink coverage over the ranges of the given [BSFDataSet](#)

See Also

[BSFDataSet](#), [makeBindingSites](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# plotting a single object
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1)
rangeCoveragePlot(bds, subset.chromosome = "chr22")

# plotting multiple objects
bds1 <- makeBindingSites(object = bds, bsSize = 3, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
bds2 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
l = list(`1. bsSize = 3` = bds1, `2. bsSize = 9` = bds2)
rangeCoveragePlot(l, subset.chromosome = "chr22")
```

reproducibilityCutoffPlot

Plot to that shows how many replicates support each binding site

Description

Plotting function for settings specified in [reproducibilityFilter](#).

Usage

```
reproducibilityCutoffPlot(
  object,
  cutoff = 0.05,
  min.crosslinks = 1,
  max.range = 20,
  ...
)
```

Arguments

object	a BSFDataSet object
cutoff	a vector of length = 1, or of length = levels(meta\$conditions) with a single number (between 0-1) indicating the quantile cutoff
min.crosslinks	numeric of length = 1, defines the lower boundary for the minimum number of crosslinks a binding site has to be supported by all replicates, regardless of the replicate specific quantile threshold
max.range	maximum number of crosslinks per sites that should be shown
...	further arguments passed to ggplot

Value

a plot of type ggplot2 showing the per replicate reproducibility cutoffs based on a given quantile threshold

See Also

[reproducibilityFilter](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# merge binding sites
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minC1Sites = 1)
```

```

# use the same cutoff for both conditions
suppressWarnings(reproducibilityCutoffPlot(bds, max.range = 20, cutoff = c(0.05)))

# use different cutoffs for each condition
suppressWarnings(reproducibilityCutoffPlot(bds, max.range = 20, cutoff = c(0.1)))

```

reproducibilityFilter *Replicate reproducibility filter function*

Description

For each replicate the number of binding sites with a certain number of crosslinks is calculated. A quantile based threshold (cutoff) is applied to each replicate. This indicates how many of the merged binding sites are supported by crosslinks from the respective replicate. Next, one can specify how many replicates need to pass the defined threshold for a binding site to be considered reproducible.

Usage

```

reproducibilityFilter(
  object,
  cutoff = NULL,
  nReps = NULL,
  minCrosslinks = 1,
  returnType = c("BSFDataSet", "data.frame"),
  n.reps = lifecycle::deprecated(),
  min.crosslinks = lifecycle::deprecated(),
  quiet = FALSE
)

```

Arguments

<code>object</code>	a BSFDataSet object
<code>cutoff</code>	numeric; percentage cutoff to be used for the reproducibility quantile filtering
<code>nReps</code>	numeric; number of replicates that must meet the cutoff defined in <code>cutoff</code> for a binding site to be called reproducible. Defaults to N-1.
<code>minCrosslinks</code>	numeric; minimal number of crosslinks a binding site needs to have to be called reproducible. Acts as a lower boundary for <code>cutoff</code> . Defaults to 1.
<code>returnType</code>	one of "BSFDataSet" or "data.frame". "BSFDataSet" is the default and "matrix" can be used for easy plotting.
<code>n.reps</code>	deprecated -> use <code>nReps</code> instead
<code>min.crosslinks</code>	deprecated -> use <code>minCrosslinks</code> instead
<code>quiet</code>	logical; whether to print messages

Details

If `cutoff` is a single number then the indicated cutoff will be applied to all replicates. If it is a vector then each element in the vector is applied to all replicates of the respective condition. The order is hereby given by the levels of the condition column of the meta data (see `BSFDataSet, getMeta`). If the condition specific filter is applied, a meta column is added to the GRanges of the BSFDataSet object, indicating the support for each condition.

If `nReps` is a single number then this number is used as threshold for all binding sites. If it is a vector then it is applied to the replicates of the respective condition (like in `cutoff`). This allows the application of different thresholds for experiments of different experimental conditions. If the condition specific filter is applied, a meta column is added to the GRanges of the BSFDataSet object, indicating the support for each condition.

The function is part of the standard workflow performed by `BSFind`.

Value

an object of type BSFDataSet

See Also

`BSFind, reproducibilityFilterPlot, reproducibilitySamplesPlot, reproducibilityScatterPlot`

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# merge binding sites
bds <- makeBindingSites(object = bds, bsSize = 9)

# use default return with condition specific threshold
bds = reproducibilityFilter(bds, cutoff = 0.1, nReps = 1)
```

reproducibilityFilterPlot

Plot to that shows the crosslink site distribution per replicate

Description

A diagnostic function that plots the number of crosslinks sites over the number of crosslink in these sites and highlights the replicate specific reproducibility cutoff that is derived from that distribution. The function `reproducibilityFilter` is expected to be executed prior to calling this plot function.

Usage

```
reproducibilityFilterPlot(object, plotRange = 20)
```

Arguments

object	a BSFDataSet object
plotRange	numeric; number of crosslinks per sites that should be shown before summing them up

Value

a plot of type [ggplot](#)

See Also

[reproducibilityFilter](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
bds = reproducibilityFilter(bds)
reproducibilityFilterPlot(bds)
```

reproducibilitySamplesPlot

UpSet-plot to that shows how each replicate supports binding sites

Description

A diagnostic function that plots the set sizes for each replicate, indicating how many binding site the specific replicate supports given its specific threshold. The function [reproducibilityFilter](#) is expected to be executed prior to calling this plot function.

Usage

```
reproducibilitySamplesPlot(
  object,
  nIntersections = 20,
  show.title = TRUE,
  text.size = NULL
)
```

Arguments

object	a BSFDataSet object
nIntersections	numeric; number of intersection to be shown
show.title	logical; if plot title should be visible
text.size	numeric; fontsize of all numbers on axis

Value

a plot of type `ggplot`

See Also

[reproducibilityFilter](#), [reproducibilityFilterPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
bds = reproducibilityFilter(bds)
reproducibilitySamplesPlot(bds)
```

reproducibilityScatterPlot

Plot that shows binding site reproducibility as scatter

Description

Function compute the number of crosslinks per binding site on a log2 scale for each sample. Samples are pairwise correlated as a scatter and pairwise pearson correlation is shown.

Usage

```
reproducibilityScatterPlot(object, quiet = FALSE)
```

Arguments

object	a BSFDataSet object
quiet	logical; whether to print messages

Details

Unlike most plotting functions, this function is actively calculating the values to plot.

Value

an object of class `ggplot2`

See Also

[BSFind](#), [reproducibilityFilter](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 3, sub.chr = "chr22")
reproducibilityScatterPlot(bds)
```

setMeta

Setter method for the meta data of the BSFDataSet object

Description

Meta data is stored as a `data.frame` and must contain the columns "condition", "clPlus" and "clMinus".

Usage

```
setMeta(object, ...)

## S4 method for signature 'BSFDataSet'
setMeta(object, newMeta)
```

Arguments

object	a BSFDataSet object
...	additional arguments
newMeta	the replacement meta data table

Value

an object of type `BSFDataSet` with updated meta data

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

nMeta = getMeta(bds)
setMeta(bds, nMeta)
```

setName	<i>Setter method for the names of the BSFDataSet object The name slot holds the name information of the dataset</i>
---------	---

Description

Setter method for the names of the BSFDataSet object The name slot holds the name information of the dataset

Usage

```
setName(object, ...)

## S4 method for signature 'BSFDataSet'
setName(object, newName)
```

Arguments

object	a BSFDataSet object
...	additional arguments
newName	a character that is the name

Value

object of type [BSFDataSet](#) with updated name

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = setName(bds, "test01")
```

setRanges	<i>Setter method for the ranges of the BSFDataSet object The GRanges object that holds the genomic ranges information can be replaced.</i>
-----------	--

Description

Setter method for the ranges of the BSFDataSet object The GRanges object that holds the genomic ranges information can be replaced.

Usage

```
setRanges(object, ...)

## S4 method for signature 'BSFDataSet'
setRanges(object, newRanges, dropSeqlevels = TRUE, quiet = FALSE)
```

Arguments

object	a BSFDataSet object
...	additional arguments
newRanges	an object of type GRanges
dropSeqlevels	enforce seqnames to be the same in ranges and signal, by dropping unused seqlevels which is required for most downstream functions such as coverageOverRanges
quiet	logical; whether to print messages

Value

object of type [BSFDataSet](#) with updated ranges

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

rng = getRanges(bds)
rng = rng + 10
bdsNew = setRanges(bds, rng)
```

`setSignal`

Setter method for the signal data of the BSFDataSet object

Description

Signal data is loaded from the path specified in [getMeta](#) columns "clPlus" and "clMinus" and stored as a list of RLE lists.

Usage

```
setSignal(object, ...)

## S4 method for signature 'BSFDataSet'
setSignal(object, newSignal, dropSeqlevels = TRUE, quiet = FALSE)
```

Arguments

object	a BSFDataSet object
...	additional arguments
newSignal	list of RLE lists
dropSeqlevels	enforce seqnames to be the same in ranges and signal, by dropping unused seqlevels which is required for most downstream functions such as <code>coverageOverRanges</code>
quiet	logical; whether to print messages

Value

an object of type [BSFDataSet](#) with updated signal

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

sgn = getSignal(bds)
sgn = lapply(sgn, function(selStrand){
  lapply(selStrand, function(chrList){
    chrList[names(chrList) == "chr22"]
  })
})
bdsNew = setSignal(bds, sgn)
```

setSummary*Setter method for the summary slot of the BSFDataSet object*

Description

The summary slot is used to track information of the filtering steps applied in the [makeBindingSites](#) function

Usage

```
setSummary(object, ...)

## S4 method for signature 'BSFDataSet'
setSummary(object, summary)
```

Arguments

object	a BSFDataSet object
...	additional arguments
summary	a data.frame with the summary information to be stored in BSFDataSet

Value

an object of type [BSFDataSet](#) with updated summary info

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

df = data.frame(processingStep = c(1,2),
parameter = c(3,4))
bds = setSummary(bds, df)
```

show*Show method to for the BSFDataSet*

Description

Prints the information for each of the input data slots in the [BSFDataSet](#) object.

Usage

```
## S4 method for signature 'BSFDataSet'  
show(object)
```

Arguments

object a BSFDataSet object

Value

shows the current object state

See Also

[BSFDataSet](#)

Examples

```
# load data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
  
show(bds)
```

subset-BSFDataSet*Subset a BSFDataSet object*

Description

You can subset [BSFDataSet](#) by identifier or by position using the `[`` operator. Empty seqlevels are being droppend after the subset.

Usage

```
## S4 method for signature 'BSFDataSet,ANY,ANY,ANY'  
x[i, j, ..., drop = FALSE]
```

Arguments

x	A BSFDataSet object.
i	Position of the identifier or the name of the identifier itself.
j	Not used.
...	Additional arguments not used here.
drop	if the signal not covered by the subsetted ranges should be dropped or not

Value

A [BSFDataSet](#) object.

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = bds[1:10]
```

summary

Summary method to for the BSFDataSet

Description

Prints the summaryinformation for the [BSFDataSet](#) object. This includes information on samples, conditions and crosslinks.

Usage

```
## S4 method for signature 'BSFDataSet'
summary(object)
```

Arguments

object	a BSFDataSet object
--------	-------------------------------------

Value

summary of the current object

See Also

[BSFDataSet](#)

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

summary(bds)
```

supportRatio

Support ratio function for BSFDataSet objects

Description

Functions that computes a ratio to determine how well a given binding site with is supported by the crosslink coverage of the data. For a given BSFDataSet object binding sites are computed for each width indicated in the `bsWidths` vector (using the `coverageOverRanges` function). These coverages are compared to the coverage of regions flanking the binding sites. If not indicated in `bsFlank` these regions are of the same width as the binding sites.

Usage

```
supportRatio(object, bsWidths, bsFlank = NA, sub.chr = NA, ...)
```

Arguments

<code>object</code>	a BSFDataSet object
<code>bsWidths</code>	a numeric vector indicating the different binding site width to compute the ratio for
<code>bsFlank</code>	optional; a numeric vector of the same length as <code>bsWidth</code> used to specify the width of the flanking regions
<code>sub.chr</code>	chromosome identifier (eg, chr1, chr2) used for subsetting the BSFDataSet object.
<code>...</code>	further arguments passed to <code>makeBindingSites</code>

Details

Testing the width of 3nt for example, would result in a coverage within all 3nt wide binding sites (c_1) and a coverage computed on the adjacent 3nt flanking the binding sites up- and downstream (f_1, f_2). Based on these numbers the ratio is computed by: $c_1/(1/2(f_1+f_2))$.

The median over all ratios is reported as representative value.

Value

an object of class `data.frame`

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

suppressWarnings(supportRatio(bds, bsWidths = c(3,7)))
```

supportRatioPlot	<i>Plot that shows the binding site support ratio</i>
------------------	---

Description

Function that shows a ratio to determine how well a given binding site width is supported by the crosslink coverage of the data. Ratios are computed using the [supportRatio](#) function.

Usage

```
supportRatioPlot(object, bsWidths, bsFlank = NA, ...)
```

Arguments

object	a BSFDataSet object
bsWidths	a numeric vector indicating the different binding site width to compute the ratio for
bsFlank	optional; a numeric vector of the same length as bsWidth used to specify the width of the flanking regions
...	further arguments passed to makeBindingSites

Details

The higher the ratio, the more does the given binding site width captures the enrichment of crosslinks compared to the local surrounding. A ratio equal to 1 would mean no enrichment at all.

Value

an object of class ggplot2

Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

suppressWarnings(supportRatioPlot(bds, bsWidths = c(3,7),
minWidth = 1, minCISites = 1, minCrosslinks = 2))
```

targetGeneSpectrumPlot

Bar-chart to show the hosting gene types of binding sites

Description

A diagnostic function that plots the gene type of the hosting gene for each binding site. The function [assignToGenes](#) is expected to be executed prior to calling this plot function.

Usage

```
targetGeneSpectrumPlot(object, showNGroups = 5, text.size = 4)
```

Arguments

object	a BSFDataSet object
showNGroups	numeric; the number of different gene types to show
text.size	numeric; the size of the text elements on the plot

Value

a plot of type [ggplot](#)

See Also

[assignToGenes](#) [geneOverlapsPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
targetGeneSpectrumPlot(bds)
```

transcriptRegionOverlapsPlot

UpSet-plot to that shows the transcript region overlaps

Description

A diagnostic function that plots the transcript regions of binding sites on overlapping loci. The function [assignToTranscriptRegions](#) is expected to be executed prior to calling this plot function.

Usage

```
transcriptRegionOverlapsPlot(object, text.size = NULL, show.title = TRUE)
```

Arguments

object	a BSFDataSet object
text.size	numeric; fontsize of all numbers on axis
show.title	logical; if plot title should be visible

Value

a plot of type [ggplot](#)

See Also

[assignToTranscriptRegions](#) [transcriptRegionSpectrumPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
transcriptRegionOverlapsPlot(bds)
```

transcriptRegionSpectrumPlot*Bar-chart to show the hosting transcript regions of binding sites*

Description

A diagnostic function that plots the transcript regions of the hosting gene for each binding site. The function [assignToTranscriptRegions](#) is expected to be executed prior to calling this plot function.

Usage

```
transcriptRegionSpectrumPlot(
  object,
  values = c("asis", "percentage"),
  normalize = FALSE,
  normalize.factor = c("sum", "median", "mean"),
  show.others = FALSE,
  text.size = 4
)
```

Arguments

object	a BSFDataSet object
values	character; if values should be presented 'as-is', that means for example as frequencies in case <code>normalize = FALSE</code> , or as percentages
normalize	logical; whether to normalize values
normalize.factor	character; indicate by what factor values should be normalized to region length by
show.others	logical; whether to show 'others' category. Has to be false if <code>normalize = TRUE</code>
text.size	numeric; font size of the numbers to be displayed on each bar

Details

Count frequencies can be normalized to the length of the hosting region with option `normalize`. The specific factor how the hosting region length is used is given by `normalize.factor`. In the case of `normalize.factor = "sum"` binding site frequencies are divided by the summed length of all regions that host the specific binding site.

Further with option `values` once can indicate whether raw or normalized frequencies should be shown 'as-is' or normalized to 'percentages'.

Value

a plot of type [ggplot](#)

See Also

[assignToTranscriptRegions](#) [transcriptRegionOverlapsPlot](#)

Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
transcriptRegionSpectrumPlot(bds)
```

Index

+ , BSFDataSet, BSFDataSet-method
 (add-BSFDataSet), 3
[], BSFDataSet, ANY, ANY, ANY-method
 (subset-BSFDataSet), 73

add-BSFDataSet, 3
annotateWithScore, 5, 14, 16, 17, 46
assignToGenes, 6, 14, 16, 17, 19, 35, 39, 41,
 77
assignToTranscriptRegions, 8, 14, 16, 17,
 35, 41, 78–80

bindingSiteCoveragePlot, 9
bindingSiteDefinednessPlot, 11, 24
BSFDataSet, 3, 4, 6–11, 12, 13, 15, 17–19, 21,
 22, 24, 26–30, 32–34, 36–50, 52–62,
 65, 66, 68–74, 77–79
BSFDataSet, (BSFDataSet), 12
BSFDataSet-class, (BSFDataSet), 12
BSFDataSetFromBigWig (BSFDataSet), 12
BSFind, 5, 7, 9, 11, 12, 13, 19, 23, 24, 26, 33,
 35, 36, 41, 49, 55, 56, 58, 59, 61, 65,
 67

calculateBsBackground, 18, 22, 28, 38, 52
calculateBsFoldChange, 20, 40, 41, 53–55
calculateSignalToFlankScore, 12, 14, 17,
 23
clipCoverage, 24
collapseReplicates, 26
combineBSF, 4, 19, 20, 27
CompressedGRangesList, 8, 17
coverageOverRanges, 29, 75

DESeq, 20–22
duplicatedSitesPlot, 30

estimateBsWidth, 14, 15, 17, 31, 32, 34
estimateBsWidthPlot, 17, 33, 34, 58
exportTargetGenes, 34
exportToBED, 35

filterBsBackground, 19, 20, 22, 36, 52
format, 35

geneOverlapsPlot, 7, 39, 77
geneRegulationPlot, 40
GenomicRanges, 5, 7, 17, 18, 32, 40, 57–59
getMeta, 42, 44, 65, 71
getMeta, BSFDataSet-method (getMeta), 42
getName, 42
getName, BSFDataSet-method (getName), 42
getRanges, 43
getRanges, BSFDataSet-method
 (getRanges), 43
getSignal, 44
getSignal, BSFDataSet-method
 (getSignal), 44
getSummary, 45
getSummary, BSFDataSet-method
 (getSummary), 45
ggplot, 12, 31, 34, 39, 46, 50, 52–55, 60, 66,
 67, 77–79
ggsave, 61
globalScorePlot, 5, 46

imputeBsDifferencesForTestdata, 46

lfcShrink, 21, 22

makeBindingSites, 14, 17, 33, 45, 47, 49–51,
 62, 72
makeBsSummaryPlot, 49, 49
mergeCrosslinkDiagnosticsPlot, 49, 50
mergeSummaryPlot, 51

option, 56
overlaps, 7, 9, 58

plotBsBackgroundFilter, 22, 38, 52
plotBsMA, 53
plotBsVolcano, 54
processingStepsFlowChart, 17, 28, 55

processingStepsTable, 56
pureClipGeneWiseFilter, 14–17, 30, 31, 33, 57
pureClipGlobalFilter, 13, 15, 17, 58, 59, 60
pureClipGlobalFilterPlot, 59, 59

quickFigure, 60

rangeCoveragePlot, 61
reproducibilityCutoffPlot, 63
reproducibilityFilter, 14, 17, 63, 64, 65–67
reproducibilityFilterPlot, 65, 65, 67
reproducibilitySamplesPlot, 65, 66
reproducibilityScatterPlot, 65, 67
results, 21, 22

setMeta, 68
setMeta, BSFDataSet-method (setMeta), 68
setName, 69
setName, BSFDataSet-method (setName), 69
setRanges, 70
setRanges, BSFDataSet-method
(setRanges), 70
setSignal, 71
setSignal, BSFDataSet-method
(setSignal), 71
setSummary, 72
setSummary, BSFDataSet-method
(setSummary), 72
show, 73
show, BSFDataSet-method (show), 73
subset-BSFDataSet, 73
summary, 74
summary, BSFDataSet-method (summary), 74
supportRatio, 75, 76
supportRatioPlot, 76

targetGeneSpectrumPlot, 7, 39, 77
transcriptRegionOverlapsPlot, 9, 78, 80
transcriptRegionSpectrumPlot, 9, 78, 79