

# Package ‘CSOA’

February 1, 2026

**Type** Package

**Title** Calculate per-cell gene signature scores in scRNA-seq data using cell set overlaps

**Version** 1.1.1

**Description** Cell Set Overlap Analysis (CSOA) is a tool for calculating per-cell gene signature scores in an scRNA-seq dataset. CSOA constructs a set for each gene in the signature, consisting of the cells that highly express the gene. Next, all overlaps of pairs of cell sets are computed, ranked, filtered and scored. The CSOA per-cell score is calculated by summing up all products of the overlap scores and the min-max-normalized expression of the two involved genes. CSOA can run on a Seurat object, a SingleCellExperiment object, a matrix and a dgCMatrix.

**License** MIT + file LICENSE

**Imports** bayesbio, dplyr, ggplot2, henna, kerntools, methods, qs, reshape2, rlang, Seurat, SeuratObject, SummarizedExperiment, spatstat.utils, stats, textshape, wesanderson

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Suggests** BiocStyle, knitr, patchwork, rmarkdown, scRNASeq, scuttle, stringr, testthat (>= 3.0.0)

**biocViews** Software, SingleCell, GeneSetEnrichment, GeneExpression

**VignetteBuilder** knitr

**URL** <https://github.com/andrei-stoica26/CSOA>

**BugReports** <https://github.com/andrei-stoica26/CSOA/issues>

**Config/testthat.edition** 3

**git\_url** <https://git.bioconductor.org/packages/CSOA>

**git\_branch** devel

**git\_last\_commit** c85d2c7

**git\_last\_commit\_date** 2025-12-02

**Repository** Bioconductor 3.23

**Date/Publication** 2026-02-01

**Author** Andrei-Florian Stoica [aut, cre] (ORCID:  
[<https://orcid.org/0000-0002-5253-0826>](https://orcid.org/0000-0002-5253-0826))

**Maintainer** Andrei-Florian Stoica <[andreistoica@foxmail.com](mailto:andreistoica@foxmail.com)>

## Contents

attachCellScores.default	2
basicHeatmap	4
breakWeakTies	5
cellDistribution	6
cellSetsOverlaps	6
computePairScores	7
computePCPairScores	8
edgeLists.default	8
expMat	9
featureWes	10
geneRadialPlot	11
generateOverlaps	13
getPairs	14
networkPlotDF	14
overlapCutoffPlot	15
overlapGenes	16
overlapNetworkPlot	16
overlapPairs	17
percentileSets	18
prefilterOverlaps	19
processOverlaps	19
qGrab	20
runCSOA	21
scoreCells	22
scoreCellsCore	24
scoreModules	25
wesBinaryGradient	26

## Index

27

---

### attachCellScores.default

*Attach CSOA scores to object*

---

#### Description

This function attaches the data frame of CSOA scores to the input object.

**Usage**

```
## Default S3 method:  
attachCellScores(scObj, scoreDF, ...)  
  
## S3 method for class 'Seurat'  
attachCellScores(scObj, scoreDF, ...)  
  
## S3 method for class 'SingleCellExperiment'  
attachCellScores(scObj, scoreDF, ...)  
  
## S3 method for class 'matrix'  
attachCellScores(scObj, scoreDF, ...)  
  
## S3 method for class 'dgCMatrix'  
attachCellScores(scObj, scoreDF, ...)  
  
attachCellScores(scObj, ...)
```

**Arguments**

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
scoreDF	Data frame of CSOA scores.
...	Additional arguments.

**Details**

If the input object is of the Seurat or SingleCellExperiment class, it will be returned with added CSOA scores. Otherwise, a list containing the expression matrix and the CSOA scores data frame will be returned.

**Value**

A Seurat object with CSOA scores added to metadata.  
A SingleCellExperiment object with CSOA scores added to `colData`.  
A list containing the expression matrix and the CSOA scores data frame.  
A list containing the expression matrix and the CSOA scores data frame.

**Examples**

```
library(Seurat)  
mat <- matrix(0, 500, 300)  
rownames(mat) <- paste0('G', seq(500))  
colnames(mat) <- paste0('C', seq(300))  
mat[sample(8000)] <- sample(20, 8000, TRUE)  
seuratObj <- CreateSeuratObject(mat)  
seuratObj <- NormalizeData(seuratObj)  
scores <- data.frame(CSOA = runif(300))  
seuratObj <- attachCellScores(seuratObj, scores)
```

```
head(seuratObj$CSOA)
```

---

basicHeatmap	<i>Plot a simple heatmap</i>
--------------	------------------------------

---

## Description

This function plots a simple heatmap, with clustering but no dendograms.

## Usage

```
basicHeatmap(
  mat,
  aesNames = c("x", "y", "Score"),
  title = "Heatmap",
  axisTextSize = 7,
  palType = "fillCont",
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2,
  ...
)
```

## Arguments

mat	A matrix.
aesNames	A character vector of length 3 representing the y, x and fill aes elements.
title	Plot title.
axisTextSize	Axis text size.
palType	Palette type: color or fill, continuous or discrete. Accepted values are 'color-Cont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.
...	Other arguments passed to henna::centerTitle.

## Value

A ggplot object.

## Examples

```
mat <- matrix(0, 10, 20)
mat[sample(length(mat), 50)] <- runif(50, max = 2.5)
basicHeatmap(mat)
```

---

breakWeakTies	<i>Remove overlap pairs with low Jaccard scores</i>
---------------	---

---

## Description

This function iteratively removes all overlap pairs with neighbor Jaccard score below a fixed cutoff until no overlap pairs can be removed. Subsequently, overlap ranks are recalculated.

## Usage

```
breakWeakTies(  
  overlapDF,  
  cutoff = 1/3,  
  doConnComp = FALSE,  
  mtMethod = c("BY", "BH")  
)
```

## Arguments

overlapDF	An overlap data frame.
cutoff	A cutoff used in the filtering of edges with low Jaccard scores.
doConnComp	Whether to calculate the connected components.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').

## Details

The function removes overlaps for which the two involved genes record too few shared neighbors—genes whose cell set significantly overlaps with those of both overlap genes.

## Value

An overlap data frame in which edges with low Jaccard scores have been removed.

## Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),  
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),  
  ratio=runif(10, 2, 10),  
  pval=runif(10, 0, 1e-10))  
breakWeakTies(overlapDF, cutoff=0.1)
```

---

cellDistribution	<i>Show the distribution of cell sets among cells</i>
------------------	---

---

## Description

This function returns a logical matrix that shows the representation of cell sets among all cells.

## Usage

```
cellDistribution(cellSets, allCells)
```

## Arguments

cellSets	A list of character vectors.
allCells	Names of all cells in the dataset.

## Value

A logical matrix with genes as rows and cells as columns.

## Examples

```
cellSets <- list(c('A', 'H', 'J'),
c('B', 'D', 'E', 'F', 'J'),
c('C', 'I', 'L'))
allCells <- LETTERS[seq(15)]
cellDistribution(cellSets, allCells)
```

---

cellSetsOverlaps	<i>Calculates the significance of overlaps of pairs of cells sets</i>
------------------	---

---

## Description

This function computes the statistical significance of overlaps of pairs of cell sets.

## Usage

```
cellSetsOverlaps(cellSets, nCells, pairs = NULL, overlapFileName = NULL)
```

**Arguments**

cellSets	A list of character arrays.
nCells	The total number of cells in the Seurat object.
pairs	Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.
overlapFileName	The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different jaccardCutoff parameters in breakWeakTies. Default is NULL (the overlap data frame will not be saved).

**Value**

A data frame listing statistics for all cell set overlaps: cell set sizes, recorded and expected shared cells, the recorded-over-expected ratio and the hypergeometric p-value.

**Examples**

```
cellSets <- list(G1 = c('A', 'H', 'J'),
G2 = c('B', 'D', 'E', 'F', 'J'),
G3 = c('C', 'I', 'L'))
cellSetsOverlaps(cellSets, 40)
```

computePairScores      *Compute aggregate gene pair scores*

**Description**

This function assesses the relative contribution of each gene pair to the CSOA score

**Usage**

```
computePairScores(
  overlapDF,
  pcPairScores,
  pairFileName = "pairs",
  keepOverlapOrder = FALSE
)
```

**Arguments**

overlapDF	An overlap data frame.
pcPairScores	A date frame of pair scores in each cell for each pair in the overlap data frame.
pairFileName	The name of the file where the pair data frame will be saved.
keepOverlapOrder	Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.

**Value**

A data frame with overlap and pair scores and ranks.

---

computePCPairScores	<i>Compute per-cell gene pair scores</i>
---------------------	--

---

**Description**

This function scores each gene pair corresponding to a top overlap in each cell.

**Usage**

```
computePCPairScores(overlapDF, normExp)
```

**Arguments**

overlapDF	An overlap data frame.
normExp	A min-max normalized expression matrix of the genes involved in top overlaps.

**Details**

The score is calculated by multiplying the overlap score with the min-max-normalized expression of the two corresponding genes.

**Value**

A data frame with gene pairs as rows and cells as columns.

---

edgeLists.default	<i>Extract the edge list from overlap data frame or list of overlap data frames</i>
-------------------	---

---

**Description**

This function creates a list of data frames with three columns: gene1, gene2 and group. If overlapObj is an overlap data frame, the groups correspond to the connected components. If it is a list of overlap data frames, the groups must be specified as groupNames.

**Usage**

```
## Default S3 method:  
edgeLists(overlapObj, ...)  
  
## S3 method for class 'data.frame'  
edgeLists(overlapObj, ...)  
  
## S3 method for class 'list'  
edgeLists(overlapObj, groupNames, cutoff = NULL, ...)  
  
edgeLists(overlapObj, ...)
```

**Arguments**

overlapObj	An overlap data frame or list of overlap data frames.
...	Additional arguments.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames.
cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed.

**Value**

A list of data frames.

---

expMat	<i>Extracts the data expression matrix from object</i>
--------	--

---

**Description**

This function extracts the data expression matrix from object as a non-sparse matrix. Selected genes can be specified as input.

**Usage**

```
expMat(scObj, ...)  
  
## Default S3 method:  
expMat(scObj, genes = NULL, ...)  
  
## S3 method for class 'Seurat'  
expMat(scObj, ...)  
  
## S3 method for class 'SingleCellExperiment'  
expMat(scObj, ...)
```

```
## S3 method for class 'dgCMatrix'
expMat(scObj, ...)

## S3 method for class 'matrix'
expMat(scObj, ...)
```

### Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
...	Additional arguments.
genes	Genes retained in the expression matrix. If NULL, all genes will be retained

### Value

An expression matrix.

### Examples

```
library(Seurat)
mat <- matrix(0, 6, 4)
mat[sample(1:length(mat), 7)] <- sample(3, 7, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- NormalizeData(seuratObj)
expMat(seuratObj)
```

---

featureWes

*A feature plot with a more distinctive color scheme.*

---

### Description

This function customizes the appearance of Seurat::FeaturePlot for improved distinctiveness and aesthetics.

### Usage

```
featureWes(
  seuratObj,
  feature,
  title = feature,
  idClass = NULL,
  labelSize = 3.5,
  titleSize = 12,
  wesPal = "Royal1",
  wesLow = 3,
  wesHigh = 2,
  ...
)
```

**Arguments**

seuratObj	A Seurat object.
feature	Seurat feature.
title	Plot title.
idClass	Column to be used for labelling. If NULL, no column-based labels will be generated.
labelSize	Size of labels. Ignored if idClass is NULL.
titleSize	Title size.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.
...	Additional arguments passed to Seurat::FeaturePlot.

**Value**

A ggplot object.

**Examples**

```
library(Seurat)
mat <- matrix(0, 3000, 800)
mat[sample(length(mat), 90000)] <- sample(8, 90000, TRUE)
seuratObj <- CreateSeuratObject(counts = mat)
seuratObj <- FindVariableFeatures(seuratObj, nfeatures=200)
seuratObj <- NormalizeData(seuratObj)
seuratObj <- ScaleData(seuratObj)
seuratObj <- RunPCA(seuratObj, verbose=FALSE)
seuratObj <- RunUMAP(seuratObj, dims=1:20, verbose=FALSE)
featureWes(seuratObj, 'Feature3')
```

**Description**

This function draws a radial plot for an overlap data frame to illustrate gene participation in top overlaps.

## Usage

```
geneRadialPlot(
  overlapObj,
  title = "Top overlap genes plot",
  degreeLegendTitle = "Number of top overlaps",
  groupLegendTitle = "Group",
  extraCircles = 2,
  groupNames = NULL,
  cutoff = NULL,
  ...
)
```

## Arguments

overlapObj	An overlap data frame or list of overlap data frames.
title	Plot title.
degreeLegendTitle	The title of the degree legend.
groupLegendTitle	The title of the group legend. If NULL, no groups will be distinguished.
extraCircles	Number of extra circles to be displayed on the plot.
groupNames	Names of groups. If provided, must be a vector of the same length as the list of overlap data frames.
cutoff	Number of retained edges from each overlap data frame after refiltering. If NULL (as default), no refiltering will be performed.
...	Additional parameters passed to henna::radialPlot.

## Details

The function can separate genes by groups. The groups can be, for instance, different gene sets, or different connected components of the same overlap data frame. A wrapper around henna::radialPlot

## Value

A ggplot object.

## Examples

```
edgesDF <- data.frame(gene1 = paste0('G', c(1, 2, 3, 4, 7, 8, 10,
11, 11, 10, 10, 10)),
gene2 = paste0('G', c(2, 5, 1, 8, 4, 9, 12,
13, 14, 13, 16, 14)))
edgesDF <- henna::connectedComponents(edgesDF, 'group')
geneRadialPlot(edgesDF, groupLegendTitle='Component', extraCircles=1)
```

---

generateOverlaps	<i>Generate overlaps of cell sets for input genes</i>
------------------	---

---

## Description

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile. Subsequently, overlaps of pairs of the constructed cell sets are assessed for statistical significance.

## Usage

```
generateOverlaps(
  geneSetExp,
  percentile = 90,
  pairs = NULL,
  overlapFileName = NULL
)
```

## Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
percentile	A positive number under 100.
pairs	Pairs of cell sets to be assessed. If NULL (as default), all pairs will be assessed.
overlapFileName	The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different jaccardCutoff parameters in breakWeakTies. Default is NULL (the overlap data frame will not be saved).

## Details

Wrapper around percentileSets and cellSetsOverlaps.

## Value

A data frame listing statistics for all cell set overlaps

## Examples

```
mat <- matrix(0, 2000, 500)
rownames(mat) <- paste0('G', seq(2000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 270000)] <- sample(50, 270000, TRUE)
mat <- mat[paste0('G', sample(2000, 5)), ]
generateOverlaps(mat)
```

---

getPairs	<i>Get all unordered pairs of two elements from a vector</i>
----------	--

---

### Description

This function returns all unordered pairs of two elements from a vector.

### Usage

```
getPairs(v)
```

### Arguments

v	A vector.
---	-----------

### Value

A list of vectors of length 2.

### Examples

```
v <- c('ASD', 'VBN', 'HJKL')
getPairs(v)
```

---

networkPlotDF	<i>Prepare overlap data frame for network plot</i>
---------------	--

---

### Description

This function prepares a ranked and filtered overlap data frame for network plot.

### Usage

```
networkPlotDF(overlapDF, rankCol = "rank", edgeScale = 2)
```

### Arguments

overlapDF	Overlap data frame.
rankCol	Name of the rank column.
edgeScale	Scaling factor used in generating edge weights.

### Value

A data frame ready to serve as input to networkPlot.

---

overlapCutoffPlot *Plot the selection of overlaps*

---

## Description

This function illustrates the process of selecting the overlap rank cutoff by plotting rank frequencies against ranks and showcasing the convex hull of the rank-frequency points.

## Usage

```
overlapCutoffPlot(  
  overlapDF,  
  title = "Overlap cutoff plot",  
  palette = c("purple", "yellow"),  
  hullWidth = 0.8,  
  xLab = "Overlap rank",  
  yLab = "Frequency",  
  legendLabs = c("Accepted overlaps", "Discarded overlaps"),  
  pointShape = 24,  
  ...  
)
```

## Arguments

overlapDF	Processed overlap data frame created with <code>processOverlaps</code> .
title	Plot title.
palette	Color palette. Must have two colors, the first one representing accepted overlaps and the other representing discarded overlaps.
hullWidth	Width of the convex hull.
xLab	x axis label.
yLab	y axis label.
legendLabs	Legend labels.
pointShape	Point shape.
...	Additional arguments passed to <code>henna::hullPlot</code> .

## Details

A wrapper around `henna::hullPlot`.

## Value

A `ggplot` object.

## Examples

```
overlapDF <- data.frame(gene1=paste0('G', c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
  gene2=paste0('G', c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
  rank=c(1, 2, 3, 4, 4, 6, 7, 7, 7, 10))
overlapCutoffPlot(overlapDF)
```

overlapGenes

*Get all genes from an overlap data frame*

## Description

This function gets all genes from an overlap data frame.

## Usage

```
overlapGenes(overlapDF, components = NULL)
```

## Arguments

- |            |   |
|------------|---|
| overlapDF  | Overlap data frame.   |
| components | A numeric vector representing the connected components of the overlap data frame graph. |

## Value

A character vector of genes.

## Examples

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
  gene2 = paste0('G', c(2, 7, 8)))
overlapGenes(overlapDF)
```

overlapNetworkPlot

*Plot the overlaps as a network*

## Description

This function plots the graph of the overlap data frame, with genes as vertices and overlaps as edges.

**Usage**

```
overlapNetworkPlot(  
  overlapDF,  
  title = "Top overlaps network plot",  
  nodeColor = "orange",  
  edgeColor = "green4",  
  ...  
)
```

**Arguments**

overlapDF	Overlap data frame.
title	Plot title.
nodeColor	The color of nodes. If NULL, the default henna::networkPlot color scheme will be used, which uses different colors for nodes belonging to different connected components.
edgeColor	The color of edges.
...	Additional parameters passed to henna::networkPlot.

**Details**

A thin wrapper around henna::networkPlot.

**Value**

An overlap network plot.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 5, 6, 7, 17)),  
  gene2 = paste0('G', c(2, 5, 8, 11, 11, 11)),  
  rank = c(1, 1, 3, 3, 3, 3))  
overlapNetworkPlot(overlapDF)
```

---

overlapPairs

*Extract gene pairs from overlap data frame*

---

**Description**

This function extracts the gene pairs from an overlap data frame.

**Usage**

```
overlapPairs(overlapDF)
```

**Arguments**

overlapDF      Overlap data frame.

**Value**

A list of gene pairs.

**Examples**

```
overlapDF <- data.frame(gene1 = paste0('G', c(1, 2, 3)),
gene1 = paste0('G', c(2, 7, 8)))
overlapPairs(overlapDF)
```

percentileSets      *Generates cell expressing input genes at an input percentile*

**Description**

This function constructs, for each gene in the expression matrix, a set of cells expressing the gene at or above the input percentile.

**Usage**

```
percentileSets(geneSetExp, percentile = 90)
```

**Arguments**

geneSetExp      A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.  
percentile      A positive number under 100.

**Value**

A named list of character vectors of length equaling the number of input genes. Each vector stores the cells expressing the gene at or above the input percentile.

**Examples**

```
mat <- matrix(0, 1000, 500)
rownames(mat) <- paste0('G', seq(1000))
colnames(mat) <- paste0('C', seq(500))
mat[sample(length(mat), 70000)] <- sample(50, 70000, TRUE)
mat <- mat[paste0('G', sample(1000, 3)), ]
percentileSets(mat)
```

---

prefilterOverlaps	<i>Prefilter overlaps based on adjusted p-value</i>
-------------------	---

---

### Description

This function computes adjusted p-value and prefilters overlaps based on it.

### Usage

```
prefilterOverlaps(overlapDF, mtMethod = c("BY", "BH"))
```

### Arguments

overlapDF	Overlap data frame.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').

### Value

A prefiltered overlap data frame.

---

processOverlaps	<i>Process data frame of overlaps of cell sets</i>
-----------------	--

---

### Description

This function filters, ranks and scores previously generated overlaps of cell sets.

### Usage

```
processOverlaps(
  overlapDF,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  ...
)
```

### Arguments

overlapDF	Overlap data frame.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
...	Additional arguments passed to <code>mtCorrectDF</code> .

**Details**

Wrapper around `byCorrectDF`, `rankOverlaps`, `prepareFiltering`, `filterOverlaps` and `scoreOverlaps`. If `jaccardCutoff` is not `NULL`, it also calls `breakWeakTies` between `filterOverlaps` and `scoreOverlaps`.

**Value**

A data frame consisting of filtered, ranked and scored cell sets overlaps

**Examples**

```
overlapDF <- data.frame(gene1=paste0('G',
c(1, 3, 7, 6, 8, 2, 4, 3, 4, 5)),
gene2=paste0('G',
c(2, 7, 2, 5, 4, 5, 1, 2, 2, 8)),
ratio=runif(10, 2, 10),
pval=runif(10, 0, 1e-10))
processOverlaps(overlapDF)
```

---

**qGrab**

*Read and delete a .qs file*

---

**Description**

This functions reads a .qs file, deletes it, and returns its content.

**Usage**

```
qGrab(qsFile)
```

**Arguments**

`qsFile` Name of .qs file with path.

**Value**

The content of the .qs file.

**Examples**

```
library(qs)
qsave(c(1, 2, 3), 'temp.qs')
qGrab('temp.qs')
```

---

runCSOA	<i>Run the CSOA pipeline</i>
---------	------------------------------

---

## Description

This function generates cell set overlaps for input gene sets based on percentiles of gene expression, computes the significance of these overlaps, ranks, filters and scores the overlaps, and builds a per-cell score by summing the products of overlap scores and the min-max-normalized expression of the corresponding pairs of genes.

## Usage

```
runCSOA(
  scObj,
  geneSets,
  percentile = 90,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  overlapFileName = NULL,
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE,
  ...
)
```

## Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
geneSets	Named list of character vectors of which each must contain at least two genes.
percentile	A positive number under 100.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
overlapFileName	The name of the file where the overlap data frame will be saved. This option can be used to save time when performing exploratory analyses such as trying different jaccardCutoff parameters in <code>breakWeakTies</code> . Default is NULL (the overlap data frame will not be saved).
pairFileTemplate	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).
keepOverlapOrder	Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if <code>pairFileTemplate</code> is NULL.

... Additional arguments.

### Details

Wrapper around expMat, generateOverlaps, scoreCells and attachCellScores.

### Value

An object of the same class as scObj with per-gene-set CSOA scores assigned for each cell.

### Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min = 14, max = 15),
nrow = 200, ncol = 31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
df <- runCSOA(mat, list(a = geneSet1, b = geneSet2))
head(df)
```

### scoreCells

*Generate CSOA scores from overlap data frame and list of pairs*

### Description

This function scores an overlap data frame using its associated list of pairs. The overlap data frame is split based on the overlaps corresponding to each gene set and scored, and the output is rejoined as a data frame.

### Usage

```
scoreCells(
  geneSetExp,
  overlapDF,
  setPairs,
  geneSetNames,
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileTemplate = NULL,
  keepOverlapOrder = FALSE,
  ...
)
```

## Arguments

geneSetExp	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
overlapDF	Overlap data frame.
setPairs	A list of overlaps corresponding to each input gene set.
geneSetNames	Character vector of names of gene sets.
mtMethod	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').
jaccardCutoff	A cutoff used in the filtering of edges with low Jaccard scores. If NULL (as default), no filtering of such edges will be performed.
osMethod	Method used to compute overlap scores. Options are "log" and "minmax".
pairFileTemplate	Character object used in the naming of the files where the pair data frames will be saved. Default is NULL (the pair data frames will not be saved).
keepOverlapOrder	Keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order. Ignored if pairFileTemplate is NULL.
...	Additional arguments passed to mtCorrectDF.

## Details

This function calls scoreCells to score each gene set data frame split from the full overlap data frame.

## Value

A data frame whose columns correspond to the CSOA scores of the input gene sets.

## Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes <- paste0('G', seq(200))
mat[genes, 20:50] <- matrix(runif(200 * 31, min=14, max=15),
nrow=200, ncol=31)
geneSet1 <- paste0('G', seq(1, 150))
geneSet2 <- paste0('G', seq(50, 200))
geneSets <- list(geneSet1, geneSet2)
geneSets <- lapply(geneSets, sort)
setPairs <- lapply(geneSets, getPairs)
pairs <- Reduce(union, setPairs)
genes <- union(geneSet1, geneSet2)
mat <- mat[genes, ]
overlapDF <- generateOverlaps(mat, pairs=pairs)
scoreDF <- scoreCells(mat, overlapDF, setPairs, c('set1', 'set2'))
head(scoreDF)
```

---

<code>scoreCellsCore</code>	<i>Generate CSOA scores from overlap data frame for a single gene set</i>
-----------------------------	---

---

## Description

This function computes per-cell CSOA scores from overlap data frame for a single gene set.

## Usage

```
scoreCellsCore(
  geneSetExp,
  overlapDF,
  colStr = "CSOA",
  mtMethod = c("BY", "BH"),
  jaccardCutoff = NULL,
  osMethod = c("log", "minmax"),
  pairFileName = NULL,
  keepOverlapOrder = FALSE,
  ...
)
```

## Arguments

<code>geneSetExp</code>	A gene expression non-sparse matrix with the rows restricted to the genes for which cell sets will be computed.
<code>overlapDF</code>	Overlap data frame.
<code>colStr</code>	Name of column where CSOA scores will be stored.
<code>mtMethod</code>	Multiple testing correction method. Choose between Benjamini-Yekutieli ('BY') and Benjamini-Hochberg('BH').
<code>jaccardCutoff</code>	A cutoff used in the filtering of edges with low Jaccard scores. If <code>NULL</code> (as default), no filtering of such edges will be performed.
<code>osMethod</code>	Method used to compute overlap scores. Options are "log" and "minmax".
<code>pairFileName</code>	The name of the file where the pair data frame will be saved.
<code>keepOverlapOrder</code>	Whether to keep the rank-based order of overlaps in the pair score file, as opposed to changing it to a pair score-based order.
<code>...</code>	Additional arguments passed to <code>mtCorrectDF</code> .

## Value

A data frame with a column corresponding to the CSOA scores.

---

scoreModules	<i>Run CSOA separately on the connected components of the overlap graph</i>
--------------	---

---

## Description

This function runs CSOA on the connected components of the graph having the filtered overlaps as edges.

## Usage

```
scoreModules(
  scObj,
  networkDF,
  components,
  colStrTemplate = "CSOA_component",
  ...
)
```

## Arguments

scObj	A Seurat object, SingleCellExperiment object, or expression matrix.
networkDF	A data frame with gene1, gene2 and component columns.
components	A numeric vector representing the connected components of the overlap data frame graph.
colStrTemplate	Character used in the naming of the component gene sets.
...	Additional parameters passed to runCSOAMultiple.

## Value

An object of the same class as scObj with CSOA scores corresponding to the genes defining each connected components assigned for each cell.

## Examples

```
mat <- matrix(0, 500, 300)
rownames(mat) <- paste0('G', seq(500))
colnames(mat) <- paste0('C', seq(300))
mat[sample(8000)] <- runif(8000, max=13)
genes1 <- paste0('G', seq(100))
mat[genes1, 20:50] <- matrix(runif(100 * 31, min = 14, max = 15),
nrow = 100, ncol = 31)
genes2 <- paste0('G', seq(101, 200))
mat[genes2, 70:100] <- matrix(runif(100 * 31, min = 14, max = 15),
nrow = 100, ncol = 31)
genes <- union(genes1, genes2)
mat <- mat[genes, ]
```

```
overlapDF <- generateOverlaps(mat)
overlapDF <- processOverlaps(overlapDF)
overlapDF <- henna::connectedComponents(overlapDF)
df <- scoreModules(mat, overlapDF, unique(overlapDF$component))[[2]]
head(df)
```

---

wesBinaryGradient	<i>Adds a gradient color scale using two wesanderson colors</i>
-------------------	---

---

## Description

This function adds a gradient color scale to a ggplot object using a wesanderson palette, an index marking low values, and an index marking high values. The indices are used to select colors from the wesanderson palette of choice.

## Usage

```
wesBinaryGradient(p, palType, wesPal = "Royal1", wesLow = 3, wesHigh = 2, ...)
```

## Arguments

p	A ggplot object.
palType	Palette type: color or fill, continuous or discrete. Accepted values are 'colorCont', 'fillCont', 'colDis' and 'fillDis'. The function shows a warning and does not change the color scheme if a different value is passed here.
wesPal	A wesanderson palette.
wesLow	Index of color marking low values.
wesHigh	Index of color marking high values.
...	Arguments passed to other functions.

## Value

A ggplot object with a new color scheme.

# Index

\* **internal**  
  computePairScores, 7  
  computePCPairScores, 8  
  edgeLists.default, 8  
  networkPlotDF, 14  
  prefilterOverlaps, 19  
  scoreCellsCore, 24  
  wesBinaryGradient, 26

attachCellScores  
  (attachCellScores.default), 2  
attachCellScores.default, 2

basicHeatmap, 4  
breakWeakTies, 5

cellDistribution, 6  
cellSetsOverlaps, 6  
computePairScores, 7  
computePCPairScores, 8

edgeLists (edgeLists.default), 8  
edgeLists.default, 8  
expMat, 9

featureWes, 10

geneRadialPlot, 11  
generateOverlaps, 13  
getPairs, 14

networkPlotDF, 14

overlapCutoffPlot, 15  
overlapGenes, 16  
overlapNetworkPlot, 16  
overlapPairs, 17

percentileSets, 18  
prefilterOverlaps, 19  
processOverlaps, 19

qGrab, 20  
runCSOA, 21  
scoreCells, 22  
scoreCellsCore, 24  
scoreModules, 25

wesBinaryGradient, 26