

Package ‘EDASeq’

February 1, 2026

Version 2.45.0

Title Exploratory Data Analysis and Normalization for RNA-Seq

Description Numerical and graphical summaries of RNA-Seq read data.

Within-lane normalization procedures to adjust for GC-content effect (or other gene-level effects) on read counts: loess robust local regression, global-scaling, and full-quantile normalization (Risso et al., 2011). Between-lane normalization procedures to adjust for distributional differences between lanes (e.g., sequencing depth): global-scaling and full-quantile normalization (Bullard et al., 2010).

Author Davide Risso [aut, cre, cph], Sandrine Dudoit [aut], Ludwig Geistlinger [ctb]

Maintainer Davide Risso <risso.davide@gmail.com>

Date 08-30-2011

Depends Biobase (>= 2.15.1), ShortRead (>= 1.11.42)

Imports methods, graphics, BiocGenerics, IRanges (>= 1.13.9),
aroma.light, Rsamtools (>= 1.5.75), biomaRt, Biostrings,
AnnotationDbi, GenomicFeatures, GenomicRanges, BiocManager

Suggests BiocStyle, knitr, yeastRNASEq, leeBamViews, edgeR,
KernSmooth, testthat, DESeq2, rmarkdown

VignetteBuilder knitr

License Artistic-2.0

LazyLoad yes

biocViews ImmunoOncology, Sequencing, RNASEq, Preprocessing,
QualityControl, DifferentialExpression

URL <https://github.com/drisso/EDASeq>

BugReports <https://github.com/drisso/EDASeq/issues>

RoxygenNote 7.1.0

git_url <https://git.bioconductor.org/packages/EDASeq>

git_branch devel

git_last_commit 1f147bc

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-02-01

Contents

EDASeq-package	2
barplot-methods	3
betweenLaneNormalization-methods	3
biasBoxplot-methods	5
biasPlot-methods	6
boxplot-methods	7
getGeneLengthAndGCContent	7
MDPlot-methods	8
meanVarPlot-methods	9
newSeqExpressionSet	9
plot-methods	10
plotNtFrequency-methods	11
plotPCA-methods	11
plotQuality-methods	12
plotRLE-methods	13
SeqExpressionSet-class	14
withinLaneNormalization-methods	16
yeastGC	17
yeastLength	18

Index

19

EDASeq-package

Exploratory Data Analysis and Normalization for RNA-Seq data

Description

Numerical summaries and graphical representations of some key features of the data along with implementations of both within-lane normalization methods for GC content bias and between-lane normalization methods to adjust for sequencing depth and possibly other differences in distribution.

Details

The [SeqExpressionSet](#) class is used to store gene-level counts along with sample information. It extends the virtual class [eSet](#). See the help page of the class for details.

"Read-level" information is managed via the [FastqFileList](#) and [BamFileList](#) classes of [Rsamtools](#).

Most used graphic tools for the [FastqFileList](#) and [BamFileList](#) objects are: 'barplot', 'plotQuality', 'plotNtFrequency'. For [SeqExpressionSet](#) objects are: 'biasPlot', 'meanVarPlot', 'MDPlot'.

To perform gene-level normalization use the functions 'withinLaneNormalization' and 'betweenLaneNormalization'.

See the package vignette for a typical Exploratory Data Analysis example.

Author(s)

Davide Risso and Sandrine Dudoit. Maintainer: Davide Risso <risso.davide@gmail.com>

References

- J. H. Bullard, E. A. Purdom, K. D. Hansen and S. Dudoit (2010). Evaluation of statistical methods for normalization and differential expression in mRNA-Seq experiments. *BMC Bioinformatics* Vol. 11, Article 94.
- D. Risso, K. Schwartz, G. Sherlock and S. Dudoit (2011). GC-Content Normalization for RNA-Seq Data. Technical Report No. 291, Division of Biostatistics, University of California, Berkeley, Berkeley, CA.

Description

High-level functions to produce barplots of some complex objects.

Methods

- `signature(height = "BamFile")` Usage: `barplot(height,strata=c("rname","strand"))` It produces a barplot of the total number of reads in each chromosome (if "rname") or strand.
- `signature(height = "BamFileList")` It produces a barplot of the total number of reads in each object in height. If `unique=TRUE` is specified, it stratified the total by uniquely/non-uniquely mapped reads.
- `signature(height = "FastqFileList")` It produces a barplot of the total number of reads in each object in height.

Description

Between-lane normalization for sequencing depth and possibly other distributional differences between lanes.

Usage

```
betweenLaneNormalization(x, which=c("median","upper","full"), offset=FALSE, round=TRUE)
```

Arguments

x	A numeric matrix representing the counts or a <code>SeqExpressionSet</code> object.
which	Method used to normalized. See the details section and the reference below for details.
offset	Should the normalized value be returned as an offset leaving the original counts unchanged?
round	If TRUE the normalization returns rounded values (pseudo-counts). Ignored if offset=TRUE.

Details

This method implements three normalizations described in Bullard et al. (2010). The methods are:

- median:** a scaling normalization that forces the median of each lane to be the same.
- upper:** the same but with the upper quartile.
- full:** a non linear full quantile normalization, in the spirit of the one used in microarrays.

Methods

`signature(x = "matrix")` It returns a matrix with the normalized counts if `offset=FALSE` or with the offset if `offset=TRUE`.

`signature(x = "SeqExpressionSet")` It returns a `linkS4class{SeqExpressionSet}` with the normalized counts in the `normalizedCounts` slot and with the offset in the `offset` slot (if `offset=TRUE`).

Author(s)

Davide Risso.

References

- J. H. Bullard, E. A. Purdom, K. D. Hansen and S. Dudoit (2010). Evaluation of statistical methods for normalization and differential expression in mRNA-Seq experiments. *BMC Bioinformatics* Vol. 11, Article 94.
- D. Risso, K. Schwartz, G. Sherlock and S. Dudoit (2011). GC-Content Normalization for RNA-Seq Data. Manuscript in Preparation.

Examples

```
library(yeastRNASeq)
data(geneLevelData)
data(yeastGC)

sub <- intersect(rownames(geneLevelData), names(yeastGC))

mat <- as.matrix(geneLevelData[sub, ])

data <- newSeqExpressionSet(mat,
```

```
phenoData=AnnotatedDataFrame(  
  data.frame(conditions=factor(c("mut", "mut", "wt", "wt")),  
            row.names=colnames(geneLevelData))),  
  featureData=AnnotatedDataFrame(data.frame(gc=yeastGC[sub])))  
  
norm <- betweenLaneNormalization(data, which="full", offset=FALSE)
```

biasBoxplot-methods *Methods for Function biasBoxplot in Package EDASeq*

Description

`biasBoxplot` produces a boxplot representing the distribution of a quantity of interest (e.g. gene counts, log-fold-changes, ...) stratified by a covariate (e.g. gene length, GC-content, ...).

Usage

```
biasBoxplot(x,y,num.bins,...)
```

Arguments

- | | |
|----------|--|
| x | A numeric vector with the quantity of interest (e.g. gene counts, log-fold-changes, ...) |
| y | A numeric vector with the covariate of interest (e.g. gene length, GC-content, ...) |
| num.bins | A numeric value specifying the number of bins in which to stratify y. Default to 10. |
| ... | See par |

Methods

`signature(x = "numeric", y = "numeric", num.bins = "numeric")` It plots a line representing the regression of every column of the matrix `x` on the numeric covariate `y`. One can pass the usual graphical parameters as additional arguments (see [par](#)).

Examples

```
library(yeastRNASeq)
data(geneLevelData)
data(yeastGC)

sub <- intersect(rownames(geneLevelData), names(yeastGC))

mat <- as.matrix(geneLevelData[sub,])

data <- newSeqExpressionSet(mat,
                           phenoData=AnnotatedDataFrame(
                               data.frame(conditions=factor(c("mut", "mut", "wt", "wt"))),
```

```

  row.names=colnames(geneLevelData))),
  featureData=AnnotatedDataFrame(data.frame(gc=yeastGC[sub])))

lfc <- log(geneLevelData[sub, 3] + 1) - log(geneLevelData[sub, 1] + 1)

biasBoxplot(lfc, yeastGC[sub], las=2, cex.axis=.7)

```

biasPlot-methods
*Methods for Function biasPlot in Package **EDASeq***

Description

biasPlot produces a plot of the [lowess](#) regression of the counts on a covariate of interest, typically the GC-content or the length of the genes.

Methods

`signature(x = "matrix", y = "numeric")` It plots a line representing the regression of every column of the matrix `x` on the numeric covariate `y`. One can pass the usual graphical parameters as additional arguments (see [par](#)).

`signature(x = "SeqExpressionSet", y = "character")` It plots a line representing the regression of every lane in `x` on the covariate specified by `y`. `y` must be one of the column of the `featureData` slot of the `x` object. One can pass the usual graphical parameters as additional arguments (see [par](#)). The parameter `color_code` (optional) must be a number specifying the column of `phenoData` to be used for color-coding. By default it is color-coded according to the first column of `phenoData`. If `legend=TRUE` and `col` is not specified a legend with the information stored in `phenoData` is added.

Examples

```

library(yeastRNASeq)
data(geneLevelData)
data(yeastGC)

sub <- intersect(rownames(geneLevelData), names(yeastGC))

mat <- as.matrix(geneLevelData[sub,])

data <- newSeqExpressionSet(mat,
                           phenoData=AnnotatedDataFrame(
                             data.frame(conditions=factor(c("mut", "mut", "wt", "wt"))),
                             row.names=colnames(geneLevelData))),
                           featureData=AnnotatedDataFrame(data.frame(gc=yeastGC[sub])))

biasPlot(data, "gc", ylim=c(0,5), log=TRUE)

```

Description

High-level functions to produce boxplots of some complex objects.

Methods

`signature(x = "FastqQuality")` It plots the distribution of the quality per read position.

`signature(x = "SeqExpressionSet")` It plots the distribution of the log counts in each lane of x.

Description

Automatically retrieves gene length and GC-content information from Biomart or org.db packages.

Usage

```
getGeneLengthAndGCContent(id, org, mode=c("biomart", "org.db"))
```

Arguments

<code>id</code>	Character vector of one or more ENSEMBL or ENTREZ gene IDs.
<code>org</code>	Organism three letter code, e.g. 'hsa' for 'Homo sapiens'. See also: http://www.genome.jp/kegg/catalog/organism.html . In org.db mode, this can be also a specific genome assembly, e.g. 'hg38' or 'sacCer3'.
<code>mode</code>	Mode to retrieve the information. Defaults to 'biomart'. See Details.

Details

The 'biomart' mode is based on functionality from the biomaRt package and retrieves the required information from the BioMart database. This is available for all ENSEMBL organisms and is typically most current, but can be time-consuming when querying several thousand genes at a time.

The 'org.db' mode uses organism-based annotation packages from Bioconductor. This is much faster than the 'biomart' mode, but is only available for selected model organism currently supported by BioC annotation functionality.

Results for the same gene ID(s) can differ between both modes as they are based on different sources for the underlying genome assembly. While the 'biomart' mode uses the latest ENSEMBL version, the 'org.db' mode uses BioC annotation packages typically built from UCSC.

Value

A numeric matrix with two columns: gene length and GC-content.

Author(s)

Ludwig Geistlinger <Ludwig.Geistlinger@bio.ifi.lmu.de>

See Also

[getSequence](#) to retrieve a genomic sequence from BioMart, [genes](#) to extract genomic coordinates from a TxDb object, [getSeq](#) to extract genomic sequences from a BSgenome object, [alphabetFrequency](#) to calculate nucleotide frequencies.

Examples

```
getGeneLengthAndGCContent("ENSG00000012048", "hsa")
```

Description

MDPlot produces a mean-difference smooth scatterplot of two lanes in an experiment.

Usage

```
MDPlot(x, y, ...)
```

Arguments

- x Either a numeric matrix or a [SeqExpressionSet](#) object containing the gene expression.
- y A numeric vector specifying the lanes to be compared.
- ... See [par](#)

Details

The mean-difference (MD) plot is a useful plot to visualize difference in two lanes of an experiment. From a MDPlot one can see if normalization is needed and if a linear scaling is sufficient or nonlinear normalization is more effective.

The MDPlot also plots a lowess fit (in red) underlying a possible trend in the bias related to the mean expression.

Methods

```
signature(x = "matrix", y = "numeric")
signature(x = "SeqExpressionSet", y = "numeric")
```

Examples

```
library(yeastRNASeq)
data(geneLevelData)
data(yeastGC)

sub <- intersect(rownames(geneLevelData), names(yeastGC))

mat <- as.matrix(geneLevelData[sub,])

data <- newSeqExpressionSet(mat,
                           phenoData=AnnotatedDataFrame(
                               data.frame(conditions=factor(c("mut", "mut", "wt", "wt"))),
                               row.names=colnames(geneLevelData))),
                           featureData=AnnotatedDataFrame(data.frame(gc=yeastGC[sub])))

MDPlot(data,c(1,3))
```

Description

meanVarPlot produces a smoothScatter plot of the mean variance relation.

Methods

`signature(x = "SeqExpressionSet")` It takes as additional argument `log`, which if true consider the logarithm of the counts before computing mean and variance. To avoid missing values, we consider the maximum between 0 and the log of the counts. Along with the scatter plot the function plots a line representing the [lowess](#) fit.

Description

User-level function to create new objects of the class [SeqExpressionSet](#).

Usage

```
newSeqExpressionSet(counts,
                   normalizedCounts = matrix(data=NA, nrow=nrow(counts), ncol=ncol(counts), dimnames=dimnames(counts)),
                   offset = matrix(data=0, nrow=nrow(counts), ncol=ncol(counts), dimnames=dimnames(counts)),
                   phenoData = annotatedDataFrameFrom(counts, FALSE),
                   featureData = annotatedDataFrameFrom(counts, TRUE),
                   ...)
```

Arguments

counts	A matrix containing the counts for an RNA-Seq experiment. One column for each lane and one row for each gene.
normalizedCounts	A matrix with the same dimensions of counts with the normalized counts.
offset	A matrix with the same dimensions of counts defining the offset (usually useful for normalization purposes). See the package vignette for a discussion on the offset.
phenoData	A data.frame or AnnotatedDataFrame with sample information, such as biological condition, library preparation protocol, flow-cell,...
featureData	A data.frame or AnnotatedDataFrame with feature information, such as gene length, GC-content, ...
...	Other arguments will be passed to the constructor inherited from eSet .

Value

An object of class [SeqExpressionSet](#).

Author(s)

Davide Risso

See Also

[SeqExpressionSet](#)

Examples

```
counts <- matrix(data=0, nrow=100, ncol=4)
for(i in 1:4) {
  counts[, i] <- rpois(100, lambda=50)
}
cond <- c(rep("A", 2), rep("B", 2))

counts <- newSeqExpressionSet(counts, phenoData=data.frame(conditions=cond))
```

Description

High-level function to produce plots given one `BamFileList` object and one `FastqFileList` object.

Methods

`signature(x = "BamFileList", y = "FastqFileList")` It produce a barplot of the percentage of mapped reads. If `strata=TRUE` it stratifies the bars according to the unique/non-unique mapped reads. To be meaningful, `x` should be a set of aligned reads and `y` a set of raw reads on the same samples.

plotNtFrequency-methods

*Methods for Function plotNtFrequency in Package **EDASeq***

Description

Plots the nucleotide frequencies per position.

Methods

`signature(x = "ShortRead")`
`signature(x = "BamFile")`

It plots the nucleotide frequencies per position, averaging all the reads in `x`.

plotPCA-methods

*Methods for Function plotPCA in Package **EDASeq***

Description

`plotPCA` produces a Principal Component Analysis (PCA) plot of the counts in object

Usage

```
## S4 method for signature 'matrix'
plotPCA(object, k=2, labels=TRUE, isLog=FALSE, ...)
## S4 method for signature 'SeqExpressionSet'
plotPCA(object, k=2, labels=TRUE, ...)
```

Arguments

<code>object</code>	Either a numeric matrix or a <code>SeqExpressionSet</code> object containing the gene expression.
<code>k</code>	The number of principal components to be plotted.
<code>labels</code>	Logical. If <code>TRUE</code> , and <code>k=2</code> , it plots the <code>colnames</code> of <code>object</code> as point labels.
<code>isLog</code>	Logical. Set to <code>TRUE</code> if the data are already on the log scale.
<code>...</code>	See <code>par</code>

Details

The Principal Component Analysis (PCA) plot is a useful diagnostic plot to highlight differences in the distribution of replicate samples, by projecting the samples into a lower dimensional space.

If there is strong differential expression between two classes, one expects the samples to cluster by class in the first few Principal Components (PCs) (usually 2 or 3 components are enough). This plot also highlights possible batch effects and/or outlying samples.

Methods

```
signature(x = "matrix")  
signature(x = "SeqExpressionSet")
```

Examples

plotQuality-methods *Methods for Function plotQuality in Package EDASeq*

Description

`plotQuality` produces a plot of the quality of the reads.

Methods

- signature(x = "BamFileList") It produces a plot that summarizes the per-base mean quality of the reads of each BAM file in x.
- signature(x = "BamFile") It produces a boxplot of the per-base distribution of the quality scores of the reads in x.
- signature(x = "FastqFileList") It produces a plot that summarizes the per-base mean quality of the reads of each FASTQ file in x.

Details

Since FASTQ files can be very long, it can be very expensive to process a whole file. One way to avoid this, is to consider a subset of the file and then plot the quality of the subset. As long as one assumes that the subset is random, this is a good approximation. The function [FastaSampler](#) of [ShortRead](#) can be used for this. See its help page for an example.

plotRLE-methods

*Methods for Function plotRLE in Package **EDASeq***

Description

plotRLE produces a Relative Log Expression (RLE) plot of the counts in x

Usage

```
plotRLE(x, ...)
```

Arguments

- | | |
|-----|--|
| x | Either a numeric matrix or a SeqExpressionSet object containing the gene expression. |
| ... | See par |

Details

The Relative Log Expression (RLE) plot is a useful diagnostic plot to visualize the differences between the distributions of read counts across samples.

It shows the boxplots of the log-ratios of the gene-level read counts of each sample to those of a reference sample (defined as the median across the samples). Ideally, the distributions should be centered around the zero line and as tight as possible. Clear deviations indicate the need for normalization and/or the presence of outlying samples.

Methods

```
signature(x = "matrix")
signature(x = "SeqExpressionSet")
```

Examples

```
library(yeastRNASeq)
data(geneLevelData)

mat <- as.matrix(geneLevelData)

data <- newSeqExpressionSet(mat,
                           phenoData=AnnotatedDataFrame(
                               data.frame(conditions=factor(c("mut", "mut", "wt", "wt"))),
```

```

row.names=colnames(geneLevelData))))
```

```
plotRLE(data, col=rep(2:3, each=2))
```

SeqExpressionSet-class

"SeqExpressionSet" class for collections of short reads

Description

This class represents a collection of digital expression data (usually counts from RNA-Seq technology) along with sample information.

Objects from the Class

Objects of this class can be created from a call to the [newSeqExpressionSet](#) constructor.

Extends

Class eSet, directly. Class VersionedBiobase, by class eSet, distance 2. Class Versioned, by class eSet, distance 3.

Slots

Inherited from eSet:

assayData Contains matrices with equal dimensions, and with column number equal to `nrow(phenoData).assayData` must contain a matrix `counts` with rows representing features (e.g., genes) and columns representing samples. The optional matrices `normalizedCounts` and `offset` can be added to represent a normalization in terms of pseudo-counts or offset, respectively, to be used for subsequent analyses. See the vignette for details. Class: [AssayData-class](#).

phenoData Sample information. For compatibility with DESeq, there should be at least the column `conditions`. See [eSet](#) for details.

featureData Feature information. It is recommended to include at least length and GC-content information. This slot is used for `withinLaneNormalization`. See [eSet](#) for details.

experimentData See [eSet](#)

annotation See [eSet](#)

protocolData See `link{eSet}`

Methods

See [eSet](#) for inherited methods. Additional methods:

counts signature(object="SeqExpressionSet"): returns the counts matrix.

counts<- signature(object = "SeqExpressionSet"): method to replace the counts matrix.

normCounts signature(object="SeqExpressionSet"): returns the normalizedCounts matrix.

normCounts<- signature(object = "SeqExpressionSet"): method to replace the normalizedCounts matrix.

offst signature(object = "SeqExpressionSet"): returns the offset matrix.

offst<- signature(object = "SeqExpressionSet"): method to replace the offset slot.

boxplot signature(x = "SeqExpressionSet"): produces a boxplot of the log counts.

meanVarPlot signature(x = "SeqExpressionSet"): produces a [smoothScatter](#) plot of the mean variance relation. See [meanVarPlot](#) for details.

biasPlot signature(x = "SeqExpressionSet", y = "character"): produces a plot of the [lowess](#) regression of the counts on some covariate of interest (usually GC-content or length). See [biasPlot](#) for details.

withinLaneNormalization signature(x = "SeqExpressionSet", y = "missing"): within lane normalization for GC-content (or other lane specific) bias. See [withinLaneNormalization](#) for details.

betweenLaneNormalization signature(x = "SeqExpressionSet"): between lane normalization for sequencing depth and possibly other distributional differences between lanes. See [betweenLaneNormalization](#) for details.

Author(s)

Davide Risso <risso.davide@gmail.com>

See Also

[eSet](#), [newSeqExpressionSet](#), [biasPlot](#), [withinLaneNormalization](#), [betweenLaneNormalization](#)

Examples

```
showMethods(class="SeqExpressionSet", where=getNamespace("EDASeq"))

counts <- matrix(data=0, nrow=100, ncol=4)
for(i in 1:4) {
  counts[,i] <- rpois(100,lambda=50)
}
cond <- c(rep("A", 2), rep("B", 2))

data <- newSeqExpressionSet(counts, phenoData=AnnotatedDataFrame(data.frame(conditions=cond)))

head(counts(data))
boxplot(data, col=as.numeric(pData(data)[,1])+1)
```

withinLaneNormalization-methods

*Methods for Function `withinLaneNormalization` in Package
EDASeq*

Description

Within-lane normalization for GC-content (or other lane-specific) bias.

Usage

```
withinLaneNormalization(x, y, which=c("loess", "median", "upper", "full"), offset=FALSE, num.bins=10, round=FALSE)
```

Arguments

<code>x</code>	A numeric matrix representing the counts or a SeqExpressionSet object.
<code>y</code>	A numeric vector representing the covariate to normalize for (if <code>x</code> is a matrix) or a character vector with the name of the covariate (if <code>x</code> is a SeqExpressionSet object). Usually it is the GC-content.
<code>which</code>	Method used to normalized. See the details section and the reference below for details.
<code>offset</code>	Should the normalized value be returned as an offset leaving the original counts unchanged?
<code>num.bins</code>	The number of bins used to stratify the covariate for <code>median</code> , <code>upper</code> and <code>full</code> methods. Ignored if <code>loess</code> . See the reference for a discussion on the number of bins.
<code>round</code>	If <code>TRUE</code> the normalization returns rounded values (pseudo-counts). Ignored if <code>offset=TRUE</code> .

Details

This method implements four normalizations described in Risso et al. (2011).

The `loess` normalization transforms the data by regressing the counts on `y` and subtracting the loess fit from the counts to remove the dependence.

The `median`, `upper` and `full` normalizations are based on the stratification of the genes based on `y`. Once the genes are stratified in `num.bins` strata, the methods work as follows.

`median`: scales the data to have the same median in each bin.

`upper`: the same but with the upper quartile.

`full`: forces the distribution of each stratum to be the same using a non linear full quantile normalization, in the spirit of the one used in microarrays.

Methods

`signature(x = "matrix", y = "numeric")` It returns a matrix with the normalized counts if `offset=FALSE` or with the offset if `offset=TRUE`.

`signature(x = "SeqExpressionSet", y = "character")` It returns a `SeqExpressionSet` with the normalized counts in the `normalizedCounts` slot and with the offset in the `offset` slot (if `offset=TRUE`).

Author(s)

Davide Risso.

References

D. Risso, K. Schwartz, G. Sherlock and S. Dudoit (2011). GC-Content Normalization for RNA-Seq Data. Manuscript in Preparation.

Examples

```
library(yeastRNASeq)
data(geneLevelData)
data(yeastGC)

sub <- intersect(rownames(geneLevelData), names(yeastGC))

mat <- as.matrix(geneLevelData[sub, ])

data <- newSeqExpressionSet(mat,
                           phenoData=AnnotatedDataFrame(
                               data.frame(conditions=factor(c("mut", "mut", "wt", "wt")),
                                         row.names=colnames(geneLevelData))),
                           featureData=AnnotatedDataFrame(data.frame(gc=yeastGC[sub])))

norm <- withinLaneNormalization(data, "gc", which="full", offset=FALSE)
```

yeastGC

GC-content of S. Cerevisiae genes

Description

This data set gives the GC-content (proportion of G and C) of the genes of *S. Cerevisiae*, from SGD release 64 annotation.

Format

A vector containing 6717 observations.

Source

SGD release 64: <http://www.yeastgenome.org>

yeastLength

Length of S. Cerevisiae genes

Description

This data set gives the length (in base pairs) of the genes of *S. Cerevisiae*, from SGD release 64 annotation.

Format

A vector containing 6717 observations.

Source

SGD release 64: <http://www.yeastgenome.org>

Index

* **classes**
 SeqExpressionSet-class, 14

* **datasets**
 yeastGC, 17
 yeastLength, 18

* **methods**
 barplot-methods, 3
 betweenLaneNormalization-methods,
 3
 biasBoxplot-methods, 5
 biasPlot-methods, 6
 boxplot-methods, 7
 MDPlot-methods, 8
 meanVarPlot-methods, 9
 plot-methods, 10
 plotNtFrequency-methods, 11
 plotPCA-methods, 11
 plotQuality-methods, 12
 plotRLE-methods, 13
 withinLaneNormalization-methods,
 16

 alphabetFrequency, 8
 AnnotatedDataFrame, 10

 BamFileList, 2
 barplot, BamFile-method
 (barplot-methods), 3
 barplot, BamFileList-method
 (barplot-methods), 3
 barplot, FastqFileList-method
 (barplot-methods), 3
 barplot-methods, 3
 betweenLaneNormalization, 15
 betweenLaneNormalization
 (betweenLaneNormalization-methods),
 3
 betweenLaneNormalization, matrix-method
 (betweenLaneNormalization-methods),
 3

 betweenLaneNormalization, SeqExpressionSet-method
 (betweenLaneNormalization-methods),
 3

 betweenLaneNormalization-methods, 3

 biasBoxplot (biasBoxplot-methods), 5

 biasBoxplot, numeric, numeric, numeric-method
 (biasBoxplot-methods), 5

 biasBoxplot, numeric, numeric-method
 (biasBoxplot-methods), 5

 biasBoxplot-methods, 5

 biasPlot, 15

 biasPlot (biasPlot-methods), 6

 biasPlot, matrix, numeric-method
 (biasPlot-methods), 6

 biasPlot, SeqExpressionSet, character-method
 (biasPlot-methods), 6

 biasPlot-methods, 6

 boxplot, FastqQuality-method
 (boxplot-methods), 7

 boxplot, SeqExpressionSet-method
 (boxplot-methods), 7

 boxplot-methods, 7

 counts, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 counts<-, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 EDASeq (EDASeq-package), 2

 EDASeq-package, 2

 eSet, 2, 10, 14, 15

 exprs, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 exprs<-, SeqExpressionSet, ANY-method
 (SeqExpressionSet-class), 14

 FastqFileList, 2

 FastqSampler, 13

 genes, 8

getGeneLengthAndGCContent, 7
 getSeq, 8
 getSequence, 8

 initialize, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 lowess, 6, 9, 15

 MDPlot (MDPlot-methods), 8
 MDPlot, matrix, numeric-method
 (MDPlot-methods), 8
 MDPlot, SeqExpressionSet, numeric-method
 (MDPlot-methods), 8
 MDPlot-methods, 8
 meanVarPlot, 15
 meanVarPlot (meanVarPlot-methods), 9
 meanVarPlot, SeqExpressionSet-method
 (meanVarPlot-methods), 9
 meanVarPlot-methods, 9

 newSeqExpressionSet, 9, 14, 15
 normCounts (SeqExpressionSet-class), 14
 normCounts, SeqExpressionSet-method
 (SeqExpressionSet-class), 14
 normCounts<- (SeqExpressionSet-class),
 14
 normCounts<-, SeqExpressionSet, ANY-method
 (SeqExpressionSet-class), 14
 normCounts<-, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 offst (SeqExpressionSet-class), 14
 offst, SeqExpressionSet-method
 (SeqExpressionSet-class), 14
 offst<- (SeqExpressionSet-class), 14
 offst<-, SeqExpressionSet, ANY-method
 (SeqExpressionSet-class), 14
 offst<-, SeqExpressionSet-method
 (SeqExpressionSet-class), 14

 par, 5, 6, 8, 11, 13
 plot, BamFileList, FastqFileList-method
 (plot-methods), 10
 plot-methods, 10
 plotNtFrequency
 (plotNtFrequency-methods), 11
 plotNtFrequency, BamFile-method
 (plotNtFrequency-methods), 11

plotNtFrequency, ShortRead-method
 (plotNtFrequency-methods), 11
 plotNtFrequency-methods, 11
 plotPCA (plotPCA-methods), 11
 plotPCA, matrix-method
 (plotPCA-methods), 11
 plotPCA, SeqExpressionSet-method
 (plotPCA-methods), 11
 plotPCA-methods, 11
 plotQuality (plotQuality-methods), 12
 plotQuality, BamFile-method
 (plotQuality-methods), 12
 plotQuality, BamFileList-method
 (plotQuality-methods), 12
 plotQuality, FastqFileList-method
 (plotQuality-methods), 12
 plotQuality-methods, 12
 plotRLE (plotRLE-methods), 13
 plotRLE, matrix-method
 (plotRLE-methods), 13
 plotRLE, SeqExpressionSet-method
 (plotRLE-methods), 13
 plotRLE-methods, 13

 Rsamtools, 2

 SeqExpressionSet, 2, 4, 8–11, 13, 16, 17
 SeqExpressionSet-class, 14
 smoothScatter, 15

 withinLaneNormalization, 14, 15
 withinLaneNormalization
 (withinLaneNormalization-methods),
 16
 withinLaneNormalization, matrix, numeric-method
 (withinLaneNormalization-methods),
 16
 withinLaneNormalization, SeqExpressionSet, character-method
 (withinLaneNormalization-methods),
 16
 withinLaneNormalization-methods, 16

 yeastGC, 17
 yeastLength, 18