

Package ‘EnMCB’

February 1, 2026

Type Package

Title Predicting Disease Progression Based on Methylation Correlated Blocks using Ensemble Models

Version 1.23.0

Date 2023-3-13

Author Xin Yu

Maintainer Xin Yu <whirlsyu@gmail.com>

Depends R (>= 4.0)

Encoding UTF-8

Imports survivalROC, glmnet, rms, mboost, Matrix, igraph, methods, survivalsvm, ggplot2, boot, e1071, survival, BiocFileCache

VignetteBuilder knitr

Suggests SummarizedExperiment, testthat, Biobase, survminer, affycoretools, knitr, plotROC, limma, rmarkdown

Description Creation of the correlated blocks using DNA methylation profiles.

Machine learning models can be constructed to predict differentially methylated blocks and disease progression.

License GPL-2

BugReports <https://github.com/whirlsyu/EnMCB/issues>

biocViews Normalization, DNAMethylation, MethylationArray, SupportVectorMachine

LazyData FALSE

RoxygenNote 7.2.3

git_url <https://git.bioconductor.org/packages/EnMCB>

git_branch devel

git_last_commit 8ef58ef

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-02-01

Contents

anno_matrix	2
as.data.frame.ridgemat	3
as.ridgemat	3
CompareMCB	4
create_demo	5
demo_data	6
demo_MCBinformation	6
demo_survival_data	7
DiffMCB	7
draw_survival_curve	9
ensemble_model	10
ensemble_prediction	11
fast_roc_calculation	12
IdentifyMCB	13
IdentifyMCB_parallel	14
metricMCB	16
metricMCB.cv	18
multi_coxph	20
predict.mcb.coxph.penal	21
pre_process_methylation	21
univ_coxph	22

Index

24

anno_matrix	<i>IlluminaHumanMethylation450kanno</i>
-------------	-----------------------------------------

Description

IlluminaHumanMethylation450kanno

Usage

```
data(anno_matrix)
```

Format

IlluminaHumanMethylation450kanno.ilmn12.hg19 annotation file. This data have several columns

```
as.data.frame.ridgemat
  data frame ridge matrix
```

Description

data frame ridge matrix

Usage

```
## S3 method for class 'ridgemat'
as.data.frame(x, ...)
```

Arguments

x	data vector
...	other parameters pass to as.data.frame.model.matrix()

```
as.ridgemat      ridge matrix
```

Description

as.matrix attempts to turn its argument

Usage

```
as.ridgemat(x)
```

Arguments

x	data vector
---	-------------

CompareMCB

*Compare multiple methylation correlated blocks lists***Description**

This function is used to find the Methylation correlated blocks that differentially expressed between groups. This function calculates attractors of all the MCBs among the groups and find the attractor MCBs.

Usage

```
CompareMCB(
  MCBs,
  method = c("attractors")[1],
  p_value = 0.05,
  min_CpGs = 5,
  platform = "Illumina Methylation 450K"
)
```

Arguments

MCBs	Methylation correlated blocks list.
method	method used for calculation of differential expression, should be one of "attractors", "t-test". Default is "attractors".
p_value	p value threshold for the test.
min_CpGs	threshold for minimum CpGs must included in the individual MCBs.
platform	This parameter indicates the platform used to produce the methylation profile.

Details

Currently, only illumina 450k platform is supported, the methylation profile need to convert into matrix format.

Value

Object of class `list` with elements:

MCBsites	Character set contains all CpG sites in MCBs.
MCBinformation	Matrix contains the information of results.

Author(s)

Xin Yu

References

Xin Yu, De-Xin Kong, EnMCB: an R/bioconductor package for predicting disease progression based on methylation correlated blocks using ensemble models, Bioinformatics, 2021, btab415

Examples

```
data('demo_data', package = "EnMCB")
```

create_demo

create demo matrix

Description

Demo matrix for methylation matrix.

Usage

```
create_demo(model = c("all", "short")[1])
```

Arguments

model Two options, 'all' or 'short' for creating full dataset or very brief demo.

Value

This function will generate a demo data.

Author(s)

Xin Yu

Examples

```
demo_set<-create_demo()
```

demo_data	<i>Expression matrix of demo dataset.</i>
-----------	-------------------------------------------

Description

A Expression matrix containing the 10020 CpGs beta value of 455 samples in TCGA lung Adeno-carcinoma dataset. This will call from create_demo() function.

Usage

```
data(demo_data)
```

Format

ExpressionSet:

rownames rownames of 10020 CpG features
colnames colnames of 455 samples
realdata Real data matrix for demo.

demo_MCBinformation	<i>MCB information.</i>
---------------------	-------------------------

Description

A dataset containing the number and other attributes of 94 MCBs; This results was created by the identification function IdentifyMCB. This data used for metricMCB function.

Usage

```
data(demo_MCBinformation)
```

Format

A data frame with 94 rows and 8 variables:

MCB_no MCB code
start Start point of this MCB in the chromosome.
end End point of this MCB in the chromosome.
CpGs All the CpGs probe names in the MCB.
location Start, end point and the chromosome number of this MCB.
chromosomes the chromosome number of this MCB.
length the length of bps of this MCB in the chromosome.
CpGs_num number of CpG probes of this MCB.

demo_survival_data	<i>Survival data of demo dataset.</i>
--------------------	---------------------------------------

Description

A Surv containing survival value of 455 samples in TCGA lung Adenocarcinoma dataset.

Usage

```
data(demo_survival_data)
```

Format

Surv data created by Surv() function in survival package. This data have two unnamed arguments, they will match time and event.

DiffMCB	<i>Differential expressed methylation correlated blocks</i>
---------	-------------------------------------------------------------

Description

This function is used to find the Methylation correlated blocks that differentially expressed between groups based on the attractor framework. This function calculates attractors of all the MCBs among the groups and find the attractor MCBs.

Usage

```
DiffMCB(
  methylation_matrix,
  class_vector,
  mcb_matrix = NULL,
  min.cpgsize = 5,
  pVals_num = 0.05,
  base_method = c("Fstat", "Tstat", "eBayes")[1],
  sec_method = c("ttest", "kstest")[1],
  ...
)
```

Arguments

methylation_matrix	methylation profile matrix.
class_vector	class vectors that indicated the groups.
mcb_matrix	dataframe or matrix results returned by IdentifyMCB function.

min.cpgsize	threshold for minimum CpGs must included in the individual MCBs.
pVals_num	p value threshold for the test.
base_method	base method used for calculation of differentially methylated regions, should be one of 'Fstat','Tstat','eBayes'. Default is Fstat.
sec_method	secondly method in attractor framework, should be one of 'kstest','ttest'. Default is ttest.
...	other parameters pass to the function.

Details

Currently, only illumina 450k platform is supported.

If you want to use other platform, please provide the annotation file with CpG's chromosome and loci.

The methylation profile need to convert into matrix format.

Value

Object of class `list` with elements:

global	Character set contains statistical value for all CpG sites in MCBs.
tab	Matrix contains the information of results.

Author(s)

Xin Yu

References

Xin Yu, De-Xin Kong, EnMCB: an R/bioconductor package for predicting disease progression based on methylation correlated blocks using ensemble models, Bioinformatics, 2021, btab415

Examples

```
data('demo_data', package = "EnMCB")
data('demo_survival_data', package = "EnMCB")
data('demo_MCBinformation', package = "EnMCB")
#Using survival censoring as group label just for demo,
#this may replace with disease and control group in real use.
diffMCB_results <- DiffMCB(demo_data$realdata,demo_survival_data[,2],
                           demo_MCBinformation,
                           pVals_num = 1)
```

draw_survival_curve *draw survival curve*

Description

Draw a survival curve based on survminer package. This is a wrapper function of ggsurvplot.

Usage

```
draw_survival_curve(  
  exp,  
  living_days,  
  living_events,  
  write_name,  
  title_name = "",  
  threshold = NA,  
  file = FALSE  
)
```

Arguments

exp	expression level for variable.
living_days	The survival time (days) for each individual.
living_events	The survival event for each individual, 0 indicates alive and 1 indicates death. Other choices are TRUE/FALSE (TRUE = death) or 1/2 (2=death). For interval censored data, the status indicator is 0=right censored, 1=event at time, 2=left censored, 3=interval censored.
write_name	The name for pdf file which contains the result figure.
title_name	The title for the result figure.
threshold	Threshold used to indicate the high risk or low risk.
file	If True, function will automatic generate a result pdf, otherwise it will return a ggplot object. Default is FALSE.

Value

This function will generate a pdf file with 300dpi which compare survival curves using the Kaplan-Meier (KM) test.

Author(s)

Xin Yu

Examples

```
data(demo_survival_data)
library(survival)
demo_set<-create_demo()
draw_survival_curve(demo_set[1,],
  living_days = demo_survival_data[,1],
  living_events = demo_survival_data[,2],
  write_name = "demo_data" )
```

ensemble_model

Trainging stacking ensemble model for Methylation Correlation Block

Description

Method for training a stacking ensemble model for Methylation Correlation Block.

Usage

```
ensemble_model(single_res,training_set,Surv_training,testing_set,
Surv_testing,ensemble_type)
```

Arguments

single_res	Methylation Correlation Block information returned by the IdentifyMCB function.
training_set	methylation matrix used for training the model in the analysis.
Surv_training	Survival function contain the survival information for training.
testing_set	methylation matrix used for testing the model in the analysis.
Surv_testing	Survival function contain the survival information for testing.
ensemble_type	Secondary model use for ensemble, one of "Cox", "C-index" and "feature weighted linear regression". "feature weighted linear regression" only uses two meta-features namely kurtosis and S.D.

Value

Object of class `list` with elements (XXX repesents the model you choose):

cox	Model object for the cox model at first level.
svm	Model object for the svm model at first level.
enet	Model object for the enet model at first level.
mboost	Model object for the mboost model at first level.
stacking	Model object for the stacking model.

Author(s)

Xin Yu

References

Xin Yu et al. 2019 Predicting disease progression in lung adenocarcinoma patients based on methylation correlated blocks using ensemble machine learning classifiers (under review)

Examples

```
#import datasets
library(survival)
data(demo_survival_data)
datamatrix<-create_demo()
data(demo_MCBinformation)
#select MCB with at least 3 CpGs.
demo_MCBinformation<-demo_MCBinformation[demo_MCBinformation[,"CpGs_num"]>2,]
trainingset<-colnames(datamatrix) %in% sample(colnames(datamatrix),0.6*length(colnames(datamatrix)))
select_single_one=1
em<-ensemble_model(t(demo_MCBinformation[select_single_one,]),
  training_set=datamatrix[,trainingset],
  Surv_training=demo_survival_data[trainingset])
```

ensemble_prediction *fitting function using stacking ensemble model for Methylation Correlation Block*

Description

predict is a generic function for predictions from the results of stacking ensemble model fitting functions. The function invokes particular methods which is the ensemble model described in the reference.

Usage

```
ensemble_prediction(ensemble_model, prediction_data, multiple_results = FALSE)
```

Arguments

ensemble_model ensemble model which built by ensemble_model() function
 prediction_data A vector, matrix, list, or data frame containing the predictions (input).
 multiple_results Boolean vector, True for including the single model results.

Value

Object of numeric class double

References

Xin Yu et al. 2019 Predicting disease progression in lung adenocarcinoma patients based on methylation correlated blocks using ensemble machine learning classifiers (under review)

Examples

```
library(survival)
#import datasets
data(demo_survival_data)
datamatrix<-create_demo()
data(demo_MCBinformation)
#select MCB with at least 3 CpGs.
demo_MCBinformation<-demo_MCBinformation[demo_MCBinformation[, "CpGs_num"]>2, ]
trainingset<-colnames(datamatrix) %in% sample(colnames(datamatrix), 0.6*length(colnames(datamatrix)))
testingset<-!trainingset
#select one MCB
select_single_one=1
em<-ensemble_model(t(demo_MCBinformation[select_single_one,]),
  training_set=datamatrix[,trainingset],
  Surv_training=demo_survival_data[trainingset])

em_prediction_results<-ensemble_prediction(ensemble_model = em,
  prediction_data = datamatrix[,testingset])
```

fast_roc_calculation *Fast calculation of AUC for ROC using parallel strategy*

Description

This function is used to create time-dependent ROC curve from censored survival data using the Kaplan-Meier (KM) or Nearest Neighbor Estimation (NNE) method of Heagerty, Lumley and Pepe, 2000

Usage

```
fast_roc_calculation(test_matrix, y_surv, predict_time = 5, roc_method = "NNE")
```

Arguments

test_matrix	Test matrix used in the analysis. Colmuns are samples, rows are markers.
y_surv	Survival information created by Surv function in survival package.
predict_time	Time point of the ROC curve, default is 5 year.
roc_method	Method for fitting joint distribution of (marker,t), either of KM or NNE, the default method is NNE.

Value

This will retrun a numeric vector contains AUC results for each row in test_matrix.

Author(s)

Xin Yu

Examples

```
data(demo_survival_data)
data('demo_data', package = "EnMCB")
demo_set<-demo_data$realdata
res<-fast_roc_calculation(demo_set[1:2,],demo_survival_data)
```

IdentifyMCB

Identification of methylation correlated blocks

Description

This function is used to partition the genome into blocks of tightly co-methylated CpG sites, Methylation correlated blocks. This function calculates Pearson correlation coefficients between the beta values of any two CpGs < CorrelationThreshold was used to identify boundaries between any two adjacent markers indicating uncorrelated methylation. Markers not separated by a boundary were combined into MCB. Pearson correlation coefficients between two adjacent CpGs were calculated.

Usage

```
IdentifyMCB(
  MethylationProfile,
  method = c("pearson", "spearman", "kendall")[1],
  CorrelationThreshold = 0.8,
  PositionGap = 1000,
  platform = "Illumina Methylation 450K",
  verbose = T
)
```

Arguments

MethylationProfile

Methylation matrix is used in the analysis.

method

method used for calculation of correlation,
should be one of "pearson","spearman","kendall". Defualt is "pearson".

CorrelationThreshold

coef correlation threshold is used for define boundaries.

PositionGap	CpG Gap between any two CpGs positioned CpG sites less than 1000 bp (default) will be calculated.
platform	This parameter indicates the platform used to produce the methylation profile. You can use your own annotation file.
verbose	True as default, which will print the block information for each chromosome.

Details

Currently, only illumina 450k platform is supported, the methylation profile need to convert into matrix format.

Value

Object of class `list` with elements:

<code>MCBsites</code>	Character set contains all CpG sites in MCBs.
<code>MCBinformation</code>	Matrix contains the information of results.

Author(s)

Xin Yu

References

Xin Yu, De-Xin Kong, EnMCB: an R/bioconductor package for predicting disease progression based on methylation correlated blocks using ensemble models, Bioinformatics, 2021, btab415

Examples

```
data('demo_data', package = "EnMCB")

# import the demo TCGA data with 10000+ CpGs site and 455 samples
# remove # to run
res<-IdentifyMCB(demo_data$realdata)
demo_MCBinformation<-res$MCBinformation
```

Description

This function is used to partition the genome into blocks of tightly co-methylated CpG sites, Methylation correlated blocks parallelly. This function calculates Pearson correlation coefficients between the beta values of any two CpGs < CorrelationThreshold was used to identify boundaries between any two adjacent markers indicating uncorrelated methylation. Markers not separated by a boundary were combined into MCB. Pearson correlation coefficients between two adjacent CpGs were calculated.

Usage

```
IdentifyMCB_parallel(
  MethylationProfile,
  method = c("pearson", "spearman", "kendall")[1],
  CorrelationThreshold = 0.8,
  PositionGap = 1000,
  platform = "Illumina Methylation 450K",
  verbose = T
)
```

Arguments

MethylationProfile	Methylation matrix is used in the analysis.
method	method used for calculation of correlation, should be one of "pearson", "spearman", "kendall". Default is "pearson".
CorrelationThreshold	cof correlation threshold is used for define boundaries.
PositionGap	CpG Gap between any two CpGs positioned CpG sites less than 1000 bp (default) will be calculated.
platform	This parameter indicates the platform used to produce the methylation profile. You can use your own annotation file.
verbose	True as default, which will print the block information for each chromosome.

Details

Currently, only illumina 450k platform is supported, the methylation profile need to convert into matrix format.

Value

Object of class `list` with elements:

MCBsites	Character set contains all CpG sites in MCBs.
MCBinformation	Matrix contains the information of results.

Author(s)

Xin Yu

References

Xin Yu, De-Xin Kong, EnMCB: an R/bioconductor package for predicting disease progression based on methylation correlated blocks using ensemble models, Bioinformatics, 2021, btab415

Examples

```
data('demo_data', package = "EnMCB")

#import the demo TCGA data with 10000+ CpGs site and 455 samples
#remove # to run
res<-IdentifyMCB_parallel(demo_data$realdata)
demo_MCBinformation<-res$MCBinformation
```

metricMCB

*Calculation of the metric matrix for Methylation Correlation Block***Description**

To enable quantitative analysis of the methylation patterns within individual Methylation Correlation Blocks across many samples, a single metric to define the methylated pattern of multiple CpG sites within each block. Compound scores which calculated all CpGs within individual Methylation Correlation Blocks by linear, SVM or elastic-net model Predict values were used as the compound methylation values of Methylation Correlation Blocks.

Usage

```
metricMCB(MCBset, training_set, Surv, testing_set,
Surv.new, Method, predict_time, ci, silent, alpha, n_mstop, n_nu, theta)
```

Arguments

MCBset	Methylation Correlation Block information returned by the IdentifyMCB function.
training_set	methylation matrix used for training the model in the analysis.
Surv	Survival function contain the survival information for training.
testing_set	methylation matrix used in the analysis. This can be missing then training set itself will be used as testing set.
Surv.new	Survival function contain the survival information for testing.

Method	model used to calculate the compound values for multiple Methylation correlation blocks. Options include "svm" "cox" "mboost" and "enet". The default option is SVM method.
predict_time	time point of the ROC curve used in the AUC calculations, default is 5 years.
ci	if True, the confidence intervals for AUC under area under the receiver operating characteristic curve will be calculated. This will be time consuming. default is False.
silent	True indicates that processing information and progress bar will be shown.
alpha	The elasticnet mixing parameter, with $0 \leq \alpha \leq 1$. $\alpha=1$ is the lasso penalty, and $\alpha=0$ the ridge penalty. It works only when "enet" Method is selected.
n_mstop	an integer giving the number of initial boosting iterations. If mstop = 0, the offset model is returned. It works only when "mboost" Method is selected.
n_nu	a double (between 0 and 1) defining the step size or shrinkage parameter in mboost model. It works only when "mboost" Method is selected.
theta	penalty used in the penalized coxph model, which is $\theta/2$ time sum of squared coefficients. default is 1. It works only when "cox" Method is selected.

Value

Object of class `list` with elements (XXX will be replaced with the model name you choose):

MCB_XXX_matrix_training	Prediction results of model for training set.
MCB_XXX_matrix_test_set	Prediction results of model for test set.
XXX_auc_results	AUC results for each model.
best_XXX_model	Model object for the model with best AUC.
maximum_auc	Maximum AUC for the whole generated models.

Author(s)

Xin Yu

References

Xin Yu et al. 2019 Predicting disease progression in lung adenocarcinoma patients based on methylation correlated blocks using ensemble machine learning classifiers (under review)

Examples

```
#import datasets
data(demo_survival_data)
datamatrix<-create_demo()
```

```

data(demo_MCBinformation)
#select MCB with at least 3 CpGs.
demo_MCBinformation<-demo_MCBinformation[demo_MCBinformation[,"CpGs_num"]>2,]

trainingset<-colnames(datamatrix) %in% sample(colnames(datamatrix),0.6*length(colnames(datamatrix)))
testingset<-!trainingset
#create the results using Cox regression.
mcb_cox_res<-metricMCB(MCBset = demo_MCBinformation,
                         training_set = datamatrix[,trainingset],
                         Surv = demo_survival_data[trainingset],
                         testing_set = datamatrix[,testingset],
                         Surv.new = demo_survival_data[testingset],
                         Method = "cox"
)

```

metricMCB.cv

Calculation of model AUC for Methylation Correlation Blocks using cross validation

Description

To enable quantitative analysis of the methylation patterns within individual Methylation Correlation Blocks across many samples, a single metric to define the methylated pattern of multiple CpG sites within each block. Compound scores which calculated all CpGs within individual Methylation Correlation Blocks by SVM model were used as the compound methylation values of Methylation Correlation Blocks.

Usage

```
metricMCB.cv(MCBset,data_set,Surv,nfold,
Method,predict_time,alpha,n_mstop,n_nu,theta,silent)
```

Arguments

MCBset	Methylation Correlation Block information returned by the IdentifyMCB function.
data_set	methylation matrix used for training the model in the analysis.
Surv	Survival function contain the survival information for training.
nfold	fold used in the cross validation procedure.
Method	model used to calculate the compound values for multiple Methylation correlation blocks. Options include "svm", "cox", "mboost", and "enet". The default option is SVM method.
predict_time	time point of the ROC curve used in the AUC calculations, default is 3 years.
alpha	The elasticnet mixing parameter, with $0 \leq \alpha \leq 1$. $\alpha=1$ is the lasso penalty, and $\alpha=0$ the ridge penalty. It works only when "enet" Method is selected.

n_mstop	an integer giving the number of initial boosting iterations. If mstop = 0, the offset model is returned. It works only when "mboost" Method is selected.
n_nu	a double (between 0 and 1) defining the step size or shrinkage parameter in mboost model. It works only when "mboost" Method is selected.
theta	penalty used in the penalized coxph model, which is theta/2 time sum of squared coefficients. default is 1. It works only when "cox" Method is selected.
silent	Ture indicates that processing information and progress bar will be shown.

Value

Object of class `list` with elements (XXX will be replaced with the model name you choose):

MCB_matrix	Prediction results of model.
auc_results	AUC results for each model.

Author(s)

Xin Yu

References

Xin Yu et al. 2019 Predicting disease progression in lung adenocarcinoma patients based on methylation correlated blocks using ensemble machine learning classifiers (under review)

Examples

```
#import datasets
data(demo_survival_data)
datamatrix<-create_demo()
data(demo_MCBinformation)
#select MCB with at least 3 CpGs.
demo_MCBinformation<-demo_MCBinformation[demo_MCBinformation[, "CpGs_num"]>2,]

trainingset<-colnames(datamatrix) %in% sample(colnames(datamatrix), 0.6*length(colnames(datamatrix)))
testingset<-!trainingset
#create the results using Cox regression.
mcbs_cox_res<-metricMCB.cv(MCBset = demo_MCBinformation,
                           data_set = datamatrix,
                           Surv = demo_survival_data,
                           Method = "cox")
```

multi_coxph	<i>multivariate survival analysis using coxph</i>
--------------------	---------------------------------------------------

Description

multivariate survival analysis using coxph

Usage

```
multi_coxph(dataframe, y_surv, digits = 4, asnumeric = TRUE)
```

Arguments

<code>dataframe</code>	Clinic data and covariates ready to be tested. Note that Rows are samples and columns are variables.
<code>y_surv</code>	Survival function contain survival data, usually are obtained form Surv() function in survival package.
<code>digits</code>	Integer indicating the number of decimal places.
<code>asnumeric</code>	indicator that the data will be (True) / not (False) transformed into numeric. Default is true.

Value

Object of class `matrix` with results.

Author(s)

Xin Yu

Examples

```
data(demo_survival_data)
data('demo_data', package = "EnMCB")
demo_set<-demo_data$realdata
res<-multi_coxph(t(demo_set), demo_survival_data)
```

```
predict.mcb.coxph.penalty
```

predict coxph penalty using MCB

Description

Compute fitted values and regression terms for a model fitted by coxph

Usage

```
## S3 method for class 'mcb.coxph.penalty'  
predict(object, newdata, ...)
```

Arguments

object	the results of a coxph fit.
newdata	Optional new data at which to do predictions. If absent predictions are for the data frame used in the original fit. When coxph has been called with a formula argument created in another context, i.e., coxph has been called within another function and the formula was passed as an argument to that function, there can be problems finding the data set. See the note below.
...	other parameters pass to predict.coxph

Value

prediction values of regression.

Author(s)

Xin Yu

```
pre_process_methylation
```

Preprocess the Beta value matrix

Description

This process is optional for the pipeline. This function pre-process the Beta matrix and transform the Beta value into M value.

Usage

```
pre_process_methylation(met,Mvalue,constant_offset,remove_na,remove_percentage)
```

Arguments

met methylation matrix for CpGs. Rows are the CpG names, columns are samples.

Mvalue Boolean value, TRUE for the M transformation.

constant_offset the constant offset used in the M transformation formula.

remove_na Boolean value, if TRUE ,CpGs with NA values will be removed.

remove_percentage If precentage of NA value exceed the threshold(percentage), the whole CpG probe will be removed. Otherwise, the NA values are replaced with rowmeans.

Value

Object of class `matrix`.

Examples

```
demo_set<-create_demo()
pre_process_methylation(demo_set,Mvalue=FALSE)
```

univ_coxph

univariate and multivariate survival analysis using coxph

Description

univariate and multivariate survival analysis using coxph

Usage

```
univ_coxph(dataframe, y_surv, digits = 4, asnumeric = TRUE)
```

Arguments

dataframe Clinic data and covariates ready to be tested. Rows are variables and columns are samples.

y_surv Survival function contain survival data, usually are obtained form `Surv()` function in survival package.

digits Integer indicating the number of decimal places.

asnumeric indicator that the data will be (True) / not (False) transformed into numeric. Default is true.

Value

Object of class `matrix` with results.

Author(s)

Xin Yu

Examples

```
data(demo_survival_data)
data('demo_data', package = "EnMCB")
demo_set<-demo_data$realdata
res<-univ_coxph(demo_set,demo_survival_data)
```

Index

- * **Correlation**
 - metricMCB, 16
 - metricMCB.cv, 18
- * **Methylation**
 - metricMCB, 16
 - metricMCB.cv, 18
- * **datasets**
 - anno_matrix, 2
 - demo_data, 6
 - demo_MCBinformation, 6
 - demo_survival_data, 7
- * **ensemble**
 - ensemble_model, 10
- * **methylation**
 - ensemble_model, 10
- * **stacking**
 - ensemble_model, 10

anno_matrix, 2
as.data.frame.ridgemat, 3
as.ridgemat, 3

CompareMCB, 4
create_demo, 5

demo_data, 6
demo_MCBinformation, 6
demo_survival_data, 7
DiffMCB, 7
draw_survival_curve, 9

ensemble_model, 10
ensemble_prediction, 11

fast_roc_calculation, 12

IdentifyMCB, 13
IdentifyMCB_parallel, 14

metricMCB, 16
metricMCB.cv, 18

multi_coxph, 20

pre_process_methylation, 21
predict.mcb.coxph.penalty, 21

univ_coxph, 22