

# Package ‘OrganismDbi’

February 2, 2026

**Title** Software to enable the smooth interfacing of different database packages

**Description** The package enables a simple unified interface to several annotation packages each of which has its own schema by taking advantage of the fact that each of these packages implements a select methods.

**Version** 1.53.2

**Encoding** UTF-8

**Depends** R (>= 2.14.0), BiocGenerics (>= 0.15.10), AnnotationDbi (>= 1.33.15), Seqinfo, GenomicFeatures (>= 1.61.4)

**Imports** methods, utils, stats, DBI, BiocManager, Biobase, graph, RBGL, S4Vectors, IRanges, GenomicRanges (>= 1.61.1)

**Suggests** txdbmaker, GenomeInfoDbData, Homo.sapiens, Rattus.norvegicus, BSgenome.Hsapiens.UCSC.hg19, AnnotationHub, FDb.UCSC.tRNAs, rtracklayer, biomaRt, RUnit, RMariaDB, BiocStyle, knitr

**Collate** AllGenerics.R AllClasses.R methods-select.R  
methods-transcripts.R createOrganismPackage.R seqinfo.R  
test\_OrganismDbi\_package.R

**License** Artistic-2.0

**biocViews** Annotation, Infrastructure

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/OrganismDbi>

**git\_branch** devel

**git\_last\_commit** a63751b

**git\_last\_commit\_date** 2025-10-31

**Repository** Bioconductor 3.23

**Date/Publication** 2026-02-01

**Author** Marc Carlson [aut],  
Martin Morgan [aut],  
Valerie Obenchain [aut],  
Aliyu Atiku Mustapha [ctb] (Converted 'OrganismDbi' vignette from

Sweave to RMarkdown / HTML.),  
 Bioconductor Package Maintainer [cre]  
**Maintainer** Bioconductor Package Maintainer <maintainer@bioconductor.org>

## Contents

makeOrganismDbFromBiomart	2
makeOrganismDbFromTxDb	5
makeOrganismDbFromUCSC	6
makeOrganismPackage	8
mapToTranscripts	10
MultiDb-class	12
rangeBasedAccessors	14

<b>Index</b>	<b>19</b>
--------------	-----------

---

### makeOrganismDbFromBiomart

*Make a OrganismDb object from annotations available on a BioMart database*

---

### Description

The `makeOrganismDbFromBiomart` function allows the user to make a `OrganismDb` object from transcript annotations available on a BioMart database. This object has all the benefits of a `TxDb`, plus an associated `OrgDb` and `GOdb` object.

### Usage

```
makeOrganismDbFromBiomart(biomart="ENSEMBL_MART_ENSEMBL",
                          dataset="hsapiens_gene_ensembl",
                          transcript_ids=NULL,
                          circ_seqs=NULL,
                          filter="",
                          id_prefix="ensembl_",
                          host="https://www.ensembl.org",
                          port,
                          keytype = "ENSEMBL",
                          orgdb = NA)
```

### Arguments

<code>biomart</code>	which BioMart database to use. Get the list of all available BioMart databases with the <code>listMarts</code> function from the <code>biomaRt</code> package. See the details section below for a list of BioMart databases with compatible transcript annotations.
----------------------	--

dataset	which dataset from BioMart. For example: "hsapiens_gene_ensembl", "mmusculus_gene_ensembl", "dmelanogaster_gene_ensembl", "celegans_gene_ensembl", "scerevisiae_gene_ensembl", etc in the ensembl database. See the examples section below for how to discover which datasets are available in a given BioMart database.
transcript_ids	optionally, only retrieve transcript annotation data for the specified set of transcript ids. If this is used, then the meta information displayed for the resulting <b>TxDb</b> object will say 'Full dataset: no'. Otherwise it will say 'Full dataset: yes'. This <b>TxDb</b> object will be embedded in the resulting <b>OrganismDb</b> object.
circ_seqs	a character vector to list out which chromosomes should be marked as circular.
filter	Additional filters to use in the BioMart query. Must be a named list. An example is filter=as.list(c(source="entrez"))
host	The host URL of the BioMart. Defaults to www.ensembl.org.
port	This argument is defunct, don't use.
id_prefix	Specifies the prefix used in BioMart attributes. For example, some BioMarts may have an attribute specified as "ensembl_transcript_id" whereas others have the same attribute specified as "transcript_id". Defaults to "ensembl_".
keytype	This indicates the kind of key that this database will use as a foreign key between it's <b>TxDb</b> object and it's <b>OrgDb</b> object. So basically whatever the column name is for the foreign key from your <b>OrgDb</b> that your <b>TxDb</b> will need to map it's GENEID on to. By default it is "ENSEMBL" since the GENEID's for most <b>biomaRt</b> based <b>TxDb</b> s will be ensembl gene ids and therefore they will need to map to ENSEMBL gene mappings from the associated <b>OrgDb</b> object.
orgdb	By default, <b>makeOrganismDbFromBiomart</b> will use the taxonomyID from your <b>txdb</b> to lookup an appropriate matching <b>OrgDb</b> object but using this you can supply a different <b>OrgDb</b> object.

## Details

**makeOrganismDbFromBiomart** is a convenience function that feeds data from a BioMart database to the lower level **OrganismDb** constructor. See [?makeOrganismDbFromUCSC](#) for a similar function that feeds data from the UCSC source.

The **listMarts** function from the **biomaRt** package can be used to list all public BioMart databases. Not all databases returned by this function contain datasets that are compatible with (i.e. understood by) **makeOrganismDbFromBiomart**. Here is a list of datasets known to be compatible (updated on Sep 24, 2014):

- All the datasets in the main Ensembl database: use biomart="ensembl".
- All the datasets in the Ensembl Fungi database: use biomart="fungi\_mart\_XX" where XX is the release version of the database e.g. "fungi\_mart\_22".
- All the datasets in the Ensembl Metazoa database: use biomart="metazoa\_mart\_XX" where XX is the release version of the database e.g. "metazoa\_mart\_22".
- All the datasets in the Ensembl Plants database: use biomart="plants\_mart\_XX" where XX is the release version of the database e.g. "plants\_mart\_22".
- All the datasets in the Ensembl Protists database: use biomart="protists\_mart\_XX" where XX is the release version of the database e.g. "protists\_mart\_22".

- All the datasets in the Gramene Mart: use `biomart="ENSEMBL_MART_PLANT"`.

Not all these datasets have CDS information.

### Value

A `OrganismDb` object.

### Author(s)

M. Carlson

### See Also

- [makeOrganismDbFromUCSC](#) for convenient ways to make a `OrganismDb` object from UCSC online resources.
- The `listMarts`, `useMart`, and `listDatasets` functions in the **biomaRt** package.
- The [OrganismDb](#) class.

### Examples

```
## Discover which datasets are available in the "ensembl" BioMart
## database:
library(biomaRt)
mart <- useEnsembl("ensembl")
datasets <- listDatasets(mart)
head(datasets)

## Retrieving an incomplete transcript dataset for Human from the
## "ensembl" BioMart database:
transcript_ids <- c(
  "ENST0000013894",
  "ENST00000268655",
  "ENST00000313243",
  "ENST00000435657",
  "ENST00000384428",
  "ENST00000478783"
)
odb <- makeOrganismDbFromBiomart(transcript_ids=transcript_ids)
odb # note that these annotations match the GRCh38 genome assembly

if (interactive()) {
  ## Now what if we want to use another mirror? We might make use of the
  ## new host argument. But wait! If we use biomaRt, we can see that
  ## this host has named the mart differently!
  listMarts(host="https://useast.ensembl.org")

  ## Therefore we must also change the name passed into the "mart"
  ## argument thusly:
  makeOrganismDbFromBiomart(
    biomart="ENSEMBL_MART_ENSEMBL",
    transcript_ids=transcript_ids,
```

```
    host="https://useast.ensembl.org"
)
}
```

---

**makeOrganismDbFromTxDb**

*Make an OrganismDb object from an existing TxDb object.*

---

**Description**

The `makeOrganismDbFromTxDb` function allows the user to make a [OrganismDb](#) object from an existing TxDb object.

**Usage**

```
makeOrganismDbFromTxDb(txdb, keytype=NA, orgdb=NA)
```

**Arguments**

txdb	a TxDb object
<hr/>	
keytype	By default, <code>makeOrganismDbFromTxDb</code> will try to guess this information based on the OrgDb object that is inferred to go with your TxDb object... But in some instances, you may need to supply an over-ride and that is what this argument is for. It is the column name of the ID type that your OrgDb will use as a foreign key when connecting to the data from the associated TxDb. So for example, if you looked at the <code>Homo.sapiens</code> package the keytype for <code>org.Hs.eg.db</code> , would be 'ENTREZID' because that is the kind of ID that matches up with it's TxDb GENEID. (Because the GENEID for that specific TxDb is from UCSC and uses entrez gene IDs)
<hr/>	
orgdb	By default, <code>makeOrganismDbFromTxDb</code> will use the taxonomyID from your txdb to lookup an appropriate matching OrgDb object but using this you can supply a different OrgDb object.

**Details**

`makeOrganismDbFromTxDb` is a convenience function that processes a TxDb object and pairs it up with GO.db and an appropriate OrgDb object to make a OrganismDb object. See [?makeOrganismDbFromBiomart](#) and [?makeOrganismDbFromUCSC](#) for a similar function that feeds data from either a BioMart or UCSC.

**Value**

A [OrganismDb](#) object.

**Author(s)**

M. Carlson

**See Also**

- [makeOrganismDbFromBiomart](#) for convenient ways to make a [OrganismDb](#) object from BioMart online resources.
- The [OrganismDb](#) class.

**Examples**

```
## Not run:
library(txdbmaker) # for makeTxDbFromUCSC()
## lets start with a txdb object
transcript_ids <- c(
  "uc009uzf.1",
  "uc009uzg.1",
  "uc009uzh.1",
  "uc009uzi.1",
  "uc009uzj.1"
)
txdbMouse <- makeTxDbFromUCSC(genome="mm9", tablename="knownGene",
                                 transcript_ids=transcript_ids)

## Using that, we can call our function to promote it to an OrgDb object:
odb <- makeOrganismDbFromTxDb(txdb=txdbMouse)

columns(odb)

## End(Not run)
```

**makeOrganismDbFromUCSC**

*Make a OrganismDb object from annotations available at the UCSC Genome Browser*

**Description**

The `makeOrganismDbFromUCSC` function allows the user to make a [OrganismDb](#) object from transcript annotations available at the UCSC Genome Browser.

**Usage**

```
makeOrganismDbFromUCSC(
  genome="hg19",
  tablename="knownGene",
  transcript_ids=NULL,
  circ_seqs=NULL,
  url="http://genome.ucsc.edu/cgi-bin/",
  goldenPath.urlgetOption("UCSC.goldenPath.url"))
```

## Arguments

genome	genome abbreviation used by UCSC and obtained by <a href="#">ucscGenomes()</a> [ , "db" ]. For example: "hg19".
tablename	name of the UCSC table containing the transcript annotations to retrieve. Use the <a href="#">supportedUCSCTables</a> utility function to get the list of supported tables. Note that not all tables are available for all genomes.
transcript_ids	optionally, only retrieve transcript annotation data for the specified set of transcript ids. If this is used, then the meta information displayed for the resulting <a href="#">OrganismDb</a> object will say 'Full dataset: no'. Otherwise it will say 'Full dataset: yes'.
circ_seqs	a character vector to list out which chromosomes should be marked as circular.
url	This argument is defunct, don't use.
goldenPath.url	use to specify the location of an alternate UCSC Genome Browser.

## Details

`makeOrganismDbFromUCSC` is a convenience function that feeds data from the UCSC source to the lower level [OrganismDb](#) function. See [?makeOrganismDbFromBiomart](#) for a similar function that feeds data from a BioMart database.

## Value

A [OrganismDb](#) object.

## Author(s)

M. Carlson

## See Also

- [makeOrganismDbFromBiomart](#) for convenient ways to make a [OrganismDb](#) object from BioMart online resources.
- [ucscGenomes](#) in the [rtracklayer](#) package.
- The [OrganismDb](#) class.

## Examples

```
## Not run:
## Display the list of genomes available at UCSC:
library(rtracklayer)
library(RMariaDB)
ucscGenomes()[ , "db"]

## Display the list of tables supported by makeOrganismDbFromUCSC():
supportedUCSCTables()

\dontrun{
## Retrieving a full transcript dataset for Yeast from UCSC:
```

```

odb1 <- makeOrganismDbFromUCSC(genome="sacCer2", tablename="ensGene")
}

## Retrieving an incomplete transcript dataset for Mouse from UCSC
## (only transcripts linked to Entrez Gene ID 22290):
transcript_ids <- c(
  "uc009uzf.1",
  "uc009uzg.1",
  "uc009uzh.1",
  "uc009uzi.1",
  "uc009uzj.1"
)

odb2 <- makeOrganismDbFromUCSC(genome="mm9", tablename="knownGene",
                                transcript_ids=transcript_ids)
odb2

## End(Not run)

```

---

**makeOrganismPackage** *Making OrganismDb packages from annotation packages.*

---

## Description

`makeOrganismPackage` is a method that generates a package that will load an appropriate `annotationOrganismDb` object that will in turn point to existing annotation packages.

## Usage

```

makeOrganismPackage (pkgname,
                     graphData,
                     organism,
                     version,
                     maintainer,
                     author,
                     destDir,
                     license="Artistic-2.0")

```

## Arguments

<code>pkgname</code>	What is the desired package name. Traditionally, this should be the genus and species separated by a ". ". So as an example, "Homo.sapiens" would be the package name for human
<code>graphData</code>	A list of short character vectors. Each character vector in the list is exactly two elements long and represents a join relationship between two packages. The names of these character vectors are the package names and the values are the foreign keys that should be used to connect each package. All foreign keys must be values that can be returned by the <code>columns</code> method for each package in question, and obviously they also must be the same kind of identifier as well.

organism	The name of the organism this package represents
version	What is the version number for this package?
maintainer	Who is the package maintainer? (must include email to be valid)
author	Who is the creator of this package?
destDir	A path where the package source should be assembled.
license	What is the license (and it's version)

## Details

The purpose of this method is to create a special package that will depend on existing annotation packages and which will load a special `annotationOrganismDb` object that will allow proper dispatch of special select methods. These methods will allow the user to easily query across multiple annotation resources via information contained by the `annotationOrganismDb` object. Because the end result will be a package that treats all the data mapped together as a single source, the user is encouraged to take extra care to ensure that the different packages used are from the same build etc.

## Value

A special package to load an [OrganismDb](#) object.

## Author(s)

M. Carlson

## See Also

[OrganismDb](#)

## Examples

```
## set up the list with the relevant relationships:
gd <- list(join1 = c(GO.db="GOID", org.Hs.eg.db="GO"),
           join2 = c(org.Hs.eg.db="ENTREZID",
                     TxBd.Hsapiens.UCSC.hg19.knownGene="GENEID"))

## sets up a temporary directory for this example
## (users won't need to do this step)
destination <- tempfile()
dir.create(destination)

## makes an Organism package for human called Homo.sapiens
if(interactive()){
  makeOrganismPackage(pkgname = "Homo.sapiens",
                     graphData = gd,
                     organism = "Homo sapiens",
                     version = "1.0.0",
                     maintainer = "Bioconductor Package Maintainer <maintainer@bioconductor.org>",
                     author = "Bioconductor Core Team",
                     destDir = destination,
                     license = "Artistic-2.0")
```

}

---

mapToTranscripts

*Map range coordinates between transcripts and genome space*

---

## Description

Map range coordinates between features in the transcriptome and genome (reference) space.

See `mapToAlignments` in the **GenomicAlignments** package for mapping coordinates between reads (local) and genome (reference) space using a CIGAR alignment.

## Usage

```
## S4 method for signature 'ANY,MultiDb'
mapToTranscripts(x, transcripts,
                  ignore.strand = TRUE,
                  extractor.fun = GenomicFeatures::transcripts, ...)
```

## Arguments

<code>x</code>	<code>GRanges-class</code> object of positions to be mapped. <code>x</code> must have names when mapping to the genome.
<code>transcripts</code>	The <code>OrganismDb</code> object that will be used to extract features using the <code>extractor.fun</code> .
<code>ignore.strand</code>	When <code>TRUE</code> , strand is ignored in overlap operations.
<code>extractor.fun</code>	Function to extract genomic features from a <code>TxDb</code> object. Valid extractor functions: <ul style="list-style-type: none"> <li>• <code>transcripts</code> ## default</li> <li>• <code>exons</code></li> <li>• <code>cds</code></li> <li>• <code>genes</code></li> <li>• <code>promoters</code></li> <li>• <code>tRNAs</code></li> <li>• <code>transcriptsBy</code></li> <li>• <code>exonsBy</code></li> <li>• <code>cdsBy</code></li> <li>• <code>intronsByTranscript</code></li> <li>• <code>fiveUTRsByTranscript</code></li> <li>• <code>threeUTRsByTranscript</code></li> </ul>
<code>...</code>	Additional arguments passed to <code>extractor.fun</code> functions.

## Details

Mapping is attempted between all elements of `x` and all elements of `transcripts`.

Each genomic range in `x` is mapped to the local position in the `transcripts` ranges. A successful mapping occurs when the genomic range in `x` is completely within the `transcripts` range, equivalent to:

```
findOverlaps(..., type="within")
```

Transcriptome-based coordinates start counting at 1 at the beginning of the `transcripts` range and return positions where the genomic range in `x` was aligned. The `seqlevels` of the return object are taken from the `transcripts` object and should be transcript names.

## Value

An object the same class as `x`.

Parallel methods return an object the same shape as `x`. Ranges that cannot be mapped (out of bounds or strand mismatch) are returned as zero-width ranges starting at 0 with a seqname of "UNMAPPED".

Non-parallel methods return an object that varies in length similar to a `Hits` object. The result only contains mapped records, strand mismatch and out of bound ranges are not returned. `xHits` and `transcriptsHits` metadata columns indicate the elements of `x` and `transcripts` used in the mapping.

When present, names from `x` are propagated to the output. When mapping to transcript coordinates, `seqlevels` of the output are the names on the `transcripts` object; most often these will be transcript names. When mapping to the genome, `seqlevels` of the output are the `seqlevels` of `transcripts` which are usually chromosome names.

## Author(s)

V. Obenchain, M. Lawrence and H. Pagès; ported to work with OrganismDbi by Marc Carlson

## See Also

- [mapToTranscripts](#).

## Examples

```
## -----
## A. Basic Use
## -----
```

  

```
library(Homo.sapiens)
x <- GRanges("chr5",
             IRanges(c(173315331,174151575), width=400,
                     names=LETTERS[1:2]))
```

  

```
## Map to transcript coordinates:
mapToTranscripts(x, Homo.sapiens)
```

## Description

The OrganismDb class is a container for storing knowledge about existing Annotation packages and the relationships between these resources. The purpose of this object and it's associated methods is to provide a means by which users can conveniently query for data from several different annotation resources at the same time using a familiar interface.

The supporting methods `select`, `columns` and `keys` are used together to extract data from an `OrganismDb` object in a manner that should be consistent with how these are used on the supporting annotation resources.

The family of `seqinfo` style getters (`seqinfo`, `seqlevels`, `seqlengths`, `isCircular`, `genome`, and `seqnameStyle`) is also supported for `OrganismDb` objects provided that the object in question has an embedded `TxDb` object.

## Methods

In the code snippets below, `x` is a `OrganismDb` object.

`keytypes(x)`: allows the user to discover which keytypes can be passed in to `select` or `keys` and the `keytype` argument.

`keys(x, keytype, pattern, column, fuzzy)`: Return keys for the database contained in the `TxDb` object .

The `keytype` argument specifies the kind of keys that will be returned and is always required. If `keys` is used with `pattern`, it will pattern match on the `keytype`.

But if the `column` argument is also provided along with the `pattern` argument, then `pattern` will be matched against the values in `column` instead.

If `keys` is called with `column` and no `pattern` argument, then it will return all keys that have corresponding values in the `column` argument.

Thus, the behavior of `keys` all depends on how many arguments are specified.

Use of the `fuzzy` argument will toggle fuzzy matching to TRUE or FALSE. If `pattern` is not used, `fuzzy` is ignored.

`columns(x)`: shows which kinds of data can be returned for the `OrganismDb` object.

`select(x, keys, columns, keytype)`: When all the appropriate arguments are specifiedm `select` will retrieve the matching data as a `data.frame` based on parameters for selected keys and `columns` and `keytype` arguments.

`mapIds(x, keys, columns, keytype, ..., multiVals)`: When all the appropriate arguments are specifiedm `mapIds` will retrieve the matching data as a vector or list based on parameters for selected keys and `columns` and `keytype` arguments. The `multiVals` argument can be used to choose the format of the values returned. Possible values for `multiVals` are:

**first:** This value means that when there are multiple matches only the 1st thing that comes back will be returned. This is the default behavior

**list:** This will just returns a list object to the end user

**filter:** This will remove all elements that contain multiple matches and will therefore return a shorter vector than what came in whenever some of the keys match more than one value

**asNA:** This will return an NA value whenever there are multiple matches

**CharacterList:** This just returns a SimpleCharacterList object

**FUN:** You can also supply a function to the `multiVals` argument for custom behaviors. The function must take a single argument and return a single value. This function will be applied to all the elements and will serve a 'rule' that for which thing to keep when there is more than one element. So for example this example function will always grab the last element in each result: `last <- function(x){x[[length(x)]]}`

**selectByRanges(x, ranges, columns, overlaps, ignore.strand):** When all the appropriate arguments are specified, `selectByRanges` will return an annotated GRanges object that has been generated based on what you passed in to the `ranges` argument and whether that overlapped with what you specified in the `overlaps` argument. Internally this function will get annotation features and overlaps by calling the appropriate annotation methods indicated by the `overlaps` argument. The value for `overlaps` can be any of: gene, tx, exons, cds, 5utr, introns or 3utr. The default value is 'tx' which will return to you, your annotated ranges based on whether the overlapped with the transcript ranges of any gene in the associated TxDb object based on the gene models it contains. Also: the number of ranges returned to you will match the number of genes that your `ranges` argument overlapped for the type of overlap that you specified. So if some of your ranges are large and overlap several features then you will get many duplicated ranges returned with one for each gene that has an overlapping feature. The `columns` values that you request will be returned in the `mcols` for the annotated GRanges object that is the return value for this function. Finally, the `ignore.strand` argument is provided to indicate whether or not `findOverlaps` should ignore or respect the strand.

**selectRangesById(x, keys, columns, keytype, feature):** When all the appropriate arguments are specified, `selectRangesById` will return a GRangesList object that correspond to gene models GRanges for the keys that you specify with the `keys` and `keytype` arguments. The annotation ranges retrieved for this will be specified by the `feature` argument and can be: gene, tx, exon or cds. The default is 'tx' which will return the transcript ranges for each gene as a GRanges object in the list. Extra data can also be returned in the `mcols` values for those GRanges by using the `columns` argument.

**resources(x):** shows where the db files are for resources that are used to store the data for the OrganismDb object.

**TxDb(x):** Accessor for the TxDb object of a OrganismDb object.

**TxDb(x) <- value:** Allows you to swap in an alternative TxDb for a given OrganismDb object. This is most often useful when combined with `saveDb(TxDb, file)`, which returns the saved TxDb, so that you can save a TxDb to disc and then assign the saved version right into your OrganismDb object.

## Author(s)

Marc Carlson

## See Also

- [AnnotationDb-class](#) for more descriptsion of methods `select`,`keytypes`,`keys` and `columns`.
- [makeOrganismPackage](#) for functions used to generate an OrganismDb based package.

- **rangeBasedAccessors** for the range based methods used in extracting data from a OrganismDb object.
- Topics in the Seqinfo package:
  - seqinfo
  - seqlevels
  - seqlengths
  - isCircular
  - genome

## Examples

```

## load a package that creates an OrganismDb
library(Homo.sapiens)
ls(2)
## then the methods can be used on this object.
columns <- columns(Homo.sapiens)[c(7,10,11,12)]
keys <- head(keys(org.Hs.eg.db, "ENTREZID"))
keytype <- "ENTREZID"
res <- select(Homo.sapiens, keys, columns, keytype)
head(res)
res <- mapIds(Homo.sapiens, keys=c('1','10'), column='ALIAS',
              keytype='ENTREZID', multiVals="CharacterList")

## get symbols for ranges in question:
ranges <- GRanges(seqnames=Rle(c('chr11')), c(2)),
                  IRanges(start=c(107899550, 108025550),
                          end=c(108291889, 108050000)), strand='*',
                  seqinfo=seqinfo(Homo.sapiens))
selectByRanges(Homo.sapiens, ranges, 'SYMBOL')

## Or extract the gene model for the 'A1BG' gene:
selectRangesById(Homo.sapiens, 'A1BG', keytype='SYMBOL')

## Get the DB connections or DB file paths associated with those for
## each.
dbconn(Homo.sapiens)
dbfile(Homo.sapiens)

## extract the taxonomyId
taxonomyId(Homo.sapiens)

##extract the resources
resources(Homo.sapiens)

```

## Description

Generic functions to extract genomic features from an object. This page documents the methods for [OrganismDb](#) objects only.

## Usage

```
## S4 method for signature 'MultiDb'
transcripts(x, columns=c("TXID", "TXNAME"), filter=NULL)

## S4 method for signature 'MultiDb'
exons(x, columns="EXONID", filter=NULL)

## S4 method for signature 'MultiDb'
cds(x, columns="CDSID", filter=NULL)

## S4 method for signature 'MultiDb'
genes(x, columns="GENEID", filter=NULL)

## S4 method for signature 'MultiDb'
transcriptsBy(x, by, columns, use.names=FALSE,
              outerMcols=FALSE)

## S4 method for signature 'MultiDb'
exonsBy(x, by, columns, use.names=FALSE, outerMcols=FALSE)

## S4 method for signature 'MultiDb'
cdsBy(x, by, columns, use.names=FALSE, outerMcols=FALSE)

## S4 method for signature 'MultiDb'
getTxDbIfAvailable(x, ...)

## S4 method for signature 'MultiDb'
asBED(x)
## S4 method for signature 'MultiDb'
asGFF(x)

## S4 method for signature 'MultiDb'
tRNAs(x)
## S4 method for signature 'MultiDb'
promoters(x, upstream=2000, downstream=200, use.names=TRUE, ...)

## S4 method for signature 'GenomicRanges,MultiDb'
distance(x, y, ignore.strand=FALSE,
         ..., id, type=c("gene", "tx", "exon", "cds"))

## S4 method for signature 'BSgenome'
extractTranscriptSeqs(x, transcripts, strand = "+")
```

```

## S4 method for signature 'MultiDb'
extractUpstreamSeqs(x, genes, width=1000, exclude.seqlevels=NULL)

## S4 method for signature 'MultiDb'
intronsByTranscript(x, use.names=FALSE)
## S4 method for signature 'MultiDb'
fiveUTRsByTranscript(x, use.names=FALSE)
## S4 method for signature 'MultiDb'
threeUTRsByTranscript(x, use.names=FALSE)

## S4 method for signature 'MultiDb'
isActiveSeq(x)

```

## Arguments

x	A <b>MultiDb</b> object, except in the <code>extractTranscriptSeqs</code> method where it is a <code>BSgenome</code> object and the second argument is a <b>MultiDb</b> object.
...	Arguments to be passed to or from methods.
by	One of "gene", "exon", "cds" or "tx". Determines the grouping.
columns	The columns or kinds of metadata that can be retrieved from the database. All possible columns are returned by using the <code>columns</code> method.
filter	Either NULL or a named list of vectors to be used to restrict the output. Valid names for this list are: "gene_id", "tx_id", "tx_name", "tx_chrom", "tx_strand", "exon_id", "exon_name", "exon_chrom", "exon_strand", "cds_id", "cds_name", "cds_chrom", "cds_strand" and "exon_rank".
use.names	Controls how to set the names of the returned <b>GRangesList</b> object. These functions return all the features of a given type (e.g. all the exons) grouped by another feature type (e.g. grouped by transcript) in a <b>GRangesList</b> object. By default (i.e. if <code>use.names</code> is FALSE), the names of this <b>GRangesList</b> object (aka the group names) are the internal ids of the features used for grouping (aka the grouping features), which are guaranteed to be unique. If <code>use.names</code> is TRUE, then the names of the grouping features are used instead of their internal ids. For example, when grouping by transcript (by="tx"), the default group names are the transcript internal ids ("tx_id"). But, if <code>use.names</code> =TRUE, the group names are the transcript names ("tx_name"). Note that, unlike the feature ids, the feature names are not guaranteed to be unique or even defined (they could be all NAs). A warning is issued when this happens. See <code>?id2name</code> for more information about feature internal ids and feature external names and how to map the formers to the latters. Finally, <code>use.names</code> =TRUE cannot be used when grouping by gene by="gene". This is because, unlike for the other features, the gene ids are external ids (e.g. Entrez Gene or Ensembl ids) so the db doesn't have a "gene_name" column for storing alternate gene names.
upstream	For promoters : An <code>integer(1)</code> value indicating the number of bases upstream from the transcription start site. For additional details see <code>?`promoters,GRanges-method`</code> .
downstream	For promoters : An <code>integer(1)</code> value indicating the number of bases downstream from the transcription start site. For additional details see <code>?`promoters,GRanges-method`</code> .

y	For distance, a <a href="#">MultiDb</a> instance. The id is used to extract ranges from the <a href="#">MultiDb</a> which are then used to compute the distance from x.
id	A character vector the same length as x. The id must be identifiers in the <a href="#">MultiDb</a> object. type indicates what type of identifier id is.
type	A character(1) describing the id. Must be one of 'gene', 'tx', 'exon' or 'cds'.
ignore.strand	A logical indicating if the strand of the ranges should be ignored. When TRUE, strand is set to '+'.
outerMcols	A logical indicating if the the 'outer' mcols (metadata columns) should be populated for some range based accesors which return a GRangesList object. By default this is FALSE, but if TRUE then the outer list object will also have it's metadata columns (mcols) populated as well as the mcols for the 'inner' GRanges objects.
transcripts	An object representing the exon ranges of each transcript to extract. It must be a <a href="#">GRangesList</a> or <a href="#">MultiDb</a> object while the x is a BSgenome object. Internally, it's turned into a <a href="#">GRangesList</a> object with <a href="#">exonsBy(transcripts, by="tx", use.names=TRUE)</a> .
strand	Only supported when x is a DNAString object. Can be an atomic vector, a factor, or an <a href="#">Rle</a> object, in which case it indicates the strand of each transcript (i.e. all the exons in a transcript are considered to be on the same strand). More precisely: it's turned into a factor (or factor- <a href="#">Rle</a> ) that has the "standard strand levels" (this is done by calling the <a href="#">strand</a> function on it). Then it's recycled to the length of <a href="#">IntegerRangesList</a> object transcripts if needed. In the resulting object, the i-th element is interpreted as the strand of all the exons in the i-th transcript. strand can also be a list-like object, in which case it indicates the strand of each exon, individually. Thus it must have the same <i>shape</i> as <a href="#">IntegerRangesList</a> object transcripts (i.e. same length plus <code>strand[[i]]</code> must have the same length as <code>transcripts[[i]]</code> for all i). strand can only contain "+" and/or "-" values. "*" is not allowed.
genes	An object containing the locations (i.e. chromosome name, start, end, and strand) of the genes or transcripts with respect to the reference genome. Only <a href="#">GenomicRanges</a> and <a href="#">MultiDb</a> objects are supported at the moment. If the latter, the gene locations are obtained by calling the <a href="#">genes</a> function on the <a href="#">MultiDb</a> object internally.
width	How many bases to extract upstream of each TSS (transcription start site).
exclude.seqlevels	A character vector containing the chromosome names (a.k.a. sequence levels) to exclude when the genes are obtained from a <a href="#">MultiDb</a> object.

## Details

These are the range based functions for extracting transcript information from a [MultiDb](#) object.

## Value

a GRanges or GRangesList object

**Author(s)**

M. Carlson

**See Also**

- [MultiDb-class](#) for how to use the simple "select" interface to extract information from a MultiDb object.
- [transcripts](#) for the original transcripts method and related methods.
- [transcriptsBy](#) for the original transcriptsBy method and related methods.

**Examples**

```
## extracting all transcripts from Homo.sapiens with some extra metadata
library(Homo.sapiens)
cols = c("TXNAME", "SYMBOL")
res <- transcripts(Homo.sapiens, columns=cols)

## extracting all transcripts from Homo.sapiens, grouped by gene and
## with extra metadata
res <- transcriptsBy(Homo.sapiens, by="gene", columns=cols)

## list possible values for columns argument:
columns(Homo.sapiens)

## Get the TxDb from an MultiDb object (if it's available)
getTxDbIfAvailable(Homo.sapiens)

## Other functions listed above should work in way similar to their TxDb
## counterparts. So for example:
promoters(Homo.sapiens)
## Should give the same value as:
promoters(getTxDbIfAvailable(Homo.sapiens))
```

# Index

- \* **methods**
  - mapToTranscripts, 10
  - rangeBasedAccessors, 14
- \* **utilities**
  - mapToTranscripts, 10
- AnnotationDb-class, 13
- asBED, MultiDb-method
  - (rangeBasedAccessors), 14
- asGFF, MultiDb-method
  - (rangeBasedAccessors), 14
- cds, MultiDb-method
  - (rangeBasedAccessors), 14
- cdsBy, MultiDb-method
  - (rangeBasedAccessors), 14
- class:MultiDb (MultiDb-class), 12
- class:OrganismDb (MultiDb-class), 12
- columns, MultiDb-method (MultiDb-class), 12
- dbconn, MultiDb-method (MultiDb-class), 12
- dbfile, MultiDb-method (MultiDb-class), 12
- distance, GenomicRanges, MultiDb-method
  - (rangeBasedAccessors), 14
- exons, MultiDb-method
  - (rangeBasedAccessors), 14
- exonsBy, 17
- exonsBy, MultiDb-method
  - (rangeBasedAccessors), 14
- extractTranscriptSeqs, 16
- extractTranscriptSeqs, BSgenome-method
  - (rangeBasedAccessors), 14
- extractUpstreamSeqs, MultiDb-method
  - (rangeBasedAccessors), 14
- fiveUTRsByTranscript, MultiDb-method
  - (rangeBasedAccessors), 14
- genes, 17
- genes, MultiDb-method
  - (rangeBasedAccessors), 14
- GenomicRanges, 17
- getTxDbIfAvailable
  - (rangeBasedAccessors), 14
- getTxDbIfAvailable, MultiDb-method
  - (rangeBasedAccessors), 14
- GRangesList, 16, 17
- id2name, 16
- IntegerRangesList, 17
- intronsByTranscript, MultiDb-method
  - (rangeBasedAccessors), 14
- isActiveSeq, MultiDb-method
  - (rangeBasedAccessors), 14
- isActiveSeq<, MultiDb-method
  - (rangeBasedAccessors), 14
- keys, MultiDb-method (MultiDb-class), 12
- keytypes, MultiDb-method
  - (MultiDb-class), 12
- listDatasets, 4
- listMarts, 2, 4
- makeOrganismDbFromBiomart, 2, 5–7
- makeOrganismDbFromTxDb, 5
- makeOrganismDbFromUCSC, 3–5, 6
- makeOrganismPackage, 8, 13
- mapIds, MultiDb-method (MultiDb-class), 12
- mapToTranscripts, 10, 11
- mapToTranscripts, ANY, MultiDb-method
  - (mapToTranscripts), 10
- metadata, MultiDb-method
  - (MultiDb-class), 12
- MultiDb, 16, 17
- MultiDb (MultiDb-class), 12
- MultiDb-class, 12, 18

OrganismDb, 2–7, 9, 15  
OrganismDb (MultiDb-class), 12  
OrganismDb-class (MultiDb-class), 12  
  
promoters, MultiDb-method  
    (rangeBasedAccessors), 14  
  
rangeBasedAccessors, 14, 14  
resources (MultiDb-class), 12  
resources, MultiDb-method  
    (MultiDb-class), 12  
Rle, 17  
  
select, MultiDb-method (MultiDb-class),  
    12  
selectByRanges (MultiDb-class), 12  
selectByRanges, MultiDb-method  
    (MultiDb-class), 12  
selectRangesById (MultiDb-class), 12  
selectRangesById, MultiDb-method  
    (MultiDb-class), 12  
seqinfo, MultiDb-method (MultiDb-class),  
    12  
strand, 17  
  
taxonomyId, MultiDb-method  
    (MultiDb-class), 12  
threeUTRsByTranscript, MultiDb-method  
    (rangeBasedAccessors), 14  
transcripts, 18  
transcripts, MultiDb-method  
    (rangeBasedAccessors), 14  
transcriptsBy, 18  
transcriptsBy, MultiDb-method  
    (rangeBasedAccessors), 14  
tRNAs, MultiDb-method  
    (rangeBasedAccessors), 14  
TxDb, 3, 12  
TxDb (MultiDb-class), 12  
TxDb, OrganismDb-method (MultiDb-class),  
    12  
TxDb<- (MultiDb-class), 12  
TxDb<-, OrganismDb-method  
    (MultiDb-class), 12  
  
ucscGenomes, 7  
useMart, 4