

Package ‘gemma.R’

February 1, 2026

Title A wrapper for Gemma's Restful API to access curated gene expression data and differential expression analyses

Version 3.7.1

Description Low- and high-level wrappers for Gemma's RESTful API. They enable access to curated expression and differential expression data from over 10,000 published studies. Gemma is a web site, database and a set of tools for the meta-analysis, re-use and sharing of genomics data, currently primarily targeted at the analysis of gene expression profiles.

URL <https://pavlidislab.github.io/gemma.R/>,
<https://github.com/PavlidisLab/gemma.R>

License Apache License (>= 2)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

BugReports <https://github.com/PavlidisLab/gemma.R/issues>

Imports magrittr, glue, memoise, jsonlite, data.table, rlang,
lubridate, utils, stringr, SummarizedExperiment, Biobase,
tibble, tidyr, S4Vectors, httr, rappdirs, bit64, assertthat,
digest, R.utils, kableExtra, base64enc

Suggests testthat (>= 2.0.0), rmarkdown, knitr, dplyr, covr, ggplot2,
ggrepel, BiocStyle, microbenchmark, magick, purrr, pheatmap,
viridis, poolr, listviewer, shiny

Config/testthat/edition 2

VignetteBuilder knitr

biocViews Software, DataImport, Microarray, SingleCell,
ThirdPartyClient, DifferentialExpression, GeneExpression,
Bayesian, Annotation, ExperimentalDesign, Normalization,
BatchEffect, Preprocessing

git_url <https://git.bioconductor.org/packages/gemma.R>

git_branch devel

git_last_commit ee7b6e9

git_last_commit_date 2026-01-13

Repository Bioconductor 3.23

Date/Publication 2026-02-01

Author Javier Castillo-Arnemann [aut] (ORCID:

<<https://orcid.org/0000-0002-5626-9004>>),

Jordan Sicherman [aut] (ORCID: <<https://orcid.org/0000-0001-8160-4567>>),

Ogan Mancarci [aut] (ORCID: <<https://orcid.org/0000-0002-1452-0889>>),

Guillaume Poirier-Morency [aut] (ORCID:

<<https://orcid.org/0000-0002-6554-0441>>),

Paul Pavlidis [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-0426-5028>>)

Maintainer Paul Pavlidis <paul@msl.ubc.ca>

Contents

.getResultSets	4
.get_dataset_expression_for_genes	5
.get_dataset_expression_for_genes_in_taxon	6
.get_gene_differential_expression_values	7
.get_gene_differential_expression_values_in_taxon	9
accessField	10
blank_processor	11
checkBounds	11
encode	12
filter_properties	12
forget_gemma_memoised	13
gemma.R	13
gemmaCache	14
gemmaPath	14
gemma_call	15
gemma_kable	15
gemma_memoise	16
get_all_pages	16
get_annotation_children	17
get_annotation_parents	18
get_child_terms	19
get_datasets	20
get_datasets_by_ids	22
get_dataset_annotations	24
get_dataset_differential_expression_analyses	25
get_dataset_expression	27
get_dataset_expression_for_genes	28
get_dataset_object	29
get_dataset_platforms	30
get_dataset_processed_expression	31

get_dataset_publications	32
get_dataset_quantitation_types	34
get_dataset_raw_expression	35
get_dataset_samples	36
get_dataset_subset_groups	37
get_dataset_subset_samples	38
get_differential_expression_values	39
get_genes	40
get_gene_differential_expression_values	42
get_gene_go_terms	43
get_gene_locations	45
get_gene_probes	46
get_platforms_by_ids	47
get_platform_annotations	49
get_platform_datasets	50
get_platform_element_genes	52
get_result_sets	54
get_taxa	56
get_taxa_by_ids	56
get_taxon_datasets	57
isEmpty	60
make_design	60
memoise	61
nullCheck	61
processAnnotations	62
processBibliographicReferenceValueObject	62
processCharacteristicValueObject	63
processDatasetResultSets	63
processDatasets	64
processDEA	65
processDEcontrasts	66
processDEMatrix	67
processDifferentialExpressionAnalysisResultByGeneValueObject_tsv	67
processDifferentialExpressionAnalysisResultSetValueObject	68
processElements	68
processExpressionMatrix	69
processFile	70
processGemmaArray	70
processGeneLocation	71
processGenes	71
processGO	72
processPlatforms	73
processQuantitationTypeValueObject	74
processResultSetFactors	75
processSamples	75
processSearchAnnotations	76
processTaxon	76
process_search	77

search_annotations	77
search_datasets	78
search_gemma	81
setGemmaPath	82
set_gemma_user	82
subset_factorValues	83
update_result	84
validateBoolean	84
validateID	85
validateLimit	85
validateOptionalID	86
validateOptionalQuery	86
validateOptionalTaxon	87
validatePositiveInteger	87
validateQuery	88
validateResultType	88
validateSingleID	89
validateSort	89
validateTaxa	90
validateTaxon	90
validateURI	91
Index	92

<code>.getResultSets</code>	<i>Retrieve a single analysis result set by its identifier</i>
-----------------------------	--

Description

Retrieve a single analysis result set by its identifier

Usage

```
.getResultSets(  
  resultSet = NA_character_,  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE)  
)
```

Arguments

- | | |
|-----------|---|
| resultSet | An expression analysis result set numerical identifier. |
| raw | TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results. |

<code>memoised</code>	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
<code>file</code>	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
<code>overwrite</code>	Whether or not to overwrite if a file exists at the specified filename.

Value

Varies

Examples

```
# gemma.R:::getResultSets(523099)
```

`.get_dataset_expression_for_genes`

Retrieve the expression data matrix of a set of datasets and genes

Description

Retrieve the expression data matrix of a set of datasets and genes

Usage

```
.get_dataset_expression_for_genes(  
  datasets,  
  genes,  
  keepNonSpecific = FALSE,  
  consolidate = NA_character_,  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE)  
)
```

Arguments

<code>datasets</code>	A vector of dataset IDs or short names
<code>genes</code>	A vector of NCBI IDs, Ensembl IDs or gene symbols.
<code>keepNonSpecific</code>	logical. FALSE by default. If TRUE, results from probesets that are not specific to the gene will also be returned.

<code>consolidate</code>	An option for gene expression level consolidation. If empty, will return every probe for the genes. "pickmax" to pick the probe with the highest expression, "pickvar" to pick the prove with the highest variance and "average" for returning the average expression
<code>raw</code>	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
<code>memoised</code>	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
<code>file</code>	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
<code>overwrite</code>	Whether or not to overwrite if a file exists at the specified filename.

Value

A list of data frames

Examples

```
get_dataset_expression_for_genes("GSE2018", genes = c(10225, 2841))
```

```
.get_dataset_expression_for_genes_in_taxon
```

Retrieve the expression data matrix of a set of datasets and genes

Description

Retrieve the expression data matrix of a set of datasets and genes

Usage

```
.get_dataset_expression_for_genes_in_taxon(
  datasets,
  genes,
  keepNonSpecific = FALSE,
  consolidate = NA_character_,
  taxon,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

<code>datasets</code>	A comma-delimited list of dataset IDs or short names. The value may be compressed with gzip and encoded with base64.
<code>genes</code>	A comma-delimited list of NCBI IDs, Ensembl IDs or gene symbols. The value may be compressed with gzip and encoded with base64.
<code>keepNonSpecific</code>	boolean
<code>consolidate</code>	An option for gene expression level consolidation.
<code>taxon</code>	A numerical taxon identifier or an ncbi taxon identifier or a taxon identifier that matches either its scientific or common name
<code>raw</code>	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
<code>memoised</code>	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
<code>file</code>	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
<code>overwrite</code>	Whether or not to overwrite if a file exists at the specified filename.

Value

Varies

`.get_gene_differential_expression_values`

Retrieve the differential expression results for a given gene among datasets matching the provided query and filter

Description

Retrieve the differential expression results for a given gene among datasets matching the provided query and filter

Usage

```
.get_gene_differential_expression_values(  
  gene,  
  query = NA_character_,  
  taxa = NA_character_,  
  uris = NA_character_,  
  filter = NA_character_,
```

```

threshold = 1,
raw = getOption("gemma.raw", FALSE),
memoised = getOption("gemma.memoised", FALSE),
file = getOption("gemma.file", NA_character_),
overwrite = getOption("gemma.overwrite", FALSE)
)

```

Arguments

gene	An ensembl gene identifier which typically starts with <code>ensg</code> or an ncbi gene identifier or an official gene symbol approved by hgnc
query	The search query. Queries can include plain text or ontology terms They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
taxa	A vector of taxon common names (e.g. human, mouse, rat). Providing multiple species will return results for all species. These are appended to the filter and equivalent to filtering for <code>taxon.commonName</code> property
uris	A vector of ontology term URIs. Providing multiple terms will return results containing any of the terms and their children. These are appended to the filter and equivalent to filtering for <code>allCharacteristics.valueUri</code>
filter	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
threshold	number
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A `data.table` containing differential expression results. This table is stripped down some relevant information for speed of execution. Details about the contrasts can be accessed via [get_result_sets](#) function

The fields of the output `data.table` are:

- `result.ID`: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- `contrast.ID`: Id of the specific contrast factor. Together with the `result.ID` they uniquely represent a given contrast.
- `experiment.ID`: Id of the source experiment
- `factor.coefficient`: Model coefficient calculated for the specific contrast factor
- `factor.logfc`: Log 2 fold change calculated for the specific contrast factor
- `factor.pvalue`: p values calculated for the specific contrast factor

Examples

```
# get all differential expression results for ENO2
# from datasets marked with the ontology term for brain
head(get_gene_differential_expression_values(2026, uris = "http://purl.obolibrary.org/obo/UBERON_0000955"))
```

```
.get_gene_differential_expression_values_in_taxon
```

Retrieve the differential expression results for a given gene and taxa among datasets matching the provided query and filter

Description

Retrieve the differential expression results for a given gene and taxa among datasets matching the provided query and filter

Usage

```
.get_gene_differential_expression_values_in_taxon(  
  gene,  
  query = NA_character_,  
  taxon = NA_character_,  
  uris = NA_character_,  
  filter = NA_character_,  
  threshold = 1,  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE)  
)
```

Arguments

<code>gene</code>	An ensembl gene identifier which typically starts with <code>ensg</code> or an ncbi gene identifier or an official gene symbol approved by hgnc
-------------------	---

query	The search query. Queries can include plain text or ontology terms. They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
taxon	A numerical taxon identifier or an ncbi taxon identifier or a taxon identifier that matches either its scientific or common name
uris	A vector of ontology term URIs. Providing multiple terms will return results containing any of the terms and their children. These are appended to the filter and equivalent to filtering for <code>allCharacteristics.valueUri</code>
filter	Filter results by matching expression. Use <code>filter_properties</code> function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
threshold	number
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

Varies

accessField	<i>Access the field in a list</i>
-------------	-----------------------------------

Description

This function accesses named field within the elements of a list. If an element lacks the field, it's filled in by `natype`.

Usage

```
accessField(d, field, natype = NA)
```

Arguments

d	Input data list
field	Field name to access in each element
natype	What to fill in when field is unavailable

Value

A vector of elements

blank_processor	<i>A blank processor that returns data as is</i>
-----------------	--

Description

A blank processor that returns data as is

Usage

```
blank_processor(data)
```

Arguments

data	any data
------	----------

Value

Data as is

checkBounds	<i>Replace missing data with NAs</i>
-------------	--------------------------------------

Description

Replace missing data with NAs

Usage

```
checkBounds(x, natype = NA)
```

Arguments

x	Data
natype	type of NA to replace the missing data with

Value

Data or NA in case of an out of bounds error

encode	<i>URL encode a string safely</i>
--------	-----------------------------------

Description

URL encode a string safely

Usage

```
encode(url)
```

Arguments

url	The string to URL encode. Vectors are delimited by a comma.
-----	---

Value

A URL encoding of url

filter_properties	<i>Return all supported filter properties</i>
-------------------	---

Description

Some functions such as [get_datasets](#) and [get_platforms_by_ids](#) include a filter argument that allows creation of more complex queries. This function returns a list of supported properties to be used in those filters

Usage

```
filter_properties()
```

Value

A list of data.tables that contain supported properties and their data types

Examples

```
filter_properties()
```

forget_gemma_memoised *Clear gemma.R cache*

Description

Forget past results from memoised calls to the Gemma API (ie. using functions with memoised = TRUE)

Usage

```
forget_gemma_memoised()
```

Value

TRUE to indicate cache was cleared.

Examples

```
forget_gemma_memoised()
```

gemma.R	<i>gemma.R package: Access curated gene expression data and differential expression analyses</i>
---------	--

Description

This package contains wrappers and convenience functions for Gemma's RESTful API that enables access to curated expression and differential expression data from over 15,000 published studies (as of mid-2022). Gemma (<https://gemma.msl.ubc.ca>) is a web site, database and a set of tools for the meta-analysis, re-use and sharing of transcriptomics data, currently primarily targeted at the analysis of gene expression profiles.

Details

Most users will want to start with the high-level functions like [get_dataset_object](#), [get_differential_expression_val](#) and [get_platform_annotations](#). Additional lower-level methods are available that directly map to the Gemma RESTful API methods.

For more information and detailed usage instructions check the [README](#), the [function reference](#) and the [vignette](#).

All software-related questions should be posted to the Bioconductor Support Site: <https://support.bioconductor.org>

Author(s)

Javier Castillo-Arnemann, Jordan Sicherman, Ogan Mancarci, Guillaume Poirier-Morency

References

Lim, N. et al., Curation of over 10 000 transcriptomic studies to enable data reuse, Database, 2021.
<https://doi.org/10.1093/database/baab006>

See Also

Useful links:

- <https://pavlidislab.github.io/gemma.R/>
- <https://github.com/PavlidisLab/gemma.R>
- Report bugs at <https://github.com/PavlidisLab/gemma.R/issues>

gemmaCache

Gemma Cache

Description

Gemma Cache

Usage

gemmaCache()

Value

A memoise filesystem

gemmaPath

Get gemma path

Description

Get gemma path

Usage

gemmaPath()

Value

Link to Gemma API

`gemma_call`*Custom gemma call*

Description

A minimal function to create custom calls. Can be used to acquire unimplemented endpoints and/or raw output without any processing. Refer to the [API documentation](#).

Usage

```
gemma_call(call, ..., json = TRUE)
```

Arguments

<code>call</code>	Gemma API endpoint.
<code>...</code>	parameters included in the call
<code>json</code>	If TRUE will parse the content as a list

Value

A list if `json = TRUE` and an `httr` response if `FALSE`

Examples

```
# get singular value decomposition for the dataset
gemma_call('datasets/{dataset}/svd', dataset = 1)
```

`gemma_kable`*Create printable tables out of gemma.R outputs*

Description

Creates a [kable](#) where certain columns are automatically shortened to better fit a document.

Usage

```
gemma_kable(table)
```

Arguments

<code>table</code>	A <code>data.table</code> or <code>data.frame</code> outputted by a <code>gemma.R</code> function
--------------------	---

gemma_memoise	<i>Enable and disable memoisation of gemma.R functions</i>
---------------	--

Description

Enable and disable memoisation of gemma.R functions

Usage

```
gemma_memoise(
  memoised = FALSE,
  cache = rappdirs::user_cache_dir(appname = "gemmaR")
)
```

Arguments

memoised	boolean. If TRUE memoisation will be enabled
cache	File path or "cache_in_memory". File path will chose a location to save the cache files for memoisation. "cache_in_memory" will store the cache in the current R session

get_all_pages	<i>Get all pages of a paginated call</i>
---------------	--

Description

Given a Gemma.R output from a function with offset and limit arguments, returns the output from all pages. All arguments other than offset, limit

Usage

```
get_all_pages(
  query,
  step_size = 100,
  binder = rbind,
  directory = NULL,
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```


Arguments

query	Output from a gemma.R function with offset and limit argument
step_size	Size of individual calls to the server. 100 is the maximum value
binder	Binding function for the calls. If raw = FALSE use rbind to combine the data.tables. If not, use c to combine lists
directory	Directory to save the output from the individual calls to. If provided, each page is saved to separate files.
file	The name of a file to save the results to, or NULL to not write results to a file. This function always saves the output as an RDS file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data.table or a list containing data from all pages.

get_annotation_children

Retrieve children of a given annotation

Description

Acquires child terms of a given URI based on ontologies loaded into Gemma. Propagated relations are **subClassOf** and **has_part**

Usage

```
get_annotation_children(
  uri,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

uri	Term URI
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.

file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with annotations (annotation search result value objects) matching the given identifiers. A list if raw = TRUE. A 400 error if required parameters are missing.

The fields of the output data.table are:

- category.name: Category that the annotation belongs to
- category.URI: URI for the category.name
- value.name: Annotation term
- value.URI: URI for the value.name

Examples

```
get_annotation_children("http://purl.obolibrary.org/obo/MONDO_0000408")
```

```
get_annotation_parents
```

Retrieve parents of a given annotation

Description

Acquires parent terms of a given URI based on ontologies loaded into Gemma. Propagated relations are **subClassOf** and **has_part**

Usage

```
get_annotation_parents(
  uri,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

uri	Term URI
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with annotations (annotation search result value objects) matching the given identifiers. A list if `raw = TRUE`. A 400 error if required parameters are missing.

The fields of the output data.table are:

- `category.name`: Category that the annotation belongs to
- `category.URI`: URI for the category.name
- `value.name`: Annotation term
- `value.URI`: URI for the value.name

Examples

```
get_annotation_parents("http://purl.obolibrary.org/obo/MONDO_0000408")
```

get_child_terms	<i>Return child terms of a term</i>
-----------------	-------------------------------------

Description

When querying for ontology terms, Gemma propagates these terms to include any datasets with their child terms in the results. This function returns these children for any number of terms, including all children and the terms itself in the output vector

Usage

```
get_child_terms(terms)
```

Arguments

terms	An array of terms
-------	-------------------

Value

An array containing descendants of the annotation terms, including the terms themselves

Examples

```
get_child_terms("http://purl.obolibrary.org/obo/MONDO_0000408")
```

get_datasets

*Retrieve all datasets***Description**

Retrieve all datasets

Usage

```
get_datasets(
  query = NA_character_,
  filter = NA_character_,
  taxa = NA_character_,
  uris = NA_character_,
  offset = 0L,
  limit = 20L,
  sort = "+id",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

query	The search query. Queries can include plain text or ontology terms. They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
filter	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
taxa	A vector of taxon common names (e.g. human, mouse, rat). Providing multiple species will return results for all species. These are appended to the filter and equivalent to filtering for taxon.commonName property
uris	A vector of ontology term URIs. Providing multiple terms will return results containing any of the terms and their children. These are appended to the filter and equivalent to filtering for allCharacteristics.valueUri
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the totalElements attribute in the output to compile all data if needed.
sort	Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.

raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the queried dataset(s). A list if `raw = TRUE`. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- `experiment.shortName`: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- `experiment.name`: Full title of the dataset
- `experiment.ID`: Internal ID of the dataset.
- `experiment.description`: Description of the dataset
- `experiment.troubled`: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- `experiment.accession`: Accession ID of the dataset in the external database it was taken from
- `experiment.database`: The name of the database where the dataset was taken from
- `experiment.URI`: URI of the original database
- `experiment.sampleCount`: Number of samples in the dataset
- `experiment.batchEffectText`: A text field describing whether the dataset has batch effects
- `experiment.batchCorrected`: Whether batch correction has been performed on the dataset.
- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch counfoud is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species

- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
get_datasets()
get_datasets(taxa = c("mouse", "human"), uris = "http://purl.obolibrary.org/obo/UBERON_0002048")
# filter below is equivalent to the call above
get_datasets(filter = "taxon.commonName in (mouse,human) and allCharacteristics.valueUri = http://purl.obolibrary.org/obo/UBERON_0002048")
get_datasets(query = "lung")
```

<code>get_datasets_by_ids</code>	<i>Retrieve datasets by their identifiers</i>
----------------------------------	---

Description

Retrieve datasets by their identifiers

Usage

```
get_datasets_by_ids(
  datasets = NA_character_,
  filter = NA_character_,
  taxa = NA_character_,
  uris = NA_character_,
  offset = 0L,
  limit = 20L,
  sort = "+id",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

<code>datasets</code>	Numerical dataset identifiers or dataset short names. If not specified, all datasets will be returned instead
<code>filter</code>	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")

taxa	A vector of taxon common names (e.g. human, mouse, rat). Providing multiple species will return results for all species. These are appended to the filter and equivalent to filtering for <code>taxon.commonName</code> property
uris	A vector of ontology term URIs. Providing multiple terms will return results containing any of the terms and their children. These are appended to the filter and equivalent to filtering for <code>allCharacteristics.valueUri</code>
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with <code>offset</code> and the <code>totalElements</code> attribute in the output to compile all data if needed.
sort	Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the queried dataset(s). A list if `raw = TRUE`. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- `experiment.shortName`: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- `experiment.name`: Full title of the dataset
- `experiment.ID`: Internal ID of the dataset.
- `experiment.description`: Description of the dataset
- `experiment.troubled`: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- `experiment.accession`: Accession ID of the dataset in the external database it was taken from
- `experiment.database`: The name of the database where the dataset was taken from
- `experiment.URI`: URI of the original database
- `experiment.sampleCount`: Number of samples in the dataset
- `experiment.batchEffectText`: A text field describing whether the dataset has batch effects

- `experiment.batchCorrected`: Whether batch correction has been performed on the dataset.
- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch confound is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
get_datasets_by_ids("GSE2018")
get_datasets_by_ids(c("GSE2018", "GSE2872"))
```

```
get_dataset_annotations
```

Retrieve the annotations of a dataset

Description

Retrieve the annotations of a dataset

Usage

```
get_dataset_annotations(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```


Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the annotations of the queried dataset. A list if `raw = TRUE`. A 404 error if the given identifier does not map to any object.

The fields of the output `data.table` are:

- `class.name`: Name of the annotation class (e.g. organism part)
- `class.URI`: URI for the annotation class
- `term.name`: Name of the annotation term (e.g. lung)
- `term.URI`: URI for the annotation term
- `object.class`: Class of object that the term originated from.

Examples

```
get_dataset_annotations("GSE2018")
```

```
get_dataset_differential_expression_analyses
```

Retrieve annotations and surface level stats for a dataset's differential analyses

Description

Retrieve annotations and surface level stats for a dataset's differential analyses

Usage

```
get_dataset_differential_expression_analyses(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the differential expression analysis of the queried dataset. Note that this function does not return differential expression values themselves. Use [get_differential_expression_values](#) to get differential expression values (see examples).

The fields of the output `data.table` are:

- `result.ID`: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- `contrast.ID`: ID of the specific contrast factor. Together with the `result.ID` they uniquely represent a given contrast.
- `experiment.ID`: ID of the source experiment
- `factor.category`: Category for the contrast
- `factor.category.URI`: URI for the contrast category
- `factor.ID`: ID of the factor
- `baseline.factors`: Characteristics of the baseline. This field is a `data.table`
- `experimental.factors`: Characteristics of the experimental group. This field is a `data.table`
- `isSubset`: TRUE if the result set belong to a subset, FALSE if not. Subsets are created when performing differential expression to avoid unhelpful comparisons.
- `subsetFactor`: Characteristics of the subset. This field is a `data.table`
- `probes.analyzed`: Number of probesets represented in the contrast
- `genes.analyzed`: Number of genes represented in the contrast

Examples

```
result <- get_dataset_differential_expression_analyses("GSE2872")
get_differential_expression_values(resultSet = result$result.ID[1])
```

```
get_dataset_expression
```

Retrieve processed expression data of a dataset

Description

This function is deprecated in favor of [get_dataset_processed_expression](#)

Usage

```
get_dataset_expression(
  dataset,
  filter = FALSE,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
filter	This argument is ignored due to deprecation of the function
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

If `raw` is FALSE (default), a data table of the expression matrix for the queried dataset. If `raw` is TRUE, returns the binary file in raw form.

Examples

```
get_dataset_expression("GSE2018")
```

get_dataset_expression_for_genes

Retrieve the expression data matrix of a set of datasets and genes

Description

Retrieve the expression data matrix of a set of datasets and genes

Usage

```
get_dataset_expression_for_genes(
  datasets,
  genes,
  keepNonSpecific = FALSE,
  consolidate = NA_character_,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

datasets	A vector of dataset IDs or short names
genes	A vector of NCBI IDs, Ensembl IDs or gene symbols.
keepNonSpecific	logical. FALSE by default. If TRUE, results from probesets that are not specific to the gene will also be returned.
consolidate	An option for gene expression level consolidation. If empty, will return every probe for the genes. "pickmax" to pick the probe with the highest expression, "pickvar" to pick the probe with the highest variance and "average" for returning the average expression
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A list of data frames

Examples

```
get_dataset_expression_for_genes("GSE2018", genes = c(10225, 2841))
```

get_dataset_object	<i>Compile gene expression data and metadata</i>
--------------------	--

Description

Return an annotated Bioconductor-compatible data structure or a long form tibble of the queried dataset, including expression data and the experimental design.

Usage

```
get_dataset_object(
  datasets,
  genes = NULL,
  keepNonSpecific = FALSE,
  consolidate = NA_character_,
  resultSets = NULL,
  contrasts = NULL,
  metaType = "text",
  type = "se",
  memoised = getOption("gemma.memoised", FALSE)
)
```

Arguments

datasets	A vector of dataset IDs or short names
genes	A vector of NCBI IDs, Ensembl IDs or gene symbols.
keepNonSpecific	logical. FALSE by default. If TRUE, results from probesets that are not specific to the gene will also be returned.
consolidate	An option for gene expression level consolidation. If empty, will return every probe for the genes. "pickmax" to pick the probe with the highest expression, "pickvar" to pick the probe with the highest variance and "average" for returning the average expression
resultSets	Result set IDs of the a differential expression analysis. Optional. If provided, the output will only include the samples from the subset used in the result set ID. Must be the same length as datasets.'
contrasts	Contrast IDs of a differential expression contrast. Optional. Need resultSets to be defined to work. If provided, the output will only include samples relevant to the specific contrats.

metaType	How should the metadata information should be included. Can be "text", "uri" or "both". "text" and "uri" options
type	"se" for a SummarizedExperiment or "eset" for Expression Set. We recommend using SummarizedExperiments which are more recent. See the Summarized experiment vignette or the ExpressionSet vignette for more details. "tidy" for a long form data frame compatible with tidyverse functions. 'list' to return a list containing individual data frames containing expression values, design and the experiment.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.

Value

A list of [SummarizedExperiments](#), [ExpressionSets](#) or a tibble containing metadata and expression data for the queried datasets and genes. Metadata will be expanded to include a variable number of factors that annotates samples from a dataset but will always include single "factorValues" column that houses data.tables that include all annotations for a given sample.

Examples

```
get_dataset_object("GSE2018")
```

get_dataset_platforms *Retrieve the platforms of a dataset*

Description

Retrieve the platforms of a dataset

Usage

```
get_dataset_platforms(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the platform(s). A list if `raw = TRUE`. A 404 error if the given identifier does not map to any object

The fields of the output data.table are:

- `platform.ID`: Internal identifier of the platform
- `platform.shortName`: Shortname of the platform.
- `platform.name`: Full name of the platform.
- `platform.description`: Free text description of the platform
- `platform.troubled`: Whether or not the platform was marked "troubled" by a Gemma process or a curator
- `platform.experimentCount`: Number of experiments using the platform within Gemma
- `platform.type`: Technology type for the platform.
- `taxon.name`: Name of the species platform was made for
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
get_dataset_platforms("GSE2018")
```

```
get_dataset_processed_expression
```

Retrieve processed expression data of a dataset

Description

Retrieve processed expression data of a dataset

Usage

```
get_dataset_processed_expression(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

If `raw` is FALSE (default), a data table of the expression matrix for the queried dataset. If `raw` is TRUE, returns the binary file in raw form.

Examples

```
get_dataset_processed_expression("GSE2018")
```

```
get_dataset_publications
```

Retrieve all publications associated with a dataset

Description

Retrieve all publications associated with a dataset

Usage

```
get_dataset_publications(  
  dataset,  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE)  
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data.table containing references. The fields of the output data.table are:

- title: Title of the paper
- authors: List of authors
- citation: Citation string for the paper
- pmid: PMID of the paper
- url: Pubmed URL of the paper

Examples

```
get_dataset_publications(1)
```

```
get_dataset_quantitation_types
```

Retrieve quantitation types of a dataset

Description

Retrieve quantitation types of a dataset

Usage

```
get_dataset_quantitation_types(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data.table containing the quantitation types

The fields of the output data.table are:

- id: If of the quantitation type. Any raw quantitation type can be accessed by [get_dataset_raw_expression](#) function using this id.
- name: Name of the quantitation type
- description: Description of the quantitation type
- type: Type of the quantitation type. Either raw or processed. Each dataset will have one processed quantitation type which is the data returned using [get_dataset_processed_expression](#)

- **ratio**: Whether or not the quantitation type is a ratio of multiple quantitation types. Typically TRUE for processed TWOCOLOR quantitation type.
- **preferred**: The preferred raw quantitation type. This version is used in generation of the processed data within gemma.
- **recomputed**: If TRUE this quantitation type is generated by recomputing raw data files Gemma had access to.

Examples

```
get_dataset_quantitation_types("GSE59918")
```

```
get_dataset_raw_expression
```

Retrieve raw expression data of a dataset

Description

Retrieve raw expression data of a dataset

Usage

```
get_dataset_raw_expression(
  dataset,
  quantitationType,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
quantitationType	Quantitation type id. These can be acquired using get_dataset_quantitation_types function. This endpoint can only return non-processed quantitation types.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

If raw is FALSE (default), a data table of the expression matrix for the queried dataset. If raw is TRUE, returns the binary file in raw form.

Examples

```
q_types <- get_dataset_quantitation_types("GSE59918")
get_dataset_raw_expression("GSE59918", q_types$id[q_types$name == "Counts"])
```

get_dataset_samples	<i>Retrieve the samples of a dataset</i>
---------------------	--

Description

Retrieve the samples of a dataset

Usage

```
get_dataset_samples(
  dataset,
  useProcessedQuantitationType = TRUE,
  quantitationType = NA_character_,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
useProcessedQuantitationType	If TRUE, returns the samples according to the processed quantitation type. This is set to TRUE by default to ensure output of this function always matches with get_dataset_processed_expression , otherwise for single cell experiments in particular, the output will not include cell types.
quantitationType	If provided, returns the samples based on a given quantitation type. Using useProcessedQuantitationType instead should cover most use cases.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.

file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the samples of the queried dataset. A list if raw = TRUE. A 404 error if the given identifier does not map to any object.

The fields of the output data.table are:

- sample.name: Internal name given to the sample.
- sample.ID: Internal ID of the sample
- sample.description: Free text description of the sample
- sample.outlier: Whether or not the sample is marked as an outlier
- sample.accession: Accession ID of the sample in it's original database
- sample.database: Database of origin for the sample
- sample.characteristics: Characteristics of the sample. This field is a data table
- sample.factorValues: Experimental factor values of the sample. This field is a data table

Examples

```
head(get_dataset_samples("GSE2018"))
```

```
get_dataset_subset_groups
```

Obtain all the subset groups of a dataset

Description

Obtain all the subset groups of a dataset

Usage

```
get_dataset_subset_groups(
  dataset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

Varies

get_dataset_subset_samples

Obtain the samples of a specific subset of a dataset

Description

Obtain the samples of a specific subset of a dataset

Usage

```
get_dataset_subset_samples(
  dataset,
  subset,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

dataset	A numerical dataset identifier or a dataset short name
subset	integer ID of the subset (eg. as returned by get_dataset_subset_groups).
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

Varies

get_differential_expression_values
*Retrieve differential expression results***Description**

Retrieves the differential expression result set(s) associated with the dataset. To get more information about the contrasts in individual resultSets and annotation terms associated them, use [get_dataset_differential_expression_analyses\(\)](#)

Usage

```
get_differential_expression_values(
  dataset = NA_character_,
  resultSets = NA_integer_,
  keepNonSpecific = FALSE,
  readableContrasts = FALSE,
  memoised = getOption("gemma.memoised", FALSE)
)
```

Arguments

dataset	A dataset identifier.
resultSets	resultSet identifiers. If a dataset is not provided, all result sets will be downloaded. If it is provided it will only be used to ensure all result sets belong to the dataset.
keepNonSpecific	logical. FALSE by default. If TRUE, results from probesets that are not specific to the gene will also be returned.
readableContrasts	If FALSE (default), the returned columns will use internal contrasts IDs as names. Details about the contrasts can be accessed using get_dataset_differential_expression_analyses() . If TRUE IDs will be replaced with human readable contrast information.

memoised Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing `options(gemma.memoised = TRUE)` will ensure that the cache is always used. Use `forget_gemma_memoised` to clear the cache.

Details

In Gemma each result set corresponds to the estimated effects associated with a single factor in the design, and each can have multiple contrasts (for each level compared to baseline). Thus a dataset with a 2x3 factorial design will have two result sets, one of which will have one contrast, and one having two contrasts.

The methodology for differential expression is explained in [Curation of over 10000 transcriptomic studies to enable data reuse](#). Briefly, differential expression analysis is performed on the dataset based on the annotated experimental design with up to two or three potentially nested factors. Gemma attempts to automatically assign baseline conditions for each factor. In the absence of a clear control condition, a baseline is arbitrarily selected. A generalized linear model with empirical Bayes shrinkage of t-statistics is fit to the data for each platform element (probe/gene) using an implementation of the limma algorithm. For RNA-seq data, we use weighted regression, applying the voom algorithm to compute weights from the mean–variance relationship of the data. Contrasts of each condition are then computed compared to the selected baseline. In some situations, Gemma will split the data into subsets for analysis. A typical such situation is when a ‘batch’ factor is present and confounded with another factor, the subsets being determined by the levels of the confounding factor.

Value

A list of data tables with differential expression values per result set.

Examples

```
get_differential_expression_values("GSE2018")
```

get_genes	<i>Retrieve all genes</i>
-----------	---------------------------

Description

Retrieve all genes

Usage

```
get_genes(
  genes,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```


Arguments

genes	A vector of NCBI IDs, Ensembl IDs or gene symbols.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the queried gene(s) A list if `raw = TRUE`.

The fields of the output data.table are:

- `gene.symbol`: Symbol for the gene
- `gene.ensembl`: Ensembl ID for the gene
- `gene.NCBI`: NCBI id for the gene
- `gene.name`: Name of the gene
- `gene.aliases`: Gene aliases. Each row includes a vector
- `gene.MFX.rank`: Multifunctionality rank for the gene
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
get_genes("DYRK1A")
get_genes(c("DYRK1A", "PTEN"))
```

```
get_gene_differential_expression_values
```

Retrieve the differential expression results for a given gene among datasets matching the provided query and filter

Description

Retrieve the differential expression results for a given gene among datasets matching the provided query and filter

Usage

```
get_gene_differential_expression_values(
  gene,
  query = NA_character_,
  taxa = NA_character_,
  uris = NA_character_,
  filter = NA_character_,
  threshold = 1,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

gene	An ensembl gene identifier which typically starts with ensg or an ncbi gene identifier or an official gene symbol approved by hgnc
query	The search query. Queries can include plain text or ontology terms They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
taxa	A vector of taxon common names (e.g. human, mouse, rat). Providing multiple species will return results for all species. These are appended to the filter and equivalent to filtering for taxon.commonName property
uris	A vector of ontology term URIs. Providing multiple terms will return results containing any of the terms and their children. These are appended to the filter and equivalent to filtering for allCharacteristics.valueUri
filter	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
threshold	number

raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A `data.table` containing differential expression results. This table is stripped down some relevant information for speed of execution. Details about the contrasts can be accessed via `get_result_sets` function

The fields of the output `data.table` are:

- `result.ID`: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- `contrast.ID`: Id of the specific contrast factor. Together with the `result.ID` they uniquely represent a given contrast.
- `experiment.ID`: Id of the source experiment
- `factor.coefficient`: Model coefficient calculated for the specific contrast factor
- `factor.logfc`: Log 2 fold change calculated for the specific contrast factor
- `factor.pvalue`: p values calculated for the specific contrast factor

Examples

```
# get all differential expression results for ENO2
# from datasets marked with the ontology term for brain
head(get_gene_differential_expression_values(2026, uris = "http://purl.obolibrary.org/obo/UBERON_0000955"))
```

<code>get_gene_go_terms</code>	<i>Retrieve the GO terms associated to a gene</i>
--------------------------------	---

Description

Retrieve the GO terms associated to a gene

Usage

```
get_gene_go_terms(
  gene,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

gene	An ensembl gene identifier which typically starts with ensg or an ncbi gene identifier or an official gene symbol approved by hgnc
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the GO terms assigned to the queried gene. A list if `raw = TRUE`. A 404 error if the given identifier does not map to any object.

The fields of the output `data.table` are:

- `term.name`: Name of the term
- `term.ID`: ID of the term
- `term.URI`: URI of the term

Examples

```
get_gene_go_terms(3091)
```

get_gene_locations	Retrieve the physical locations of a given gene
--------------------	---

Description

Retrieve the physical locations of a given gene

Usage

```
get_gene_locations(  
  gene,  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE)  
)
```

Arguments

gene	An ensembl gene identifier which typically starts with ensng or an ncbi gene identifier or an official gene symbol approved by hgnc
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the physical location of the queried gene. A list if `raw = TRUE`. A 404 error if the given identifier does not map to any object.

The fields of the output `data.table` are:

- `chromosome`: Name of the chromosome the gene is located
- `strand`: Which strand the gene is located
- `nucleotide`: Nucleotide number for the gene
- `length`: Gene length
- `taxon.name`: Name of the taxon

- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal ID for the taxon given by Gemma
- `taxon.NCBI`: NCBI ID for the taxon
- `taxon.database.name`: Name of the database used in Gemma for the taxon

Examples

```
get_gene_locations("DYRK1A")
get_gene_locations(1859)
```

<code>get_gene_probes</code>	<i>Retrieve the probes associated to a genes across all platforms</i>
------------------------------	---

Description

Retrieve the probes associated to a genes across all platforms

Usage

```
get_gene_probes(
  gene,
  offset = 0L,
  limit = 20L,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

<code>gene</code>	An ensembl gene identifier which typically starts with <code>ensg</code> or an ncbi gene identifier or an official gene symbol approved by hgnc
<code>offset</code>	The offset of the first retrieved result.
<code>limit</code>	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with <code>offset</code> and the <code>totalElements</code> attribute in the output to compile all data if needed.
<code>raw</code>	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
<code>memoised</code>	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.

file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the probes representing a gene across all platforms. A list if raw = TRUE. A 404 error if the given identifier does not map to any genes.

The fields of the output data.table are:

- element.name: Name of the element. Typically the probeset name
- element.description: A free text field providing optional information about the element
- platform.shortName: Shortname of the platform given by Gemma. Typically the GPL identifier.
- platform.name: Full name of the platform
- platform.ID: Id number of the platform given by Gemma
- platform.type: Type of the platform.
- platform.description: Free text field describing the platform.
- platform.troubled: Whether the platform is marked as troubled by a Gemma curator.
- taxon.name: Name of the species platform was made for
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

Examples

```
get_gene_probes(1859)
```

get_platforms_by_ids *Retrieve all platforms matching a set of platform identifiers*

Description

Retrieve all platforms matching a set of platform identifiers

Usage

```
get_platforms_by_ids(
  platforms = NA_character_,
  filter = NA_character_,
  taxa = NA_character_,
  offset = 0L,
  limit = 20L,
  sort = "+id",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

platforms	Platform numerical identifiers or platform short names. If not specified, all platforms will be returned instead
filter	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
taxa	A vector of taxon common names (e.g. human, mouse, rat). Providing multiple species will return results for all species. These are appended to the filter and equivalent to filtering for taxon.commonName property
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the totalElements attribute in the output to compile all data if needed.
sort	Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the platform(s). A list if raw = TRUE. A 404 error if the given identifier does not map to any object

The fields of the output data.table are:

- platform.ID: Internal identifier of the platform
- platform.shortName: Shortname of the platform.
- platform.name: Full name of the platform.
- platform.description: Free text description of the platform
- platform.troubled: Whether or not the platform was marked "troubled" by a Gemma process or a curator
- platform.experimentCount: Number of experiments using the platform within Gemma
- platform.type: Technology type for the platform.
- taxon.name: Name of the species platform was made for
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

Examples

```
get_platforms_by_ids("GPL1355")
get_platforms_by_ids(c("GPL1355", "GPL96"))
```

```
get_platform_annotations
```

Retrieve Platform Annotations by Gemma

Description

Gets Gemma's platform annotations including mappings of microarray probes to genes.

Usage

```
get_platform_annotations(
  platform,
  annotType = c("noParents", "allParents", "bioProcess"),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE),
  memoised = getOption("gemma.memoise", FALSE),
  unzip = FALSE
)
```

Arguments

platform	A platform numerical identifiers or platform short name.
annotType	Which GO terms should the output include
file	Where to save the annotation file to, or empty to just load into memory
overwrite	Whether or not to overwrite an existing file
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
unzip	Whether or not to unzip the file (if @param file is not empty)

Value

A table of annotations

- **ElementName:** Probeset names provided by the platform. Gene symbols for generic annotations typically used for RNA-seq experiments.
- **GeneSymbols:** Genes that were found to be aligned to the probe sequence. Note that it is possible for probes to be non-specific. Alignment to multiple genes are indicated with gene symbols separated by "|"s
- **GeneNames:** Name of the gene
- **GOTerms:** GO Terms associated with the genes. `annotType` argument can be used to choose which terms should be included.
- **GemmaIDs and NCBIIDs:** respective IDs for the genes.

Examples

```
head(get_platform_annotations("GPL96"))
head(get_platform_annotations('Generic_human_ncbiIds'))
```

`get_platform_datasets` *Retrieve all experiments using a given platform*

Description

Retrieve all experiments using a given platform

Usage

```
get_platform_datasets(
  platform,
  offset = 0L,
  limit = 20L,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
```

```

    file = getOption("gemma.file", NA_character_),
    overwrite = getOption("gemma.overwrite", FALSE)
  )

```

Arguments

platform	A platform numerical identifier or a platform short name
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the totalElements attribute in the output to compile all data if needed.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the queried dataset(s). A list if raw = TRUE. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- experiment.shortName: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- experiment.name: Full title of the dataset
- experiment.ID: Internal ID of the dataset.
- experiment.description: Description of the dataset
- experiment.troubled: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- experiment.accession: Accession ID of the dataset in the external database it was taken from
- experiment.database: The name of the database where the dataset was taken from
- experiment.URI: URI of the original database
- experiment.sampleCount: Number of samples in the dataset
- experiment.batchEffectText: A text field describing whether the dataset has batch effects
- experiment.batchCorrected: Whether batch correction has been performed on the dataset.

- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch confound is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
head(get_platform_datasets("GPL1355"))
```

```
get_platform_element_genes
```

Retrieve the genes associated to a probe in a given platform

Description

Retrieve the genes associated to a probe in a given platform

Usage

```
get_platform_element_genes(
  platform,
  probe,
  offset = 0L,
  limit = 20L,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

platform	A platform numerical identifier or a platform short name
probe	A probe name or it's numerical identifier
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the totalElements attribute in the output to compile all data if needed.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with information about the queried gene(s) A list if raw = TRUE.

The fields of the output data.table are:

- gene.symbol: Symbol for the gene
- gene.ensembl: Ensembl ID for the gene
- gene.NCBI: NCBI id for the gene
- gene.name: Name of the gene
- gene.aliaes: Gene aliases. Each row includes a vector
- gene.MFX.rank: Multifunctionality rank for the gene
- taxon.name: Name of the species
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

Examples

```
get_platform_element_genes("GPL1355", "AFFX_Rat_beta-actin_M_at")
```

get_result_sets

*Retrieve all result sets matching the provided criteria***Description**

Returns queried result set

Usage

```
get_result_sets(
  datasets = NA_character_,
  resultSets = NA_character_,
  filter = NA_character_,
  offset = 0,
  limit = 20,
  sort = "+id",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

datasets	A vector of dataset IDs or short names
resultSets	A resultSet identifier. Note that result set identifiers are not static and can change when Gemma re-runs analyses internally. When using these as inputs, try to make sure you access a currently existing result set ID by basing them on result sets returned for a particular dataset or filter used in get_result_sets
filter	Filter results by matching expression. Use filter_properties function to get a list of all available parameters. These properties can be combined using "and" "or" clauses and may contain common operators such as "=", "<" or "in". (e.g. "taxon.commonName = human", "taxon.commonName in (human,mouse)", "id < 1000")
offset	The offset of the first retrieved result.
limit	Defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the totalElements attribute in the output to compile all data if needed.
sort	Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Details

Output and usage of this function is mostly identical to `get_dataset_differential_expression_analyses`. The principal difference being the ability to restrict your result sets, being able to query across multiple datasets and being able to use the filter argument to search based on result set properties.

Value

A data table with information about the queried result sets. Note that this function does not return differential expression values themselves. Use `get_differential_expression_values` to get differential expression values

- `result.ID`: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- `contrast.ID`: Id of the specific contrast factor. Together with the `result.ID` they uniquely represent a given contrast.
- `experiment.ID`: Id of the source experiment
- `factor.category`: Category for the contrast
- `factor.category.URI`: URI for the contrast category
- `factor.ID`: ID of the factor
- `baseline.factors`: Characteristics of the baseline. This field is a `data.table`
- `experimental.factors`: Characteristics of the experimental group. This field is a `data.table`
- `isSubset`: TRUE if the result set belong to a subset, FALSE if not. Subsets are created when performing differential expression to avoid unhelpful comparisons.
- `subsetFactor`: Characteristics of the subset. This field is a `data.table`

Examples

```
get_result_sets(dataset = 1)
# get all contrasts comparing disease states. use filter_properties to see available options
get_result_sets(filter = "baselineGroup.characteristics.value = disease")
```

get_taxa

Get taxa

Description

Returns taxa and their versions used in Gemma

Usage

```
get_taxa(memoised = getOption("gemma.memoised", FALSE))
```

Arguments

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
----------	--

Value

A data frame including the names, IDs and database information about the taxons

Examples

```
get_taxa()
```

get_taxa_by_ids

Retrieve taxa by their identifiers

Description

Retrieve taxa by their identifiers

Usage

```
get_taxa_by_ids(
  taxa,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```


Arguments

taxa	Limits the result to entities with given identifiers. A vector of identifiers. Identifiers can be the any of the following: • taxon ID • scientific name • common name Retrieval by ID is more efficient. Do not combine different identifiers in one query. For convenience, below is a list of officially supported taxa																																
	<table><tr><th>ID</th><th>Comm.name</th><th>Scient.name</th><th>NcbiID</th></tr><tr><td>1</td><td>human</td><td>Homo sapiens</td><td>9606</td></tr><tr><td>2</td><td>mouse</td><td>Mus musculus</td><td>10090</td></tr><tr><td>3</td><td>rat</td><td>Rattus norvegicus</td><td>10116</td></tr><tr><td>11</td><td>yeast</td><td>Saccharomyces cerevisiae</td><td>4932</td></tr><tr><td>12</td><td>zebrafish</td><td>Danio rerio</td><td>7955</td></tr><tr><td>13</td><td>fly</td><td>Drosophila melanogaster</td><td>7227</td></tr><tr><td>14</td><td>worm</td><td>Caenorhabditis elegans</td><td>6239</td></tr></table>	ID	Comm.name	Scient.name	NcbiID	1	human	Homo sapiens	9606	2	mouse	Mus musculus	10090	3	rat	Rattus norvegicus	10116	11	yeast	Saccharomyces cerevisiae	4932	12	zebrafish	Danio rerio	7955	13	fly	Drosophila melanogaster	7227	14	worm	Caenorhabditis elegans	6239
ID	Comm.name	Scient.name	NcbiID																														
1	human	Homo sapiens	9606																														
2	mouse	Mus musculus	10090																														
3	rat	Rattus norvegicus	10116																														
11	yeast	Saccharomyces cerevisiae	4932																														
12	zebrafish	Danio rerio	7955																														
13	fly	Drosophila melanogaster	7227																														
14	worm	Caenorhabditis elegans	6239																														
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.																																
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.																																
file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.																																
overwrite	Whether or not to overwrite if a file exists at the specified filename.																																

Value

A data table with the queried taxa's details.

Examples

```
gemma.R::get_taxa_by_ids(c("mouse", "human"))
```

get_taxon_datasets	<i>Retrieve the datasets for a given taxon</i>
--------------------	--

Description

This function is deprecated in favor of [get_datasets](#)

Usage

```
get_taxon_datasets(  
  taxon,  
  offset = 0L,  
  limit = 20,  
  sort = "+id",  
  raw = getOption("gemma.raw", FALSE),  
  memoised = getOption("gemma.memoised", FALSE),  
  file = getOption("gemma.file", NA_character_),  
  overwrite = getOption("gemma.overwrite", FALSE),  
  ...  
)
```

Arguments

taxon can either be Taxon ID, Taxon NCBI ID, or one of its string identifiers: scientific name, common name. It is recommended to use Taxon ID for efficiency. Please note, that not all taxa have all the possible identifiers available. Use the [get_taxa_by_ids](#) function to retrieve the necessary information. For convenience, below is a list of officially supported taxa:

ID	Comm.name	Scient.name	NcbiID
1	human	Homo sapiens	9606
2	mouse	Mus musculus	10090
3	rat	Rattus norvegicus	10116
11	yeast	Saccharomyces cerevisiae	4932
12	zebrafish	Danio rerio	7955
13	fly	Drosophila melanogaster	7227
14	worm	Caenorhabditis elegans	6239

offset The offset of the first retrieved result.

limit Optional, defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the `totalElements` [attribute](#) in the output to compile all data if needed.

sort Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.

raw TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing `options(gemma.memoised = TRUE)` will ensure that the cache is always used. Use [forget_gemma_memoised](#) to clear the cache.

file The name of a file to save the results to, or NULL to not write results to a file. If `raw == TRUE`, the output will be a JSON file. Otherwise, it will be a RDS file.

overwrite Whether or not to overwrite if a file exists at the specified filename.

... Kept for compatibility. Ignored

Value

A data table with information about the queried dataset(s). A list if raw = TRUE. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- `experiment.shortName`: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- `experiment.name`: Full title of the dataset
- `experiment.ID`: Internal ID of the dataset.
- `experiment.description`: Description of the dataset
- `experiment.troubled`: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- `experiment.accession`: Accession ID of the dataset in the external database it was taken from
- `experiment.database`: The name of the database where the dataset was taken from
- `experiment.URI`: URI of the original database
- `experiment.sampleCount`: Number of samples in the dataset
- `experiment.batchEffectText`: A text field describing whether the dataset has batch effects
- `experiment.batchCorrected`: Whether batch correction has been performed on the dataset.
- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch counfoud is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
get_taxon_datasets("human")
```

isEmpty	<i>Check for empty arguments</i>
---------	----------------------------------

Description

Gemma functions accept typed NAs instead of simple NULLS. I believe this was done as a non-standard-in-R way of specifying data types for the users. Usually this is fine but it makes checking for emptiness a bit annoying since a user can still provide NULLs to make them empty

Usage

```
isEmpty(x)
```

Arguments

x	A parameter that can be NA or NULL when empty
---	---

make_design	<i>Make simplified design frames</i>
-------------	--------------------------------------

Description

Using on the output of [get_dataset_samples](#), this function creates a simplified design table, granting one column to each experimental variable

Usage

```
make_design(samples, metaType = "text")
```

Arguments

samples	An output from get_dataset_samples . The output should not be raw
metaType	Type of metadata to include in the output. "text", "uri" or "both"

Value

A data.frame including the design table for the dataset

Examples

```
samples <- get_dataset_samples('GSE46416')
make_design(samples)
```

memoise	<i>Memoise doc</i>
---------	--------------------

Description

Memoise doc

Arguments

memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
----------	--

nullCheck	<i>Avoid NULLS as data.table columns</i>
-----------	--

Description

Avoid NULLS as data.table columns

Usage

```
nullCheck(x, natype = NA)
```

Arguments

x	A value that might be null
natype	What to fill in when data is unavailable

Value

x as is or natypee

processAnnotations	<i>Processes JSON as annotations</i>
--------------------	--------------------------------------

Description

Processes JSON as annotations

Usage

```
processAnnotations(d)
```

Arguments

d	The JSON to process
---	---------------------

Value

A data table with information about the annotations of the queried dataset. A list if raw = TRUE. A 404 error if the given identifier does not map to any object.

The fields of the output data.table are:

- `class.name`: Name of the annotation class (e.g. organism part)
- `class.URI`: URI for the annotation class
- `term.name`: Name of the annotation term (e.g. lung)
- `term.URI`: URI for the annotation term
- `object.class`: Class of object that the term originated from.

processBibliographicReferenceValueObject	<i>processBibliographicReferenceValueObject</i>
--	---

Description

processBibliographicReferenceValueObject

Usage

```
processBibliographicReferenceValueObject(d)
```

Value

A data.table containing references. The fields of the output data.table are:

- title: Title of the paper
- authors: List of authors
- citation: Citation string for the paper
- pmid: PMID of the paper
- url: Pubmed URL of the paper

processCharacteristicValueObject
Processes JSON as a factor

Description

Processes JSON as a factor

Usage

```
processCharacteristicValueObject(d)
```

Arguments

d The JSON to process

Value

A processed data.table

processDatasetResultSets
Processes JSON as a datasets result set

Description

Processes JSON as a datasets result set

Usage

```
processDatasetResultSets(d)
```

Arguments

d The JSON to process

Value

A data table with the queried datasets' resultSet ID(s). A list if `raw = TRUE`. Use [get_differential_expression_values](#) to get differential expression values (see examples). Use [get_dataset_differential_expression_analyses](#) to get more detailed information about a result set.

The fields of the output data.table are:

- `resultSet.id`: Internal ID given to the result set. Can be used to access the results using [get_differential_expression_values](#)
- `factor.category`: What is the category splitting the experimental groups in the result set (e.g. disease)
- `factor.levels`: What are the conditions that are compared in the result set (e.g control, bipolar disorder)

processDatasets

Processes JSON as a vector of datasets

Description

Processes JSON as a vector of datasets

Usage

```
processDatasets(d)
```

Arguments

`d` The JSON to process

Value

A data table with information about the queried dataset(s). A list if `raw = TRUE`. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- `experiment.shortName`: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- `experiment.name`: Full title of the dataset
- `experiment.ID`: Internal ID of the dataset.
- `experiment.description`: Description of the dataset
- `experiment.troubled`: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- `experiment.accession`: Accession ID of the dataset in the external database it was taken from
- `experiment.database`: The name of the database where the dataset was taken from

- `experiment.URI`: URI of the original database
- `experiment.sampleCount`: Number of samples in the dataset
- `experiment.batchEffectText`: A text field describing whether the dataset has batch effects
- `experiment.batchCorrected`: Whether batch correction has been performed on the dataset.
- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch confound is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

`processDEA`*Processes JSON as a differential expression analysis*

Description

Processes JSON as a differential expression analysis

Usage

```
processDEA(d)
```

Arguments

<code>d</code>	The JSON to process
----------------	---------------------

Value

A data table with information about the differential expression analysis of the queried dataset. Note that this function does not return differential expression values themselves. Use [get_differential_expression_values](#) to get differential expression values (see examples).

The fields of the output data.table are:

- `result.ID`: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- `contrast.ID`: Id of the specific contrast factor. Together with the `result.ID` they uniquely represent a given contrast.
- `experiment.ID`: Id of the source experiment
- `factor.category`: Category for the contrast
- `factor.category.URI`: URI for the contrast category
- `factor.ID`: ID of the factor
- `baseline.factors`: Characteristics of the baseline. This field is a data.table
- `experimental.factors`: Characteristics of the experimental group. This field is a data.table
- `isSubset`: TRUE if the result set belong to a subset, FALSE if not. Subsets are created when performing differential expression to avoid unhelpful comparisons.
- `subsetFactor`: Characteristics of the subset. This field is a data.table
- `probes.analyzed`: Number of probesets represented in the contrast
- `genes.analyzed`: Number of genes represented in the contrast

processDEcontrasts	<i>Replaces factor ids by the factors strings in DE table columns</i>
--------------------	---

Description

Replaces factor ids by the factors strings in DE table columns

Usage

```
processDEcontrasts(rs, rsID)
```

Arguments

`rs` The resultSet matrix to process

Value

A processed matrix

processDEMatrix	<i>Processes differential expression matrix</i>
-----------------	---

Description

Processes differential expression matrix

Usage

```
processDEMatrix(m)
```

Arguments

m	The differential expression matrix to process
---	---

Value

A processed matrix

processDifferentialExpressionAnalysisResultByGeneValueObject_tsv	<i>processDifferentialExpressionAnalysisResultByGeneValueObject_tsv</i>
--	---

Description

processDifferentialExpressionAnalysisResultByGeneValueObject_tsv

Usage

```
processDifferentialExpressionAnalysisResultByGeneValueObject_tsv(content)
```

Value

A data.table containing differential expression results. This table is stripped down some relevant information for speed of execution. Details about the contrasts can be accessed via [get_result_sets](#) function

The fields of the output data.table are:

- result.ID: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- contrast.ID: Id of the specific contrast factor. Together with the result.ID they uniquely represent a given contrast.
- experiment.ID: Id of the source experiment
- factor.coefficient: Model coefficient calculated for the specific contrast factor
- factor.logfc: Log 2 fold change calculated for the specific contrast factor
- factor.pvalue: p values calculated for the specific contrast factor

processDifferentialExpressionAnalysisResultSetValueObject
Process JSON of a result set

Description

Process JSON of a result set

Usage

processDifferentialExpressionAnalysisResultSetValueObject(d)

Value

A data table with information about the queried result sets. Note that this function does not return differential expression values themselves. Use [get_differential_expression_values](#) to get differential expression values

- result.ID: Result set ID of the differential expression analysis. May represent multiple factors in a single model.
- contrast.ID: Id of the specific contrast factor. Together with the result.ID they uniquely represent a given contrast.
- experiment.ID: Id of the source experiment
- factor.category: Category for the contrast
- factor.category.URI: URI for the contrast category
- factor.ID: ID of the factor
- baseline.factors: Characteristics of the baseline. This field is a data.table
- experimental.factors: Characteristics of the experimental group. This field is a data.table
- isSubset: TRUE if the result set belong to a subset, FALSE if not. Subsets are created when performing differential expression to avoid unhelpful comparisons.
- subsetFactor: Characteristics of the subset. This field is a data.table

processElements *Processes JSON as a vector of elements*

Description

Processes JSON as a vector of elements

Usage

processElements(d)

Arguments

d The JSON to process

Value

A data table with information about the probes representing a gene across all platrofms. A list if raw = TRUE. A 404 error if the given identifier does not map to any genes.

The fields of the output data.table are:

- element.name: Name of the element. Typically the probeset name
- element.description: A free text field providing optional information about the element
- platform.shortName: Shortname of the platform given by Gemma. Typically the GPL identifier.
- platform.name: Full name of the platform
- platform.ID: Id number of the platform given by Gemma
- platform.type: Type of the platform.
- platform.description: Free text field describing the platform.
- platform.troubled: Whether the platform is marked as troubled by a Gemma curator.
- taxon.name: Name of the species platform was made for
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

processExpressionMatrix

Processes expression matrix

Description

Processes expression matrix

Usage

```
processExpressionMatrix(m)
```

Arguments

m The expression matrix to process

Value

A processed matrix

processFile	<i>Processes a response as a gzip file</i>
-------------	--

Description

Processes a response as a gzip file

Usage

```
processFile(content)
```

Arguments

content	The content from an http_get request
---------	--------------------------------------

Value

A processed data.table

processGemmaArray	<i>Processes JSON as an array</i>
-------------------	-----------------------------------

Description

Processes JSON as an array

Usage

```
processGemmaArray(d)
```

Arguments

d	The JSON to process
---	---------------------

Value

A data table with information about the probes representing the gene across different platforms.

processGeneLocation	<i>Processes JSON as a vector of gene locations</i>
---------------------	---

Description

Processes JSON as a vector of gene locations

Usage

```
processGeneLocation(d)
```

Arguments

d	The JSON to process
---	---------------------

Value

A data table with information about the physical location of the queried gene. A list if raw = TRUE.
A 404 error if the given identifier does not map to any object.

The fields of the output data.table are:

- chromosome: Name of the chromosome the gene is located
- strand: Which strand the gene is located
- nucleotide: Nucleotide number for the gene
- length: Gene length
- taxon.name: Name of the taxon
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal ID for the taxon given by Gemma
- taxon.NCBI: NCBI ID for the taxon
- taxon.database.name: Name of the database used in Gemma for the taxon

processGenes	<i>Processes JSON as a vector of genes</i>
--------------	--

Description

Processes JSON as a vector of genes

Usage

```
processGenes(d)
```

Arguments

d The JSON to process

Value

A data table with information about the queried gene(s) A list if raw = TRUE.

The fields of the output data.table are:

- gene.symbol: Symbol for the gene
- gene.ensembl: Ensembl ID for the gene
- gene.NCBI: NCBI id for the gene
- gene.name: Name of the gene
- gene.aliaes: Gene aliases. Each row includes a vector
- gene.MFX.rank: Multifunctionality rank for the gene
- taxon.name: Name of the species
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

processGO

Processes JSON as GO terms

Description

Processes JSON as GO terms

Usage

processGO(d)

Arguments

d The JSON to process

Value

A data table with information about the GO terms assigned to the queried gene. A list if raw = TRUE.
A 404 error if the given identifier does not map to any object.

The fields of the output data.table are:

- term.name: Name of the term
- term.ID: ID of the term
- term.URI: URI of the term

processPlatforms	<i>Processes JSON as a vector of platforms</i>
------------------	--

Description

Processes JSON as a vector of platforms

Usage

```
processPlatforms(d)
```

Arguments

d	The JSON to process
---	---------------------

Value

A data table with information about the platform(s). A list if raw = TRUE. A 404 error if the given identifier does not map to any object

The fields of the output data.table are:

- platform.ID: Internal identifier of the platform
- platform.shortName: Shortname of the platform.
- platform.name: Full name of the platform.
- platform.description: Free text description of the platform
- platform.troubled: Whether or not the platform was marked "troubled" by a Gemma process or a curator
- platform.experimentCount: Number of experiments using the platform within Gemma
- platform.type: Technology type for the platform.
- taxon.name: Name of the species platform was made for
- taxon.scientific: Scientific name for the taxon
- taxon.ID: Internal identifier given to the species by Gemma
- taxon.NCBI: NCBI ID of the taxon
- taxon.database.name: Underlying database used in Gemma for the taxon
- taxon.database.ID: ID of the underlying database used in Gemma for the taxon

processQuantitationTypeValueObject
processQuantitationTypeValueObject

Description

processQuantitationTypeValueObject

Usage

processQuantitationTypeValueObject(d)

Arguments

d The JSON to process

Value

A data.table containing the quantitation types

The fields of the output data.table are:

- id: If of the quantitation type. Any raw quantitation type can be accessed by [get_dataset_raw_expression](#) function using this id.
- name: Name of the quantitation type
- description: Description of the quantitation type
- type: Type of the quantitation type. Either raw or processed. Each dataset will have one processed quantitation type which is the data returned using [get_dataset_processed_expression](#)
- ratio: Whether or not the quantitation type is a ratio of multiple quantitation types. Typically TRUE for processed TWOCOLOR quantitation type.
- preferred: The preferred raw quantitation type. This version is used in generation of the processed data within gemma.
- recomputed: If TRUE this quantitation type is generated by recomputing raw data files Gemma had access to.

`processResultSetFactors`*Processes JSON as a result set*

Description

Processes JSON as a result set

Usage

```
processResultSetFactors(d)
```

Arguments

d The JSON to process

Value

A processed data.table

`processSamples`*Processes JSON as a vector of samples*

Description

Processes JSON as a vector of samples

Usage

```
processSamples(d)
```

Arguments

d The JSON to process

Value

A data table with information about the samples of the queried dataset. A list if raw = TRUE. A 404 error if the given identifier does not map to any object.

The fields of the output data.table are:

- sample.name: Internal name given to the sample.
- sample.ID: Internal ID of the sample
- sample.description: Free text description of the sample
- sample.outlier: Whether or not the sample is marked as an outlier

- `sample.accession`: Accession ID of the sample in it's original database
- `sample.database`: Database of origin for the sample
- `sample.characteristics`: Characteristics of the sample. This field is a data table
- `sample.factorValues`: Experimental factor values of the sample. This field is a data table

<code>processSearchAnnotations</code>	<i>Processes JSON as an annotation</i>
---------------------------------------	--

Description

Processes JSON as an annotation

Usage

`processSearchAnnotations(d)`

Arguments

`d` The JSON to process

Value

A data table with annotations (annotation search result value objects) matching the given identifiers. A list if `raw = TRUE`. A 400 error if required parameters are missing.

The fields of the output `data.table` are:

- `category.name`: Category that the annotation belongs to
- `category.URI`: URI for the `category.name`
- `value.name`: Annotation term
- `value.URI`: URI for the `value.name`

<code>processTaxon</code>	<i>Processes JSON as a vector of taxa</i>
---------------------------	---

Description

Processes JSON as a vector of taxa

Usage

`processTaxon(d)`

Arguments

d The JSON to process

Value

A processed data.table

- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

process_search	<i>Returns the ids of the found results</i>
----------------	---

Description

Returns the ids of the found results

Usage

```
process_search(d)
```

Value

A data.table or a list of resultObjects

search_annotations	<i>Search for annotation tags</i>
--------------------	-----------------------------------

Description

Search for annotation tags

Usage

```
search_annotations(
  query,
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

query	The search query. Queries can include plain text or ontology terms They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing <code>options(gemma.memoised = TRUE)</code> will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.
file	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

A data table with annotations (annotation search result value objects) matching the given identifiers. A list if `raw = TRUE`. A 400 error if required parameters are missing.

The fields of the output `data.table` are:

- `category.name`: Category that the annotation belongs to
- `category.URI`: URI for the `category.name`
- `value.name`: Annotation term
- `value.URI`: URI for the `value.name`

Examples

```
search_annotations("traumatic")
```

search_datasets

Retrieve datasets associated to an annotation tags search

Description

This function is deprecated in favor of [get_datasets](#)

Usage

```
search_datasets(
  query,
  taxon = NA_character_,
  offset = 0L,
  limit = 20L,
  sort = "+id",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE),
  attributes = getOption("gemma.attributes", TRUE),
  ...
)
```

Arguments

query The search query. Either plain text ('traumatic'), or an ontology term URI ('http://purl.obolibrary.org/obo/UBERON_0002048'). Datasets that contain the given string in their short or full name will also be matched. Can be multiple identifiers separated by commas.

taxon Can either be Taxon ID, Taxon NCBI ID, or one of its string identifiers: scientific name, common name. It is recommended to use Taxon ID for efficiency. Please note, that not all taxa have all the possible identifiers available. Use the [get_taxa_by_ids](#) function to retrieve the necessary information. For convenience, below is a list of officially supported taxa:

ID	Comm.name	Scient.name	NcbiID
1	human	Homo sapiens	9606
2	mouse	Mus musculus	10090
3	rat	Rattus norvegicus	10116
11	yeast	Saccharomyces cerevisiae	4932
12	zebrafish	Danio rerio	7955
13	fly	Drosophila melanogaster	7227
14	worm	Caenorhabditis elegans	6239

offset The offset of the first retrieved result.

limit Optional, defaults to 20. Limits the result to specified amount of objects. Has a maximum value of 100. Use together with offset and the [totalElements](#) [attribute](#) in the output to compile all data if needed.

sort Order results by the given property and direction. The '+' sign indicate ascending order whereas the '-' indicate descending.

raw TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.

memoised Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing `options(gemma.memoised`

	= TRUE) will ensure that the cache is always used. Use <code>forget_gemma_memoised</code> to clear the cache.
<code>file</code>	The name of a file to save the results to, or NULL to not write results to a file. If <code>raw == TRUE</code> , the output will be a JSON file. Otherwise, it will be a RDS file.
<code>overwrite</code>	Whether or not to overwrite if a file exists at the specified filename.
<code>attributes</code>	If TRUE additional information from the call will be added into the output object's attributes such as offset and available elements.
<code>...</code>	Kept for compatibility, ignored.

Value

A data table with information about the queried dataset(s). A list if `raw = TRUE`. Returns an empty list if no datasets matched.

The fields of the output data.table are:

- `experiment.shortName`: Shortname given to the dataset within Gemma. Often corresponds to accession ID
- `experiment.name`: Full title of the dataset
- `experiment.ID`: Internal ID of the dataset.
- `experiment.description`: Description of the dataset
- `experiment.troubled`: Did an automatic process within gemma or a curator mark the dataset as "troubled"
- `experiment.accession`: Accession ID of the dataset in the external database it was taken from
- `experiment.database`: The name of the database where the dataset was taken from
- `experiment.URI`: URI of the original database
- `experiment.sampleCount`: Number of samples in the dataset
- `experiment.batchEffectText`: A text field describing whether the dataset has batch effects
- `experiment.batchCorrected`: Whether batch correction has been performed on the dataset.
- `experiment.batchConfound`: 0 if batch info isn't available, -1 if batch counfoud is detected, 1 if batch information is available and no batch confound found
- `experiment.batchEffect`: -1 if batch p value < 0.0001, 1 if batch p value > 0.1, 0 if otherwise and when there is no batch information is available or when the data is confounded with batches.
- `experiment.rawData`: -1 if no raw data available, 1 if raw data was available. When available, Gemma reprocesses raw data to get expression values and batches
- `geeq.qScore`: Data quality score given to the dataset by Gemma.
- `geeq.sScore`: Suitability score given to the dataset by Gemma. Refers to factors like batches, platforms and other aspects of experimental design
- `taxon.name`: Name of the species
- `taxon.scientific`: Scientific name for the taxon
- `taxon.ID`: Internal identifier given to the species by Gemma
- `taxon.NCBI`: NCBI ID of the taxon
- `taxon.database.name`: Underlying database used in Gemma for the taxon
- `taxon.database.ID`: ID of the underlying database used in Gemma for the taxon

Examples

```
search_datasets("bipolar", taxon = "human")
```

search_gemma

Search everything in Gemma

Description

Search everything in Gemma

Usage

```
search_gemma(
  query,
  taxon = NA_character_,
  platform = NA_character_,
  limit = 100,
  resultType = "experiment",
  raw = getOption("gemma.raw", FALSE),
  memoised = getOption("gemma.memoised", FALSE),
  file = getOption("gemma.file", NA_character_),
  overwrite = getOption("gemma.overwrite", FALSE)
)
```

Arguments

query	The search query. Queries can include plain text or ontology terms They also support conjunctions ("alpha AND beta"), disjunctions ("alpha OR beta") grouping ("(alpha OR beta) AND gamma"), prefixing ("alpha*"), wildcard characters ("BRCA?") and fuzzy matches ("alpha~").
taxon	A numerical taxon identifier or an ncbi taxon identifier or a taxon identifier that matches either its scientific or common name
platform	A platform numerical identifier or a platform short name
limit	Defaults to 100 with a maximum value of 2000. Limits the number of returned results. Note that this function does not support pagination.
resultType	The kind of results that should be included in the output. Can be experiment, gene, platform or a long object type name, documented in the API documentation.
raw	TRUE to receive results as-is from Gemma, or FALSE to enable parsing. Raw results usually contain additional fields and flags that are omitted in the parsed results.
memoised	Whether or not to save to cache for future calls with the same inputs and use the result saved in cache if a result is already saved. Doing options(gemma.memoised = TRUE) will ensure that the cache is always used. Use forget_gemma_memoised to clear the cache.

file	The name of a file to save the results to, or NULL to not write results to a file. If raw == TRUE, the output will be the raw endpoint from the API, likely a JSON or a gzip file. Otherwise, it will be a RDS file.
overwrite	Whether or not to overwrite if a file exists at the specified filename.

Value

If raw = FALSE and resultType is experiment, gene or platform, a data.table containing the search results. If it is any other type, a list of results. A list with additional details about the search if raw = TRUE

Examples

```
search_gemma("bipolar")
```

setGemmaPath	<i>Set gemma path</i>
--------------	-----------------------

Description

Set gemma path

Usage

```
setGemmaPath(path)
```

Arguments

path	"dev", "prod" or a link to use to access gemma API
------	--

Value

Link to Gemma API

set_gemma_user	<i>Authentication by user name</i>
----------------	------------------------------------

Description

Allows the user to access information that requires logging in to Gemma. To log out, run set_gemma_user without specifying the username or password.

Usage

```
set_gemma_user(username = NULL, password = NULL)
```

Arguments

username	Your username (or empty, if logging out)
password	Your password (or empty, if logging out)

Value

TRUE if authentication is successful, FALSE if not

subset_factorValues	<i>Get a subset of an array of factorValues</i>
---------------------	---

Description

Get a subset of an array of factorValues

Usage

```
subset_factorValues(  
  factorValues,  
  factorValue = NULL,  
  differential_expressions = NULL,  
  resultSet = NULL,  
  contrast = NULL  
)
```

Arguments

factorValue	unimplemented
differential_expressions	

Value

a boolean vector, samples representing the resultSet and/or the contrast are set to TRUE

update_result	<i>Update result</i>
---------------	----------------------

Description

Re-runs the function used to create a gemma.R output to update the data at hand. Useful if you have a reason to believe parts of the data has changed since your last accession and you wish to update while decoupling the update process from your original code used to generate the data.

Usage

```
update_result(query)
```

Arguments

query	Output from a gemma.R function
-------	--------------------------------

Details

Note that if you have used the file and overwrite arguments with the original call, this will also repeat to regenerate the file based on your initial preference

Examples

```
annots <- get_dataset_annotations(1)
# wait for a couple of years..
# wonder if the results are the same
updated_annots <- update_result(annots)

# also works with outputs of get_all_pages
platforms <- get_all_pages(get_platforms_by_ids())
updated_platforms <- update_result(platforms)
```

validateBoolean	<i>Validate a boolean value</i>
-----------------	---------------------------------

Description

Validate a boolean value

Usage

```
validateBoolean(name, ...)
```

Arguments

name	The variable name
...	Any boolean types

Value

The validated boolean as a character string (true or false), or stop with an error message

validateID	<i>Validate identifiers (ie. gene ID, platform ID, etc.) that are homogeneous (either all numerics or all not)</i>
------------	--

Description

Validate identifiers (ie. gene ID, platform ID, etc.) that are homogeneous (either all numerics or all not)

Usage

validateID(name, ...)

Arguments

name	The variable name
...	Any identifiers

Value

The validated identifiers, or stop with an error message

validateLimit	<i>Validate a limit value</i>
---------------	-------------------------------

Description

Validate a limit value

Usage

validateLimit(name, ...)

Arguments

name	The variable name
...	Any possible integers

Value

The validated integers, or stop with an error message

validateOptionalID	<i>Validate identifiers (ie. gene ID, platform ID, etc.) that are homogeneous (either all numerics or all not)</i>
--------------------	--

Description

Validate identifiers (ie. gene ID, platform ID, etc.) that are homogeneous (either all numerics or all not)

Usage

validateOptionalID(name, ...)

Arguments

name	The variable name
...	Any identifiers

Value

The validated identifiers, or stop with an error message

validateOptionalQuery	<i>Validate am optional query</i>
-----------------------	-----------------------------------

Description

Validate am optional query

Usage

validateOptionalQuery(name, ...)

Arguments

name	The variable name
...	Any queries

Value

The validated queries

validateOptionalTaxon *Validate a taxon using the acceptable taxa entries*

Description

Validate a taxon using the acceptable taxa entries

Usage

```
validateOptionalTaxon(name, ...)
```

Arguments

name	The variable name
...	Any taxa to validate

Value

The validated taxon, or stop with an error message

validatePositiveInteger
 Validate a non-negative integer value

Description

Validate a non-negative integer value

Usage

```
validatePositiveInteger(name, ...)
```

Arguments

name	The variable name
...	Any possible integers

Value

The validated integers, or stop with an error message

validateQuery	<i>Validate a query</i>
---------------	-------------------------

Description

Validate a query

Usage

validateQuery(name, ...)

Arguments

name	The variable name
...	Any queries

Value

The validated queries, or stop with an error message

validateResultType	<i>Validate result types</i>
--------------------	------------------------------

Description

Validate result types

Usage

validateResultType(name, ...)

Arguments

name	The variable name
...	result types

Value

Validated result types. Either returned as they are or they will be replaced from human readable variants

validateSingleID	<i>Validate a single identifier(ie. gene ID, platform ID, etc.)</i>
------------------	---

Description

Validate a single identifier(ie. gene ID, platform ID, etc.)

Usage

validateSingleID(name, ...)

Arguments

name	The variable name
...	An identifier

Value

The validated identifier, or stop with an error message

validateSort	<i>Validate a sort argument</i>
--------------	---------------------------------

Description

Validate a sort argument

Usage

validateSort(name, ...)

Arguments

name	The variable name
...	Any sort arguments

Value

The validated sort arguments, or stop with an error message

`validateTaxa`*Validate taxa using the acceptable taxa entries*

Description

Validate taxa using the acceptable taxa entries

Usage

```
validateTaxa(name, ...)
```

Arguments

<code>name</code>	The variable name
<code>...</code>	Any taxa to validate

Value

The validated taxa, or stop with an error message

`validateTaxon`*Validate a taxon using the acceptable taxa entries*

Description

Validate a taxon using the acceptable taxa entries

Usage

```
validateTaxon(name, ...)
```

Arguments

<code>name</code>	The variable name
<code>...</code>	Any taxa to validate

Value

The validated taxon, or stop with an error message

validateURI	<i>Validate string</i>
-------------	------------------------

Description

Validate string

Usage

validateURI(name, ...)

Index

* annotation

get_annotation_children, [17](#)
 get_annotation_parents, [18](#)
 search_annotations, [77](#)

* dataset

get_dataset_annotations, [24](#)
 get_dataset_differential_expression_analyses, [25](#)
 get_dataset_expression_for_genes, [28](#)
 get_dataset_object, [29](#)
 get_dataset_platforms, [30](#)
 get_dataset_processed_expression, [31](#)
 get_dataset_publications, [32](#)
 get_dataset_quantitation_types, [34](#)
 get_dataset_raw_expression, [35](#)
 get_dataset_samples, [36](#)
 get_datasets, [20](#)
 get_datasets_by_ids, [22](#)
 get_differential_expression_values, [39](#)

* gene

get_gene_differential_expression_values, [42](#)
 get_gene_go_terms, [43](#)
 get_gene_locations, [45](#)
 get_gene_probes, [46](#)
 get_genes, [40](#)

* internal

.getResultSets, [4](#)
 .get_dataset_expression_for_genes, [5](#)
 .get_dataset_expression_for_genes_in_taxon, [6](#)
 .get_gene_differential_expression_values, [7](#)
 .get_gene_differential_expression_values_in_taxon, [9](#)

accessField, [10](#)

blank_processor, [11](#)

checkBounds, [11](#)

encode, [12](#)

gemmaCache, [14](#)

gemmaPath, [14](#)

get_dataset_expression, [27](#)

get_dataset_subset_groups, [37](#)

get_dataset_subset_samples, [38](#)

get_taxa_by_ids, [56](#)

get_taxon_datasets, [57](#)

isEmpty, [60](#)

memoise, [61](#)

nullCheck, [61](#)

process_search, [77](#)

processAnnotations, [62](#)

processBibliographicReferenceValueObject, [62](#)

processCharacteristicValueObject, [63](#)

processDatasetResultSets, [63](#)

processDatasets, [64](#)

processDEA, [65](#)

processDEcontrasts, [66](#)

processDEMatrix, [67](#)

processDifferentialExpressionAnalysisResultByGeneValueObject, [67](#)

processDifferentialExpressionAnalysisResultSetValueObject, [68](#)

processElements, [68](#)

processExpressionMatrix, [69](#)

processFile, [70](#)

processGemmaArray, [70](#)

processGeneLocation, [71](#)

processGenes, [71](#)

processGO, [72](#)

processPlatforms, [73](#)

processQuantitationTypeValueObject, [74](#)

- processResultSetFactors, 75
- processSamples, 75
- processSearchAnnotations, 76
- processTaxon, 76
- search_datasets, 78
- setGemmaPath, 82
- subset_factorValues, 83
- validateBoolean, 84
- validateID, 85
- validateLimit, 85
- validateOptionalID, 86
- validateOptionalQuery, 86
- validateOptionalTaxon, 87
- validatePositiveInteger, 87
- validateQuery, 88
- validateResultType, 88
- validateSingleID, 89
- validateSort, 89
- validateTaxa, 90
- validateTaxon, 90
- validateURI, 91
- * **misc**
 - filter_properties, 12
 - forget_gemma_memoised, 13
 - gemma_call, 15
 - gemma_kable, 15
 - gemma_memoise, 16
 - get_all_pages, 16
 - get_child_terms, 19
 - get_result_sets, 54
 - make_design, 60
 - search_gemma, 81
 - set_gemma_user, 82
 - update_result, 84
- * **platform**
 - get_platform_annotations, 49
 - get_platform_datasets, 50
 - get_platform_element_genes, 52
 - get_platforms_by_ids, 47
- * **taxon**
 - get_taxa, 56
- .getResultSets, 4
- .get_dataset_expression_for_genes, 5
- .get_dataset_expression_for_genes_in_taxon, 6
- .get_gene_differential_expression_values, 7
- .get_gene_differential_expression_values_in_taxon, 9
- accessField, 10
- attribute, 20, 23, 46, 48, 51, 53, 54, 58, 79
- blank_processor, 11
- checkBounds, 11
- encode, 12
- ExpressionSet, 30
- filter_properties, 8, 10, 12, 20, 22, 42, 48, 54
- forget_gemma_memoised, 5–8, 10, 13, 17, 19, 21, 23, 25–28, 30–36, 38–41, 43–46, 48, 50, 51, 53, 55–58, 61, 78, 80, 81
- gemma.R, 13
- gemma.R-package (gemma.R), 13
- gemma_call, 15
- gemma_kable, 15
- gemma_memoise, 16
- gemmaCache, 14
- gemmaPath, 14
- get_all_pages, 16
- get_annotation_children, 17
- get_annotation_parents, 18
- get_child_terms, 19
- get_dataset_annotations, 24
- get_dataset_differential_expression_analyses, 25, 39, 55, 64
- get_dataset_differential_expression_analyses(), 39
- get_dataset_expression, 27
- get_dataset_expression_for_genes, 28
- get_dataset_object, 13, 29
- get_dataset_platforms, 30
- get_dataset_processed_expression, 27, 31, 34, 36, 74
- get_dataset_publications, 32
- get_dataset_quantitation_types, 34, 35
- get_dataset_raw_expression, 34, 35, 74
- get_dataset_samples, 36, 60
- get_dataset_subset_groups, 37, 38
- get_dataset_subset_samples, 38
- get_datasets, 12, 20, 57, 78
- get_datasets_by_ids, 22
- get_differential_expression_values, 13, 26, 39, 55, 64, 66, 68

get_gene_differential_expression_values, 42
get_gene_go_terms, 43
get_gene_locations, 45
get_gene_probes, 46
get_genes, 40
get_platform_annotations, 13, 49
get_platform_datasets, 50
get_platform_element_genes, 52
get_platforms_by_ids, 12, 47
get_result_sets, 8, 43, 54, 54, 67
get_taxa, 56
get_taxa_by_ids, 56, 58, 79
get_taxon_datasets, 57

isEmpty, 60

kable, 15

make_design, 60
memoise, 61

nullCheck, 61

process_search, 77
processAnnotations, 62
processBibliographicReferenceValueObject, 62
processCharacteristicValueObject, 63
processDatasetResultSets, 63
processDatasets, 64
processDEA, 65
processDEcontrasts, 66
processDEMatrix, 67
processDifferentialExpressionAnalysisResultByGeneValueObject_tsv, 67
processDifferentialExpressionAnalysisResultSetValueObject, 68
processElements, 68
processExpressionMatrix, 69
processFile, 70
processGemmaArray, 70
processGeneLocation, 71
processGenes, 71
processGO, 72
processPlatforms, 73
processQuantitationTypeValueObject, 74
processResultSetFactors, 75
processSamples, 75
processSearchAnnotations, 76
processTaxon, 76

search_annotations, 77
search_datasets, 78
search_gemma, 81
set_gemma_user, 82
setGemmaPath, 82
subset_factorValues, 83
SummarizedExperiment, 30

update_result, 84

validateBoolean, 84
validateID, 85
validateLimit, 85
validateOptionalID, 86
validateOptionalQuery, 86
validateOptionalTaxon, 87
validatePositiveInteger, 87
validateQuery, 88
validateResultType, 88
validateSingleID, 89
validateSort, 89
validateTaxa, 90
validateTaxon, 90
validateURI, 91