

# Package ‘poem’

February 2, 2026

**Title** POpulation-based Evaluation Metrics

**Version** 1.3.0

## Description

This package provides a comprehensive set of external and internal evaluation metrics. It includes metrics for assessing partitions or fuzzy partitions derived from clustering results, as well as for evaluating subpopulation identification results within embeddings or graph representations. Additionally, it provides metrics for comparing spatial domain detection results against ground truth labels, and tools for visualizing spatial errors.

**BugReports** <https://github.com/RoseYuan/poem/issues>

**License** GPL (>= 3)

**URL** <https://roseyuan.github.io/poem/>

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Depends** R (>= 4.0)

**Imports** aricode, BiocNeighbors, BiocParallel, bluster, clevr, clue, cluster, elsa, fclust, igraph, Matrix, matrixStats, mclustcomp, methods, pdist, sp, spdep, stats, utils, SpatialExperiment, SummarizedExperiment

**Suggests** testthat (>= 3.0.0), BiocStyle, knitr, DT, dplyr, kableExtra, scico, cowplot, ggnetwork, ggplot2, tidyR, STextampleData

**VignetteBuilder** knitr

**biocViews** DimensionReduction, Clustering, GraphAndNetwork, Spatial, ATACSeq, SingleCell, RNASeq, Software, Visualization

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/poem>

**git\_branch** devel

**git\_last\_commit** e74dd69

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2026-02-01

**Author** Siyuan Luo [cre, aut] (ORCID: <<https://orcid.org/0009-0007-6404-3244>>),  
Pierre-Luc Germain [aut, ctb] (ORCID:  
<<https://orcid.org/0000-0003-3418-4218>>)

**Maintainer** Siyuan Luo <[roseluosy@gmail.com](mailto:roseluosy@gmail.com)>

## Contents

.check_duplicated_samples . . . . .	3
.compute_cluster_core_distance . . . . .	4
.compute_cross_dists . . . . .	4
.compute_mutual_reach_dists . . . . .	5
.compute_pair_to_pair_dists . . . . .	5
.convert_singleton_clusters_to_noise . . . . .	6
.fn_density_separation . . . . .	6
.fn_density_sparseness . . . . .	7
.get_internal_objects . . . . .	7
.get_submatrix . . . . .	8
CDbw . . . . .	8
CHAOS . . . . .	10
dbcv . . . . .	10
ELSA . . . . .	12
emb2knn . . . . .	13
emb2snn . . . . .	13
findSpatialKNN . . . . .	14
FMeasure . . . . .	15
fuzzyHardMetrics . . . . .	16
fuzzyHardMetrics2 . . . . .	18
fuzzyHardSpotConcordance . . . . .	19
fuzzyPartitionMetrics . . . . .	21
getEmbeddingClassMetrics . . . . .	22
getEmbeddingElementMetrics . . . . .	23
getEmbeddingGlobalMetrics . . . . .	24
getEmbeddingMetrics . . . . .	24
getFuzzyLabel . . . . .	26
getFuzzyPartitionElementMetrics . . . . .	26
getFuzzyPartitionMetrics . . . . .	28
getGraphClassMetrics . . . . .	30
getGraphElementMetrics . . . . .	32
getGraphMetrics . . . . .	33
getNeighboringPairConcordance . . . . .	35
getPairConcordance . . . . .	36
getPartitionClassMetrics . . . . .	37
getPartitionElementMetrics . . . . .	37

.check_duplicated_samples	3
getPartitionGlobalMetrics . . . . .	38
getPartitionMetrics . . . . .	39
getSpatialClassExternalMetrics . . . . .	41
getSpatialClassInternalMetrics . . . . .	42
getSpatialElementExternalMetrics . . . . .	43
getSpatialElementInternalMetrics . . . . .	44
getSpatialExternalMetrics . . . . .	44
getSpatialGlobalExternalMetrics . . . . .	47
getSpatialGlobalInternalMetrics . . . . .	48
getSpatialInternalMetrics . . . . .	49
knnComposition . . . . .	51
matchSets . . . . .	52
metric_info . . . . .	53
mockData . . . . .	53
nnWeightedAccuracy . . . . .	54
noisy_moon . . . . .	55
PAS . . . . .	55
setMatchingAccuracy . . . . .	56
silhouetteWidths . . . . .	56
spatialARI . . . . .	57
sp_toys . . . . .	59
toyExamples . . . . .	59
<b>Index</b>	<b>60</b>

---

.check\_duplicated\_samples  
*Check Duplicated Samples*

---

## Description

Checks for duplicated samples in matrix X.

## Usage

```
.check_duplicated_samples(X, threshold = 1e-09)
```

## Arguments

X	Numeric matrix of samples.
threshold	Numeric, the distance threshold to consider samples as duplicates.

## Value

None

---

**.compute\_cluster\_core\_distance**  
*Compute Cluster Core Distance*

---

### Description

Computes the core distance for each point in a cluster.

### Usage

`.compute_cluster_core_distance(dists, d)`

### Arguments

<code>dists</code>	Numeric matrix of distances.
<code>d</code>	Integer, the dimensionality.

### Value

Numeric vector of core distances for each point.

---

**.compute\_cross\_dists** *Compute Cross Distances*

---

### Description

Computes the cross distances between two sets of indices in matrix `X`.

### Usage

`.compute_cross_dists(X, inds_a, inds_b, distance)`

### Arguments

<code>X</code>	Numeric matrix of samples.
<code>inds_a</code>	Integer vector of indices for the first set.
<code>inds_b</code>	Integer vector of indices for the second set.
<code>distance</code>	String specifying the distance metric.

### Value

Numeric matrix of cross distances.

---

.compute\_mutual\_reach\_dists

*Compute Mutual Reachability Distances*

---

### Description

Computes the mutual reachability distances between points.

### Usage

.compute\_mutual\_reach\_dists(dists, d)

### Arguments

dists            Numeric matrix of distances.  
d                Float, the dimensionality.

### Value

A list containing core distances and mutual reachability distances.

---

.compute\_pair\_to\_pair\_dists

*Compute Pair to Pair Distances*

---

### Description

Compute the pairwise distances between points in matrix X.

### Usage

.compute\_pair\_to\_pair\_dists(X, distance = "euclidean")

### Arguments

X                Numeric matrix.  
distance        String specifying the metric to compute the distances.

### Value

Numeric matrix of pairwise distances with self-distances set to Inf.

---

.convert\_singleton\_clusters\_to\_noise  
*Convert Singleton Clusters to Noise*

---

**Description**

Converts clusters containing a single instance to noise.

**Usage**

```
.convert_singleton_clusters_to_noise(labels, noise_id)
```

**Arguments**

labels	Integer vector of cluster IDs.
noise_id	Integer, the ID for noise.

**Value**

Integer vector with singleton clusters converted to noise.

---

.fn\_density\_separation  
*Density Separation of a Pair of Clusters*

---

**Description**

Computes the density separation between two clusters.

**Usage**

```
.fn_density_separation(  

  cls_i,  

  cls_j,  

  dists,  

  internal_core_dists_i,  

  internal_core_dists_j  

)
```

**Arguments**

cls_i	Integer, first cluster index.
cls_j	Integer, second cluster index.
dists	Numeric matrix of distances.
internal_core_dists_i	Numeric vector of core distances for cluster i.
internal_core_dists_j	Numeric vector of core distances for cluster j.

### Value

A list containing the cluster indices and their density separation.

---

.fn\_density\_sparseness

*Density Sparseness of a Cluster*

---

### Description

Computes the density sparseness for a given cluster.

### Usage

```
.fn_density_sparseness(cls_inds, dists, d, use_igraph_mst)
```

### Arguments

cls_inds	Integer vector of cluster indices.
dists	Numeric matrix of distances.
d	Integer, the dimensionality.
use_igraph_mst	Logical flag to use MST implementation in igraph. Currently only mst from igraph is implemented.

### Value

A list containing the density sparseness, internal core distances, and internal node indices.

---

.get\_internal\_objects *Get Internal Objects*

---

### Description

Computes the internal nodes and edges using Minimum Spanning Tree.

### Usage

```
.get_internal_objects(mutual_reach_dists, use_igraph_mst = TRUE)
```

### Arguments

mutual_reach_dists	Numeric matrix representing mutual reachability distances.
use_igraph_mst	Logical flag to use MST implementation in igraph. Currently only mst from igraph is implemented.

**Value**

A list containing the indices of internal nodes and their edge weights.

---

.get_submatrix	<i>Get Sub matrix</i>
----------------	-----------------------

---

**Description**

Extract a sub matrix from a matrix based on optional row and column indices.

**Usage**

```
.get_submatrix(arr, inds_a = NULL, inds_b = NULL)
```

**Arguments**

arr	Numeric matrix.
inds_a	Optional integer vector for row indices.
inds_b	Optional integer vector for column indices.

**Value**

Numeric matrix representing the sub matrix.

---

CDBW	<i>Calculate CDBW index</i>
------	-----------------------------

---

**Description**

Computes the CDBW-index (Halkidi and Vazirgiannis 2008; Halkidi, Vazirgiannis and Hennig, 2015). This function is directly copied from the fpc CRAN package and was written by Christian Hennig. It is included here to reduce the package dependencies (since fpc has a few not-so-light dependencies that aren't required here).

**Usage**

```
CDBW(
  x,
  labels,
  r = 10,
  s = seq(0.1, 0.8, by = 0.1),
  clusterstdev = TRUE,
  trace = FALSE
)
```

## Arguments

x	Something that can be coerced into a numerical matrix, with elements as rows.
labels	A vector of integers with length = <code>nrow(x)</code> indicating the cluster for each observation.
r	Number of cluster border representatives.
s	Vector of shrinking factors.
clusterstdev	Logical. If TRUE, the neighborhood radius for intra-cluster density is the within-cluster estimated squared distance from the mean of the cluster; otherwise it is the average of these over all clusters.
trace	Logical; whether to print processing info.

## Value

A vector with the following values (see refs for details):

cdbw	value of CDbw index (the higher the better).
cohesion	cohesion.
compactness	compactness.
sep	separation.

## Author(s)

Christian Hennig

## References

Halkidi, M. and Vazirgiannis, M. (2008) A density-based cluster validity approach using multi-representatives. *Pattern Recognition Letters* 29, 773-786.

Halkidi, M., Vazirgiannis, M. and Hennig, C. (2015) Method-independent indices for cluster validation. In C. Hennig, M. Meila, F. Murtagh, R. Rocci (eds.) *Handbook of Cluster Analysis*, CRC Press/Taylor & Francis, Boca Raton.

## Examples

```
d1 <- mockData()
CDbw(d1[,seq_len(2)], d1[,3])
```

CHAOS

*Calculate CHAOS score***Description**

CHAOS score measures the clustering performance by calculating the mean length of the graph edges in the 1-nearest neighbor (1NN) graph for each cluster, averaged across clusters. Lower CHAOS score indicates better spatial domain clustering performance.

**Usage**

```
CHAOS(labels, location, BNPARAM = NULL)
```

**Arguments**

labels	Cluster labels.
location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
BNPARAM	BNPARAM object passed to <a href="#">findKNN</a> specifying the kNN approximation method to use. Defaults to exact for small datasets, and Annoy for larger ones.

**Value**

A numeric value for CHAOS score.

**Examples**

```
data(sp_toys)
data <- sp_toys
CHAOS(data$label, data[,c("x", "y")])
CHAOS(data$p1, data[,c("x", "y")])
CHAOS(data$p2, data[,c("x", "y")])
```

dbcv

*Calculate DBCV Metric***Description**

Compute the DBCV (Density-Based Clustering Validation) metric.

**Usage**

```
dbcv(
  X,
  labels,
  distance = "euclidean",
  noise_id = -1,
  check_duplicates = FALSE,
  use_igraph_mst = TRUE,
  BPPARAM = BiocParallel::SerialParam(),
  ...
)
```

**Arguments**

X	Numeric matrix of samples.
labels	Integer vector of cluster IDs.
distance	String specifying the distance metric. "squeuclidean", or possible method in stats::dist(). By default "euclidean".
noise_id	Integer, the cluster ID in y for noise (default -1).
check_duplicates	Logical flag to check for duplicate samples.
use_igraph_mst	Logical flag to use igraph's MST implementation. Currently only mst from igraph is implemented.
BPPARAM	BiocParallel params for multithreading (default none)
...	Ignored

**Details**

This implementation will not fully reproduce the results of other existing implementations (e.g. <https://github.com/FelSiq/DBCV>) due to the different algorithms used for computing the Minimum Spanning Tree.

**Value**

A list:

vcs	Numeric vector of validity index for each cluster.
dbcv	Numeric value representing the overall DBCV metric.

**References**

Davoud Moulavi, et al. 2014; 10.1137/1.9781611973440.96.

## Examples

```
data(noisy_moon)
data <- noisy_moon
dbcv(data[, c("x", "y")], data$kmeans_label)
dbcv(data[, c("x", "y")], data$hdbSCAN_label)
```

---

ELSA

*Calculate ELSA scores*

---

## Description

Calculating the Entropy-based Local indicator of Spatial Association (ELSA) scores, which consist of Ea, Ec and the overall ELSA.

## Usage

```
ELSA(labels, location, k = 10)
```

## Arguments

labels	Cluster labels.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	Number of nearest neighbors.

## Value

A dataframe containing the Ea, Ec and ELSA for all samples in the dataset.

## References

Naimi, Babak, et al., 2019; 10.1016/j.spasta.2018.10.001

## Examples

```
data(sp_toys)
data <- sp_toys
ELSA(data$label, data[,c("x", "y")], k=6)
ELSA(data$p1, data[,c("x", "y")], k=6)
ELSA(data$p2, data[,c("x", "y")], k=6)
```

---

emb2knn*Computes k nearest neighbors from embedding*

---

## Description

Computes k nearest neighbors from embedding.

## Usage

```
emb2knn(x, k, BNPARAM = NULL)
```

## Arguments

x A numeric matrix (with features as columns and items as rows) from which nearest neighbors will be computed.

k The number of nearest neighbors.

BNPARAM A BiocNeighbors parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

## Value

A knn list.

## Examples

```
d1 <- mockData()  
emb2knn(as.matrix(d1[,seq_len(2)]),k=5)
```

---

emb2snn*Computes shared nearest neighbors from embedding*

---

## Description

computes shared nearest neighbors from embedding.

## Usage

```
emb2snn(x, k, type = "rank", BNPARAM = NULL)
```

**Arguments**

x	A numeric matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
k	The number of nearest neighbors.
type	A string specifying the type of weighting scheme to use for shared neighbors. Possible choices include "rank", "number", and "jaccard". See type in <a href="#">bluster::neighborsToSNNGraph</a> for details.
BNPARAM	A BiocNeighbors parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

**Value**

An igraph object.

**Examples**

```
d1 <- mockData()
emb2snn(as.matrix(d1[, seq_len(2)]), k=5)
```

---

**findSpatialKNN**

*Find the k nearest spatial neighbors*

---

**Description**

For a given dataset, find the k nearest neighbors for each object based on their spatial locations, with the option of handling ties.

**Usage**

```
findSpatialKNN(
  location,
  k,
  keep_ties = TRUE,
  useMedianDist = FALSE,
  BNPARAM = NULL
)
```

**Arguments**

location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
k	The number of nearest neighbors to look at.
keep_ties	A Boolean indicating if ties are counted once or not. If TRUE, neighbors of the same distances will be included even if it means returning more than k neighbors.

useMedianDist	Use the median distance of the k nearest neighbor as maximum distance to be included. Ignored if <code>keep_ties=FALSE</code> .
BNPARAM	BNPARAM object passed to <a href="#">findKNN</a> specifying the kNN approximation method to use. Defaults to exact for small datasets, and Annoy for larger ones.

### Value

A list of indices.

### Examples

```
data(sp_toys)
data <- sp_toys
findSpatialKNN(data[,c("x", "y")], k=6)
```

---

## FMeasure

*Calculate F measure*

---

### Description

Compute the F measure between two clustering results. This is directly copied from the package `FlowSOM`.

### Usage

```
FMeasure(true, pred, silent = TRUE)
```

### Arguments

true	Array containing real cluster labels for each sample
pred	Array containing predicted cluster labels for each sample
silent	Logical, if FALSE, print some information about precision and recall

### Value

F measure score

---

fuzzyHardMetrics*Compute fuzzy-hard versions of pair-sorting partition metrics*

---

**Description**

Computes fuzzy-hard versions of pair-sorting partition metrics to compare a hard clustering with both a fuzzy and hard truth. This was especially designed for cases where the fuzzy truth represents an uncertainty of a hard truth. Briefly put, the maximum of the pair concordance between the clustering and either the hard or the fuzzy truth is used, and the hard truth is used to compute completeness. See [fuzzyPartitionMetrics](#) for the more standard implementation of the metrics.

**Usage**

```
fuzzyHardMetrics(
  hardTrue,
  fuzzyTrue,
  hardPred,
  nperms = NULL,
  returnElementPairAccuracy = FALSE,
  lowMemory = NULL,
  verbose = TRUE,
  BPPARAM = BiocParallel::SerialParam()
)
```

**Arguments**

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels. Must have the same length as hardPred.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue. Also note that the columns of fuzzyTrue should be in the order of the levels (or integer values) of hardTrue.
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
lowMemory	Logical; whether to use the slower, low-memory algorithm. By default this is enabled if the projected memory usage is higher than ~2GB.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
BPPARAM	BiocParallel params for multithreading (default none)

## Value

A list of metrics:

NDC	Hullermeier's NDC (fuzzy rand index)
ACI	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
fuzzyWH	Fuzzy Wallace Homogeneity index
fuzzyWC	Fuzzy Wallace Completeness index
fuzzyAWH	Adjusted fuzzy Wallace Homogeneity index
fuzzyAWC	Adjusted fuzzy Wallace Completeness index

## Author(s)

Pierre-Luc Germain

## References

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

## See Also

[fuzzyPartitionMetrics\(\)](#).

## Examples

```
# generate a fuzzy truth:  
fuzzyTrue <- matrix(c(  
  0.95, 0.025, 0.025,  
  0.98, 0.01, 0.01,  
  0.96, 0.02, 0.02,  
  0.95, 0.04, 0.01,  
  0.95, 0.01, 0.04,  
  0.99, 0.005, 0.005,  
  0.025, 0.95, 0.025,  
  0.97, 0.02, 0.01,  
  0.025, 0.025, 0.95),  
  ncol = 3, byrow=TRUE)  
# a hard truth:  
hardTrue <- apply(fuzzyTrue, 1, FUN=which.max)  
# some predicted labels:  
hardPred <- c(1,1,1,1,1,1,2,2,2)  
fuzzyHardMetrics(hardTrue, fuzzyTrue, hardPred, nperms=3)
```

---

fuzzyHardMetrics2	<i>Compute fuzzy-hard metrics with lower memory requirement</i>
-------------------	---

---

## Description

This is a slightly slower, but low-memory version of [fuzzyHardMetrics](#).

## Usage

```
fuzzyHardMetrics2(
  hardTrue,
  fuzzyTrue,
  hardPred,
  nperms = 10,
  returnElementPairAccuracy = FALSE,
  verbose = TRUE,
  BPPARAM = BiocParallel::SerialParam()
)
```

## Arguments

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels. Must have the same length as hardPred.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue. Also note that the columns of fuzzyTrue should be in the order of the levels (or integer values) of hardTrue.
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
BPPARAM	BiocParallel params for multithreading (default none)

## Value

A list of metrics:

ND <sub>C</sub>	Hullermeier's NDC (fuzzy rand index)
-----------------	--------------------------------------

ACI	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
fuzzyWH	Fuzzy Wallace Homogeneity index
fuzzyWC	Fuzzy Wallace Completeness index
fuzzyAWH	Adjusted fuzzy Wallace Homogeneity index
fuzzyAWC	Adjusted fuzzy Wallace Completeness index

### Author(s)

Pierre-Luc Germain

### References

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
 D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

### See Also

[fuzzyHardMetrics\(\)](#)

### Examples

```
# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue, 1, FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
pom:::fuzzyHardMetrics2(hardTrue, fuzzyTrue, hardPred, nperms=3)
```

---

### fuzzyHardSpotConcordance

*Per-element maximal concordance between a hard and a fuzzy partition*

---

### Description

Per-element maximal concordance between a hard clustering and hard and fuzzy ground truth labels.

**Usage**

```
fuzzyHardSpotConcordance(
  hardTrue,
  fuzzyTrue,
  hardPred,
  useNegatives = TRUE,
  verbose = TRUE
)
```

**Arguments**

hardTrue	A vector of true cluster labels
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue.
hardPred	A vector of predicted cluster labels
useNegatives	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
verbose	Logical; whether to print expected memory usage for large datasets.

**Value**

A numeric vector of concordance scores for each element of hardPred

**Examples**

```
# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue, 1, FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
fuzzyHardSpotConcordance(hardTrue, fuzzyTrue, hardPred)
```

---

**fuzzyPartitionMetrics** *Compute fuzzy-fuzzy versions of pair-sorting partition metrics*

---

## Description

Computes fuzzy versions of pair-sorting partition metrics. This is largely based on the permutation-based implementation by Antonio D'Ambrosio from the ConsRankC1ass package, modified to also compute the fuzzy versions of the adjusted Wallace indices, implement multithreading, and adjust the number of permutations according to their variability.

## Usage

```
fuzzyPartitionMetrics(
  P,
  Q,
  computeWallace = TRUE,
  nperms = NULL,
  verbose = TRUE,
  returnElementPairAccuracy = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  tnorm = c("product", "min", "lukasiewicz")
)
```

## Arguments

P	A object coercible to a numeric matrix with membership probability of elements (rows) in ground-truth classes (columns).
Q	A object coercible to a numeric matrix with membership probability of elements (rows) in predicted clusters (columns). Must have the same number of rows as P.
computeWallace	Logical; whether to compute the individual fuzzy versions of the Wallace indices (increases running time).
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
BPPARAM	BiocParallel params for multithreading (default none)
tnorm	Which type of t-norm operation to use for class membership of pairs (either product, min, or lukasiewicz) when calculating the Wallace indices. Does not influence the NDC/ACI metrics.

**Value**

When `returnElementPairAccuracy` is FALSE, return a list of metrics:

<code>NDC</code>	Hullermeier's NDC (fuzzy rand index)
<code>ACI</code>	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
<code>fuzzyWH</code>	Fuzzy Wallace Homogeneity index
<code>fuzzyWC</code>	Fuzzy Wallace Completeness index
<code>fuzzyAWH</code>	Adjusted fuzzy Wallace Homogeneity index
<code>fuzzyAWC</code>	Adjusted fuzzy Wallace Completeness index

**Author(s)**

Pierre-Luc Germain

**References**

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
 D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

**Examples**

```
# generate fuzzy partitions:
```

---

```
getEmbeddingClassMetrics
  getEmbeddingClassMetrics
```

---

**Description**

Computes class-level, embedding-based metrics.

**Usage**

```
getEmbeddingClassMetrics(
  x,
  labels,
  metrics = c("meanSW", "minSW", "pnSW", "dbcv"),
  distance = "euclidean",
  ...
)
```

**Arguments**

- x A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
- labels A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
- metrics The metrics to compute.
- distance The distance metric to use (default euclidean).
- ... Optional arguments. See details.

**Value**

A data.frame of metrics for each node/element of x.

**getEmbeddingElementMetrics**  
*getEmbeddingElementMetrics*

**Description**

Computes element-level, embedding-based metrics.

**Usage**

```
getEmbeddingElementMetrics(
  x,
  labels,
  metrics = c("SW"),
  distance = "euclidean",
  ...
)
```

**Arguments**

- x A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
- labels A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
- metrics The metrics to compute. Currently, only the silhouette width is supported at the node-level.
- distance The distance metric to use (default euclidean).
- ... Optional arguments. See details.

**Value**

A data.frame of metrics for each node/element of x.

---

getEmbeddingGlobalMetrics  
*getEmbeddingGlobalMetrics*

---

## Description

Computes dataset-level, embedding-based metrics.

## Usage

```
getEmbeddingGlobalMetrics(  

  x,  

  labels,  

  metrics = c("meanSW", "meanClassSW", "pnSW", "minClassSW", "cdbw", "cohesion",  

    "compactness", "sep", "dbcv"),  

  distance = "euclidean",  

  ...  

)
```

## Arguments

x	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
labels	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute.
distance	The distance metric to use (default euclidean).
...	Optional arguments. See details.

## Value

A data.frame (with 1 row) of metrics.

---

getEmbeddingMetrics    *Compute embedding-based metrics*

---

## Description

Computes embedding-based metrics for the specified level.

## Usage

```
getEmbeddingMetrics(
  x,
  labels,
  metrics = NULL,
  distance = "euclidean",
  level = "class",
  ...
)
```

## Arguments

<code>x</code>	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
<code>labels</code>	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>metrics</code>	The metrics to compute. See details.
<code>distance</code>	The distance metric to use (default euclidean).
<code>level</code>	The level to calculate the metrics. Options include "element", "class" and "dataset".
...	Optional arguments. See details.

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are: "SW".
- If `level = "class"`, the allowed `metrics` are: "meanSW", "minSW", "pnSW", "dbcv".
- If `level = "dataset"`, the allowed `metrics` are: "meanSW", "meanClassSW", "pnSW", "minClassSW", "cdbw", "cohesion", "compactness", "sep", "dbcv".

The function(s) that the optional arguments ... passed to depend on the value of `level`:

- If `level = "element"`, optional arguments are passed to `stats::dist()`.
- If `level = "class"`, optional arguments are passed to `dbcv()`.
- If `level = "dataset"`, optional arguments are passed to `dbcv()` or `Cdbw()`.

## Value

A data.frame of metrics.

## Examples

```
d1 <- mockData()
getEmbeddingMetrics(d1[,seq_len(2)], labels=d1$class,
metrics=c("meanSW", "minSW", "pnSW", "dbcv"), level="class")
```

---

getFuzzyLabel	<i>Get fuzzy representation of labels</i>
---------------	---

---

## Description

Get fuzzy representation of labels according to the spatial neighborhood label composition.

## Usage

```
getFuzzyLabel(labels, location, k = 6, alpha = 0.5, ...)
```

## Arguments

labels	An anomic vector of cluster labels
location	A matrix or data.frame of coordinates
k	The wished number of nearest neighbors
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
...	Passed to <a href="#">findSpatialKNN()</a> .

## Value

A matrix of fuzzy memberships.

## Examples

```
data(sp_toys)
data <- sp_toys
getFuzzyLabel(data$label, data[,c("x", "y")], k=6)
```

---

getFuzzyPartitionElementMetrics	<i>getFuzzyPartitionElementMetrics</i>
---------------------------------	--

---

## Description

Computes a selection of external fuzzy clustering evaluation metrics at the element level.

**Usage**

```
getFuzzyPartitionElementMetrics(
  hardTrue = NULL,
  fuzzyTrue = NULL,
  hardPred = NULL,
  fuzzyPred = NULL,
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  metrics = c("fuzzySPC"),
  useNegatives = TRUE,
  verbose = TRUE,
  usePairs = TRUE
)
```

**Arguments**

hardTrue	A vector of true cluster labels
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue.
hardPred	A vector of predicted cluster labels
fuzzyPred	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
fuzzy_true	Logical; whether the truth is fuzzy.
fuzzy_pred	Logical; whether the prediction is fuzzy.
metrics	The metrics to compute. Currently only "fuzzySPC" is included at the element level.
useNegatives	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
verbose	Logical; whether to print expected memory usage for large datasets.
usePairs	Logical; whether to compute over pairs instead of elements. Only useful when fuzzy_true=TRUE and fuzzy_pred=FALSE.

**Value**

A datafram of metric values.

---

**getFuzzyPartitionMetrics**  
*Compute external metrics for fuzzy clusterings*

---

## Description

Computes a selection of external fuzzy clustering evaluation metrics.

## Usage

```
getFuzzyPartitionMetrics(
  hardTrue = NULL,
  fuzzyTrue = NULL,
  hardPred = NULL,
  fuzzyPred = NULL,
  metrics = c("fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC"),
  level = "class",
  nperms = NULL,
  verbose = TRUE,
  BPPARAM = BiocParallel::SerialParam(),
  useNegatives = TRUE,
  usePairs = NULL,
  lowMemory = NULL,
  ...
)
```

## Arguments

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
fuzzyPred	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
metrics	The metrics to compute. See details.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).

BPPARAM	BiocParallel params for multithreading (default none)
useNegatives	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
usePairs	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
lowMemory	Logical, whether to use a low memory mode. This is only useful when <code>hardTrue</code> and <code>fuzzyPred</code> is used. If TRUE, the function will compute the metrics in a low memory mode, which is slower but uses less memory. If FALSE, the function will compute the metrics in a high memory mode, which is faster but uses more memory. By default it is set automatically based on the size of the input data. See <code>fuzzyHardMetrics</code> .
...	Optional arguments for <code>fuzzyPartitionMetrics</code> : <code>tnorm</code> . Only useful when <code>fuzzyTrue</code> and <code>fuzzyPred</code> is used.

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are: "fuzzySPC".
- If `level = "class"`, the allowed `metrics` are: "fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC".
- If `level = "dataset"`, the allowed `metrics` are: "fuzzyRI", "fuzzyARI", "fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC".

## Value

A data frame of metric results.

## Examples

```
# generate fuzzy partitions:
m1 <- matrix(c(0.95, 0.025, 0.025,
               0.98, 0.01, 0.01,
               0.96, 0.02, 0.02,
               0.95, 0.04, 0.01,
               0.95, 0.01, 0.04,
               0.99, 0.005, 0.005,
               0.025, 0.95, 0.025,
               0.97, 0.02, 0.01,
               0.025, 0.025, 0.95),
               ncol = 3, byrow=TRUE)
m2 <- matrix(c(0.95, 0.025, 0.025,
               0.98, 0.01, 0.01,
               0.96, 0.02, 0.02,
               0.025, 0.95, 0.025,
               0.02, 0.96, 0.02,
               0.01, 0.98, 0.01,
               0.05, 0.05, 0.95,
               0.02, 0.02, 0.96,
```

```

  0.01, 0.01, 0.98),
  ncol = 3, byrow=TRUE)
colnames(m1) <- colnames(m2) <- LETTERS[seq_len(3)]
getFuzzyPartitionMetrics(fuzzyTrue=m1, fuzzyPred=m2, level="class")

# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue, 1, FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,2,2,2)
getFuzzyPartitionMetrics(hardPred=hardPred, hardTrue=hardTrue,
fuzzyTrue=fuzzyTrue, nperms=3, level="class")
getFuzzyPartitionMetrics(hardTrue=hardPred, hardPred=hardTrue,
fuzzyPred=fuzzyTrue, nperms=3, level="class")

```

---

getGraphClassMetrics *getGraphClassMetrics*

---

## Description

Computes a selection of supervised graph evaluation metrics using ground truth class labels. The metrics are reported (as average) per class.

## Usage

```

getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

## S4 method for signature 'list'
getGraphClassMetrics(x, labels, metrics, directed = NULL, k = NULL, ...)

## S4 method for signature 'data.frame'
getGraphClassMetrics(

```

```

  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)

## S4 method for signature 'matrix'
getGraphClassMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)

## S4 method for signature 'igraph'
getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

## S4 method for signature 'dist'
getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

```

## Arguments

- x** Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
- labels** Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of x.
- metrics** The metrics to compute. See details.
- directed** Logical; whether to compute the metrics in a directed fashion. If left to NULL, conventional choices will be made per metric (adhesion, cohesion, PWC AMSP

	undirected, others directed).
...	Optional arguments for <code>emb2knn()</code> or <code>emb2snn()</code> .
k	The number of nearest neighbors to compute and/or use. Can be omitted if x is a graph or list of nearest neighbors.
shared	Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if x is not an embedding or dist object.

**Value**

A data.frame of metrics for each class.

---

**getGraphElementMetrics**  
*getGraphElementMetrics*

---

**Description**

Computes a selection of supervised graph evaluation metrics using ground truth class labels. The metrics are reported (as average) per node/element.

**Usage**

```
getGraphElementMetrics(x, labels, directed = NULL, ...)

## S4 method for signature 'list'
getGraphElementMetrics(x, labels, metrics, directed = NULL, k = NULL, ...)

## S4 method for signature 'data.frame'
getGraphElementMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)

## S4 method for signature 'matrix'
getGraphElementMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
```

```

  ...
)

## S4 method for signature 'igraph'
getGraphElementMetrics(x, labels, directed = NULL, ...)

## S4 method for signature 'dist'
getGraphElementMetrics(x, labels, directed = NULL, ...)

```

### Arguments

<code>x</code>	Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
<code>labels</code>	Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of <code>x</code> .
<code>directed</code>	Logical; whether to compute the metrics in a directed fashion. If left to <code>NULL</code> , conventional choices will be made per metric (adhesion, cohesion, PWC AMSP undirected, others directed).
<code>...</code>	Optional arguments for <code>emb2knn()</code> or <code>emb2snn()</code> .
<code>metrics</code>	The metrics to compute. See details.
<code>k</code>	The number of nearest neighbors to compute and/or use. Can be omitted if <code>x</code> is a graph or list of nearest neighbors.
<code>shared</code>	Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if <code>x</code> is not an embedding or dist object.

### Value

A data.frame of metrics for each node/element of `x`.

---

<code>getGraphMetrics</code>	<i>Compute graph-based metrics</i>
------------------------------	------------------------------------

---

### Description

Computes a selection of graph evaluation metrics using class labels.

### Usage

```
getGraphMetrics(
  x,
  labels,
  metrics = NULL,
  directed = NULL,
  k = 10,
```

```

shared = FALSE,
level = "class",
...
)

```

## Arguments

<code>x</code>	Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
<code>labels</code>	Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of <code>x</code> .
<code>metrics</code>	The metrics to compute. See details.
<code>directed</code>	Logical; whether to compute the metrics in a directed fashion. If left to NULL, conventional choices will be made per metric (adhesion, cohesion, PWC AMSP undirected, others directed).
<code>k</code>	The number of nearest neighbors to compute and/or use. Can be omitted if <code>x</code> is a graph or list of nearest neighbors.
<code>shared</code>	Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if <code>x</code> is not an embedding or dist object.
<code>level</code>	The level to calculate the metrics. Options include "element", "class" and "dataset".
<code>...</code>	Optional arguments for <code>emb2knn()</code> or <code>emb2snn()</code> .

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are: "SI", "ISI", "NP", "NCE" (see below for details).
- If `level = "class"`, the allowed `metrics` are:
  - "SI": Simpson's Index.
  - "ISI": Inverse Simpson's Index
  - "NP": Neighborhood Purity
  - "AMSP": Adjusted Mean Shortest Path
  - "PWC": Proportion of Weakly Connected
  - "NCE": Neighborhood Class Enrichment
  - "adhesion": adhesion of a graph, is the minimum number of nodes that must be removed to split a graph.
  - "cohesion": cohesion of a graph, is the minimum number of edges that must be removed to split a graph.
- If `level = "dataset"`, the allowed `metrics` are: "SI", "ISI", "NP", "AMSP", "PWC", "NCE", "adhesion", "cohesion".

**Value**

A data.frame of metrics.

**Examples**

```
d1 <- mockData()
getGraphMetrics(d1[, seq_len(2)], labels=d1$class, level="class")
```

**getNeighboringPairConcordance**

*Per-element local concordance between a clustering and a ground truth*

**Description**

Per-element local concordance between a clustering and a ground truth

**Usage**

```
getNeighboringPairConcordance(
  true,
  pred,
  location,
  k = 20L,
  useNegatives = FALSE,
  distWeights = TRUE,
  BNPARAM = NULL
)
```

**Arguments**

<code>true</code>	A vector of true class labels
<code>pred</code>	A vector of predicted clusters
<code>location</code>	A matrix or data.frame with spatial dimensions as columns. Alternatively, a nearest neighbor object as produced by <a href="#">findKNN</a> .
<code>k</code>	Approximate number of nearest neighbors to consider
<code>useNegatives</code>	Logical; whether to include the concordance of negative pairs in the score (default FALSE).
<code>distWeights</code>	Logical; whether to weight concordance by distance (default TRUE).
<code>BNPARAM</code>	A BiocNeighbors parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

**Value**

A vector of concordance scores

## Examples

```
data(sp_toys)
data <- sp_toys
getNeighboringPairConcordance(data$label, data$p1, data[,c("x", "y")], k=6)
```

---

getPairConcordance	<i>Per-element pair concordance score</i>
--------------------	---

---

## Description

Per-element pair concordance between a clustering and a ground truth. Note that by default, negative pairs (i.e. that are split in both the predicted and true groupings) are not counted. To count it (as in the standard Rand Index), use `useNegatives=TRUE`.

## Usage

```
getPairConcordance(
  true,
  pred,
  usePairs = TRUE,
  useNegatives = FALSE,
  adjust = FALSE
)
```

## Arguments

<code>true</code>	A vector of true class labels
<code>pred</code>	A vector of predicted clusters
<code>usePairs</code>	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
<code>useNegatives</code>	Logical; whether to include the consistency of negative pairs in the score (default FALSE).
<code>adjust</code>	Logical; whether to adjust for chance. Only implemented for <code>useNegatives=FALSE</code> (doesn't make sense on a element-level otherwise).

## Value

A vector of concordance scores

---

```
getPartitionClassMetrics
  getPartitionClassMetrics
```

---

## Description

Computes a selection of external evaluation metrics for partition. The metrics are reported per class.

## Usage

```
getPartitionClassMetrics(
  true,
  pred,
  metrics = c("WC", "WH", "AWC", "AWH", "FM")
)
```

## Arguments

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. If omitted, main metrics will be computed.

## Value

A data frame of metrics.

---

```
getPartitionElementMetrics
  getPartitionElementMetrics
```

---

## Description

Computes a selection of external evaluation metrics for partition. The metrics are reported per element.

## Usage

```
getPartitionElementMetrics(
  true,
  pred,
  metrics = c("SPC"),
  usePairs = TRUE,
  useNegatives = TRUE
)
```

**Arguments**

true	A vector of true class labels
pred	A vector of predicted clusters
metrics	The metrics to compute.
usePairs	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
useNegatives	Logical; whether to include the consistency of negative pairs in the score (default FALSE).

**Value**

A dataframe of metrics.

---

**getPartitionGlobalMetrics**  
*getPartitionGlobalMetrics*

---

**Description**

Computes a selection of external evaluation metrics for partition. The metrics are reported per dataset.

**Usage**

```
getPartitionGlobalMetrics(
  true,
  pred,
  metrics = c("RI", "WC", "WH", "ARI", "NCR", "AWC", "AWH", "MI", "AMI", "VI", "EH",
             "EC", "VM", "FM"),
  ...
)
```

**Arguments**

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. If omitted, main metrics will be computed. See below for more details.
...	Optional arguments for MI, VI, or VM. See <a href="#">clevr::mutual_info()</a> , <a href="#">clevr::variation_info()</a> and <a href="#">clevr::v_measure()</a> for more details.

**Value**

A dataframe of metric results. Possible metrics are:

RI	Rand Index
WC	Wallace Completeness
WH	Wallace Homogeneity
ARI	Adjusted Rand Index
AWC	Adjusted Wallace Completeness
AWH	Adjusted Wallace Homogeneity
NCR	Normalized class size Rand index
MI	Mutual Information
AMI	Adjusted Mutual Information
VI	Variation of Information
EH	(Entropy-based) Homogeneity
EC	(Entropy-based) Completeness
VM	V-measure
FM	F-measure/weighted average F1 score
VDM	Van Dongen Measure
MHM	Meila-Heckerman Measure
MMM	Maximum-Match Measure
Mirkin	Mirkin Metric
Accuracy	Set Matching Accuracy

---

getPartitionMetrics *Compute partition-based metrics*

---

**Description**

Computes a selection of external evaluation metrics for partition.

**Usage**

```
getPartitionMetrics(true, pred, metrics = NULL, level = "class", ...)
```

**Arguments**

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. If omitted, main metrics will be computed. See details.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
...	Optional arguments for MI, VI, or VM. See <a href="#">clevr::mutual_info()</a> , <a href="#">clevr::variation_info()</a> and <a href="#">clevr::v_measure()</a> for more details.

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are:
  - "SPC": Spot-wise Pair Concordance.
  - "ASPC": Adjusted Spot-wise Pair Concordance.
- If `level = "class"`, the allowed `metrics` are: "WC", "WH", "AWC", "AWH", "FM" (see below for details).
- If `level = "dataset"`, the allowed `metrics` are:
  - "RI": Rand Index
  - "WC": Wallace Completeness
  - "WH": Wallace Homogeneity
  - "ARI": Adjusted Rand Index
  - "AWC": Adjusted Wallace Completeness
  - "AWH": Adjusted Wallace Homogeneity
  - "NCR": Normalized class size Rand index
  - "MI": Mutual Information
  - "AMI": Adjusted Mutual Information
  - "VI": Variation of Information
  - "EH": (Entropy-based) Homogeneity
  - "EC": (Entropy-based) Completeness
  - "VM": V-measure
  - "FM": F-measure/weighted average F1 score
  - "VDM": Van Dongen Measure
  - "MHM": Meila-Heckerman Measure
  - "MMM": Maximum-Match Measure
  - "Mirkin": Mirkin Metric
  - "Accuracy": Set Matching Accuracy

## Value

A data.frame of metrics.

## Examples

```
true <- rep(LETTERS[seq_len(3)], each=10)
pred <- c(rep("A", 8), rep("B", 9), rep("C", 3), rep("D", 10))
getPartitionMetrics(true, pred, level="class")
getPartitionMetrics(true, pred, level="dataset")
```

---

```
getSpatialClassExternalMetrics
```

*Compute class-level external evaluation metrics for spatially-resolved data*

---

## Description

Computes a selection of external clustering evaluation metrics for spatial data at the class/cluster level.

## Usage

```
getSpatialClassExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("nsWH", "nsAWH", "nsWC", "nsAWC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  lowMemory = NULL,
  ...
)
```

## Arguments

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
location	A matrix or data.frame of coordinates
k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics.
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
metrics	a vector of metric names to compute.
fuzzy_true	Logical; whether to compute fuzzy class memberships for true.
fuzzy_pred	Logical; whether to compute fuzzy class memberships for pred.
lowMemory	Logical, whether to use a low memory mode. This is only useful when hardTrue and fuzzyPred is used. If TRUE, the function will compute the metrics in a low

memory mode, which is slower but uses less memory. If FALSE, the function will compute the metrics in a high memory mode, which is faster but uses more memory. By default it is set automatically based on the size of the input data. See [fuzzyHardMetrics](#).

... Optional params for [fuzzyPartitionMetrics](#) or [findSpatialKNN](#).

## Value

A data.frame of metrics.

---

`getSpatialClassInternalMetrics`

*Compute class-level internal evaluation metrics for spatially-resolved data*

---

## Description

Computes a selection of internal clustering evaluation metrics for spatial data for each class.

## Usage

```
getSpatialClassInternalMetrics(
  labels,
  location,
  k = 6,
  metrics = c("CHAOS", "PAS", "ELSA"),
  ...
)
```

## Arguments

<code>labels</code>	A vector containing the labels to be evaluated.
<code>location</code>	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
<code>k</code>	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
<code>metrics</code>	Possible metrics: "CHAOS", "PAS" and "ELSA".
...	Optional params for <a href="#">PAS()</a> .

## Value

A dataframe of metric values.

---

```
getSpatialElementExternalMetrics
  getSpatialElementExternalMetrics
```

---

## Description

Computes a selection of external clustering evaluation metrics for spatial data at the element level.

## Usage

```
getSpatialElementExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("nsSPC", "NPC", "SpatialSPC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)
```

## Arguments

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
location	A matrix or data.frame of coordinates
k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
metrics	a vector of metric names to compute.
fuzzy_true	Logical; whether to compute fuzzy class memberships for true.
fuzzy_pred	Logical; whether to compute fuzzy class memberships for pred.
...	Optional params for <a href="#">getFuzzyPartitionElementMetrics()</a> or <a href="#">findSpatialKNN()</a> .

## Value

A data.frame of metrics.

---

**getSpatialElementInternalMetrics**

*Compute spot-level internal evaluation metrics for spatially-resolved data*

---

**Description**

Computes a selection of internal clustering evaluation metrics for spatial data at each spot level.

**Usage**

```
getSpatialElementInternalMetrics(
  labels,
  location,
  k = 6,
  metrics = c("PAS", "ELSA"),
  ...
)
```

**Arguments**

<code>labels</code>	A vector containing the labels to be evaluated.
<code>location</code>	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
<code>k</code>	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
<code>metrics</code>	Possible metrics: "PAS" and "ELSA".
<code>...</code>	Optional params for <a href="#">PAS()</a> .

**Value**

A data frame containing the metric values for all samples in the dataset. If PAS is calculated, the value is a Boolean about the abnormality of a spot. If ELSA is calculated, Ea, Ec and ELSA for all spots will be returned.

---

**getSpatialExternalMetrics**

*Calculate Spatial External Metrics*

---

**Description**

A generic function to calculate spatial external metrics. It can be applied to raw components (`true`, `pred`, `location`) or directly to a `SpatialExperiment` object.

**Usage**

```
getSpatialExternalMetrics(  
  object = NULL,  
  true,  
  pred,  
  location = NULL,  
  k = 6,  
  alpha = 0.5,  
  level = "class",  
  metrics = NULL,  
  fuzzy_true = TRUE,  
  fuzzy_pred = FALSE,  
  ...  
)  
  
## S4 method for signature 'missing'  
getSpatialExternalMetrics(  
  object = NULL,  
  true,  
  pred,  
  location = NULL,  
  k = 6,  
  alpha = 0.5,  
  level = "class",  
  metrics = NULL,  
  fuzzy_true = TRUE,  
  fuzzy_pred = FALSE,  
  ...  
)  
  
## S4 method for signature 'SpatialExperiment'  
getSpatialExternalMetrics(  
  object = NULL,  
  true,  
  pred,  
  location = NULL,  
  k = 6,  
  alpha = 0.5,  
  level = "class",  
  metrics = NULL,  
  fuzzy_true = TRUE,  
  fuzzy_pred = FALSE,  
  ...  
)
```

## Arguments

object	The main input. Can be a <code>SpatialExperiment</code> object or missing (when using <code>true</code> , <code>pred</code> , and <code>location</code> directly).
true	When <code>object</code> is missing: a vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list. When <code>object</code> is a <code>SpatialExperiment</code> object: the column name in <code>colData(object)</code> containing the true labels.
pred	When <code>object</code> is missing: a vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list. When <code>object</code> is a <code>SpatialExperiment</code> object: the column name in <code>colData(object)</code> containing the predicted labels.
location	A matrix or data.frame of coordinates
k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
metrics	The metrics to compute. See details.
fuzzy_true	Logical; whether to compute fuzzy class memberships for <code>true</code> .
fuzzy_pred	Logical; whether to compute fuzzy class memberships for <code>pred</code> .
...	Additional arguments passed to specific methods.

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are: "nsSPC", "NPC", "SpatialSPC".
- If `level = "class"`, the allowed `metrics` are: "nsWH", "nsAWH", "nsWC", "nsAWC".
- If `level = "dataset"`, the allowed `metrics` are: "nsRI", "nsARI", "nsWH", "nsAWH", "nsWC", "nsAWC", "nsAccuracy", "SpatialRI", "SpatialARI".

## Value

A data.frame of metrics based on the specified input.

## Examples

```
# Example with individual components
data(sp_toys)
data <- sp_toys
getSpatialExternalMetrics(true=data$label, pred=data$p1,
location=data[,c("x", "y")], k=6, level="class")
```

```

# Example with SpatialExperiment object
se_object <- SpatialExperiment::SpatialExperiment(assays=matrix(NA,
  ncol = nrow(data[,c("x", "y")]),
  nrow = ncol(data[,c("x", "y")])),
  spatialCoords=as.matrix(data[,c("x", "y")]))
SummarizedExperiment::colData(se_object) <-
  cbind(SummarizedExperiment::colData(se_object),
  data.frame(true=data$label, pred=data$p1))
getSpatialExternalMetrics(object=se_object, true="true", pred="pred", k=6,
  level="class")

```

---

### getSpatialGlobalExternalMetrics

*Compute dataset-level external evaluation metrics for spatially-resolved data*

---

## Description

Computes a selection of external clustering evaluation metrics for spatial data at the dataset level. Options include a series of fuzzy pair-counting metrics and set matching-based accuracy.

## Usage

```
getSpatialGlobalExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("nsRI", "nsARI", "nsWH", "nsAWH", "nsWC", "nsAWC", "nsAccuracy",
  "SpatialRI", "SpatialARI"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  lowMemory = NULL,
  ...
)
```

## Arguments

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
location	A matrix or data.frame of coordinates
k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.

alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
metrics	a vector of metric names to compute.
fuzzy_true	Logical; whether to compute fuzzy class memberships for true.
fuzzy_pred	Logical; whether to compute fuzzy class memberships for pred.
lowMemory	Logical, whether to use a low memory mode. This is only useful when hardTrue and fuzzyPred is used. If TRUE, the function will compute the metrics in a low memory mode, which is slower but uses less memory. If FALSE, the function will compute the metrics in a high memory mode, which is faster but uses more memory. By default it is set automatically based on the size of the input data. See <a href="#">fuzzyHardMetrics</a> .
...	Optional params for <a href="#">fuzzyPartitionMetrics</a> or <a href="#">findSpatialKNN</a> .

### Value

A data.frame of metrics.

---

## getSpatialGlobalInternalMetrics

*Compute dataset-level internal evaluation metrics for spatially-resolved data*

---

### Description

Computes a selection of internal clustering evaluation metrics for spatial data at the dataset level. MPC, PC and PE are internal metrics for fuzzy clustering, and their implementations in package `fclust` are used.

### Usage

```
getSpatialGlobalInternalMetrics(
  labels,
  location,
  k = 6,
  metrics = c("PAS", "ELSA", "CHAOS"),
  ...
)
```

## Arguments

labels	A vector containing the labels to be evaluated.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
metrics	The metrics to compute. See below for more details.
...	Optional arguments for <a href="#">PAS()</a> .

## Value

A named vector containing metric values. Possible metrics are:

PAS	Proportion of abnormal spots (PAS score).
ELSA	Entropy-based Local indicator of Spatial Association (ELSA score).
CHAOS	Spatial Chaos Score.
MPC	Modified partition coefficient
PC	Partition coefficient
PE	Partition entropy

## References

Yuan, Zhiyuan, et al., 2024; 10.1038/s41592-024-02215-8  
 Naimi, Babak, et al., 2019; 10.1016/j.spasta.2018.10.001  
 Wang, et al., 2022; 10.1016/j.ins.2022.11.010

## getSpatialInternalMetrics

*Compute internal metrics for spatial data*

## Description

A generic function to compute a selection of internal clustering evaluation metrics for spatial data. It can be applied to raw components (labels, location) or directly to a `SpatialExperiment` object.

## Usage

```
getSpatialInternalMetrics(
  object = NULL,
  labels,
  location = NULL,
  k = 6,
  level = "class",
  metrics = c("CHAOS", "PAS", "ELSA"),
```

```

  ...
)

## S4 method for signature 'missing'
getSpatialInternalMetrics(
  object = NULL,
  labels,
  location = NULL,
  k = 6,
  level = "class",
  metrics = c("CHAOS", "PAS", "ELSA"),
  ...
)

## S4 method for signature 'SpatialExperiment'
getSpatialInternalMetrics(
  object = NULL,
  labels,
  location = NULL,
  k = 6,
  level = "class",
  metrics = c("CHAOS", "PAS", "ELSA"),
  ...
)

```

## Arguments

object	The main input. Can be a <code>SpatialExperiment</code> object or missing (when using <code>labels</code> , and <code>location</code> directly).
labels	When <code>object</code> is missing: a vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list. When <code>object</code> is a <code>SpatialExperiment</code> object: the column name in <code>colData(object)</code> containing the labels.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
metrics	The metrics to compute. See details.
...	Optional params for <a href="#">PAS()</a> .

## Details

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed `metrics` are: "PAS", "ELSA".

- If `level = "class"`, the allowed metrics are: "CHAOS", "PAS", "ELSA".
- If `level = "dataset"`, the allowed metrics are:
  - "PAS": Proportion of abnormal spots (PAS score)
  - "ELSA": Entropy-based Local indicator of Spatial Association (ELSA score)
  - "CHAOS": Spatial Chaos Score.
  - "MPC": Modified partition coefficient
  - "PC": Partition coefficient
  - "PE": Partition entropy

### Value

A data.frame of metrics.

### Examples

```
# Example with individual components
data(sp_toys)
data <- sp_toys
getSpatialInternalMetrics(labels=data$label, location=data[,c("x", "y")],
                           k=6, level="class")

# Example with SpatialExperiment object
se_object <- SpatialExperiment::SpatialExperiment(assays=matrix(NA,
                                                               ncol = nrow(data[,c("x", "y")]),
                                                               nrow = ncol(data[,c("x", "y")])),
                                                               spatialCoords=as.matrix(data[,c("x", "y")]))
SummarizedExperiment::colData(se_object) <-
cbind(SummarizedExperiment::colData(se_object),
      data.frame(label=data$label))
getSpatialInternalMetrics(object=se_object, labels="label", k=6,
                           level="class")
```

---

## knnComposition

*Compute neighborhood composition*

---

### Description

For a given dataset with locations and labels, compute the label composition of the neighborhood for each sample.

### Usage

```
knnComposition(location, k = 6, labels, alpha = 0.5, ...)
```

**Arguments**

location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
k	The number of nearest neighbors to look at.
labels	A vector containing the label for the dataset.
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
...	Optional arguments for <a href="#">findSpatialKNN()</a> .

**Value**

A numerical matrix indicating the composition, where rows correspond to samples and columns correspond to the classes in label.

**Examples**

```
data(sp_toys)
data <- sp_toys
knnComposition(data[,c("x", "y")], k=6, data$label)
```

matchSets

*Match two partitions using Hungarian algorithm***Description**

Match sets from a partitions to a reference partition using the Hungarian algorithm to optimize F1 scores.

**Usage**

```
matchSets(pred, true, forceMatch = TRUE, returnIndices = is.integer(true))
```

**Arguments**

pred	An integer or factor of cluster labels
true	An integer or factor of reference labels
forceMatch	Logical; whether to enforce a match for every set of pred
returnIndices	Logical; whether to return indices rather than levels

**Value**

A vector of matching sets (i.e. level) from true for every set (i.e. level) of pred.

---

**metric\_info***Metrics Information*

---

**Description**

A dataframe storing the information of all metrics. The code to generate the dataset is at system.file('inst/scripts/', 'metric\_info.R', package='poem').

**Usage**

```
metric_info
```

**Format**

```
metric_info:  
A data frame.
```

---

**mockData***Generate mock multidimensional data*

---

**Description**

Generates mock multidimensional data of a given number of classes of points, for testing.

**Usage**

```
mockData(  
  Ns = c(25, 15),  
  classDiff = 2,  
  Sds = 1,  
  ndims = 2,  
  spread = c(1, 2),  
  rndFn = rnorm  
)
```

**Arguments**

Ns	A vector of more than one positive integers specifying the number of elements of each class.
classDiff	The distances between the classes. If there are more than 2 classes, this can be a <code>dist</code> object or a symmetric matrix of <code>length(Ns)-1</code> columns/rows where the lower triangle indicates the desired distances between classes.
Sds	The standard deviation. Can either be a fixed value, a value per class, or a matrix of values for each class (rows) and dimension (column).
ndims	The number of dimensions to generate (default 2).

spread	The spread of the points. Can either be a fixed value, a value per class, or a matrix of values for each class (rows) and dimension (col).
rndFn	The random function, by default <code>rnorm</code> , but should also work for <code>rlnorm</code> and similar.

**Value**

A data.frame with coordinates and a `class` column.

**Examples**

```
d <- mockData()
```

---

<code>nnWeightedAccuracy</code>	<i>nnWeightedAccuracy</i>
---------------------------------	---------------------------

---

**Description**

Computes an accuracy score which weighs elements/spots that are misclassified by the proportion of their (spatial) neighborhood that is not of the element/spot's predicted class. This reduces the weight of misclassifications happening at the boundary between domains.

**Usage**

```
nnWeightedAccuracy(true, pred, location, k = 5, ...)
```

**Arguments**

true	True class labels (vector coercible to factor)
pred	Predicted labels (vector coercible to factor)
location	The spatial coordinates to compute the nearest neighbors.
k	Number of nearest neighbors
...	Optional params passed to <a href="#">findSpatialKNN()</a> .

**Value**

A scalar representing the weighted accuracy.

---

noisy_moon	<i>The noisy moon dataset</i>
------------	-------------------------------

---

## Description

A simple toy dataset consists of two interleaving half circles. The code to generate the dataset is at `system.file('inst/scripts/', 'noisy_moon.R', package='poem')`.

## Usage

```
noisy_moon
```

## Format

**noisy\_moon:**

A data frame with 100 rows and 5 columns:

**x, y** Coordinates of each observations.

**label** Ground truth labels. Either 1 or 2.

**kmeans\_label** Predicted clustering labels using kmeans with 2 centers.

**hdbscan\_label** Predicted clustering labels using hdbscan with `minPts = 5`.

---

PAS	<i>Calculate PAS score</i>
-----	----------------------------

---

## Description

PAS score measures the clustering performance by calculating the randomness of the spots that located outside of the spatial region where it was clustered to. Lower PAS score indicates better spatial domain clustering performance.

## Usage

```
PAS(labels, location, k = 10, ...)
```

## Arguments

<b>labels</b>	Cluster labels.
<b>location</b>	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
<b>k</b>	Number of nearest neighbors.
<b>...</b>	Optional params for <a href="#">findSpatialKNN()</a> .

## Value

A numeric value for PAS score, and a boolean vector about the abnormal spots.

## Examples

```
data(sp_toys)
data <- sp_toys
PAS(data$label, data[,c("x", "y")], k=6)
PAS(data$p1, data[,c("x", "y")], k=6)
PAS(data$p2, data[,c("x", "y")], k=6)
```

setMatchingAccuracy *The non-spatially-weighted counterpart of nnWeightedAccuracy*

## Description

The non-spatially-weighted counterpart of nnWeightedAccuracy

## Usage

```
setMatchingAccuracy(true, pred)
```

## Arguments

true	True class labels (vector coercible to factor)
pred	Predicted labels (vector coercible to factor)

## Value

A scalar representing the weighted accuracy.

silhouetteWidths *silhouetteWidths*

## Description

Computes the silhouette widths. If the dataset is sufficiently small for the `cluster::silhouette` implementation to work, this will be used. Otherwise a slower chunked implementation is used.

## Usage

```
silhouetteWidths(x, labels)
```

## Arguments

x	A numeric matrix or data.frame with observations as rows.
labels	An integer/factor vector of clustering labels, or length equal to the number of rows in x.

**Value**

A numeric vector of silhouette widths for each element of  $x$ .

**Examples**

```
# generate dummy data
m <- matrix(rnorm(100*3),ncol=3)
labels <- sample.int(3,100,replace=TRUE)
# calculate SWs:
sw <- silhouetteWidths(m, labels)
```

spatialARI

*Spatially aware ARI from Yan, Yingqiao, et al. (2025).***Description**

Computes the spatial Rand Index and spatial ARI (Yan, Feng and Luo, 2025). Note that by default, the decay functions are different from those of the original publication (see details for more information), but the latter can be replicated with `original=TRUE`.

**Usage**

```
spatialARI(
  true,
  pred,
  location,
  normCoords = TRUE,
  lambda = 0.8,
  fbeta = 4,
  hbeta = 1,
  spotWise = FALSE,
  nChunks = NULL,
  original = FALSE,
  f = function(x) {
    lambda * exp(-x * fbeta)
  },
  h = function(x) {
    lambda * (1 - exp(-x * hbeta))
  }
)
```

**Arguments**

<code>true</code>	A vector of true class labels
<code>pred</code>	A vector of predicted clusters
<code>location</code>	A matrix of spatial coordinates, with dimensions as columns

normCoords	Logical; whether to normalize the coordinates to 0-1.
lambda	The alpha used in the f and h functions (default 0.8) in Yan, Feng and Luo, 2025.
fbeta, hbeta	Additional factors used in the exponential decay functions (see details). A higher value means a faster decay. These are ignored if original=TRUE.
spotWise	Logical; whether to return the spot-wise spatial concordance (not adjusted for chance).
nChunks	The number of processing chunks. If NULL, this will be determined automatically based on the size of the dataset, so as to remain below 2GB RAM usage.
original	Logical; whether to use the original h/f functions from Yan, Feng and Luo (default FALSE). If set to TRUE, the arguments fbeta, hbeta, f and h are ignored.
f	The f function, which determines the positive contribution of pairs that are in different partitions in the reference, but grouped together in the clustering, based on the distance between mates.
h	The h function, which determines the positive contribution of pairs that are in the same partition in the reference, but different ones in the clustering, based on the distance between mates.

## Details

This is a reimplementation of the method from the `spARI` package, made more scalable (i.e. a bit slower but more memory-efficient) through chunk-based processing, extensible to more than 2 dimensions, and with some additional options. Note that by default, this will not produce the same results as the original method: to do so, set `original=TRUE`. In our exploration of the method and its behavior, we found the decay to be too slow, and we therefore 1) do not square the distances, and 2) introduced a beta parameter in each function which allows to scale it (a higher beta parameter means a faster decay).

By default, chunking to keep RAM usage roughly below 2GB. Higher speed can be achieved (at higher memory costs) for larger datasets by limiting the number of chunks. The memory usage if done in a single chunk should be roughly  $4e-5 * nrow(location)^2$  Mb, and this scales down linearly with the number of chunks.

## Value

A vector containing the spatial Rand Index (spRI) and spatial adjusted Rand Index (spARI). Alternatively, if `spotWise=TRUE`, a vector of spatial pair concordances for each spot.

## Author(s)

Pierre-Luc Germain

## References

Yan, Feng and Luo, biorxiv 2025, <https://doi.org/10.1101/2025.03.25.645156>

## Examples

```
data(sp_toys)
spatialARI(true=sp_toys$label, pred=sp_toys$p2, location = sp_toys[,1:2])
```

---

sp\_toys

*Toy examples of spatial data*

---

## Description

Toy examples of spatial data. The code to generate the dataset is at `system.file('inst/scripts/','sp_toys.R', package='poem')`.

## Usage

`sp_toys`

## Format

**sp\_toys:**

A data frame with 240 rows and 11 columns, representing a 16 x 15 array of spots:

**x, y** Coordinates of each spots.

**row, col** The row and column index of each spots.

**label** Ground truth labels. Either 1 or 2.

**p1-p6** Hypothetical predicted spatial clustering labels.

---

toyExamples

*Toy embedding examples*

---

## Description

Toy example 2D embeddings of elements of different classes, with varying mixing and spread. Graphs 1-3 all have 20 elements of each of 4 classes, but that are mixed in different fashion in the embedding space. Graphs 4-7 all have 100 elements of class1 and 60 of class2, and the class1 elements vary in their spread. The code to generate the dataset is at `system.file('inst/scripts/','graph_example.R', package='poem')`.

## Usage

`toyExamples`

## Format

**toyExamples:**

A data frame.

**graph** The name of the embedding to which the element belongs.

**x, y** Coordinates in the 2D embedding.

**class** The class to which the element belongs.

# Index

- \* **datasets**
  - metric\_info, 53
  - noisy\_moon, 55
  - sp\_toys, 59
  - toyExamples, 59
- \* **internal**
  - .check\_duplicated\_samples, 3
  - .compute\_cluster\_core\_distance, 4
  - .compute\_cross\_dists, 4
  - .compute\_mutual\_reach\_dists, 5
  - .compute\_pair\_to\_pair\_dists, 5
  - .convert\_singleton\_clusters\_to\_noise, 6
  - .fn\_density\_separation, 6
  - .fn\_density\_sparseness, 7
  - .get\_internal\_objects, 7
  - .get\_submatrix, 8
- FMeasure, 15
- fuzzyHardMetrics2, 18
- getEmbeddingClassMetrics, 22
- getEmbeddingElementMetrics, 23
- getEmbeddingGlobalMetrics, 24
- getFuzzyPartitionElementMetrics, 26
- getGraphClassMetrics, 30
- getGraphElementMetrics, 32
- getPartitionClassMetrics, 37
- getPartitionElementMetrics, 37
- getPartitionGlobalMetrics, 38
- getSpatialClassExternalMetrics, 41
- getSpatialClassInternalMetrics, 42
- getSpatialElementExternalMetrics, 43
- getSpatialElementInternalMetrics, 44
- getSpatialGlobalExternalMetrics, 47
- getSpatialGlobalInternalMetrics, 48
- nnWeightedAccuracy, 54
- setMatchingAccuracy, 56
- silhouetteWidths, 56
- .check\_duplicated\_samples, 3
- .compute\_cluster\_core\_distance, 4
- .compute\_cross\_dists, 4
- .compute\_mutual\_reach\_dists, 5
- .compute\_pair\_to\_pair\_dists, 5
- .convert\_singleton\_clusters\_to\_noise, 6
- .fn\_density\_separation, 6
- .fn\_density\_sparseness, 7
- .get\_internal\_objects, 7
- .get\_submatrix, 8

- bluster::neighborsToSNNGraph(), 14
- CDbw, 8
- CDbw(), 25
- CHAOS, 10
- clevr::mutual\_info(), 38, 39
- clevr::v\_measure(), 38, 39
- clevr::variation\_info(), 38, 39
- dbcv, 10
- dbcv(), 25
- ELSA, 12
- emb2knn, 13
- emb2knn(), 32–34
- emb2snn, 13
- emb2snn(), 32–34
- findKNN, 10, 15, 35
- findSpatialKNN, 14, 42, 48
- findSpatialKNN(), 26, 43, 52, 54, 55
- FMeasure, 15
- fuzzyHardMetrics, 16, 18, 29, 42, 48
- fuzzyHardMetrics(), 19
- fuzzyHardMetrics2, 18
- fuzzyHardSpotConcordance, 19

fuzzyPartitionMetrics, 16, 21, 29, 42, 48  
fuzzyPartitionMetrics(), 17

getEmbeddingClassMetrics, 22  
getEmbeddingElementMetrics, 23  
getEmbeddingGlobalMetrics, 24  
getEmbeddingMetrics, 24  
getFuzzyLabel, 26  
getFuzzyPartitionElementMetrics, 26  
getFuzzyPartitionElementMetrics(), 43  
getFuzzyPartitionMetrics, 28  
getGraphClassMetrics, 30  
getGraphClassMetrics, data.frame-method  
    (getGraphClassMetrics), 30  
getGraphClassMetrics, dist-method  
    (getGraphClassMetrics), 30  
getGraphClassMetrics, igraph-method  
    (getGraphClassMetrics), 30  
getGraphClassMetrics, list-method  
    (getGraphClassMetrics), 30  
getGraphClassMetrics, matrix-method  
    (getGraphClassMetrics), 30  
getGraphElementMetrics, 32  
getGraphElementMetrics, data.frame-method  
    (getGraphElementMetrics), 32  
getGraphElementMetrics, dist-method  
    (getGraphElementMetrics), 32  
getGraphElementMetrics, igraph-method  
    (getGraphElementMetrics), 32  
getGraphElementMetrics, list-method  
    (getGraphElementMetrics), 32  
getGraphElementMetrics, matrix-method  
    (getGraphElementMetrics), 32  
getGraphMetrics, 33  
getNeighboringPairConcordance, 35  
getPairConcordance, 36  
getPartitionClassMetrics, 37  
getPartitionElementMetrics, 37  
getPartitionGlobalMetrics, 38  
getPartitionMetrics, 39  
getSpatialClassExternalMetrics, 41  
getSpatialClassInternalMetrics, 42  
getSpatialElementExternalMetrics, 43  
getSpatialElementInternalMetrics, 44  
getSpatialExternalMetrics, 44  
getSpatialExternalMetrics, missing-method  
    (getSpatialExternalMetrics), 44  
getSpatialExternalMetrics, SpatialExperiment-method  
    (getSpatialExternalMetrics), 44

getSpatialGlobalExternalMetrics, 47  
getSpatialGlobalInternalMetrics, 48  
getSpatialInternalMetrics, 49  
getSpatialInternalMetrics, missing-method  
    (getSpatialInternalMetrics), 49  
getSpatialInternalMetrics, SpatialExperiment-method  
    (getSpatialInternalMetrics), 49

knnComposition, 51

matchSets, 52  
metric\_info, 53  
mockData, 53

nnWeightedAccuracy, 54  
noisy\_moon, 55

PAS, 55  
PAS(), 42, 44, 49, 50

setMatchingAccuracy, 56  
silhouetteWidths, 56  
sp\_toys, 59  
spatialARI, 57  
stats::dist(), 25

toyExamples, 59