

Package ‘SpikeInSubset’

February 3, 2026

Title Part of Affymetrix's Spike-In Experiment Data

Version 1.51.0

Author Rafael Irizarry <rafa@ds.dfci.harvard.edu> and Zhijin Wu

Maintainer Robert D Shear <rshear@ds.dfci.harvard.edu>

URL <https://bioconductor.org/packages/SpikeInSubset>

BugReports <https://github.com/rafalab/SpikeInSubset/issues>

Description

Includes probe-level and expression data for the HGU133 and HGU95 spike-in experiments

License LGPL

Depends R (>= 2.4.0), Biobase (>= 2.5.5), affy (>= 1.23.4)

biocViews ExperimentData, MicroarrayData

git_url <https://git.bioconductor.org/packages/SpikeInSubset>

git_branch devel

git_last_commit f815c90

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2026-02-03

Contents

hgu133a.spikein.xhyb	2
SpikeIn	2

Index

4

hgu133a.spikein.xhyb *Cross hybridizers*

Description

Probe Sets likely to crosshybridize to spiked-in probesets in the Affymetrix HGU133A spike in. This object is list. Each component of the list contains probeset names of possible crosshybridizers. The sequences of each spiked-in clone were collected and blasted against all HG-U133A target sequences. Target sequences are the ~600bp regions from which probes were selected. Thresholds of 100, 150 and 200bp were used and define the three components of the list.

Usage

```
data(hgu133a.spikein.xhyb)
```

Format

A list

Source

Simon Cawley <simon_cawley@affymetrix.com>

SpikeIn

Subset of Affymetrix SpikeIn Experiment Data

Description

Probe-level and pre-processed data for six arrays (two triplicates) from the HGU95 and HGU133 SpikeIn experiments.

Usage

```
data(spikein95)
data(rma95)
data(mas95)

data(spikein133)
data(rma133)
data(mas133)
```

Format

SpikeIn is [ProbeSet](#) containing the \$PM\$ and \$MM\$ intensities for a gene spiked in at different concentrations. Use pData to see the concentrations.

Source

`spikein95` and `spikein133` are instances of `ProbeSet` with the probe-level data for six arrays (two triplicates) from the HGU95 and HGU133 SpikeIn experiments respectively. `rma95` and `rma133` contain the data pre-processed with RMA. `mas95` and `mas133` contain the data preprocessed with mas5 (expression and present/absent calls). The calls are in objects called `pacalls95` and `pacalls133`.

For more information see Irizarry, R.A., et al. NAR (2003) <http://www.biostat.jhsph.edu/~ririzarr/papers/index.html>

Index

* datasets

hgu133a.spikein.xhyb, [2](#)

SpikeIn, [2](#)

hgu133a.spikein.xhyb, [2](#)

mas133 (SpikeIn), [2](#)

mas95 (SpikeIn), [2](#)

pacalls133 (SpikeIn), [2](#)

pacalls95 (SpikeIn), [2](#)

ProbeSet, [2](#), [3](#)

rma133 (SpikeIn), [2](#)

rma95 (SpikeIn), [2](#)

SpikeIn, [2](#)

spikein133 (SpikeIn), [2](#)

spikein95 (SpikeIn), [2](#)