

Package ‘StatescopeR’

June 5, 2026

Type Package

Title StatescopeR framework for discovery of cell states from cell type-specific gene expression profiles inferred from bulk mRNA profiles

Version 1.1.0

Depends R (>= 4.6.0)

Imports S4Vectors, SummarizedExperiment, reticulate, methods, SingleCellExperiment, matrixStats, scran, basilisk, Matrix, ComplexHeatmap, ggplot2, cowplot, utils

Suggests BiocStyle, knitr, RefManageR, rmarkdown, sessioninfo, scRNAseq, scuttle, testthat

Description

StatescopeR is an R wrapper around Statescope, a computational framework designed to discover cell states from cell type-specific gene expression profiles inferred from bulk RNA profiles.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

StagedInstall no

biocViews GeneExpression, RNASeq, SingleCell, Bayesian, Transcriptomics, Software

URL <https://github.com/tgac-vumc/StatescopeR>

BugReports <https://github.com/tgac-vumc/StatescopeR/issues>

VignetteBuilder knitr

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/StatescopeR>

git_branch devel

git_last_commit 1593c2f

git_last_commit_date 2026-04-28

Repository Bioconductor 3.24

Date/Publication 2026-06-04

Author Mischa Steketeer [aut, cre] (ORCID: <https://orcid.org/0000-0001-7138-7554>),
 Bauke Ylstra [ths] (ORCID: <https://orcid.org/0000-0001-9479-3010>),
 Yongsoo Kim [ths] (ORCID: <https://orcid.org/0000-0002-2995-2131>),
 KWF Kankerbestrijding [fnd]

Maintainer Mischa Steketeer <m.f.b.steketeer@amsterdamumc.nl>

Contents

StatescopeR-package	2
barplot_stateloadings	3
BLADE_deconvolution	4
create_signature	5
fetch_signature	6
fraction_eval	7
fraction_heatmap	8
gather_true_fractions	8
Refinement	9
select_genes	10
StateDiscovery	12
statescope	13
Index	14

StatescopeR-package	<i>The StatescopeR package</i>
---------------------	--------------------------------

Description

framework for discovery of cell states from bulk mRNA profiles

Details

StatescopeR starts from lognormalized cp10k single cell data and a bulk RNA dataset to be used for deconvolution and cell state analysis. From this point StatescopeR has some functions to create a signature and select genes for deconvolution. [create_signature](#) creates a signature of lognormalized cp10k single cell data for deconvolution and cell state analysis. [select_genes](#) selects genes which best discriminate cell types for use in deconvolution. Alternatively you can also use: [fetch_signature](#) to fetch one of the premade signatures + [selected_genes](#) from <https://github.com/tgac-vumc/StatescopeData> After these steps and proper cp10k normalization of the bulk mRNA deconvolution and cell state analysis can be done with the following functions: [BLADE_deconvolution](#) estimates cell fractions from bulk mRNA. [Refinement](#) refines cell type-specific gene expression profile estimates to better capture inter-sample variability. [StateDiscovery](#) discovery cell states from inferred cell type-specific gene expression profiles.

After these steps the following functions provide some evaluation and plotting functions: [gather_true_fractions](#) gets true cell fractions from scRNAseq data. [fraction_eval](#) plots the correlation of estimated vs true cell fractions over all samples. [fraction_heatmap](#) plots a heatmap of estimated cell fractions. [barplot_stateloadings](#) plots a barplot showing the top n most important stateloadings.

Author(s)

Maintainer: Mischa Steketeer <m.f.b.steketeer@amsterdamumc.nl> ([ORCID](#))

Other contributors:

- Bauke Ylstra <b.ylstra@amsterdamumc.nl> ([ORCID](#)) [thesis advisor]
- Yongsoo Kim <yo.kim@amsterdamumc.nl> ([ORCID](#)) [thesis advisor]
- KWF Kankerbestrijding [funder]

See Also

Useful links:

- <https://github.com/tgac-vumc/StatescopeR>
- Report bugs at <https://github.com/tgac-vumc/StatescopeR/issues>

barplot_stateloadings *Create a barplot of top stateloadings*

Description

Create a barplot of top stateloadings

Usage

```
barplot_stateloadings(Statescope, top_n = 1)
```

Arguments

Statescope	SummarizedExperiment object from StateDiscovery
top_n	integer selecting how many genes to show per state

Value

A barplot rendered to the active graphics device

Examples

```
## ## Load Discovered Statescope object
load(system.file("extdata", "example_Statescope_Discovered.RData",
  package = "StatescopeR"
))

## Plot fraction heatmap
barplot_stateloadings(Statescope, top_n = 1)
```

BLADE_deconvolution *Run BLADE deconvolution*

Description

BLADE_deconvolution.R Runs BLADE to estimate cell fractions from bulk mRNA

Usage

```
BLADE_deconvolution(
  signature,
  bulk,
  genes,
  prior = NULL,
  cores = 1L,
  Alpha = 1L,
  Alpha0 = 1000L,
  Kappa0 = 1L,
  sY = 1L,
  Nrep = 10L,
  Nrepfinal = 1000L
)
```

Arguments

signature	SimpleList with mu and sigma, both nGene x nCelltype dataframes, respectively mean gene expression and mean-variance corrected variance per cell type
bulk	nSample x nGene mRNA to be deconvolved
genes	subset of genes to be used for deconvolution
prior	(optional) nSample x nCelltype matrix with prior fraction expectations
cores	number of cores to use for paralellization
Alpha	BLADE Hyperparameter
Alpha0	BLADE Hyperparameter
Kappa0	BLADE Hyperparameter
sY	BLADE Hyperparameter
Nrep	Number of BLADE initializations
Nrepfinal	Number of maximum optimization iterations

Value

SummarizedExperiment object with BLADE output and estimated fractions

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
  library(scRNAseq)
  library(scuttle)
  ## Load SegerstolpePancreas data set
  scRNAseq <- SegerstolpePancreasData()
```

```

## remove duplicate genes
scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]
## Subset to 1 healthy and 2 type 2 diabetes samples
scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
  "H3",
  "T2D1", "T2D2"
)]
## remove cells with no cell type label
scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

## remove very rare cell types (<100 cells in total data set)
celltypes_to_remove <-
names(table(scRNAseq$`cell type`)[(table(scRNAseq$`cell type`) < 100)])
scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

## Create pseudobulk and normalize to cp10k
pseudobulk <- aggregateAcrossCells(scRNAseq, ids = scRNAseq$individual)
normcounts(pseudobulk) <- calculateCPM(pseudobulk) / 100
pseudobulk <- as(pseudobulk, "SummarizedExperiment")
rownames(pseudobulk) <- rownames(scRNAseq)

## Load signature
load(system.file("extdata", "example_signature.RData",
  package = "StatescopeR"
))

## Load selected_genes
load(system.file("extdata", "example_selected_genes.RData",
  package = "StatescopeR"
))

## Load prior
load(system.file("extdata", "example_prior.RData",
  package = "StatescopeR"
))

## Perform Deconvolution with BLADE
Statescope <- BLADE_deconvolution(
  signature, pseudobulk, selected_genes,
  prior, 1L,
  Nrep = 1L
)

## show estimated fractions
S4Vectors::metadata(Statescope)$fractions
}

```

create_signature

Create scRNAseq Signature

Description

create_signature Creates signature from scRNAseq data

Usage

```
create_signature(scRNAseq, hvg_genes = FALSE, n_hvg_genes = 3000L, labels)
```

Arguments

scRNAseq	SingleCellExperiment object of which to make signature
hvg_genes	boolean which chooses if mu and omega should be subset to highly variable genes or not
n_hvg_genes	int which allows the users to choose the number of highly variable genes
labels	character vector for the cell type labels

Value

SimpleList DataFrames for Mu (mean per gene per cell type) and Omega (variance corrected std.dev per gene per cell type)

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
  library(scRNAseq)
  library(scuttle)
  ## Load scRNAseq
  scRNAseq <- scRNAseq::SeegerstolpePancreasData()

  ## remove NA cells
  scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

  ## Normalize (cp10k) and logtransform scRNAseq
  cpm(scRNAseq) <- scuttle::calculateCPM(scRNAseq)
  SingleCellExperiment::logcounts(scRNAseq) <- log1p(cpm(scRNAseq) / 100)

  ## Create signature
  signature <- create_signature(scRNAseq, labels = scRNAseq$`cell type`)
}
```

fetch_signature	<i>Fetch scRNAseq Signature</i>
-----------------	---------------------------------

Description

fetch_signature Fetches signature from StatescopeData repository

Usage

```
fetch_signature(tumor_type, n_celltypes)
```

Arguments

tumor_type	string choosing the tumor type from available signatures at: https://github.com/tgac-vumc/StatescopeData
n_celltypes	integer choosing the number of cell types of the signature from: https://github.com/tgac-vumc/StatescopeData

Value

SimpleList with DataFrames for Mu (mean per gene per cell type) and Omega (variance corrected std.dev per gene per cell type) and vector of selected genes for deconvolution chosen by AutoGeneS

Examples

```
signature <- fetch_signature('PDAC', 7)
selected_genes <- signature$selected_genes
```

fraction_eval	<i>Create a barplot of TRUE vs estimated cfs</i>
---------------	--

Description

Create a barplot of TRUE vs estimated cfs

Usage

```
fraction_eval(Statescope, true_fractions)
```

Arguments

Statescope SummarizedExperiment object from BLADE_deconvolution
true_fractions s4 Dataframe with true fractions to compare with estimated fractions

Value

A barplot rendered to the active graphics device

Examples

```
## Load True fractions
load(system.file("extdata", "example_true_fractions.RData",
  package = "StatescopeR"
))

## Load Deconvolved Statescope object
load(system.file("extdata", "example_Statescope_Deconvolved.RData",
  package = "StatescopeR"
))

## ## Plot fraction correlation and RMSE per ct
fraction_eval(Statescope, true_fractions)
```

`fraction_heatmap` *Create a heatmap of the estimated fractions*

Description

Create a heatmap of the estimated fractions

Usage

```
fraction_heatmap(Statescope, ...)
```

Arguments

<code>Statescope</code>	SummarizedExperiment object from BLADE_deconvolution
<code>...</code>	other parameters to pass to [ComplexHeatmap::Heatmap()]

Value

A heatmap rendered to the active graphics device

Examples

```
## Load Deconvolved Statescope object
load(system.file("extdata", "example_Statescope_Deconvolved.RData",
  package = "StatescopeR"
))

## Plot fraction heatmap
fraction_heatmap(Statescope)
```

`gather_true_fractions` *Gather true fractions*

Description

`gather_true_fractions` Gathers true fractions of all cell types per sample from scRNAseq data

Usage

```
gather_true_fractions(scRNAseq, ids, label_col)
```

Arguments

<code>scRNAseq</code>	SingleCellExperiment object of which to gather fractions per sample
<code>ids</code>	character vector with ids of samples
<code>label_col</code>	character for the column name with the cell type labels

Value

DataFrame with fractions of all cell types per sample

Examples

```

if (requireNamespace("scRNAseq", quietly = TRUE)) {
  library(scRNAseq)
  ## Load data
  scRNAseq <- scRNAseq::SegerstolpePancreasData()
  ## Subset to 1 healthy and 3 type 2 diabetes samples
  scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
    "H3",
    "T2D1", "T2D2"
  )]
  ## remove NA cells
  scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

  ## remove cells with less than 100 in total cohort
  celltypes_to_remove <- names(table(scRNAseq$`cell type`)
    [(table(scRNAseq$`cell type`) < 100)])
  scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

  true_fractions <- gather_true_fractions(scRNAseq,
    ids = scRNAseq$individual, label_col = "cell type"
  )
}

```

Refinement

*Run Refinement***Description**

Refinement.R # Perform Gene Expression Refinement

Usage

```
Refinement(Statescope, signature, bulk, cores = 1L)
```

Arguments

Statescope	SummarizedExperiment object from BLADE_deconvolution
signature	SimpleList with mu and sigma, respectively mean gene expression and mean-variance corrected variance per cell type
bulk	mRNA to be refined
cores	number of cores to use for paralellization

Details

This function takes the output from BLADE_deconvolution and refines the cell type specific gene expression by reoptimizing the initial estimates. It reoptimizes by fixing the estimated fractions and weighing the objective function value in a way that it tries to resemble the bulk RNA expression more than initially

Value

updated SummarizedExperiment object with ct_specific_gep added

Examples

```

if (requireNamespace("scRNAseq", quietly = TRUE)) {
  library(scRNAseq)
  library(scuttle)
  ## Load SegerstolpePancreas data set
  scRNAseq <- SegerstolpePancreasData()

  ## remove duplicate genes
  scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]

  ## Subset to 1 healthy and 2 type 2 diabetes samples
  scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
    "H3",
    "T2D1", "T2D2"
  )]
  ## remove cells with no cell type label
  scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

  ## remove very rare cell types (<100 cells in total data set)
  celltypes_to_remove <- names(table(scRNAseq$`cell type`)
  [(table(scRNAseq$`cell type`) < 100)])
  scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

  ## Create pseudobulk and normalize to cp10k
  pseudobulk <- aggregateAcrossCells(scRNAseq, ids = scRNAseq$individual)
  normcounts(pseudobulk) <- calculateCPM(pseudobulk) / 100
  pseudobulk <- as(pseudobulk, "SummarizedExperiment")
  rownames(pseudobulk) <- rownames(scRNAseq)
  ## Load signature
  load(system.file("extdata", "example_signature.RData",
    package = "StatescopeR"
  ))

  ## Load Deconvolved Statescope object
  load(system.file("extdata", "example_Statescope_Deconvolved.RData",
    package = "StatescopeR"
  ))

  ## Run Refinement
  Statescope <- Refinement(Statescope, signature, pseudobulk, 2L)

  ## Show cell type specific gene expression profile estimates
  S4Vectors::metadata(Statescope)$ct_specific_gexp
}

```

select_genes

Select genes using AutoGeneS

Description

select_genes.R select genes using AutoGeneS for deconvolution

Usage

```
select_genes(scRNAseq, fixed_n_features = NA, n_hvg_genes = 3000L, labels)
```

Arguments

scRNAseq	SingleCellExperiment object to use for gene selection, should be same as signature dataset
fixed_n_features	integer number of genes to pick with autogenes, default is NA which lets autogenes itself pick
n_hvg_genes	int which allows the users to choose the number of highly variable genes
labels	character vector with cell type labels

Value

Vector of genes to use for deconvolution

Examples

```
if (requireNamespace("scRNAseq", quietly = TRUE)) {
  library(scRNAseq)
  library(scuttle)
  ## Load SegerstolpePancreas data set
  scRNAseq <- SegerstolpePancreasData()

  ## remove duplicate genes
  scRNAseq <- scRNAseq[!duplicated(rownames(scRNAseq)), ]

  ## Subset to 1 healthy and 2 type 2 diabetes samples
  scRNAseq <- scRNAseq[, scRNAseq$individual %in% c(
    "H3",
    "T2D1", "T2D2"
  )]
  ## remove cells with no cell type label
  scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

  ## remove rare cell types (<100 cells in total data set)
  celltypes_to_remove <- names(table(scRNAseq$`cell type`)
    [(table(scRNAseq$`cell type`) < 100)])
  scRNAseq <- scRNAseq[, !scRNAseq$`cell type` %in% celltypes_to_remove]

  ## remove NA cells
  scRNAseq <- scRNAseq[, !is.na(scRNAseq$`cell type`)]

  ## Normalize (cp10k) and logtransform scRNAseq
  cpm(scRNAseq) <- scuttle::calculateCPM(scRNAseq)
  logcounts(scRNAseq) <- log1p(cpm(scRNAseq) / 100)

  ## Select genes by autogenes
  selected_genes <- select_genes(scRNAseq, 3L,
    n_hvg_genes = 5L,
    labels = scRNAseq$`cell type`
  ) # 3 genes
}
```

 StateDiscovery

Run StateDiscovery

Description

StateDiscovery.R Discovers states from refined ct-specific gep

Usage

```
StateDiscovery(
  Statescope,
  k = NA,
  max_clusters = 10L,
  n_iter = 10L,
  n_final_iter = 100L,
  min_cophenetic = 0.9,
  Ncores = 1L
)
```

Arguments

Statescope	SummarizedExperiment object from Statescope Refinement.
k	number of cluster to choose, default is NA for automatic selection
max_clusters	maximum allowed states per cell type.
n_iter	Number of initial cNMF restarts.
n_final_iter	Number of final cNMF restarts.
min_cophenetic	Minimum cophenetic coefficient to determine K.
Ncores	number of cores to use for parallization.

Value

SummarizedExperiment object with statescores per celltype added

Examples

```
## Load Refined Statescope object
load(system.file("extdata", "example_Statescope_Refined.RData",
  package = "StatescopeR"
))

## Discover states
Statescope <- StateDiscovery(Statescope, k = 2L, Ncores = 2L)

## Look at statescores and stateloadings
S4Vectors::metadata(Statescope)$statescores
S4Vectors::metadata(Statescope)$stateloadings
```

statescope

Python environments

Description

Python environments

Usage

statescope

Format

An object of class BasiliskEnvironment of length 1.

Index

- * **datasets**
 - statescope, [13](#)
- * **internal**
 - StatescopeR-package, [2](#)
- barplot_stateloadings, [2, 3](#)
- BLADE_deconvolution, [2, 4](#)
- create_signature, [2, 5](#)
- fetch_signature, [2, 6](#)
- fraction_eval, [2, 7](#)
- fraction_heatmap, [2, 8](#)
- gather_true_fractions, [2, 8](#)
- Refinement, [2, 9](#)
- select_genes, [2, 10](#)
- StateDiscovery, [2, 12](#)
- statescope, [13](#)
- StatescopeR (StatescopeR-package), [2](#)
- StatescopeR-package, [2](#)