

Introduction to RBM package

Dongmei Li

October 17, 2016

Clinical and Translational Science Institute, University of Rochester School of Medicine and Dentistry, Rochester, NY 14642-0708

Contents

1 Overview

This document provides an introduction to the RBM package. The RBM package executes the resampling-based empirical Bayes approach using either permutation or bootstrap tests based on moderated t-statistics through the following steps.

- Firstly, the RBM package computes the moderated t-statistics based on the observed data set for each feature using the lmFit and eBayes function.
- Secondly, the original data are permuted or bootstrapped in a way that matches the null hypothesis to generate permuted or bootstrapped resamples, and the reference distribution is constructed using the resampled moderated t-statistics calculated from permutation or bootstrap resamples.
- Finally, the p-values from permutation or bootstrap tests are calculated based on the proportion of the permuted or bootstrapped moderated t-statistics that are as extreme as, or more extreme than, the observed moderated t-statistics.

Additional detailed information regarding resampling-based empirical Bayes approach can be found elsewhere (Li et al., 2013).

2 Getting started

The RBM package can be installed and loaded through the following R code.

Install the RBM package with:

```
> source("http://bioconductor.org/biocLite.R")
> biocLite("RBM")
```

Load the RBM package with:

```
> library(RBM)
```

3 RBM_T and RBM_F functions

There are two functions in the **RBM** package: **RBM_T** and **RBM_F**. Both functions require input data in the matrix format with rows denoting features and columns denoting samples. **RBM_T** is used for two-group comparisons such as study designs with a treatment group and a control group. **RBM_F** can be used for more complex study designs such as more than two groups or time-course studies. Both functions need a vector for group notation, i.e., "1" denotes the treatment group and "0" denotes the control group. For the **RBM_F** function, a contrast vector need to be provided by users to perform pairwise comparisons between groups. For example, if the design has three groups (0, 1, 2), the **aContrast** parameter will be a vector such as ("X1-X0", "X2-X1", "X2-X0") to denote all pairwise comparisons. Users just need to add an extra "X" before the group labels to do the contrasts.

- Examples using the **RBM_T** function: **normdata** simulates a standardized gene expression data and **unifdata** simulates a methylation microarray data. The *p*-values from the **RBM_T** function could be further adjusted using the **p.adjust** function in the **stats** package through the Bejamini-Hochberg method.

```
> library(RBM)
> normdata <- matrix(rnorm(1000*6, 0, 1), 1000, 6)
> mydesign <- c(0,0,0,1,1,1)
> myresult <- RBM_T(normdata, mydesign, 100, 0.05)
> summary(myresult)

      Length Class  Mode
ordfit_t     1000 -none- numeric
ordfit_pvalue 1000 -none- numeric
ordfit_beta0  1000 -none- numeric
ordfit_beta1  1000 -none- numeric
permutation_p 1000 -none- numeric
bootstrap_p    1000 -none- numeric

> sum(myresult$permutation_p<=0.05)
[1] 39

> which(myresult$permutation_p<=0.05)
[1]  22  37  55  56 130 133 163 184 198 227 245 261 298 310 318 320 326 361 474
[20] 476 496 580 600 635 648 698 717 731 757 767 773 802 809 848 930 940 955 961
[39] 977

> sum(myresult$bootstrap_p<=0.05)
[1] 19

> which(myresult$bootstrap_p<=0.05)
```

```

[1] 10 17 36 37 39 83 144 184 205 276 310 557 719 768 775 809 876 889 940

> permutation_adjp <- p.adjust(myresult$permutation_p, "BH")
> sum(permutation_adjp<=0.05)

[1] 4

> bootstrap_adjp <- p.adjust(myresult$bootstrap_p, "BH")
> sum(bootstrap_adjp<=0.05)

[1] 0

> unifdata <- matrix(runif(1000*7,0.10, 0.95), 1000, 7)
> mydesign2 <- c(0,0,0, 1,1,1,1)
> myresult2 <- RBM_T(unifdata,mydesign2,100,0.05)
> sum(myresult2$permutation_p<=0.05)

[1] 0

> sum(myresult2$bootstrap_p<=0.05)

[1] 20

> which(myresult2$bootstrap_p<=0.05)

[1] 24 27 53 79 105 119 175 270 278 287 371 383 494 660 696 734 805 934 976
[20] 980

> bootstrap2_adjp <- p.adjust(myresult2$bootstrap_p, "BH")
> sum(bootstrap2_adjp<=0.05)

[1] 0

```

- Examples using the RBM_F function: normdata_F simulates a standardized gene expression data and unifdata_F simulates a methylation microarray data. In both examples, we were interested in pairwise comparisons.

```

> normdata_F <- matrix(rnorm(1000*9,0,2), 1000, 9)
> mydesign_F <- c(0, 0, 0, 1, 1, 1, 2, 2, 2)
> aContrast <- c("X1-X0", "X2-X1", "X2-X0")
> myresult_F <- RBM_F(normdata_F, mydesign_F, aContrast, 100, 0.05)
> summary(myresult_F)

```

	Length	Class	Mode
ordfit_t	3000	-none-	numeric
ordfit_pvalue	3000	-none-	numeric
ordfit_beta1	3000	-none-	numeric
permutation_p	3000	-none-	numeric
bootstrap_p	3000	-none-	numeric

```

> sum(myresult_F$permutation_p[, 1]<=0.05)
[1] 39

> sum(myresult_F$permutation_p[, 2]<=0.05)
[1] 44

> sum(myresult_F$permutation_p[, 3]<=0.05)
[1] 50

> which(myresult_F$permutation_p[, 1]<=0.05)
[1] 57 59 89 99 144 191 198 259 261 284 286 295 330 359 365 368 381 402 481
[20] 514 521 560 567 609 632 693 742 743 802 805 807 821 846 896 956 973 979 984
[39] 995

> which(myresult_F$permutation_p[, 2]<=0.05)
[1] 57 59 99 144 191 198 261 270 284 286 295 320 330 344 359 368 402 473 481
[20] 514 517 521 544 560 567 584 609 632 685 693 742 777 802 805 807 821 846 865
[39] 927 956 973 979 984 995

> which(myresult_F$permutation_p[, 3]<=0.05)
[1] 49 57 59 99 144 191 198 259 261 270 284 286 295 320 330 343 344 365 368
[20] 381 402 441 473 481 482 514 517 521 546 560 567 605 609 685 693 742 777 802
[39] 805 807 846 865 896 927 947 956 973 979 984 995

> con1_adjp <- p.adjust(myresult_F$permutation_p[, 1], "BH")
> sum(con1_adjp<=0.05/3)

[1] 9

> con2_adjp <- p.adjust(myresult_F$permutation_p[, 2], "BH")
> sum(con2_adjp<=0.05/3)

[1] 3

> con3_adjp <- p.adjust(myresult_F$permutation_p[, 3], "BH")
> sum(con3_adjp<=0.05/3)

[1] 12

> which(con2_adjp<=0.05/3)

[1] 59 284 973

```

```

> which(con3_adjp<=0.05/3)

[1] 59 191 198 284 286 521 560 609 693 802 973 984

> unifdata_F <- matrix(runif(1000*18, 0.15, 0.98), 1000, 18)
> mydesign2_F <- c(rep(0, 6), rep(1, 6), rep(2, 6))
> aContrast <- c("X1-X0", "X2-X1", "X2-X0")
> myresult2_F <- RBM_F(unifdata_F, mydesign2_F, aContrast, 100, 0.05)
> summary(myresult2_F)

      Length Class  Mode
ordfit_t     3000  -none- numeric
ordfit_pvalue 3000  -none- numeric
ordfit_beta1 3000  -none- numeric
permutation_p 3000  -none- numeric
bootstrap_p   3000  -none- numeric

> sum(myresult2_F$bootstrap_p[, 1]<=0.05)

[1] 48

> sum(myresult2_F$bootstrap_p[, 2]<=0.05)

[1] 46

> sum(myresult2_F$bootstrap_p[, 3]<=0.05)

[1] 44

> which(myresult2_F$bootstrap_p[, 1]<=0.05)

[1] 17 57 69 91 98 107 109 113 181 184 194 234 239 241 290 343 351 371 388
[20] 401 419 426 435 453 461 463 464 591 598 600 601 607 609 665 703 745 767 769
[39] 801 834 845 859 864 886 897 909 913 936

> which(myresult2_F$bootstrap_p[, 2]<=0.05)

[1] 17 19 57 91 107 109 113 181 184 194 239 241 290 312 343 351 371 388 426
[20] 435 453 461 463 464 488 591 598 601 607 609 638 703 745 767 769 776 801 826
[39] 834 864 897 909 913 936 959 963

> which(myresult2_F$bootstrap_p[, 3]<=0.05)

[1] 17 57 91 98 107 109 113 181 184 239 241 290 343 351 371 388 426 435 453
[20] 461 463 464 488 591 600 601 607 665 703 716 741 767 769 801 826 834 845 859
[39] 864 897 909 913 936 969

```

```

> con21_adjp <- p.adjust(myresult2_F$bootstrap_p[, 1], "BH")
> sum(con21_adjp<=0.05/3)

[1] 6

> con22_adjp <- p.adjust(myresult2_F$bootstrap_p[, 2], "BH")
> sum(con22_adjp<=0.05/3)

[1] 4

> con23_adjp <- p.adjust(myresult2_F$bootstrap_p[, 3], "BH")
> sum(con23_adjp<=0.05/3)

[1] 7

```

4 Ovarian cancer methylation example using the RBM_T function

Two-group comparisons are the most common contrast in biological and biomedical field. The ovarian cancer methylation example is used to illustrate the application of `RBM_T` in identifying differentially methylated loci. The ovarian cancer methylation example is taken from the genome-wide DNA methylation profiling of United Kingdom Ovarian Cancer Population Study (UKOPS). This study used Illumina Infinium 27k Human DNA methylation Beadchip v1.2 to obtain DNA methylation profiles on over 27,000 CpGs in whole blood cells from 266 ovarian cancer women and 274 age-matched healthy controls. The data are downloaded from the NCBI GEO website with access number GSE19711. For illustration purpose, we chose the first 1000 loci in 8 randomly selected women with 4 ovarian cancer cases (pre-treatment) and 4 healthy controls. The following codes show the process of generating significant differential DNA methylation loci using the `RBM_T` function and presenting the results for further validation and investigations.

```

> system.file("data", package = "RBM")
[1] "/private/tmp/Rtmpx6t6ju/Rinst10a2861f822b5/RBM/data"

> data(ovarian_cancer_methylation)
> summary(ovarian_cancer_methylation)

   IlmnID        Beta      exmdata2[, 2]      exmdata3[, 2]
cg00000292: 1  Min. :0.01058  Min. :0.01187  Min. :0.009103
cg00002426: 1  1st Qu.:0.04111  1st Qu.:0.04407  1st Qu.:0.041543
cg00003994: 1  Median :0.08284  Median :0.09531  Median :0.087042
cg00005847: 1  Mean   :0.27397  Mean   :0.28872  Mean   :0.283729
cg00006414: 1  3rd Qu.:0.52135  3rd Qu.:0.59032  3rd Qu.:0.558575
cg00007981: 1  Max.   :0.97069  Max.   :0.96937  Max.   :0.970155
(Other)    :994          NA's   :4
exmdata4[, 2]  exmdata5[, 2]  exmdata6[, 2]  exmdata7[, 2]
Min.   :0.01019  Min.   :0.01108  Min.   :0.01937  Min.   :0.01278
1st Qu.:0.04092 1st Qu.:0.04059  1st Qu.:0.05060  1st Qu.:0.04260

```

```

Median :0.09042   Median :0.08527   Median :0.09502   Median :0.09362
Mean   :0.28508   Mean   :0.28482   Mean   :0.27348   Mean   :0.27563
3rd Qu.:0.57502   3rd Qu.:0.57300   3rd Qu.:0.52099   3rd Qu.:0.52240
Max.   :0.96658   Max.   :0.97516   Max.   :0.96681   Max.   :0.95974
NA's    :1

exmdata8[, 2]
Min.   :0.01357
1st Qu.:0.04387
Median :0.09282
Mean   :0.28679
3rd Qu.:0.57217
Max.   :0.96268

> ovarian_cancer_data <- ovarian_cancer_methylation[, -1]
> label <- c(1, 1, 0, 0, 1, 1, 0, 0)
> diff_results <- RBM_T(aData=ovarian_cancer_data, vec_trt=label, repetition=100, alpha=0.05)
> summary(diff_results)

      Length Class  Mode
ordfit_t     1000  -none- numeric
ordfit_pvalue 1000  -none- numeric
ordfit_beta0  1000  -none- numeric
ordfit_beta1  1000  -none- numeric
permutation_p 1000  -none- numeric
bootstrap_p   1000  -none- numeric

> sum(diff_results$ordfit_pvalue<=0.05)
[1] 45

> sum(diff_results$permutation_p<=0.05)
[1] 47

> sum(diff_results$bootstrap_p<=0.05)
[1] 66

> ordfit_adjp <- p.adjust(diff_results$ordfit_pvalue, "BH")
> sum(ordfit_adjp<=0.05)
[1] 0

> perm_adjp <- p.adjust(diff_results$permutation_p, "BH")
> sum(perm_adjp<=0.05)
[1] 0

```

```

> boot_adjp <- p.adjust(diff_results$bootstrap_p, "BH")
> sum(boot_adjp<=0.05)

[1] 2

> diff_list_perm <- which(perm_adjp<=0.05)
> diff_list_boot <- which(boot_adjp<=0.05)
> sig_results_perm <- cbind(ovarian_cancer_methylation[, diff_results$ordfit_t])
> print(sig_results_perm)

[1] IlmnID
[2] Beta
[3] exmdata2[, 2]
[4] exmdata3[, 2]
[5] exmdata4[, 2]
[6] exmdata5[, 2]
[7] exmdata6[, 2]
[8] exmdata7[, 2]
[9] exmdata8[, 2]
[10] diff_results$ordfit_t[, diff_list_perm]
[11] diff_results$permutation_p[, diff_list_perm]
<0 rows> (or 0-length row.names)

> sig_results_boot <- cbind(ovarian_cancer_methylation[, diff_results$ordfit_t])
> print(sig_results_boot)

      IlmnID      Beta exmdata2[, 2] exmdata3[, 2] exmdata4[, 2]
83  cg00072216 0.04505377    0.04598964    0.04000674    0.03231534
743 cg00717862 0.07999436    0.07873347    0.06089359    0.06171374
          exmdata5[, 2] exmdata6[, 2] exmdata7[, 2] exmdata8[, 2]
83      0.04965089    0.04833366    0.03466159    0.04390894
743      0.07594936    0.09062161    0.06475791    0.07271878
      diff_results$ordfit_t[, diff_list_boot]
83                      2.514109
743                      3.444684
      diff_results$bootstrap_p[, diff_list_boot]
83                          0
743                          0

```