

Package ‘rcellminer’

July 22, 2017

Type Package

Title rcellminer: Molecular Profiles and Drug Response for the NCI-60 Cell Lines

Version 1.8.0

Date 2016-01-27

Author Augustin Luna, Vinodh Rajapakse, Fabricio Sousa

Maintainer

Augustin Luna <lunaa@cbio.mskcc.org>, Vinodh Rajapakse <vinodh.rajapakse@nih.gov>

Description The NCI-60 cancer cell line panel has been used over the course of several decades as an anti-cancer drug screen. This panel was developed as part of the Developmental Therapeutics Program (DTP, <http://dtp.nci.nih.gov/>) of the U.S. National Cancer Institute (NCI). Thousands of compounds have been tested on the NCI-60, which have been extensively characterized by many platforms for gene and protein expression, copy number, mutation, and others (Reinhold, et al., 2012). The purpose of the CellMiner project (<http://discover.nci.nih.gov/cellminer>) has been to integrate data from multiple platforms used to analyze the NCI-60 and to provide a powerful suite of tools for exploration of NCI-60 data.

License LGPL-3

LazyData true

Imports stringr, gplots, methods, shiny

Depends R (>= 3.2), Biobase, rcdk, fingerprint, rcellminerData

Suggests knitr, RColorBrewer, sqldf, BiocGenerics, testthat, BiocStyle, jsonlite

URL <http://discover.nci.nih.gov/cellminer/>

VignetteBuilder knitr

biocViews aCGH, CellBasedAssays, CopyNumberVariation, GeneExpression, Pharmacogenomics, Pharmacogenetics, miRNA, Cheminformatics, Visualization, Software, SystemsBiology

NeedsCompilation no

R topics documented:

cmVersion 3

compareFingerprints	4
crossCors	4
crossCorsSpearman	5
DrugData	6
DrugData,eSet,eSet,MIAXE-method	6
DrugData-class	7
drugDB	7
Drug_MOA_Key	8
eINetMolDataNCI60	8
fingerprintList	9
getAct	9
getAct,DrugData-method	10
getActivityRangeStats	10
getAllFeatureData	11
getAllFeatureData,MolData-method	11
getBinaryMutationData	12
getColumnQuantiles	13
getDrugActivityData	13
getDrugActivityRange	14
getDrugActivityRepeatData	14
getDrugMoaList	15
getDrugName	16
getESetList	16
getESetList,MolData-method	17
getFeatureAnnot	17
getFeatureAnnot,DrugData-method	18
getFeatureAnnot,MolData-method	18
getFeatureDataFromMatList	19
getFingerprintList	19
getMedSenLineActivity	20
getMinDrugActivityRepeatCor	21
getMoaStr	21
getMoaToCompounds	22
getMolDataMatrices	22
getMolDataType	23
getNumDrugActivityRepeats	23
getNumMissingLines	24
getRepeatAct	24
getRepeatAct,DrugData-method	25
getRsd	25
getSampleData	26
getSampleData,DrugData-method	26
getSampleData,MolData-method	27
getSmiles	27
hasMoa	28
initialize,DrugData-method	28
initialize,MolData-method	29
isPublic	29
loadCellminerPlotInfo	30
loadNciColorSet	30
MolData	31
MolData,list,MIAXE-method	31

MolData-class	32
passRuleOf5	32
passRuleOf5FromNsc	33
patternComparison	33
plotCellMiner	34
plotDrugActivityRepeats	35
plotDrugSets	36
plotStructures	36
plotStructuresFromNscs	37
rcdkplot	38
removeMolDataType	39
restrictFeatureMat	39
rowCors	40
runShinyApp	41
runShinyComparePlots	41
runShinyCompareStructures	42
runShinyCompoundBrowser	43
searchForNscs	43
selectCorrelatedRows	44
selectCorrelatedRowsFromMatrices	44
[[,MolData-method	45
[[<-,MolData-method	46
Index	47

cmVersion

CellMiner Version

Description

CellMiner Version

Details

The version of CellMiner used

Author(s)

Vinodh Rajapakse <vinodh.rajapakse AT nih.gov>

References

<http://discover.nci.nih.gov/cellminer>

compareFingerprints *Compare Structure Fingerprints to NCI DTP Compounds*

Description

This function compares the first SMILES structure to all other structures given.

Usage

```
compareFingerprints(ids = NULL, smiles = NULL, fpType = "standard",  
  verbose = TRUE, fingerprint.list = NULL)
```

Arguments

`ids` a vector of IDs corresponding to structures
`smiles` a vector of strings SMILES structures
`fpType` the type of fingerprint to be used; uses the RCDK `get.fingerprint()` (default: standard)
`verbose` a boolean whether to display debugging information
`fingerprint.list` a list of fingerprints generated with `getFingerprintList`

Value

a sorted named vector of Tanimoto distances

See Also

`rdk::get.fingerprint`

Examples

```
drugAnnot <- as(featureData(getAct(rcellminerData::drugData)), "data.frame")  
ids <- head(drugAnnot$NSC)  
smiles <- head(drugAnnot$SMILES)  
fingerprintList <- getFingerprintList(ids, smiles)  
compareFingerprints(fingerprint.list=fingerprintList)
```

crossCors *Calculate cross-correlations with between rows of input matrices*

Description

Calculate cross-correlations with between rows of input matrices

Usage

```
crossCors(X, Y = NULL, method = "pearson")
```

Arguments

X	a matrix or data.frame
Y	a matrix or data.frame
method	a string specifying the type of correlation, chosen from pearson (default) or spearman.

Value

a list containing matrices of pairwise correlations and their p-values between rows of the input matrices or dataframes.

Author(s)

Sudhir Varma, NCI-LMP, with input checks, support for Spearman's correlation added by VNR.

Examples

```
drugActData <- exprs(getAct(rcellminerData::drugData))
crossCors(drugActData[c("94600"), ], drugActData[c("727625", "670655"), ])
crossCors(drugActData[c("94600"), ], drugActData[c("727625", "670655"), ], method="spearman")
```

crossCorsSpearman	<i>Calculate Spearman's correlations with between rows of input matrices</i>
-------------------	--

Description

Calculate Spearman's correlations with between rows of input matrices

Usage

```
crossCorsSpearman(X, Y = NULL)
```

Arguments

X	a matrix or data.frame
Y	a matrix or data.frame

Value

a list containing matrices of pairwise Spearman's correlations and their p-values between rows of the input matrices or dataframes.

Examples

```
## Not run:
crossCorsSpearman(drugActData[c("94600"), ], drugActData[c("727625", "670655"), ])

## End(Not run)
```

DrugData *Returns a DrugData object.*

Description

Returns a DrugData object.

Usage

DrugData(act, repeatAct, sampleData, ...)

Arguments

act	An eSet object containing drug activity data across a set of biological samples.
repeatAct	An eSet object containing repeat drug activity experiment data with respect to the same samples associated with act.
sampleData	A MIAxE object capturing sample and other data set information.
...	Other possible parameters.

Value

A DrugData object.

DrugData,eSet,eSet,MIAxE-method
Returns a DrugData object.

Description

Returns a DrugData object.

Usage

```
## S4 method for signature 'eSet,eSet,MIAxE'
DrugData(act, repeatAct, sampleData, ...)
```

Arguments

act	An eSet object containing drug activity data across a set of biological samples.
repeatAct	An eSet object containing repeat drug activity experiment data with respect to the same samples associated with act.
sampleData	A MIAxE object capturing sample and other data set information.
...	Other possible parameters.

Value

A DrugData object.

DrugData-class	<i>An S4 class to represent drug activity and related data recorded for a set of biological samples.</i>
----------------	--

Description

An S4 class to represent drug activity and related data recorded for a set of biological samples.

Arguments

... Other possible parameters.

Slots

act An eSet object containing drug activity data across a set of biological samples.

repeatAct An eSet object containing repeat drug activity experiment data with respect to the same samples associated with act.

sampleData A MIAxE object capturing sample and other data set information.

drugDB	<i>CellMiner Drug Response Values</i>
--------	---------------------------------------

Description

CellMiner Drug Response Values

Details

A list containing response values and annotations:

- act Z-scores of the averaged negative log GI (growth inhibition) 50 values across repeats for the NCI-60; assay described here: <http://dtp.nci.nih.gov/branches/btb/ivclsp.html>
- annot
 - id Dataset identifier; NOTE: DO NOT use this column; the NSC is the primary drug identifier
 - nsc National Service Center identifier; the primary drug identifier
 - name Compound name
 - brand_name Brand name for the compound, if sold commercially
 - formula Compound chemical formula
 - testing_status Information on whether it is known if the compound is FDA approved or undergoing testing in clinical trials
 - source TODO
 - smiles Compound chemical structure as a SMILES string
 - weight Compound chemical weight in g/mol
 - mechanism Pharmacological mechanism of action
 - confidential_flag A flag to indicate if compound information is public
 - total_probes TODO

- total_good_probes TODO
- low_correlations TODO
- failure_reason TODO
- cas CAS Registry Number; NOTE: Due to data restrictions PubChem IDs are the preferred mapping ID to other datasets
- pubchem_id PubChem ID

Author(s)

Vinodh Rajapakse <vinodh.rajapakse AT nih.gov>

References

<http://discover.nci.nih.gov/cellminer/loadDownload.do>

Drug_MOA_Key	<i>A data frame with descriptive information for all compound mechanism of action (MOA) abbreviations used in CellMiner.</i>
--------------	--

Description

A data frame with descriptive information for all compound mechanism of action (MOA) abbreviations used in CellMiner.

e1NetMolDataNCI60	<i>NCI60 Molecular Data</i>
-------------------	-----------------------------

Description

Z-scores of values for a variety of assays conducted on the NCI-60 to facilitate comparison. Z-scores calculated over the 60 cell lines for the given feature.

Details

A list containing various assay values:

- cop Copy number values; Described in Pubmed ID: 24670534
- exp Expression values; Obtained from "RNA: 5 Platform Gene Transcript" <http://discover.nci.nih.gov/cellminer/loadDownload.do>; Missing values imputed using the R package "impute"
- mut Mutation values; Deleterious mutations obtained from TODO
- mir MicroRNA values; Obtained from "RNA: Agilent Human microRNA (V2)" <http://discover.nci.nih.gov/cellminer/loadDownload.do>
- pro Reverse protein lysate array values; Obtain from "Protein: Lysate Array" <http://discover.nci.nih.gov/cellminer/loadDownload.do>
- mda NCI-60 metadata.
 - CNV_GAIN Proportion of genome copy number gains; Described in Pubmed ID: 24670534
 - CNV_LOSS Proportion of genome copy number losses; Described in Pubmed ID: 24670534

- CNV_TOTAL Sum of CNV_GAIN and CNV_LOSS
- P53_BIN Binary TP53 profile curated by William Reinhold
- MSI_OGAN_BIN Binary microsatellite instability (MSI) profile curated by Ogan Abaan using COSMIC data; Obtained from Supplementary Table 1 - Ogan Whole Exome Sequencing (WES) paper in Cancer Res.
- EPITHELIAL Epithelial by tissue of origin - pattern extracted from the CellMiner cell line metadata <http://discover.nci.nih.gov/cellminer/celllineMetadata.do>
- EPITHELIAL_KURT Kurt Kohn curation for epithelial-like cell lines based on molecular parameters described in Pubmed ID: 24940735
- DELETERIOUS Total deleterious variants from WES dataset; Fabricio Sousa curation
- MISSENSE Total missense variants from WES dataset; Fabricio Sousa curation
- SILENT Total silent variants from WES dataset; Fabricio Sousa curation
- TOTAL_AA Total amino acid changing variants from WES dataset; Fabricio Sousa curation
- CELL-CELL Cell-to-cell adhesion curated by William Reinhold
- DOUBLINGTIME The doubling time pattern was extracted from the CellMiner cell line metadata <http://discover.nci.nih.gov/cellminer/celllineMetadata.do>

Author(s)

Vinodh Rajapakse <vinodh.rajapakse AT nih.gov>

References

<http://discover.nci.nih.gov/cellminer>

fingerprintList	<i>A list of pre-computed fingerprints using getFingerprintList()</i>
-----------------	---

Description

A list of pre-computed fingerprints using getFingerprintList()

getAct	<i>Returns an eSet object with drug activity data.</i>
--------	--

Description

Returns an eSet object with drug activity data.

Usage

```
getAct(object, ...)
```

Arguments

object	Object for which drug activity data is to be returned.
...	Other possible parameters.

Value

An eSet object with drug activity data.

getAct,DrugData-method

Returns an eSet object with drug activity data.

Description

Returns an eSet object with drug activity data.

Usage

```
## S4 method for signature 'DrugData'
getAct(object)
```

Arguments

object DrugData object for which drug activity data is to be returned.

Value

An eSet object with drug activity data.

getActivityRangeStats *Returns a table of activity range statistics for a set of compounds.*

Description

Returns a table of activity range statistics for a set of compounds.

Usage

```
getActivityRangeStats(nscSet, concFormat = "NegLogGI50M",
  onlyCellMinerExps = TRUE)
```

Arguments

nscSet a character vector specifying NSC identifier(s) for compound(s) of interest.
 concFormat a string selected from "NegLogGI50M" or "IC50MicroM". "NegLogGI50M" specifies activities as the negative log of the 50 inhibitory concentration (molar). "IC50MicroM" specifies activities as the 50 inhibitory concentration (micromolar).
 onlyCellMinerExps a logical value indicating whether to only return experimental data included in CellMiner (default=TRUE).

Value

a table of activity range statistics for a set of compounds.

Examples

```
nscSet <- c("609699", "740")
getActivityRangeStats(nscSet)
getActivityRangeStats(nscSet, concFormat="IC50MicroM")
```

getAllFeatureData *Returns a list of feature data matrices.*

Description

Returns a list of feature data matrices.

Usage

```
getAllFeatureData(object, ...)
```

Arguments

object Object for which a list of feature data matrices is to be returned.
... Other possible parameters.

Value

A list of feature data matrices.

getAllFeatureData, MolData-method
Returns a list of feature data matrices.

Description

Returns a list of feature data matrices.

Usage

```
## S4 method for signature 'MolData'
getAllFeatureData(object)
```

Arguments

object MolData object for which a list of feature data matrices is to be returned.

Value

A list of feature data matrices.

getBinaryMutationData *Compute a binary gene mutation data matrix from SNP and other mutation event-level data.*

Description

Compute a binary gene mutation data matrix from SNP and other mutation event-level data.

Usage

```
getBinaryMutationData(mutInfo, mutData, maxVariantFreq = 0.2,
  maxNormalPopulationFreq = 0.005, maxSiftScore = 0.05,
  minPolyPhenScore = 0.85)
```

Arguments

- | | |
|-------------------------|---|
| mutInfo | A data frame with the following named columns: Gene, the name of the gene associated with the mutation event; probe.ids, a unique identifier specifying the mutation event; SNP_1000_genome, the frequency of the mutation event in SNP 1000; ESP5400, the frequency of the mutation event in ESP5400; SNP_type, the type of mutation event, chosen from "MISSENSE", "FRAMESHIFT", "NON-FRAMESHIFT", "NONSENSE", "SPLICING"; SIFT_score, the SIFT score; Polyphen_score, the POLYPHEN score. Rownames of mutInfo should be set to probe.ids, i.e., the unique mutation event specifier. |
| mutData | A matrix with event level mutation information, with SNPs, etc. along rows and samples along columns. Rownames of mutData should exactly match those of mutInfo. The i-th row of mutInfo should thus give detailed information for the mutation event with data specified in the i-th row of mutData. |
| maxVariantFreq | The maximum proportion of mutant samples (used to exclude frequently occurring events); default value = 0.2. |
| maxNormalPopulationFreq | The maximum frequency of a mutation in the normal population (used to exclude likely germline variants); default value = 0.005. |
| maxSiftScore | The maximum accepted SIFT score (used to exclude presumed non-deleterious mutations); default value = 0.05. |
| minPolyPhenScore | The minimum accepted POLYPHEN score (used to exclude presumed non-deleterious mutations); default value = 0.85. |

Value

A binary gene mutation matrix, with genes along rows, samples along columns, and 1s indicating deleterious mutations.

getColumnQuantiles *Calculate quantile for the columns in a matrix*

Description

Calculate quantile for the columns in a matrix

Usage

```
getColumnQuantiles(X, prob, naRm = FALSE, onlyNonzeroVals = FALSE)
```

Arguments

X	the matrix
prob	a numeric probability
naRm	a boolean, whether to remove NAs
onlyNonzeroVals	a boolean, whether to only include non-zero values

Value

a vector of quantiles

Examples

```
getColumnQuantiles(matrix(1:25, nrow=5), prob = 0.5)
```

getDrugActivityData *Returns a matrix containing activity (-logGI50) data for a set of compounds.*

Description

Returns a matrix containing activity (-logGI50) data for a set of compounds.

Usage

```
getDrugActivityData(nscSet, onlyCellMinerExps = TRUE)
```

Arguments

nscSet	A string specifying the NSC identifiers for the compounds.
onlyCellMinerExps	A logical value indicating whether to compute results using only experimental data included in CellMiner (default=TRUE).

Value

a matrix with NCI-60 average (over experiments) -logGI50 activity data; compound activity profiles are along rows.

Examples

```
nscSet <- c("141540", "123127") # Etoposide, Doxorubicin.  
actData <- getDrugActivityData(nscSet)
```

getDrugActivityRange *Returns a vector of log activity range values for set of compounds.*

Description

Returns a vector of log activity range values for set of compounds.

Usage

```
getDrugActivityRange(nscSet, computeIQR = FALSE)
```

Arguments

nscSet	a character vector specifying NSC identifier(s) for compound(s) of interest.
computeIQR	logical value indicated whether inter-quartile range is to be computed; otherwise absolute range is computed (default=FALSE).

Value

a numeric vector of NCI-60 log activity (-logGI50) range values indexed by the identifiers in nscSet.

Examples

```
nscSet <- c("609699", "740")  
getDrugActivityRange(nscSet)
```

getDrugActivityRepeatData
Returns a matrix containing repeat activity experiment data for a compound.

Description

Returns a matrix containing repeat activity experiment data for a compound.

Usage

```
getDrugActivityRepeatData(nscStr, concFormat = "NegLogGI50M",  
onlyCellMinerExps = TRUE)
```

Arguments

nscStr	a string specifying the NSC identifier for the compound.
concFormat	a string selected from "NegLogGI50M" or "IC50MicroM". "NegLogGI50M" specifies activities as the negative log of the 50 inhibitory concentration (molar). "IC50MicroM" specifies activities as the 50 growth inhibitory concentration (micromolar).
onlyCellMinerExps	a logical value indicating whether to only return experimental data included in CellMiner (default=TRUE).

Value

a matrix with activity data from each experiment associated with a compound organized along the rows.

Examples

```
nscStr <- "609699"  
actData <- getDrugActivityRepeatData(nscStr, concFormat='NegLogGI50M')  
actData <- getDrugActivityRepeatData(nscStr, concFormat='IC50MicroM')
```

getDrugMoaList	<i>Get a list of applicable MOA strings for a drug.</i>
----------------	---

Description

Get a list of applicable MOA strings for a drug.

Usage

```
getDrugMoaList(nsc, moaToCompoundListMap = NULL)
```

Arguments

nsc	An NSC string.
moaToCompoundListMap	A named list of character vectors, with each name indicating an MOA class, and its corresponding character vector specifying MOA-associated drugs. If unspecified, this is constructed based on MOA information provided by CellMiner.

Details

[LINK TO MOAs?](#)

Value

A character vector giving all MOA classes for the drug.

Examples

```
getDrugMoaList("754365")
```

`getDrugName` *Get the drug names for a set of NSC identifiers.*

Description

Get the drug names for a set of NSC identifiers.

Usage

```
getDrugName(nscSet)
```

Arguments

`nscSet` A character vector of NSC strings

Value

A named character vector indicating the compound names for each NSC in `nscSet` (with an empty string returned if no such information is available, and an NA returned if the NSC is not included in the CellMiner database).

Examples

```
nscSet <- c("609699", "94600")
getDrugName(nscSet)
```

`getESetList` *Returns a list of eSet objects.*

Description

Returns a list of eSet objects.

Usage

```
getESetList(object, ...)
```

Arguments

`object` Object for which a list of eSets is to be returned.
... Other possible parameters.

Value

A list of eSet objects.

getESetList,MolData-method

Returns a list of eSet objects.

Description

Returns a list of eSet objects.

Usage

```
## S4 method for signature 'MolData'  
getESetList(object)
```

Arguments

object MolData object for which a list of eSet objects is to be returned.

Value

A list of eSet objects.

getFeatureAnnot

Returns a list of data frames with feature information.

Description

Returns a list of data frames with feature information.

Usage

```
getFeatureAnnot(object, ...)
```

Arguments

object Object for which feature data is to be returned.
... Other possible parameters.

Value

A list of data frames with feature information.

getFeatureAnnot,DrugData-method

Returns a list of data frames with feature information.

Description

Returns a list of data frames with feature information.

Usage

```
## S4 method for signature 'DrugData'  
getFeatureAnnot(object)
```

Arguments

object DrugData object for which feature data is to be returned.

Value

A named list of data frames with feature information for drugs and drug repeat experiments.

getFeatureAnnot,MolData-method

Returns a list of data frames with feature information.

Description

Returns a list of data frames with feature information.

Usage

```
## S4 method for signature 'MolData'  
getFeatureAnnot(object)
```

Arguments

object MolData object for which feature data is to be returned.

Value

A named list of data frames with feature information for available molecular data types.

getFeatureDataFromMatList

Extract from a list of matrices the data associated with a set of features.

Description

Extract from a list of matrices the data associated with a set of features.

Usage

```
getFeatureDataFromMatList(featureSet, dataMatList,  
  excludeMissingFeatures = TRUE)
```

Arguments

featureSet a character vector of feature names.
dataMatList a list of matrices with feature data organized along the rows, and feature names accessible via `rownames(dataMatList)`.
excludeMissingFeatures a logical value indicating whether features whose data cannot be found in any matrices in `dataMatList` should be excluded in the output. (default=TRUE).

Value

a single matrix containing data for all features in `featureSet`.

Examples

```
featureSet <- c("expSLFN11", "mutSLX4")  
molDataMats <- getMolDataMatrices()  
featureData <- getFeatureDataFromMatList(featureSet, molDataMats)
```

getFingerprintList *Get a list of fingerprints for a set of compounds*

Description

Get a list of fingerprints for a set of compounds

Usage

```
getFingerprintList(ids, smiles, fpType = "standard", verbose = TRUE)
```

Arguments

ids a vector of IDs corresponding to structures
smiles a vector of strings SMILES structures
fpType the type of fingerprint to be used; uses the RCDK `get.fingerprint()` (default: standard)
verbose show debugging output

Value

a list of fingerprints returned from RCDC where the list names are the IDs

See Also

rcdk::get.fingerprint

Examples

```
drugAnnot <- as(featureData(getAct(rcellminerData::drugData)), "data.frame")
ids <- head(drugAnnot$NSC)
smiles <- head(drugAnnot$SMILES)
fingerprintList <- getFingerprintList(ids, smiles)

## Not run:
# All fingerprints
ids <- drugAnnot$NSC
smiles <- drugAnnot$SMILES
fingerprintList <- getFingerprintList(ids, smiles)
save(fingerprintList, file="fingerprintList.RData")

## End(Not run)
```

`getMedSenLineActivity` *Returns a vector of median sensitive cell line activity (-logGI50) values for a set of compounds.*

Description

Returns a vector of median sensitive cell line activity (-logGI50) values for a set of compounds.

Usage

```
getMedSenLineActivity(idSet, senLineActZThreshold = 0.5,
  onlyCellMinerExps = TRUE, dataSource = "NCI60")
```

Arguments

`idSet` a character vector specifying identifier(s) for compound(s) of interest.

`senLineActZThreshold` the minimum activity z-score for a sensitive cell line (default=0.5).

`onlyCellMinerExps` a logical value indicating whether to base results strictly on experimental data included in CellMiner (default=TRUE).

`dataSource` character string indicating data source (default="NCI60"). Currently only "NCI60" is supported.

Value

a numeric vector of median sensitive cell line activity (-logGI50) values indexed by the identifiers in `idSet`.

Examples

```
idSet <- c("609699", "740")
getMedSenLineActivity(idSet)
```

```
getMinDrugActivityRepeatCor
```

Returns a table indicating, for each compound in a specified set, the least significant correlation and associated p-value between its replicate experiments.

Description

Returns a table indicating, for each compound in a specified set, the least significant correlation and associated p-value between its replicate experiments.

Usage

```
getMinDrugActivityRepeatCor(nscSet)
```

Arguments

nscSet a character vector specifying NSC identifier(s) for compound(s) of interest.

Value

a dataframe containing the following columns: NSC, cor, pval

Examples

```
nscSet <- c("123528", "339316")
repExpCorTab <- getMinDrugActivityRepeatCor(nscSet)
```

```
getMoaStr
```

Get MOA string

Description

Get MOA string

Usage

```
getMoaStr(nscStr)
```

Arguments

nscStr an NSC string

Details

[LINK TO MOAs?](#)

Value

a comma-delimited string with MOA

Examples

```
getMoaStr("94600")
getMoaStr(c("94600", "609699"))
```

getMoaToCompounds	<i>Get a named list mapping MOA classes to associated compound sets.</i>
-------------------	--

Description

Get a named list mapping MOA classes to associated compound sets.

Usage

```
getMoaToCompounds()
```

Value

a named list mapping MOA classes to associated compound sets (each represented as a character vector).

Examples

```
moaToCompounds <- getMoaToCompounds()
```

getMolDataMatrices	<i>Returns a list of molecular data type matrices, with rownames in each matrix prefixed with a data type abbreviation.</i>
--------------------	---

Description

Returns a list of molecular data type matrices, with rownames in each matrix prefixed with a data type abbreviation.

Usage

```
getMolDataMatrices(molDataMats = NULL)
```

Arguments

molDataMats	A named list of molecular data type matrices with feature data specified along the rows, and feature names indicated in the row names.
-------------	--

Value

a list containing molecular data type matrices, with rownames in each matrix prefixed with a data type abbreviation, e.g., 'exp' for mRNA expression, etc. The matrix-specific data type abbreviations are derived from the names of molDataMats.

Examples

```
molDataMats <- getMolDataMatrices()
```

getMolDataType	<i>Get the molecular data type prefixes for a set of features.</i>
----------------	--

Description

Get the molecular data type prefixes for a set of features.

Usage

```
getMolDataType(features, prefixLen = 3)
```

Arguments

features	A vector of features.
prefixLen	The length of the molecular data type prefix.

Value

A character vector of molecular data type prefixes.

#'

Examples

```
getMolDataType(c("expTP53", "copMDM2", "mutCHEK2", "mutBRAF"))
```

getNumDrugActivityRepeats	<i>Returns a vector indicating the number of drug activity repeat experiments with available data for each member of a set of compounds.</i>
---------------------------	--

Description

Returns a vector indicating the number of drug activity repeat experiments with available data for each member of a set of compounds.

Usage

```
getNumDrugActivityRepeats(nscSet, onlyCellMinerExps = TRUE)
```

Arguments

nscSet	a character vector specifying NSC identifier(s) for compound(s) of interest.
onlyCellMinerExps	a logical value indicating whether to return only the number of experiments with data included in CellMiner (default=TRUE).

Value

a numeric vector, indexed by nscSet, indicating the number of drug activity repeat experiments for each one of its compounds.

Examples

```
nscSet <- c("1", "17", "89", "609699")
getNumDrugActivityRepeats(nscSet)
```

getNumMissingLines	<i>Returns a vector indicating the number of NCI-60 cell lines with missing activity data for set of compounds.</i>
--------------------	---

Description

Returns a vector indicating the number of NCI-60 cell lines with missing activity data for set of compounds.

Usage

```
getNumMissingLines(nscSet)
```

Arguments

nscSet a character vector specifying NSC identifier(s) for compound(s) of interest.

Value

a numeric vector indicating the number of NCI-60 cell lines with missing activity data, indexed by the identifiers in nscSet.

Examples

```
nscSet <- c("1", "17", "89", "609699")
getNumMissingLines(nscSet)
```

getRepeatAct	<i>Returns an eSet object with drug repeat activity experiment data.</i>
--------------	--

Description

Returns an eSet object with drug repeat activity experiment data.

Usage

```
getRepeatAct(object, ...)
```

Arguments

object Object for which drug repeat activity experiment data is to be returned.
... Other possible parameters.

Value

An eSet object with drug repeat activity experiment data.

```
getRepeatAct,DrugData-method
```

Returns an eSet object with drug repeat activity experiment data.

Description

Returns an eSet object with drug repeat activity experiment data.

Usage

```
## S4 method for signature 'DrugData'
getRepeatAct(object)
```

Arguments

object DrugData object for which drug repeat activity experiment data is to be returned.

Value

An eSet object with drug repeat activity experiment data.

```
getRsd
```

Computes the relative standard deviation values with respect to the columns of a matrix or data.frame.

Description

Computes the relative standard deviation values with respect to the columns of a matrix or data.frame.

Usage

```
getRsd(dat, onlyReturnMedian = TRUE)
```

Arguments

dat a matrix or data.frame with numeric values.

onlyReturnMedian

a logical value indicating whether only the median column RSD value should be returned (vs. all RSD values).

Value

median RSD value over the data set columns or all RSD values, depending on value of onlyReturnMedian (default=TRUE).

Examples

```
A <- matrix(rnorm(10*60), nrow=10)
getRsd(A)
getRsd(A, onlyReturnMedian=FALSE)
```

<code>getSampleData</code>	<i>Returns a data frame with sample information.</i>
----------------------------	--

Description

Returns a data frame with sample information.

Usage

```
getSampleData(object, ...)
```

Arguments

<code>object</code>	Object for which sample data is to be returned.
<code>...</code>	Other possible parameters.

Value

A data frame with sample information.

<code>getSampleData,DrugData-method</code>	<i>Returns a data frame with sample information.</i>
--	--

Description

Returns a data frame with sample information.

Usage

```
## S4 method for signature 'DrugData'  
getSampleData(object)
```

Arguments

<code>object</code>	DrugData object for which sample data is to be returned.
---------------------	--

Value

A data frame with sample information.

getSampleData,MolData-method

Returns a data frame with sample information.

Description

Returns a data frame with sample information.

Usage

```
## S4 method for signature 'MolData'  
getSampleData(object)
```

Arguments

object MolData object for which sample data is to be returned.

Value

A data frame with sample information.

getSmiles

Get the SMILES strings for a set of NSC identifiers.

Description

Get the SMILES strings for a set of NSC identifiers.

Usage

```
getSmiles(nscSet)
```

Arguments

nscSet A character vector of NSC strings

Value

A named character vector indicating the SMILES string for each NSC in nscSet (or NA if no structural information is available).

Examples

```
nscSet <- c("609699", "94600")  
getSmiles(nscSet)
```

hasMoa	<i>Check if NSC has Mechanism of Action (MOA) Annotation</i>
--------	--

Description

Check if NSC has Mechanism of Action (MOA) Annotation

Usage

```
hasMoa(nsc)
```

Arguments

nsc	a string, an NSC identifier
-----	-----------------------------

Value

a boolean whether the NSC has an MOA

Examples

```
hasMoa("754365")
```

initialize,DrugData-method	<i>Returns a DrugData object.</i>
----------------------------	-----------------------------------

Description

Returns a DrugData object.

Usage

```
## S4 method for signature 'DrugData'
initialize(.Object, act, repeatAct, sampleData)
```

Arguments

.Object	An object: see "new()" documentation in "methods" package.
act	An eSet object containing drug activity data across a set of biological samples.
repeatAct	An eSet object containing repeat drug activity experiment data with respect to the same samples associated with act.
sampleData	A MIAXE object capturing sample and other data set information.

Value

A DrugData object.

Note

Seems to be required for definition of a constructor.

initialize,MolData-method
Returns a MolData object.

Description

Returns a MolData object.

Usage

```
## S4 method for signature 'MolData'  
initialize(.Object, eSetList, sampleData)
```

Arguments

.Object An object: see "new()" documentation in "methods" package.
eSetList A list of eSet objects for a common set of samples.
sampleData A MIAxE object capturing sample and other data set information.

Value

A MolData object.

isPublic *Check if an NSC ID is public*

Description

Check if an NSC ID is public

Usage

```
isPublic(nscs)
```

Arguments

nscs a vector of NSC string IDs

Value

a vector of boolean values of whether each NSC is public

Examples

```
isPublic("-1")  
isPublic(c("-1", "609699"))
```

loadCellminerPlotInfo *Returns data to plot CellMiner plots*

Description

Returns data to plot CellMiner plots

Usage

```
loadCellminerPlotInfo(returnDf = FALSE)
```

Arguments

returnDf a boolean if a data.frame with all information (default: FALSE)

Value

a vector of colors as strings or a data.frame with dataType, label, xMin, xMax

Examples

```
loadCellminerPlotInfo()
```

loadNciColorSet *Returns a 60-element color set that matches the color set used on <http://discover.nci.nih.gov/>*

Description

Returns a 60-element color set that matches the color set used on <http://discover.nci.nih.gov/>

Usage

```
loadNciColorSet(returnDf = FALSE)
```

Arguments

returnDf a boolean if a data.frame with tissue names and abbreviations should be returned (default: FALSE)

Value

a vector of colors as strings or a data.frame with tissues, tissue abbreviations, cell line abbreviations and colors

Examples

```
loadNciColorSet()
```

MolData *Returns a MolData object.*

Description

Returns a MolData object.

Usage

```
MolData(eSetList, sampleData, ...)
```

Arguments

eSetList	A list of eSet objects for a common set of samples.
sampleData	A MIAxE object capturing sample and other data set information.
...	Other possible parameters.

Value

A MolData object.

```
MolData(list, MIAxE-method)
```

Returns a MolData object.

Description

Returns a MolData object.

Usage

```
## S4 method for signature 'list,MIAxE'  
MolData(eSetList, sampleData, ...)
```

Arguments

eSetList	A list of eSet objects for a common set of samples.
sampleData	A MIAxE object capturing sample and other data set information.
...	Other possible parameters.

Value

A MolData object.

MolData-class	<i>An S4 class to represent molecular data recorded for a set of biological samples.</i>
---------------	--

Description

An S4 class to represent molecular data recorded for a set of biological samples.

Arguments

... Other possible parameters.

Slots

eSetList A list of eSet objects for a common set of samples.

sampleData A MIAxE object capturing sample and other data set information.

passRuleOf5	<i>Checks if SMILES passes Lipinski's Rule of 5</i>
-------------	---

Description

Checks if SMILES passes Lipinski's Rule of 5

Usage

```
passRuleOf5(smiles, acceptableViolations = 0, verbose = FALSE)
```

Arguments

smiles a string, the SMILES structure to be checked

acceptableViolations,
a number, the number of acceptable rule violations (default: 0)

verbose a boolean, whether to write out the failing criteria (default: FALSE)

Details

Uses RCDK: `org.openscience.cdk.qsar.descriptors.molecular.RuleOfFiveDescriptor`

Value

a boolean, whether the SMILES passes the criteria

Examples

```
# Docetaxel
passRuleOf5("CC1=C2C(C(=O)C3(C(CC4C(C3C(C(C2(C)C) (CC10C(=O)C(C(C5=CC=CC=C5)NC(=O)OC(C) (C)C)O)O)OC(=O)C6=CC=CC=C6) (C04)OC(=O)C)O)C)O", verbose=TRUE)
```

```
# Gemcitabine
passRuleOf5("C1=CN(C(=O)N=C1N)C2C(C(C(O2)CO)O) (F)F", verbose=TRUE)
```

passRuleOf5FromNsc *Checks if NSC passes Lipinski's Rule of 5*

Description

Checks if NSC passes Lipinski's Rule of 5

Usage

```
passRuleOf5FromNsc(nsc, acceptableViolations = 0, verbose = FALSE)
```

Arguments

nsc a string, the NSC identifier to be checked
 acceptableViolations, a number, the number of acceptable rule violations (default: 0)
 verbose a boolean, whether to write out the failing criteria (default: FALSE)

Details

Uses RCDK: org.openscience.cdk.qsar.descriptors.molecular.RuleOfFiveDescriptor

Value

a boolean or NA, whether the NSC passes the criteria or NA if the NSC had no structure

Examples

```
passRuleOf5FromNsc("94600", verbose=TRUE)
```

patternComparison *Compare an input pattern against a set of patterns.*

Description

Compare an input pattern against a set of patterns.

Usage

```
patternComparison(pattern, profileMatrixList, method = "pearson")
```

Arguments

pattern An N element input pattern specified as either a named vector or an 1 x N matrix or data frame. Names (or column names) must match the column names of each element of profileMatrixList.
 profileMatrixList A single matrix (or data frame) or a list of matrices (or data frames). Each matrix (data frame) must be k x N - that is the k patterns for comparison with the input pattern must be specified along the rows, with rownames set appropriately.
 method a string specifying the type of correlation, chosen from pearson (default) or spearman.

Value

A data frame with pattern comparison results. Specifically, if M is the total number patterns in profileMatrixList elements, an $M \times 2$ matrix is returned with sorted Pearson's correlations in the first column and corresponding p-values in the second column. Comparison pattern names are indicated in the row names.

Examples

```
drugAct <- exprs(getAct(rcellminerData::drugData))
molDataMats <- getMolDataMatrices()[c("exp", "mut")]
molDataMats <- lapply(molDataMats, function(X) X[1:10, ])
pcResults <- patternComparison(drugAct["609699", ], molDataMats)
pcResults <- patternComparison(drugAct["609699", ], molDataMats, method="spearman")
pcResults <- patternComparison(drugAct["609699", ], molDataMats$exp, method="spearman")
```

plotCellMiner

Description: Produces CellMiner-like plots in R

Description

Description: Produces CellMiner-like plots in R

Usage

```
plotCellMiner(drugAct, molData, plots, nsc = NULL, gene = NULL,
  features = NULL, sub = NULL, xLimits = NULL, xLabel = NULL,
  extraPlot = NULL, verbose = FALSE)
```

Arguments

drugAct	a matrix of drug activity values (cell lines as columns, drug entries as rows)
molData	a list of matrices a molecular
plots	a vector of characters denoting the plots to include and the order (e.g. c("mut", "drug", "cop"). Currently, supported entries mutations (mut), drug activities (drug), copy number variations (cop)
nsc	a string NSC ID that will be plotted when a "drug" entry appears in the plots vector
gene	a string HUGO gene symbol for which the "mut", "cop", or "exp" plots will be produced if in plots vector
features	a vector of strings that provide the full IDs for elements to be plotted (e.g. mutCDK4 for CDK4 mutations). This overwrites the nsc and gene parameters, but is needed in advanced plots that involve data that involves one-to-many relationships (e.g. many entries for a given gene in the exome data) and a gene symbol is ambiguous.
sub	a vector of strings with sub-titles for each plot
xLimits	a 2 number vector with the the minimum and maximum X-axis values (default: -3,3 for Z-scores, 0,1 for binary entries)
xLabel	a string for the default X-axis label
extraPlot	a list containing title, label, and values (numeric vector of length 60); only one extra plot can be included
verbose	a boolean to show debugging information

Value

None

Author(s)

Augustin Luna <augustin AT mail.nih.gov>

Examples

```

drugAct <- exprs(getAct(rcellminerData::drugData))
molData <- getMolDataMatrices()
plots <- c("mut", "drug", "cop", "xai", "pro")
plotCellMiner(drugAct, molData, plots=plots, nsc="94600", gene="CDK4", verbose=TRUE)

plots <- c("mut", "xai", "cop", "cop", "cop", "cop")
plotCellMiner(drugAct, molData, plots=plots, nsc="94600", gene=c("CDK4", "TP53",
  "BRAF", "GAPDH"), verbose=TRUE)

plotCellMiner(drugAct, molData, plots=plots, nsc=NULL, features=c("mutCDK4",
  "xaiCDK4", "exochr1:101704532_G_T", "mdais_p53_mut", "mirhsa-miR-22", "proTP53_26_GBL00064"),
  verbose=TRUE)

```

plotDrugActivityRepeats

Plot NCI-60 drug activity profiles for repeat experiments.

Description

Plot NCI-60 drug activity profiles for repeat experiments.

Usage

```

plotDrugActivityRepeats(nscStr, useZScore = FALSE, maxRepNum = 5,
  pdfFilename = NULL, pdfWidth = 12, pdfHeight = 6)

```

Arguments

nscStr	a string specifying the NSC identifier for a compound.
useZScore	a boolean specifying whether to plot z-transformed data (as opposed to -logGI50 values).
maxRepNum	an integer specifying the maximum number of repeat experiments to plot.
pdfFilename	name of a PDF output
pdfWidth	width of the PDF (default: 12)
pdfHeight	height of the PDF (default: 6)

Value

NONE

Examples

```

plotDrugActivityRepeats("609699")
plotDrugActivityRepeats("609699", useZScore=TRUE, maxRepNum=3)

```

plotDrugSets	<i>Produces a barplot of the average values for a set of NSCs with a error bar (one standard deviation)</i>
--------------	---

Description

Produces a barplot of the average values for a set of NSCs with a error bar (one standard deviation)

Usage

```
plotDrugSets(drugAct, drugs, mainLabel = "", pdfFilename = NULL,
             statistic = "mean")
```

Arguments

drugAct	a matrix of drug activity values (cell lines as columns, drug entries as rows)
drugs	a vector of NSC IDs whose values will be averaged by cell line
mainLabel	a main label for the plot
pdfFilename	a string file name for a PDF plot, no file output will be produced if this is not provided
statistic	a string, either 'mean' or 'median' (Default: mean)

Value

no values are returned

Examples

```
drugAct <- exprs(getAct(rcellminerData::drugData))
drugs <- rownames(drugAct)[1:8]
plotDrugSets(drugAct, drugs, "Test")
```

plotStructures	<i>Plot Structures</i>
----------------	------------------------

Description

Plot Structures

Usage

```
plotStructures(ids, smiles, titleCex = 1, structSize = 300,
              structAnnotPos = 50, mainLabel = "", rows = 1, cols = length(ids))
```

Arguments

ids	a vector of strings of IDs used as structure titles
smiles	a vector of strings where the strings are SMILES structures
titleCex	a number, the scaling factor for the title (default: 1)
structSize	a number, the size of the structure image (default: 200)
structAnnotPos	a number, how far above the structure to display the title (default: 50)
mainLabel	a string, the main plot label
rows	number of rows in figure (default: 1)
cols	number of columns in figure (default: input structures number)

Details

The parameter `ids` is used as a title, this function does not search for IDs, but works based off the smiles given. This is a wrapper around `rcdkplot` for plotting multiple structures.

Value

the function does not return anything

Author(s)

Augustin Luna <augustin AT mail.nih.gov>

Examples

```
drugAnnot <- as(featureData(getAct(rcellminerData::drugData)), "data.frame")
plotStructures("94600", drugAnnot["94600", "SMILES"])
plotStructures(c("609699", "94600"), drugAnnot[c("609699", "94600"), "SMILES"],
  mainLabel=c("609699", "94600"))
```

plotStructuresFromNscs

Plot the structures for NSCs

Description

Plot the structures for NSCs

Usage

```
plotStructuresFromNscs(nscs)
```

Arguments

nscs	a vector of strings of NSCs used as structure titles
------	--

Details

This is a wrapper for the `plotStructures()` function that takes only NSCs

Value

the function does not return anything

Author(s)

Augustin Luna <augustin AT mail.nih.gov>

Examples

```
plotStructuresFromNscs("94600")
plotStructuresFromNscs(c("609699", "94600"))
```

rcdkplot

Plot molecules

Description

Plot molecules in R plot window instead of separate Java window

Usage

```
rcdkplot(molecule, width = 300, height = 300, marg = 0, main = "")
```

Arguments

molecule	an RCDK molecule
width	an integer width of the molecule
height	an integer height of the molecule
marg	margin for all side of the plot (default: 0)
main	a string the main title of the figure

Details

Code taken from: <http://www.cureffi.org/2013/09/23/a-quick-intro-to-chemical-informatics-in-r/>

Value

None

Examples

```
tmp <- parse.smiles("C1=CN(C(=O)N=C1N)C2C(C(C(O2)CO)O)(F)F")
rcdkplot(tmp[[1]], width=300, height=300, main="Gemcitabine")
```

removeMolDataType	<i>Remove molecular data type prefixes from features.</i>
-------------------	---

Description

Remove molecular data type prefixes from features.

Usage

```
removeMolDataType(features, prefixLen = 3)
```

Arguments

features	A vector of features.
prefixLen	The length of the molecular data type prefix.

Details

This function is primarily used to remove prefixes from elastic net features.

Value

A named vector of features without molecular data type prefixes.

Examples

```
removeMolDataType(c("expTP53", "copMDM2", "mutCHEK2", "mutBRAF"))
```

restrictFeatureMat	<i>Restricts a feature matrix to only include features associated with a specified gene set.</i>
--------------------	--

Description

Restricts a feature matrix to only include features associated with a specified gene set.

Usage

```
restrictFeatureMat(geneSet, featureMat, prefixSet = c("cop", "exp", "mut"))
```

Arguments

geneSet	a character vector of gene names.
featureMat	a matrix or data frame with feature vectors along rows and feature names specified in rownames(featureMat).
prefixSet	a set of feature name prefixes to be prepended to each element of geneSet to obtain a collection of geneSet-associated features.

Value

a matrix containing the features in the intersection of rownames(featureMat) and the set of geneSet-derived features (obtained by prepending each element of prefixSet to each gene in geneSet).

#'

Examples

```
X <- matrix(1:25, nrow=5)
rownames(X) <- c("expA", "expB", "copC", "mutC", "expD")
restrictFeatureMat(geneSet = c("B", "C"), X)
```

rowCors

Row-wise correlations

Description

Correlation between ith row of x and ith row of y for all i

Usage

```
rowCors(X, Y)
```

Arguments

X a matrix

Y a matrix

Value

a list of two vectors: cor (correlation values) and pval (correlation p-values)

Author(s)

Sudhir Varma, NCI-LMP

Examples

```
a <- matrix(runif(100), nrow=10, ncol=10)
b <- matrix(runif(100), nrow=10, ncol=10)
c <- rowCors(a, b)
```

runShinyApp	<i>Run Shiny App</i>
-------------	----------------------

Description

Run Shiny App

Usage

```
runShinyApp(app = "shinyComparePlots", launch.browser = TRUE, port = 3838)
```

Arguments

app	string Shiny app to run (See Details, OPTIONS: shinyComparePlots, shinyCompareStructures, shinyReprodPlots, DEFAULT: shinyComparePlots)
launch.browser	launch in browser? (default: TRUE)
port	port number to use

Details

- shinyComparePlots: The "Comparison" application allows users to plot any two variables from the CellMiner data against each other. It additionally allows users to search for compound NSC IDs using names and mechanisms of action.
- shinyCompareStructures: The "Compound Browser" application allows users to see information about each compound, including structures and any repeat assay information.
- shinyReprodPlots: The "Structure Comparison" application allows users to identify similar compounds within the dataset either by NSC ID or SMILES string.

Value

None

Examples

```
# Uncomment first  
#runShinyApp()
```

runShinyComparePlots	<i>Run the Compare Plots Shiny App</i>
----------------------	--

Description

Run the Compare Plots Shiny App

Usage

```
runShinyComparePlots(launch.browser = TRUE, port = 3838)
```

Arguments

launch.browser launch in browser? (default: TRUE)
port port number to use

Value

None

Examples

```
port <-3838  
# Uncomment first  
#runShinyComparePlots(port=port)
```

runShinyCompareStructures

Run the Compare Structures Shiny App

Description

Run the Compare Structures Shiny App

Usage

```
runShinyCompareStructures(launch.browser = TRUE, port = 3838)
```

Arguments

launch.browser launch in browser? (default: TRUE)
port port number to use

Value

None

Examples

```
port <- 3838  
# Uncomment first  
#runShinyCompareStructures(port=port)
```

runShinyCompoundBrowser
Run the Compound Browser

Description

Run the Compound Browser

Usage

```
runShinyCompoundBrowser(launch.browser = TRUE, port = 3838)
```

Arguments

launch.browser launch in browser? (default: TRUE)
port port number to use

Value

None

Examples

```
port <- 3838  
# Uncomment first  
#runShinyCompoundBrowser(port=port)
```

searchForNscs *Search for NSCs*

Description

Search for NSCs

Usage

```
searchForNscs(pattern)
```

Arguments

pattern a search pattern. This string will be treated as a regular expression with the case ignored.

Details

Use this function with caution. Not all compounds have names and compounds can have many synonyms not included in CellMiner.

Value

A vector of matching NSCs

Examples

```
searchForNscs("nib$")
```

```
selectCorrelatedRows
```

Select features that are correlated with a given feature (or one or more features from a set of features).

Description

Select features that are correlated with a given feature (or one or more features from a set of features).

Usage

```
selectCorrelatedRows(Y, X, corThreshold = 0.1, useAbsCor = TRUE)
```

Arguments

Y	a vector or matrix; rows from X will be correlated with Y if Y is a vector or with rows of Y, if Y is a matrix.
X	a matrix of values that will be compared with Y (vector) or rows of Y (matrix)
corThreshold	the minimum correlation threshold for the row to be returned
useAbsCor	a logical value indicating whether absolute correlations should be used (default=TRUE).

Value

a matrix of rows of X correlated with Y (if Y is a vector) or correlated with at least one row of Y if Y is a matrix or data frame.

Examples

```
vec <- runif(10)
mat <- matrix(runif(100), 10, 10)
selectCorrelatedRows(vec, mat)
```

```
selectCorrelatedRowsFromMatrices
```

Select features that are correlated with a given feature (or one or more features from a set of features), merging results from multiple candidate feature matrices.

Description

Select features that are correlated with a given feature (or one or more features from a set of features), merging results from multiple candidate feature matrices.

Usage

```
selectCorrelatedRowsFromMatrices(Y, XList, corThreshold = 0.1,
  useAbsCor = TRUE)
```

Arguments

Y a vector or matrix; rows from each matrix element of X will be correlated with Y if Y is a vector or with rows of Y, if Y is a matrix.

XList a list of matrices whose rows will be correlated with Y (vector) or rows of Y (matrix). The rownames in each matrix element of XList must be specified to values that are unique with respect to the total set of rownames (as derived from all matrices in XList).

corThreshold the minimum correlation threshold for the row to be returned

useAbsCor a logical value indicating whether absolute correlations should be used (default=TRUE).

Value

a matrix formed from rows of matrices in XList that are correlated with Y (if Y is a vector) or correlated with at least one row of Y if Y is a matrix or data frame.

Examples

```
vec <- runif(10)
names(vec) <- 1:10
matList <- list(X1 = matrix(runif(100), 10, 10), X2 = matrix(runif(100), 10, 10))
rownames(matList$X1) <- paste0("X1_row_", 1:10)
colnames(matList$X1) <- paste0("X1_col_", 1:10)
rownames(matList$X2) <- paste0("X2_row_", 1:10)
colnames(matList$X2) <- paste0("X2_col_", 1:10)
selectCorrelatedRowsFromMatrices(vec, matList)
```

[[,MolData-method *Returns an indexed eSet object from a MolData object eSet list.*

Description

Returns an indexed eSet object from a MolData object eSet list.

Usage

```
## S4 method for signature 'MolData'
x[[i]]
```

Arguments

x A MolData object.

i Index or named item in MolData object eSet list.

Value

An indexed eSet object from a MolData object eSet list.

[[<-,MolData-method *Assigns an eSet object to a specified position in a MolData object eSet list.*

Description

Assigns an eSet object to a specified position in a MolData object eSet list.

Usage

```
## S4 replacement method for signature 'MolData'  
x[[i]] <- value
```

Arguments

x	A MolData object.
i	Index or named item in MolData object eSet list.
value	An eSet object to be assigned.

Value

An eSet object to a specified position in a MolData object eSet list.

Index

*Topic **data**

- cmVersion, 3
- Drug_MOA_Key, 8
- drugDB, 7
- elNetMolDataNCI60, 8
- fingerprintList, 9
- .DrugData (DrugData-class), 7
- .MolData (MolData-class), 32
- [[, MolData-method, 45
- [[<- , MolData-method, 46

- cmVersion, 3
- compareFingerprints, 4
- crossCors, 4
- crossCorsSpearman, 5

- Drug_MOA_Key, 8
- DrugData, 6
- DrugData, eSet, eSet, MIAXE-method, 6
- DrugData-class, 7
- drugDB, 7

- elNetMolDataNCI60, 8

- fingerprintList, 9

- getAct, 9
- getAct, DrugData-method, 10
- getActivityRangeStats, 10
- getAllFeatureData, 11
- getAllFeatureData, MolData-method, 11
- getBinaryMutationData, 12
- getColumnQuantiles, 13
- getDrugActivityData, 13
- getDrugActivityRange, 14
- getDrugActivityRepeatData, 14
- getDrugMoaList, 15
- getDrugName, 16
- getESetList, 16
- getESetList, MolData-method, 17
- getFeatureAnnot, 17
- getFeatureAnnot, DrugData-method, 18
- getFeatureAnnot, MolData-method, 18
- getFeatureDataFromMatList, 19
- getFingerprintList, 19

- getMedSenLineActivity, 20
- getMinDrugActivityRepeatCor, 21
- getMoaStr, 21
- getMoaToCompounds, 22
- getMolDataMatrices, 22
- getMolDataType, 23
- getNumDrugActivityRepeats, 23
- getNumMissingLines, 24
- getRepeatAct, 24
- getRepeatAct, DrugData-method, 25
- getRsd, 25
- getSampleData, 26
- getSampleData, DrugData-method, 26
- getSampleData, MolData-method, 27
- getSmiles, 27

- hasMoa, 28

- initialize, DrugData-method, 28
- initialize, MolData-method, 29
- isPublic, 29

- loadCellminerPlotInfo, 30
- loadNciColorSet, 30

- MolData, 31
- MolData, list, MIAXE-method, 31
- MolData-class, 32

- passRuleOf5, 32
- passRuleOf5FromNsc, 33
- patternComparison, 33
- plotCellMiner, 34
- plotDrugActivityRepeats, 35
- plotDrugSets, 36
- plotStructures, 36
- plotStructuresFromNscs, 37

- rcdkplot, 38
- removeMolDataType, 39
- restrictFeatureMat, 39
- rowCors, 40
- runShinyApp, 41
- runShinyComparePlots, 41
- runShinyCompareStructures, 42

[runShinyCompoundBrowser](#), 43

[searchForNscs](#), 43

[selectCorrelatedRows](#), 44

[selectCorrelatedRowsFromMatrices](#), 44