

Visualization of data from assays in microtitre plate or slide format

Wolfgang Huber

April 30, 2018


The `splots` package provides a single function, `plotScreen`, for visualising data in microtitre plate or slide format. Here we show a short demo of its parameters. First, we generate example data:

```
> library("splots")
> screen = lapply(1:12, function(i) cumsum(rnorm(384)))
> names(screen) = paste("plate", LETTERS[seq(along=screen)])
```


```
> toLatex(sessionInfo())
• R version 3.5.0 (2018-04-23), x86_64-apple-darwin15.6.0
• Locale: C/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
• Running under: OS X El Capitan 10.11.6
• Matrix products: default
• BLAS:
  /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRblas.0.dylib
• LAPACK:
  /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRlapack.dylib
• Base packages: base, datasets, grDevices, graphics, methods, stats, utils
• Other packages: splots 1.46.0
• Loaded via a namespace (and not attached): RColorBrewer 1.1-2, compiler 3.5.0,
  grid 3.5.0, tools 3.5.0
```

Table 1: The output of `sessionInfo` on the build system after running this vignette.


```
> plotScreen(screen, ncol=3)
```



```
> plotScreen(screen, ncol=2, do.legend=FALSE)
```



```
> plotScreen(screen, ncol=4, fill=c("white", "darkblue"),
+             main="Example data",
+             legend.label=expression(bar(x) == sum(x[i], i==1, n)))
```



```
> for(i in seq(along=screen))
+   screen[[i]][sample(384, 5)] = NA
> plotScreen(screen, ncol=4, do.names=FALSE,
+             main="Example data", legend.label="Legend label")
```

